-	本		FABRICATIO	N MATERIALS					_{→ N} 流水號:651
	· 周	PT NO	COMPONENT	DESCRIPTION	N.S. (INS)	ITEM CODE		QTY	がに入るが、OO I
			PIPE		(110)				
-	万 	1 2		304 EFW SCH10S BE ASME B36.19M 304 EFW SCH40S PE ASME B36.19M		S1P1/P-4"-1 S1P1/P-1"-4		0.3M 1.5M	
-	<u> </u>	3	REDUCER EC	C BW A403-WP304 WELD SCH10S	4 x 3	S1P1/RE-4")	K3 "	2	S12
2	後	4 5		00# SW A182-F304 MSS SP-97 BLE/PSE A403-WP304 SMLS	4 x 1 3 x 1	S1P1/SOL-4 S1P1/SE-3"E		1 2	CONN. TO C-401 F8 G9 B10 E-605/N5
=	請	6	SCH10S/SCH4 90 ELBOW 300	0S MSS-SP-95 10# SW A182-F304 ASME B16.11	1	S1P1/ES-1")	(90	2	E 76450 ① ①
		1	B16.11	NG 3000# SW A182-F304 ASME	1	S1P1/CFS-1		1	N 49600
	- 11	Ω	FLANGES W 1	50# RF A182-F304 SCH40S BORE	1	S1P1/FRSW	4"	2	
	講	0	ASME B16.5	30# NI A102-1 304 3011403 BONE	ı	OTF I/I NOW	-1	2	
	還		ERECTION M	ATERIALS					1
		PT	COMPONENT	DESCRIPTION	N.S.	ITEM CODE		QTY	FLAT FACE DOWN
		NO _	GASKETS		(INS)				2 TG TG
		9	GASKET 150#	RF 4.5 MM THICK 304SS SPIRAL APHITE FILLER W/SS304 OUTER	1	S1P1/GR-1"		1	(60506)
			RING ASME B						6 S13 C-1-60 203 EL.+3214
		10	BOLTS STUD BOLT A	193 GR.B8 W/ TWO HEX. HEAD	1/2	S1P1/BS4-1/	/2"X65L	4	
				194 GR.8 ASME B1.1 B18.2.2					750
		11		E GAUGE 150# RF TG 60506	1			1	
			SUPPORTS						3"x1"NS 28MM OFFSET ELAT FACE DOWN
		12 13 14	FLANGE GROU CRADLE SHOE FIELD SUPPOI		1 1 1	MISC/C-401 SUP/C-1"-60 SUP/FS6-1A)	1 1 1	EL.+2957
		PIECE NO <1> <3> <5>	E CUT LENGTH (229 509	NGTH FOR REFERENCE ONLY N.S. REMARKS PIECE (INS) NO 1 <2> 1 <4> 4	CUT LENGTH 554 176	N.S. REM (INS) 1	IARKS		102 11 203 5 3"x1"NS 28MM OFFSET FLAT FACE DOWN 3 4"x3"NS CONT. ON
									13MM OFFSET (3) 2 FLAT FACE DOWN
	簽								
	+								FOR CONSTRUCTION
									JUL. 04, 2025
	+								管線編號
									P-60513-1"-S1P1-C60 「① 管件序號 <1> 自管編號 [①] 管段編號 資料庫 工廠焊接 套焊 螺紋銜接 配合現場焊接 配合現場接合點 管支撑 蒸汽追蹤管 追晓从 無報 大股份有限 公司
	+								□ 管件序號 <1>直管編號 [1] 管段編號 資料庫 工廠焊接 套焊 螺紋銜接 配合現場焊接 配合現場接合點 管支撑 蒸汽追蹤管 後 須設計會驗管線 名稱 · □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □ □
		\triangle							操作壓力: 0.05 KC _{M²} G 操作溫度: -16 C 管線等級: S1P1 製 圖 陳怡如 2025.04.21 _會
	\perp	\triangle							以表示图力: 2/-0.1 Kg/g 引起引温度: 80/-26 C 保温(冷)等級: C60 以 計 黄炳富 2025.04.21 □ □ □ □ □ FU-TAI ENGINEERING CO., LTD.
	+			FOR CONSTRUCTION			黄炳富	陳逢明	試驗基準: Air
	+	<u>A</u> 序次	2025.04.21	FOR APPROVAL 修改	 		黃炳富	陳逢明 認 可	管路塗装: 管 水 塗 装
	\perp	. 4 // \	- **	12 271	J, 0 7 7		1/ 1/1	۷ ۱	至又 17 不務則