		FABRICATION MATERIALS				N			,EL	.+1886	ンケーレッチ マック
		PADRICATION WATERIALS				₩ N		F7 G11 B12	9 41		流水號:762
	PT NO	COMPONENT DESCRIPTION PIPE	N.S. (INS)	ITEM CODE	QTY			17]		105	
完	1	PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	1	S1P4/P-1"-40S	0.3M			C-401		117 EL.+1658	
	2	PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	3/4	S1P4/P-3/4"-40S	0.5M					F7 G11 B12	
	3	FITTINGS REDUCING TEE 3000# SW A182-F304 ASME	1 x 3/4	S1P4/TS-1"X3/4"	1			14	√ 		
後	4	B16.11 TEE 3000# SW A182-F304 ASME B16.11	3/4 x 3/4	S1P4/TS-3/4"	1			S1P4/VA-3/4"-4144-E			
	5	90 ELBOW 3000# SW A182-F304 ASME B16.11	1	S1P4/ES-1"X90	1				1		
	6	FLANGES FLANGE SW 150# RF A182-F304 SCH40S BORE	1	S1P4/FRSW-1"	1					124.	
速	7	ASME B16.5 FLANGE SW 150# RF A182-F304 SCH40S BORE	3/4	S1P4/FRSW-3/4"	4						
記市		ASME B16.5 ERECTION MATERIALS							44—		
還		ENECTION WATERIALS						(3	39.	4	
	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY					3/4"x3/4"NS EL.+1534	
		FITTINGS									
	8	NIPPLE (L=100MM) TOE(NPT) A312-TP304 SMLS SCH80S ASME B36.19M	3/4	S1P4/NIP-3/4"X100LXTOE	1					15	PG
	9	CAP 3000# SCRD (FNPT) A182-F304 ASME B16.11	3/4	S1P4/CT-3/4"	1		.44	138			61807 EL.+1391
	10	GASKETS GASKET 150# RF 3.0 MM THICK VIRGIN PTFE	1	S1P4/GR-1"-ZW#7500	1				~	13	EL.+1261
	11	ZW#7500 ASME B16.21/B16.5 GASKET 150# RF 3.0 MM THICK VIRGIN PTFE	3/4	S1P4/GR-3/4"-ZW#7500	4	CONT	EDOM /		60	S1P4/VA-1"-4144-E	3) 127
		ZW#7500 ASME B16.21/B16.5				CONT.	FRUM				S16
	12	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD	1/2	S1P4/BS4-1/2"X65L	20						C-401 F6 G10 B12
		HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2						F7 G11	B12	EL.+1381	I I
	13	VALVES / IN-LINE ITEMS BALL 150# RF A351-CF8/304SS+PTFE FULL PORT	1	S1P4/VA-1"-4144-E	1			S17 _	37	EL.+1261	1 NS
		FIRE SAFE WRENCH OPER. ASME B16.34 (VOC<100 vppm)		311 4/V/CT 4144 E				C-401		117	127
	14	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34 (VOC<100 vppm)	3/4	S1P4/VA-3/4"-4144-E	2			14 S1P4/VA-3/4"-4144-E	36 🔼	S17 C-401	
		INSTRUMENTS						S1P4/VA-3/4 -4144-E	(8×Z	F7 G11 B12	5
	15	PRESSURE GAUGE 150# RF PG 61807	1		1				Ĭ.	33	
		SUPPORTS							A	212711	
	- 16 17	FLANGE GROUNDING CONDUCTOR (C-401) FLANGE GROUNDING CONDUCTOR (C-401)	1 3/4	MISC/C-401 MISC/C-401	1 4					127 -	
	1	CUT PIPE LENGTH FOR REFERENCE ONLY								150	
	PIECE		CUT N LENGTH (II								
	NO - <8> <10>	LENGTH (INS) NO 99 3/4 <9> 100 3/4 <11>	126 3	NS) /4 /4				4"	35 'NS		
	<12>	104 1 <13>		1				ı	NS /		
分配 △△	1							CONT. FROM	1	(31)	
/7 🚨 🔼	1							1 3	/4"NS		FOR CONSTRUCTION
	1							1 X3/	/4 NS		JUL. 04, 2025
											33L. 34, 2323
											管線編號
											P-61824-1.1/2"-S1P4
	_					□ 管件序號 <1>直9 & 須設計會驗管線	管編號 [1] 管段編號	資料庫 名稱	工廠焊接 套	焊 螺紋銜接 配合現場焊接 配合現場接合點 管支撑 	為勝化學科技股份有限公司 ————————————————————————————————————
							操作溫度: 38	管線等級: S1P4	製圖	陳怡如 2025.04.21 會	富台工程股份有限公司 FU-TAI ENGINEERING CO., LTD.
								保溫(冷)等級:	設計	黃炳富 2025.04.21	FU-TAI ENGINEERING CO., LTD.
	<u> </u>	2025.07.03 FOR CONSTRUCTION		黃炳富	陳逢明	試驗基準: Air 8	.47 KG CM ² G X 60 分	熱追縱等級:	審核	陳安誠 2025.04.21	崙尾一期
	A	2025.04.21 FOR APPROVAL	±0 =	黃炳富	陳逢明	管路塗裝:	文 松端 () () ()	焊接基準:	認可	陳逢明 2025.04.21	建廠工程 立體配管圖 3
	序次	日期 修改	說 明	修改	認可	焊道.	撑 緊ዀ () ^マ / :	NDE 抽驗: 10 %	仪猴閪號:	C2418-4-513	檔號: P-61824-S1P4- 2