		FABRICATION MATERIALS				N			<u> </u>	<u> </u>	(49)		· · • •		流水號:123
昌	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY		}		<	12>1	127 / 4 (50)		H	OLD!	
完	1	PIPE PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	1	S1P1/P-1"-40S	14.9M			11	15 MM	48) P	<13>1 1"NS	>		
	2	PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	3/4	S1P1/P-3/4"-40S	0.1M			EL.+15091 10	05 MM		F6	G8 B11 EL.+14450	>		
	3	FITTINGS REDUCING TEE 3000# SW A182-F304 ASME	1 x 3/4	S1P1/TS-1"X3/4"	1			117 VEL.+1496	69	# P	TO GRADE		>		
後	4	B16.11 90 ELBOW 3000# SW A182-F304 ASME B16.11	1	S1P1/ES-1"X90	7		, ,	F7 G9 B11			[00.040]	PV	>		
請	5	FULL COUPLING 3000# SW A182-F304 ASME B16.11 FLANGES	1	S1P1/CFS-1"	1		122 CONT 2	FROM 1"N	\$ 7 8 7 8 8			(RV 21113	>		
速	6	FLANGE SW 150# RF A182-F304 SCH40S BORE	1	S1P1/FRSW-1"	1						<11>2	14 //"x3/4"NS	•		
	7	ASME B16.5 FLANGE SW 150# RF A182-F304 SCH40S BORE ASME B16.5	3/4	S1P1/FRSW-3/4"	1				> 4	46	20 13				
歸								<10>1	147	1	/ <14>1 LO	P1/VA-3/4"-4144			
還		ERECTION MATERIALS							19	H	(21)				
/~	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY			3		24	170				
		GASKETS						S17	3/4"NS 42	28	<15>1	22)			
	8	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	1	S1P1/GR-1"	1			SS33-1"-200L	1		23 0 E	EL.+14744			
	9	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER	3/4	S1P1/GR-3/4"	2		(5)	SRPA-1	\	~		91 S1P1/\ EL.+14653	/A-1"-2844	1	
		RING ASME B16.20/B16.5 BOLTS					∧ (EL.	+14225			16>1 25 9		S15 PO1-90		
	10	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD	1/2	S1P1/BS4-1/2"X80L	4		/1_		<u> </u>	<u> </u>		<u> </u>			
	11	HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2 STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	1/2	S1P1/BS4-1/2"X65L	8				<17	>1	(26)		14] El	+13517	
		VALVES / IN-LINE ITEMS							13	11_4	1014	S19 SRP-1 S1	19		
	12	GLOBE 800# SW A182-F304 BB OS &Y RS TRIM 304SS STELLITED LOOSE DISC API-602	1	S1P1/VA-1"-2844	1					<	29 4	SF	RP-1		
	13	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34	3/4	S1P1/VA-3/4"-4144	1					28 S18	7811		320		
		INSTRUMENTS								S1	30 7 1 2 2 2	/ A	AS2-1-0304	1	
	14	RELIEF VALVE 150# RF RV 21113 SUPPORTS	1 x 3/4		1						6023	<u></u>	S18 S1		
	15 16	PLATFORM OPENING (PO1-90) SUPPORT REINFORCING PAD (SRPA-1)	1	SUP/PO1-1" SUP/SRPA-1"	1				EL.+	9005/	32		_EL.+7481	I	
	17 18	STRUCTURE SUPPORT (SS33-1"-200L) PIPE SHOE (S1)	1 1 1	SUP/SS33-1" SUP/S1-1"	1 3							<20>1 S18			
	19 20 21	SUPPORT REINFORCING PAD (SRP-1) AUXILIARY SUPPORT (AS2-1-0304) VERTICAL ANCHOR (VA1-1)	1 1 1	SUP/SRP-1" SUP/AS2-1-1" SUP/VA1-1"	3 1 1					<	19>1 7 7 7 13	\$10 S1 S1S	9		
		. ,				_				4 EL.+6	3267	(35)	P-1		
	-	CUT PIPE LENGTH FOR REFERENCE ONLY									_ // "	25			
	PIEC NO <10>	E CUT N.S. REMARKS PIECE LENGTH (INS) NO 125 1 <11>	LENGTH (I	.S. REMARKS NS) 8/4						V	521 /A1-1 33 <21>	₩ 1 1 99	<22>1		
△ 會 簽	<12> <14>	100 1 <13> 124 1 <15>	727 75	1 1							CONT. ON	37	1"NS		EVISED
分配 / /	<16> <18> <20>	1113 1 <17> 1765 1 <19> 1091 1 <21>	968 6000 2259	1 1 1							CW-21352-8"-S E 85505	S1P1			NSTRUCTION
	<22>	505 1										148			
	-													SEF	P. 12, 2025
	-														
														管線編號	
														CW-21104-	1"-S1P1
						① 管件序號 <1> 直管編號 [1] 管段編號 資料庫 & 須設計會驗管線 名稱				工廠焊接 套焊 螺紋銜接配合現場焊接配合現場接合點管支撑 蒸汽追蹤管				鴻勝化學科技股份有限公司 E-shine Advanced Chemicals Ltd.	
	\triangle					操作壓力: 3	KC _{CM} ² G 操作温度: 39.6 ℃	管線等級: S1P1	製		謝鳳菁 2025.04.21	會		富台	L程股份有限公司 [1]
	1	2025.09.12 REVISED FOR CONSTRU	JCTION	鄧基宏	陳逢明	設計壓力:8	,	保溫(冷)等級:	設	計	鄧基宏 2025.04.21			FU-TA	I ENGINEERING CO., LTD.
		2025.07.03 FOR CONSTRUCTION			陳逢明	試驗基準: Air	一 管 材 塗 装	熱追縱等級:	審図	核	陳安誠 2025.04.21	簽 ————		編尾一期 建廠工程	管線工程 3 立體配管圖 3
	序次	2025.04.21 FOR APPROVAL	 說 明	鄧基宏 修 改	陳逢明 認 可	管路塗裝: 焊道. 塗裝:	大	焊接基準: NDE 抽驗: 10 %	認 依據	" 	陳逢明 2025.04.21 C2418-4-504	 		檔號: CW-211	
	1.1 //\	_ 784 17 181	216 77	12 6/	100 1	坐坂	1手 个跨鋼 :	IADE 1 1 10 10 10 10 10 10	12 / 213/	٠ ١١ ٣٠٠ تىسىد	C2418-4-549			1 m 3/3, 01, 211	