本		FABRICATION MATERIALS					<sub>→</sub> N 流水號:98
圖	NO —	COMPONENT DESCRIPTION		N.S. (INS)	ITEM CODE	QTY	河(小玩:96
完	1	PIPE PIPE A312-TP304 EFW SCH10S BE 0 PIPE A312-TP304 EFW SCH40S PE 0		2.1/2 3/4	S1P1F/P-2.1/2"-10S S1P1F/P-3/4"-40S	18.0M 0.1M	
<u> </u>	3	FITTINGS SOCKOLET 3000# SW A182-F304 MS 90 ELBOW LR BW A403-WP304 WEL ASME B16.9		2.1/2 x 3/4 2.1/2	S1P1F/SOL-2.1/2"X3/4" S1P1F/EB-2.1/2"X90	1 4	
請		ERECTION MATERIALS					4 /8>1
速	PT NO	COMPONENT DESCRIPTION		N.S. (INS)	ITEM CODE	QTY	18 S8 S1
歸	-	FITTINGS	FDOOL ONLO	0/4	OADAE/AUD O/AUVAOOL VITOE		
還		NIPPLE (L=100MM) TOE(NPT) A312- SCH80S CNS 6331 CAP 3000# SCRD (FNPT) A182-F304		3/4	S1P1F/NIP-3/4"X100LXTOE S1P1F/CT-3/4"	1	9500 S1P1F/VA-3/4"-1844 5 6 / EL.+7150
		VALVES / IN-LINE ITEMS  GATE 800# SW A182-F304 BB OS &Y	DS TDIM	3/4	S1P1F/VA-3/4"-1844	1	
		304SS STELLITED SOLID WEDGE AI		3/4	31F 11/VA-3/4 -1044	'	G2-2.1/2 \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
		PIPE SHOE (S1) SUPPORT REINFORCING PAD (SRP	-2.1/2)	2.1/2 2.1/2	SUP/S1-2.1/2" SUP/SRP-2.1/2"	3 3	SRP-2.1/2 <7>1) 9350 (2) EL.+6987
		PIPE GUIDE (G5-1) PIPE GUIDE (G2-2.1/2)		2.1/2 2.1/2	SUP/G5-1-2.1/2" SUP/G2-2.1/2"	1 1	560 S60 Q2.1/2"x3/4"NS
		CUT PIPE LENGTH FOR REFEREN	CE ONLY				(B) EL.+4787
	PIECE NO <6>	CUT N.S. REMARKS LENGTH (INS) 100 3/4	PIECE NO <7>	LENGTH (	N.S. REMARKS (INS) 2.1/2		3 750
	<8> <10> <12>	4310 2.1/2 370 2.1/2 4060 2.1/2	<9> <11>	1860 2 1360 2	2.1/2 2.1/2		SS TOSS
							SRP-2.1/2 2.1/2"NS/ CONT. FROM 1
							EL.+631
							CONT. ON/ 3
							FOR CONCERNATION
							FOR CONSTRUCTION
							JUL. 15, 2025
							FO-90511-2.1/2"-S1P1F
							□ 管件序號 <1>直管編號 [1] 管段編號 資料庫
							操作壓力: 10 KS <sub>M</sub> G 操作溫度: 25 ℃ 管線等級: S1P1F 製 圖 <b>陳郁惟</b> 2025.04.21 會 富台工程股份有限公司
		2025.07 15 FOR CONSTR	RUCTION		陳至欽	陳逢田	設計壓力: 12.3 KG/V G 設計溫度: 60 °C 保溫(今)等級: 設計 陳至鉉 2025.04.21 FU—TAI ENGINEERING CO., LTD.
		2025.07.15 FOR CONSTE 2025.04.21 FOR APPROV			陳至鉉	陳逢明	