<b></b>	_	FABRICATION MATERIALS			N CONT. ON	
		COMPONENT DESCRIPTION N.S. (INS)	ITEM CODE	QTY	/ IW-11135-1"-C1A1 E 105923 N 10925 EL.+2417	ハドントコル・フロサ
	_   1	PIPE A106 GR.B GALV. SMLS SCH80 PE ASME 1 B36.10M	C1A1/P-1"-80	20.5M	1668	
		FITTINGS  90 ELBOW 3000# SW A105 GALV. ASME B16.11  FULL COUPLING 3000# SW A105 GALV. ASME  1	C1A1/ES-1"X90 C1A1/CFS-1"	4 2	1"NS/	
		B16.11  ERECTION MATERIALS			3 <2>1	
捷	11	COMPONENT DESCRIPTION N.S. (INS) FITTINGS	ITEM CODE	QTY	S7 (5) (4)	
景	11 7	ADAPTER (CAMLOCK COUPLING) SCRD (MALE 1 NPT)  VALVES / IN-LINE ITEMS	C1A1/QCAAR-1"	1	(a) 1735 EL.+1717	
\(\lambda\)	5	BALL 2000PSI SCRD(NPT) A105 304SS+PTFE FULL 1 PORT FIRE SAFE WRENCH OPER. ASME B16.34	C1A1/VA-1"-4T12	2 1	2	
	6 7 8	SUPPORTS           PIPE SHOE (S1A)         1           PIPE GUIDE (G5-1)         1           ANCHOR SUPPORT (A1)         1	SUP/S1A-1" SUP/G5-1-1" SUP/A1-1"	7 4 1	S6 S1A 3500 9	
		CUT PIPE LENGTH FOR REFERENCE ONLY			S6 S1A	
	PIE0 NO <1> <3> <5>	LENGTH (INS) NO LENGT 1645 1 <2> 654 1689 1 <4> 6000	1 1	KS	® 107A	
	<7>		1		S7 G5-1 3000	
					S6 S1A 3 S7 G5-1	
					(1) 106 <sub>1</sub> 43 <sub>4</sub>	
					S6 S1A 3000 S8 A1	
					A1 <6>1/	(13) 1 <7>1
					EL.+13 EL.+14	75 S C1A1/VA-1"-4T12
<u></u> 會 第 分 配 <u>/</u> /						4 (8>1 1"NS
					FOR CONSTRUCTION	
					JUL. 04, 2025	
						管線編號 IW-11136-1"C1A1
					<ul> <li>① 管件序號 &lt;1&gt;直管編號 [1] 管段編號 資料庫</li> <li>② 須設計會驗管線</li> <li>工廠焊接 套焊 螺紋銜接 配合現場焊接 配合現場接合點 管支撑 蒸汽追蹤</li> <li>→ ← ← ← ← ← ← ← ← ← ← ← ← ← ← ← ← ← ← ←</li></ul>	Balling water in the state of t
					操作壓力: 4.5 KCM² G 操作溫度: 30 C 管線等級: C1A1 製 圖 陳怡如 2025.04.21 會	┃ ■ 富台工程股份有限公司
	$\triangle$	2025 07 02 EOD COMOTOLICTION		<b>黄</b> 炳富 陳逢明	設計壓力: 9	
		2025.07.03 FOR CONSTRUCTION			試驗基準; Air	<b>  満尾一期</b>
1 1	À	2025.04.21 FOR APPROVAL	1	黃炳富 陳逢明	管路塗装:   管    大	建廠工程 立體配管圖 1