<b></b>		FABRICATION	I MATERIALS					N									633
모	PT NO	COMPONENT	DESCRIPTION	N.S. (INS)	ITEM COD	<u>E</u>	QTY	$\overline{\mathcal{N}}$							·		
	1	PIPE PIPE A312-TP30 FITTINGS	04 EFW SCH40S PE ASME B36.19M	1	S1P1/P-1"-	40S	3.3M										
	2 3 4	TEE 3000# SW 2	A182-F304 ASME B16.11 D# SW A182-F304 ASME B16.11 D# SW A182-F304 ASME B16.11	1 x 1 1 1	S1P1/TS-1 S1P1/ES-1 S1P1/ES-1	"X90	2 3 1										
	5	FLANGES  FLANGE SW 15 ASME B16.5	i0# RF A182-F304 SCH40S BORE	1	S1P1/FRS	W-1"	3										
速		ERECTION MA	ATERIALS						20	4							
	PT NO	COMPONENT	DESCRIPTION	N.S. (INS)	ITEM COD	E -	QTY	② 	283	45°							
還	6		RF 4.5 MM THICK 304SS SPIRAL APHITE FILLER W/SS304 OUTER 6.20/B16.5	1	S1P1/GR-1	н	3	<13>1 8 1"NS F EL.+2755	H 200 1 200	57712	S10 AS4-0203 77 S G	12	3		-		
	7		93 GR.B8 W/ TWO HEX. HEAD 94 GR.8 ASME B1.1 B18.2.2	1/2	S1P1/BS4-	-1/2"X65L	12	(3) S9 C-401	F5 (	66 B7 CONN. TO	G	5-1	30	) <sup>29</sup>		5 G6 B7	
	8	BALL 150# RF A FIRE SAFE WRI (VOC<100 vppm	 A351-CF8/304SS+PTFE FULL PORT ENCH OPER. ASME B16.34	1	S1P1/VA-1	"-4144-E	1			V-601/N11 E 71300	S11 C-1-60	1022	-278 8>1	400		,23 	
	9	SUPPORTS  FLANGE GROU AUXILIARY SUF	INDING CONDUCTOR (C-401) PPORT (AS4-0203)	1 1	MISC/C-40 SUP/AS4-1	"	3 1			22.12700		EL.+2939	8 2	(17)		2	
	11 12	CRADLE SHOE PIPE GUIDE (G	(C-1-60)	1	SUP/C-1"-( SUP/G5-1-		1 1						233		C-401		
	PIEC NO <6> <8> <10> <12>	CE CUT N LENGTH (I 254 255	ILS. REMARKS PIECI INS) NO 1 <7> 1 <9> 1 <11> 1 <13>	LENGTH 354 100	N.S. RE (INS) 1 1 1 1	MARKS						8	EL.+2939// 1"NS <10>1// F5 G6 B7 1// C1"-4144-E	127	126	29 1"NS CONT. I	FROM
													С	-401	2 1"x1"NS EL.+2917		
△ 會 簽																	
分配△△	2													F0	D CONC	TDUCTIO	
														[F0	JUL. 04	TRUCTIO	IN .
														ſ	管線編號	.,	
								□ 無力 (1) 有力 (1) 有力 (2) 有力	· 管編號 [1] 管段編號	<b>玄</b> 粉 唐	丁霰悍拼   套帳	星 螺紋銜接 配合現場焊	接 配合钼锡接合點 管		P-60115-1"-		, pin- 1,
								& 須設計會驗管線		名稱 ·	<u></u> → +	<del></del>	<u> </u>		GSUDING E-2	特化學科技股份有 nine Advanced Chemic	als Ltd.
	$\triangle$							操作壓力: 0.05 KG <sub>CM</sub> <sup>2</sup> G 設計壓力: 6/HV KG <sub>CM</sub> <sup>2</sup> G		管線等級: S1F 保溫(冷)等級: C60		陳怡如 2025.04 黃炳富 2025.04	一 旹 ———		富台 FU-TA	工程股份有例 I ENGINEERING CO	艮公司 0., LTD.
	<u> </u>	2025.07.03	FOR CONSTRUCTION			黃炳富	陳逢明	試驗基準: Air	6.6 KG/M² G X 60 分	熱追縱等級:	審核	陳安誠 2025.04	<b>─</b>   帝 <b>├</b> ───		崙尾一期	管線工程	
	A	2025.04.21		+^	70	黄炳富	陳逢明	管路塗裝:	文   監督(公)(37)	焊接基準:	認可	陳逢明 2025.04	.21		建廠工程	立體配管圖	2
	序次	日期	修改	說 6	明	修改	認可	焊道, 塗裝,	撑   不銹鋼 ;	NDE 抽驗: 10	% 依據圖號:	C2418-4-509	圖號:		檔號: P-6011	5-S1P1- 2	