\overline{Z}			FABRICATION	MATERIALS				N						流水號 :1053
	- 11	PT NO	COMPONENT	DESCRIPTION	N.S. (INS)	ITEM CODE	QTY	₩ .						//ic+3 + 3//01 1 0 0 0
ラ		1		04 EFW SCH40S PE ASME B36.19M	1	S1P4/P-1"-40S	0.1M							
_		2	FLANGES FLANGE SW 15 ASME B16.5	0# RF A182-F304 SCH40S BORE	1	S1P4/FRSW-1"	1							
	美		ERECTION MA	ATERIALS										
LJ,	- 11	PT NO	COMPONENT D	DESCRIPTION	N.S. (INS)	ITEM CODE	QTY							
I .	- 11	3	NIPPLE (L=100)	MM) TOE(NPT) A312-TP304 SMLS	1	S1P4/NIP-1"X100LXTOE	1							
		4	SCH80S ASME CAP 3000# SCF GASKETS	B36.19M RD (FNPT) A182-F304 ASME B16.11	1	S1P4/CT-1"	1							
		5	ZW#7500 ASME	RF 3.0 MM THICK VIRGIN PTFE B16.21/B16.5	1	S1P4/GR-1"-ZW#7500	2							
		6		93 GR.B8 W/ TWO HEX. HEAD 94 GR.8 ASME B1.1 B18.2.2	1/2	S1P4/BS4-1/2"X65L	8			7	104 3	DRAIN		
			VALVES / IN-LINE	EITEMS						S1P4/VA-1"-4	\ 0	100 4		
		7	FIRE SAFE WRI (VOC<100 vppm	(351-CF8/304SS+PTFE FULL PORT ENCH OPER. ASME B16.34	1	S1P4/VA-1"-4144-E	1				127/ S8	H		
		8	SUPPORTS FLANGE GROU	NDING CONDUCTOR (C-401)	1	MISC/C-401	2			CONN. STR-61	101./D	168 F2 G5 B	6	
				GTH FOR REFERENCE ONLY				E 103868 <1>1 N 38141 1"NS EL.+461						
		PIECE NO <1>	LENGTH (I		CUT N.S. RI LENGTH (INS)									
												G5 B6		
	簽													
分配 △														FOR CONSTRUCTION
														JUL. 04, 2025
														JUL. 04, 2025
														答 始矩
														管線編號 TRIM-STR61101-D-1"-S1P4
								① 管件序號 & 須設計會駅		資料庫. 名稱:	工廠焊接 套焊 螺紋行		合現場接合點 管支撑 蒸	
								操作壓力: 0.6	KC/CM² G 操作溫度: 38 °C	+	製圖陳怡	2 to 0005 04 04	會	■ ■ 富台工程股份有限公司
		\triangle						設計壓力: 3.5		保溫(冷)等級:		富 2025.04.21	н	FU-TAI ENGINEERING CO., LTD.
		<u>^</u>	2025.07.03			黄炳富	陳逢明	試驗基準: Air	3.85 KC _{CM} ² G X 60 分 管 材 塗 装	熱追縱等級:	審核原安		簽	満尾一期 管線工程 建廠工程 立體配管圖
		序次	2025.04.21	FOR APPROVAL 修改	說 明	黃炳富 修 改	陳逢明 認 可	管路塗装: 焊道. 塗裝:	管 材 遂 裝	焊接基準: NDE 抽驗: 10 %	認 可 陳逢 依據圖號: C2418-	生明 2025.04.21 4-512	 圖號:	位號: TRIM-STR61101-D-S1P4- 1
			- 244	17 171		1 2 27	1 33 1	至权	1手 小野剛	1110F 1HWW . 12 /0				1 - 1 - 1