<u></u>		FABRICATION MATERIALS				N						流水號:220
	PT NO	COMPONENT DESCRIPTION	N.S. <u>IT</u> (INS)	TEM CODE	QTY							流入玩:220
		PIPE				CONT. FROM						
	1 2 3	PIPE A312-TP304 EFW SCH10S BE ASME B36.19M PIPE A312-TP304 EFW SCH10S BE ASME B36.19M PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	6 S	1P1/P-8"-10S 1P1/P-6"-10S 1P1/P-1"-40S	4.5M 2.0M 0.1M	219	S'NS					
後	4	FITTINGS REDUCING TEE BW A403-WP304 WELD SCH10S	8 x 6 S	1P1/TB-8"X6"	1							
	5 6	ASME B16.9 SOCKOLET 3000# SW A182-F304 MSS SP-97 90 ELBOW LR BW A403-WP304 WELD SCH10S		1P1/SOL-6"X1" 1P1/EB-6"X90	1 3			2822				
請		ASME B16.9 FLANGES							710			
速	7	FLANGE WN 150# RF A182-F304 SCH10S BORE ASME B16.5	8 S	1P1/FRWN-8"	1			``	103/1	4	NINIO	
歸	8	FLANGE WN 150# RF A182-F304 SCH10S BORE ASME B16.5	6 S	1P1/FRWN-6"	3						"NS	
漫	9	FLANGE SW 150# RF A182-F304 SCH40S BORE ASME B16.5	1 S	1P1/FRSW-1"	2					33		
	'									(S)		
	PT NO	COMPONENT DESCRIPTION	N.S. IT	TEM CODE	QTY						1425 2075	S22
		FITTINGS								-928	125	C-8-40-150
	10	NIPPLE (L=100MM) TOE(NPT) A312-TP304 SMLS SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F304 ASME B16.11		1P1/NIP-1"X100LXTOE	1					, I		19
		FLANGES			•						12> <u>2</u> 6 . s:	23 S1P1/VA-8"-1144 292
	12	FLANGE BLIND 150# RF A182-F304 ASME B16.5	8 S	1P1/FBR-8"	1					<u>7</u>	55 G	292
		GASKETS								53	56	F7 G13 B16
	13	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	8 S	1P1/GR-8"	2				[6 65	02	12/ G13 B16
	14	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER	6 S	1P1/GR-6"	3					EL.+9734	F8 G14 B17	20
	15	RING ASME B16.20/B16.5 GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER	1 S	1P1/GR-1"	2					EL.+9033	57 267	S1P1/VA-6"-1144
		RING ASME B16.20/B16.5 BOLTS								EL.+87	62	F8 G14 B17
	16	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD	3/4 S	1P1/BS4-3/4"X110L	16					F8 G14	B17 58	62
	17	HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2 STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	3/4 S	1P1/BS4-3/4"X105L	24						61)	
	18	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	1/2 S	1P1/BS4-1/2"X65L	8						— 905 — 902	CONN. TO
	_	VALVES / IN-LINE ITEMS									v 35 ^A	C-151B/N3 E 58425
	19	GATE 150# RF A351-CF8 BB OS &Y RS TRIM 304SS STELLITED FLEXIBLE WEDGE API-600		1P1/VA-8"-1144	1						69	N 72575 EL.+7855
	20	GATE 150# RF A351-CF8 BB OS &Y RS TRIM 304SS STELLITED FLEXIBLE WEDGE API-600 BALL 150# RF A351-CF8/304SS+PTFE FULL PORT		1P1/VA-6"-1144 1P1/VA-1"-4144	1					5		F9 G15 B18 EL.+7647
	21	FIRE SAFE WRENCH OPER. ASME B16.34	1 5	IP1/VA-1 -4144	ı					6"x1"NS	(a)	
☆ ☆ ※	22	SUPPORTS CRADLE SHOE (C-8-40-150)	8 S	UP/C-8"-40	1					EL.+7	7055	!\/ i\ \
分配 △	23	PIPE GUIDE (G5-2)		UP/G5-2-8"	1						21 (5) S1P1/VA-1"-4144 (2)	10 EL.+7516 F9 G15 B18
		CUT PIPE LENGTH FOR REFERENCE ONLY									EL.+740	/ \
	PIECI	E CUT N.S. REMARKS PIECE		REMARKS		500	REVISED				(
	NO <10> <12>	2644 8 <11>	LENGTH (INS) 479 6 383 6			FOR	CONSTRUCTIO	N			\bigwedge 1	
	<14> <16>	584 6 <15>	100 1 1795 8			S	EP. 12, 2025					
												管線編號 ICW-15314-8"-S1P1-C40
						□ 管件序號 <1>直	管編號 [1] 管段編號	資料庫 名稱		焊 螺紋銜接 配合現場焊接	配合現場接合點 管支撑 蒸汽追	^{選蹤管} 場勝化學科技股份有限公司
						7 0111		管線等級: S1P1	製圖	陳郁惟 2025.04.2	1 @	■ ■ 富台工程股份有限公司
	1	2025.09.12 REV. FOR CONSTRUCTI	ION	陳至鉉	陳逢明	,		保温(冷)等級: C40	設計	陳至鉉 2025.04.2	1 _	FU-TAI ENGINEERING CO., LTD.
		2025.07.03 FOR CONSTRUCTION		陳至鉉	陳逢明			熱追縱等級:	審核	陳安誠 2025.04.2	→ 😭	一
	序次	2025.04.21 FOR APPROVAL		陳至鉉 修 改	陳逢明 認 可	管路塗裝: 焊道. 塗裝:	支 碳鋼及不銹:		認 可	陳逢明 2025.04.2 C2418-4-525	1	建廠工程 立體配管圖 2 檔號: ICW-15314-S1P1- 2
	1/1, 1/		u/i 4/7	TE LX		塗裝・		NDE 抽驗: 10 %	IV\18X IIII JITI.	UZ410-4-0Z0	III 3/L.	1日 ルル・10077-10014-0171- 2