		FABRIC	ATION MATERIALS					N										・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・・	造。CEA
			ENT DESCRIPTION	N.S.	ITEM CODE	C	QTY	W										派八	號:654
	- 11	NO PIPE		(INS)		_													
	- - -		2-TP304 EFW SCH40S PE ASME B36.19M	1 3/4	S1P1/P-3/4"-40S	;	3.0M												
-	-	FITTINGS															٦		
	-		# SW A182-F304 ASME B16.11 V 3000# SW A182-F304 ASME B16.11	3/4 x 3/4 3/4	S1P1/TS-3/4" S1P1/ES-3/4"X90		2										3		
後	*	4 45 ELBO	V 3000# SW A182-F304 ASME B16.11	3/4	S1P1/ES-3/4"X45		1								(19			
	- 11	FLANGES	SW 150# RF A182-F304 SCH40S BORE	3/4	C4D4/EDCW/ 2/4"		3										20	200	
		ASME B1		3/4	S1P1/FRSW-3/4"		3								/				
速] - -	ERECTI	ON MATERIALS																
		PT COMPON	ENT DESCRIPTION	N.S.	ITEM CODE		QTY									<13>1	74"N8/		
	- 11	NO COMPON	ENT DESCRIPTION	(INS)	TIEW CODE	_										// Vi	93		
漫		GASKETS					_									F5 G6 B7	EL.+275	5	
	-	WOUND	150# RF 4.5 MM THICK 304SS SPIRAL N/GRAPHITE FILLER W/SS304 OUTER ME B16.20/B16.5	3/4	S1P1/GR-3/4"		3							/	* (T)	21	22.12700		S9 C-401
		BOLTS	NE B 10.20/B 10.0													I			0-401
		7 STUD BC	LT A193 GR.B8 W/ TWO HEX. HEAD	1/2	S1P1/BS4-1/2"X6	5L	12											CONN. TO V-606/N11	
			UT A194 GR.8 ASME B1.1 B18.2.2 N-LINE ITEMS							27) 3	3						200	E 69800 N 47000	
		8 BALL 150	# RF A351-CF8/304SS+PTFE FULL PORT	3/4	S1P1/VA-3/4"-414	4-E	1				> ~					/ /		EL.+2750	
		FIRE SAF (VOC<10	E WRENCH OPER. ASME B16.34) vppm)						17		(28)								
		SUPPORT	S -							,00			18						
		10 CRADLE	GROUNDING CONDUCTOR (C-401) SHOE (C-3/4-60)	3/4 3/4	MISC/C-401 SUP/C-3/4"-60		3 1	3	26		4		17						
			DE (G5-1) Y SUPPORT (AS4-0203)	3/4 3/4	SUP/G5-1-3/4" SUP/AS4-3/4"		1	EL.+3	3217	%il	 28	<11>1		45	ମ				
								-	25 <10>[S12 1 AS4-0203				45°	_				
			E LENGTH FOR REFERENCE ONLY	- CUT	N.S. REMARK				59 6 C-401 \	29	664			S10					
		PIECE CUT NO LENGTH <6> 265	N.S. REMARKS PIECE (INS) NO 3/4 <7>		N.S. REMARK (INS) 3/4	5			v			146 ^A	S11 G5-1	C-3/4-60					
		<8> 265 <10> 113	3/4 <9> 3/4 <11> 3/4 <13>	113	3/4 3/4 3/4				F5 G6 B7	(15)	(16)	EL.+29							
		<12> 251	3/4 <13>	135	3/4				9>1		//								
									117	131	\\19								
								653		F5 G6 B7	7 \\2 3/4'	x3/4"NS							
									\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	 13		+2933							
								CONT. FROM	14	C-401	(
								3/4"N	vs/ / /	\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \									
	-							2		30)									
分配								3/4"x3/4" EL.+291	'NS / /1									REVISED	
// हा / /	\exists							8	. /								FOR	CONSTRU	CTION
								S1P1/VA-3/4"-4 NC	4144-E									SEP. 12, 202	25
								NO										JEI . 12, 202	
	\neg																管線編號		
																		I-3/4"-S1P1-C6	60
								① 管件序號 <1>	直管編號 [1] 管段編			工廠焊接 套	焊 螺紋銜接 i	配合現場焊接 룝	。 合現場接合點	管支撑 蒸汽追蹤	一	油 唯 儿 解 利 壮 肌	
								& 須設計會驗管線		名稱 [:]				\times	-			E-shine Advanced Cl	hemicals Ltd.
								操作壓力: 0.05 KG _{CM²}		-	S1P1	製圖	陳怡如	2025.04.21	會			台工程股份在	有限公司
	-+-		.12 REVISED FOR CONSTR	RUCTION			陳逢明	設計壓力: 2/-0.1 KG _{CM²}			C60	設計		2025.04.21			— FL	J-TAI ENGINEERIN	IG CO., LTD.
		2025.07					陳逢明	試驗基準: Air	2.2 KG/CM ² G X 60			審核		2025.04.21	簽 ——		編尾一期 建廠工程	管線工程	
	_	2025.04		<u>÷</u> A n⊓			陳逢明	管路塗裝:	管 を 材 塗 装 で で 材 塗 装 で で で で で が 塗 装 で で で で で で で で で で で で で で で で で で	焊接基準:	40.07	認 可 佐地国蛤		2025.04.21	国验.			立體配管圖	
		次日	排 修改	說 明		沙	認可	焊道. 塗裝:	撑 不銹鋼 () :	NDE 抽驗:	10 %	以據宣號:	C2418-4-509		圖號:			60514-S1P1- 2	