<u></u>		FABRICATION MATERIALS				N S7 CONT.	ON				流水號:861
昌	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY	PW2-13 E 2272	3123-3"-S1P4				771E-5 - 5801 - C - 1
		PIPE				N 8610 EL.+22	854	1.1/2"NS			
71	1 2	PIPE A312-TP304 EFW SCH40S PE ASME B36.19M PIPE A312-TP304 EFW SCH40S PE ASME B36.19M	1.1/2 3/4	S1P4/P-1.1/2"-40S S1P4/P-3/4"-40S	3.8M 0.1M			2287			
		FITTINGS	G/ .	on on	0			512/7			
1,4	3	TEE 3000# SW A182-F304 ASME B16.11	1.1/2 x 1.1/2	S1P4/TS-1.1/2"	1						
後	5	SWAGE ECC PBE A403-WP304 SMLS SCH40S MSS-SP-95 REDUCING TEE 3000# SW A182-F304 ASME	1.1/2 x 1 1.1/2 x 3/4	S1P4/SE-1.1/2"PX1"P S1P4/TS-1.1/2"X3/4"	2						
	6	B16.11 90 ELBOW 3000# SW A182-F304 ASME B16.11	1.1/2 x 3/4 1.1/2	S1P4/IS-1.1/2 X3/4 S1P4/ES-1.1/2"X90	2				6 8 5		
		FLANGES						3	<2>1		
速	7	FLANGE SW 150# RF A182-F304 SCH40S BORE	1.1/2	S1P4/FRSW-1.1/2"	3			_	4-41		
記帚	8	ASME B16.5 FLANGE SW 150# RF A182-F304 SCH40S BORE ASME B16.5	1	S1P4/FRSW-1"	2			3 1.1/2"x1.1/2"N	/3>1		
	9	FLANGE SW 150# RF A182-F304 SCH40S BORE ASME B16.5	3/4	S1P4/FRSW-3/4"	2			EL.+1467		133 17	
還										S1P4/VA-1.1/2"-2844	
	-	ERECTION MATERIALS							4		
	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM CODE	QTY				6	CONT. ON	
		FITTINGS	()						<4>1 F7 G12 B15	2	
	10		3/4	S1P4/NIP-3/4"X100LXTOE	1			EL.	+1045 165	П	
	11	SCH80S ASME B36.19M CAP 3000# SCRD (FNPT) A182-F304 ASME B16.11	3/4	S1P4/CT-3/4"	1			F7 G12 B15		1.1/2"-4144 1.1/2"x1"NS	
		GASKETS						[17 G12 B13]	<5>1 S	8MM OFFSET FLAT FACE D	
	12	ZW#7500 ASME B16.21/B16.5	1.1/2	S1P4/GR-1.1/2"-ZW#7500	3				8 1.1/2"x3/4"NS		
	13	ZW#7500 ASME B16.21/B16.5	1	S1P4/GR-1"-ZW#7500	2				9 400 0 7	124 F8 G13 B16	
	14	GASKET 150# RF 3.0 MM THICK VIRGIN PTFE ZW#7500 ASME B16.21/B16.5	3/4	S1P4/GR-3/4"-ZW#7500	2				L.+674		
		BOLTS						S21 FS5-3-07		// //	F8 G13 B16
	15	HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	1/2	S1P4/BS4-1/2"X75L	12				S22 215	F7 G12 B15	
	16	STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2	1/2	S1P4/BS4-1/2"X65L	16				GR2-1 47	165	
		VALVES / IN-LINE ITEMS						( PV 1320	2)		18
	17	GLOBE 800# SW A182-F304 BB OS &Y RS TRIM 304SS STELLITED LOOSE DISC API-602	1.1/2	S1P4/VA-1.1/2"-2844	1			20	F9 G14 B16 <7>2	184 CON /2	IT. ON S1P4/VA-1.1/2"-4144
	18	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34	1.1/2	S1P4/VA-1.1/2"-4144 S1P4/VA-3/4"-4144	2				48		
	- 19	BALL 150# RF A351-CF8/304SS+PTFE FULL PORT FIRE SAFE WRENCH OPER. ASME B16.34	3/4	31F4/VA-3/4 -4144	ı			HOLD!	EL.+537	118 1.1/2"x1"NS	
		INSTRUMENTS							50 10 49	8MM OFFSE FLAT FACE	
	20	CONTROL VALVE 150# RF PV 13202 SUPPORTS	1		1				EL.+309	19	
	21	FIELD SUPPORT (FS5-3-07)	1.1/2	SUP/FS5-3-1.1/2"	1				DRAIN 11		P4/VA-3/4"-4144
	22		1.1/2	SUP/GR2-1.1/2"	1				105/	,	
會 簽		CUT PIPE LENGTH FOR REFERENCE ONLY							EL.1	+417/	
分配 //	$\exists$	CE CUT N.S. REMARKS PIECE	CUT N	I.S. REMARKS						F9 G14	B16
	NC <1:	> 2255 1.1/2 <2>	714 1	NS) .1/2							
	<3: <5: <7:	> 162 1.1/2 <6>		.1/2 .1/2		EOD CC	MOTDUCT	ON			
						FORCE	DNSTRUCTI	ON			
						JU	L. 04, 2025				
											管線編號
											PW2-13125-1.1/2"-S1P4
						<ul><li>① 管件序號 &lt;1&gt;直管編</li><li>&amp; 須設計會驗管線</li></ul>		資料庫 <sub>.</sub> 名稱 ·	工廠焊接 套焊 螺紋銜接 配合現場焊接 [	配合現場接合點 管支撑 蒸汽追蹤管 ————————————————————————————————————	海勝化學科技股份有限公司 E-shine Advanced Chemicals Ltd.
						操作壓力: 5.3 KG <sub>M</sub> <sup>2</sup> G 操作		〒線等級: S1P4	製 圖 陳郁惟 2025.04.21		
						/ 0111		保溫(冷)等級:	設計 陳郁惟 2025.04.21		富台工程股份有限公司 FU-TAI ENGINEERING CO., LTD.
	<u></u>	2025.07.03 FOR CONSTRUCTION		陳郁惟	陳逢明	/ 3	5 KG <sub>CM<sup>2</sup></sub> G X 60 分 ;	熱追縱等級:	審 核 陳安誠 2025.04.21	簽	<b>崙尾一期</b>
	Â	2025.04.21 FOR APPROVAL		陳郁惟	陳逢明	管路塗裝: 管	管 材 塗 装 碳鋼及不銹	焊接基準:	認 可 陳逢明 2025.04.21	×	建廠工程 立體配管圖 3
	序力	7 日期修改	說 明	修改	認可	焊道.		NDE 抽驗: 10%	依據圖號: C2418-4-528	圖號:	檔號: PW2-13125-S1P4- 1