Z			FABRICATION MATERIALS					N									流水號	:167
	51	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM	I CODE	QTY			(15)	3 EL.	+6911						
		1	PIPE	1/2	S1P1	IF/P-1/2"-40S	8.0M					14)						
-			FITTINGS						(4)									
	<u>└</u>	2	TEE 3000# SW A182-F304 ASME B16.11 90 ELBOW 3000# SW A182-F304 ASME B16.11 FLANGES	1/2 x 1/2 1/2		IF/TS-1/2" IF/ES-1/2"X90	2 5		21071 1121N	5 1764								
	青	4	FLANGE SW 150# RF A182-F304 SCH40S BORE ASME B16.5	1/2	S1P1	IF/FRSW-1/2"	1											
芝	코		ERECTION MATERIALS					CONT. ON	*									
自	帚川	PT NO	COMPONENT DESCRIPTION	N.S. (INS)	ITEM	I CODE	QTY				×6× 1							
}			FLANGES	4/0	6404	IF/FDD 4/0"	1											
12		5	FLANGE BLIND 150# RF A182-F304 ASME B16.5 GASKETS	1/2	51171	IF/FBR-1/2"	1					0067-						
		6	GASKET 150# RF 4.5 MM THICK 304SS SPIRAL WOUND W/GRAPHITE FILLER W/SS304 OUTER RING ASME B16.20/B16.5	1/2	S1P1	IF/GR-1/2"	1											
		7	BOLTS STUD BOLT A193 GR.B8 W/ TWO HEX. HEAD	1/2	S1D1	IF/BS4-1/2"X60L	4			S10 SRPA-1/2				3				
			HEAVY NUT A194 GR.8 ASME B1.1 B18.2.2 VALVES / IN-LINE ITEMS		· · · ·	,561 112 7002	·			EL.+4506_	 	S9 VA2-1/	2	EL.+4	011			
		8	GATE 800# SW A182-F304 BB OS &Y RS TRIM 304SS STELLITED SOLID WEDGE API-602	1/2	S1P1	IF/VA-1/2"-1844	1			ι	95				10			
			SUPPORTS							Ç	49		420	Z7> <u>1</u>				
		9 10	VERTICAL ANCHOR (VA2-1/2) SUPPORT REINFORCING PAD (SRPA-1/2)	1/2 1/2		/VA2-1/2" /SRPA-1/2"	1 1			(13)—						7	3 EL.+1734	
			CLIT DIDE LENGTH FOR DECEDENCE ONLY					-		·	3/	(12)		- 772			6	
		PIECE	CUT N.S. REMARKS PIECE		N.S.	REMARKS						(12)			247		3>	
		NO <1> <3>	LENGTH (INS) NO 122 1/2 <2> 95 1/2 <4>	LENGTH 129 168	(INS) 1/2 1/2					CONT. O FW-913C	N 203-2"-51	D1E			7	200	v]	
		<5> <7> <9>	100 1/2 <6> 2245 1/2 <8> 2868 1/2 <10>	100 388 1748	1/2 1/2 1/2					E 108810 N 51763)		а	9		<2>1	-127 -	
										EL.+1607	7		2 1/2"x1/2	'NS	138	160	,	
																23	5	
													<	5>1	2	\<1>1 \	1) 1 %	(1/2"NS
												8		66	1/2' BDV	NS -603_	16	
												S1I	P1F/VA-1/2"-1844 EL.+1569		.50 \EL.+161	9	CONT. ON FW-913C32-1/	/O" C4D4E
分配													<6>1	-106-	67		E 108970 N 51900 EL.+1592	71
													68	5	4 G6 B7	HOL	EL.+1592	<u>/ 1</u>
													EL.+	1463/ \\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\			.	
								FOR	CONSTRUCTI	ON								
								J	JUL. 15, 2025							管線編 FW-9	號 13C31-1/2"-S1P1F	:
								① 管件序號 <1> £	直管編號 [1] 管段編號	資料庫. 名稱		厂廠 焊接 套	焊 螺紋銜接 配合現場 		_		油降儿腹到せ饥心	有限公司
		\triangle						操作壓力: 10 KG/CM ² (G 操作溫度: 25 ℃			製圖	陳郁惟 2025.	——————————————————————————————————————			富台工程股份有	限公司
			2005 07 45				陆次四	,		保温(冷)等級:		設計	陳至鉉 2025.	04.21			FU-TAI ENGINEERING	CO., LTD.
			2025.07.15 FOR CONSTRUCTION 2025.04.21 FOR APPROVAL			陳至鉉 陳至鉉	陳逢明 陳逢明	試驗基準: Water 管路塗裝:	18.45 KC CM ² G X 60 分 管 管材塗装	熱追縱等級: 焊接基準:		審 核 認 可	陳安誠 2025. 陳逢明 2025.	── 第 ├─		編尾一 建廠工		$-\begin{pmatrix} 1\\4 \end{pmatrix}$
	_	予次	日期 修改	說 E	明	修改	認可	焊道. 塗裝・	管 材 塗 装 一 支 御保温(冷) :				C2418-4-512 C2418-4-510			檔號:	FW-913C31-S1P1F- 1	