-	本		FABRICATION	MATERIALS				_→ N 流水號:1052
1	吕	PT NO	COMPONENT D	ESCRIPTION	N.S. (INS)	ITEM CODE	QTY	がに対しるが、TUJ2
Г	元		FLANGES	0# DE 8492 E204 CCU40C DODE	2/4	CADA/EDOW 2/A	4	
		1	ASME B16.5	0# RF A182-F304 SCH40S BORE	3/4	S1P4/FRSW-3/4"	1	
-	<u> </u>		ERECTION MA	TERIALS				
	後 ===	PT NO	COMPONENT D	ESCRIPTION	N.S. (INS)	ITEM CODE	QTY	
	請	2	FITTINGS NIPPLE (L=100M	/IM) TOE(NPT) A312-TP304 SMLS	3/4	S1P4/NIP-3/4"X100LXTOE	1	
I .	速	3	SCH80S ASME			S1P4/CT-3/4"	1	
[[]	請	4	GASKETS GASKET 150# F	RF 3.0 MM THICK VIRGIN PTFE	3/4	S1P4/GR-3/4"-ZW#7500	2	
\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\\	還		ZW#7500 ASME BOLTS	B16.21/B16.5				
		5		93 GR.B8 W/ TWO HEX. HEAD 94 GR.8 ASME B1.1 B18.2.2	1/2	S1P4/BS4-1/2"X65L	8	
		6	VALVES / IN-LINE		2/4	CADADAA SAH AAAA	4	
		6		351-CF8/304SS+PTFE FULL PORT ENCH OPER. ASME B16.34	3/4	S1P4/VA-3/4"-4144	1	
								VENT
								2 105
								F1 G4 B5 117
								G4 B5 EL.+1023
								STR-21311./V S1P4/VA-3/4"-4144 E 81072
								N 65537 EL.+903
		1						
		1						
\ \ \ \ \ \ \	75							
分配 /	簽							
								FOR CONSTRUCTION
								JUL. 04, 2025
		-						管線編號
	-	-						TRIM-STR21311-V-3/4"-S1P4
			<u> </u>			ı		& 須設計會驗管線
								操作壓力: 0.05~0.5% 操作溫度: AMB~87.4c 管線等級: S1P4 製 圖 謝鳳菁 2025.04.21 會
	+		2025.07.03	FOR CONSTRUCTION		3	陳逢明	
		A		FOR APPROVAL	±0 =	鄧基宏	陳逢明	管路塗裝: 管
		序次	日期	修改	說 明	修改	認可	標道: