

Product Data

Castrol EDGE Professional A3 5W-40

Fluid TITANIUM - Stronger Under Pressure

Description

Today's engines continually push the boundaries of technology and engineering. They are smaller and ultra-efficient, without sacrificing performance. Advanced engines challenge the oil with increased pressures. These intense pressures cause friction, which can waste up to 10% of an engine's performance.

Castrol EDGE Professional is micro-filtered and certified CO₂ Neutral according to the highest global standard*. Its patented Fluid TITANIUM transforms to be stronger under pressure and reduces friction for maximum engine performance when you need it most.

Castrol EDGE Professional with Fluid TITANIUM: unlock the true performance of your engine.

Application

Castrol EDGE Professional A3 5W-40 is suitable for use in automotive gasoline and diesel vehicles where the manufacturer recommends an ACEA A3/B4, A3/B3, API SN/CF 5W-40 lubricant.

Castrol EDGE Professional A3 5W-40 is approved for use in vehicles from leading manufacturers, please refer to your owners handbook.

Advantages

Castrol EDGE Professional A3 5W-40 with Fluid TITANIUM is the natural choice for drivers who demand maximum engine performance from today's sophisticated vehicles requiring a high level of protection and higher performance oils.

Castrol EDGE Professional A3 5W-40:

- Transforms to be strongest when the pressure is highest, protecting your engine
- Reduces power-robbing friction across engine speeds and conditions
- Independently tested at the highest standards for proven performance
- Recommended by world-leading car manufacturers
- Protects the engine for the entire drain interval even under extreme pressure

^{*} in accordance with the BSI PAS 2060 specification

Typical Characteristics

Name	Method	Units	Castrol EDGE Professional A3 5W-40
Density @ 15C, Relative	ASTM D4052	g/ml	0.852
Viscosity, Kinematic 100C	ASTM D445	mm²/s	12.8
Viscosity, CCS -30C (5W)	ASTM D5293	mPa.s (cP)	6030
Viscosity, Kinematic 40C	ASTM D445	mm²/s	69
Viscosity Index	ASTM D2270	None	187
Pour Point	ASTM D97	°C	-45
Flash Point, PMCC	ASTM D93	°C	208
Ash, Sulphated	ASTM D874	% wt	1.14

Product Performance Claims

ACEA A3/B3, A3/B4 API SN/CF BMW Longlife-01 MB-Approval 226.5/ 229.3/ 229.5 Porsche A40 Renault RN0700 / RN0710 VW 502 00/ 505 00

Storage

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

Castrol EDGE Professional A3 5W-40

03 Dec 2018

Castrol, the Castrol logo and related marks are trademarks of Castrol Limited, used under licence.

This data sheet and the information it contains is believed to be accurate as of the date of printing. However, no warranty or representation, express or implied, is made as to its accuracy or completeness. Data provided is based on standard tests under laboratory conditions and is given as a guide only. Users are advised to ensure that they refer to the latest version of this data sheet. It is the responsibility of the user to evaluate and use products safely, to assess suitability for the intended application and to comply with all applicable laws and regulations. Material Safety Data Sheets are available for all our products and should be consulted for appropriate information regarding storage, safe handling, and disposal of the product. No responsibility is taken by either BP plc or its subsidiaries for any damage or injury resulting from abnormal use of the material, from any failure to adhere to recommendations, or from hazards inherent in the nature of the material. All products, services and information supplied are provided under our standard conditions of sale. You should consult our local representative if you require any further information.

Castrol (UK) Limited, PO BOX 354, Chertsey Road, Sunbury On Thames, Middlesex, TW16 9AW

www.castrol.com