

1.

(1)
 $Work = (1, 0, 1, 2)$ $Need = Max - Alloc$

	A	B	C	D
$Finish[3] = false, Need_3 \leq Work$	2	1	0	0
$\therefore Work += Alloc_3 \rightarrow (1, 0, 2, 2)$	0	0	2	1
$Finish[3] = true$	1	0	0	1
$Finish[2] = false, Need_2 \leq Work$	0	1	1	1
$\therefore Work += Alloc_2 \rightarrow (1, 1, 2, 3)$				
$Finish[2] = true$				
$Finish[1] = false, Need_1 \leq Work$				
$\therefore Work += Alloc_1 \rightarrow (1, 3, 3, 3)$				
$Finish[1] = true$				
$Finish[4] = false, Need_4 \leq Work$				
$\therefore Work += Alloc_4 \rightarrow (2, 4, 3, 3)$				
$Finish[4] = true$				

 $\therefore \text{Sequence} \langle P_3, P_2, P_1, P_4 \rangle$
 Satisfies safety requirement

(2) $Request_4 = (0, 0, 1, 1) \leq Need_4 (0, 1, 1, 1)$
 \downarrow
 doesn't satisfy $Request_4 = (0, 0, 1, 1) \leq Available (1, 0, 1, 2)$
 \downarrow
 P_4 waits, insufficient resource

(3) Alloc

	A	B	C	D
P_1	0	2	1	0
P_2	0	1	0	1
P_3	0	0	1	0
P_4	1	1	1	1

+ Request =

	A	B	C	D
P_1	2	3	1	0
P_2	0	1	1	1
P_3	1	0	1	0
P_4	1	2	1	1

Use deadlock detection algorithm

$Work = (-2, -2, -1, 1)$


For all i , $Request_i \leq Work$ is not satisfied

$\therefore Finish[i] = false$ exists, system deadlock


2. Design idea one: Use mutex lock. Only one person eats at a time.

```
82 pthread_mutex_t mutex;
83 void init() {
84     // write code if you desire.
85 }
86
87
88 void wants_to_eat(int p_no) {
89     // fixme
90     pthread_mutex_lock(&mutex);
91     pick_right_fork(p_no);
92     pick_left_fork(p_no);
93
94     eat(p_no);
95
96
97     put_left_fork(p_no);
98     put_right_fork(p_no);
99     pthread_mutex_unlock(&mutex);
100
101 }
```


Result (5 times):




Terminal window showing the execution of the program. The output displays five lines of dashes representing the state of the system, followed by the message "--] 100% done ok." and the prompt "ljj11912021@ljj11912021-virtual-machine:~/Desktop/Week12 Ass/Week12 Assignment\$".



Terminal window showing the execution of the program. The output displays five lines of dashes representing the state of the system, followed by the message "--] 100% done ok." and the prompt "ljj11912021@ljj11912021-virtual-machine:~/Desktop/Week12 Ass/Week12 Assignment\$".



Terminal window showing the execution of the program. The output displays five lines of dashes representing the state of the system, followed by the message "--] 100% done ok." and the prompt "ljj11912021@ljj11912021-virtual-machine:~/Desktop/Week12 Ass/Week12 Assignment\$".



Terminal window showing the execution of the program. The output displays five lines of dashes representing the state of the system, followed by the message "--] 100% done ok." and the prompt "ljj11912021@ljj11912021-virtual-machine:~/Desktop/Week12 Ass/Week12 Assignment\$".


```

31 void *dad(int *num){
32     for(int i=0;i<10;i++){
33         sem_wait(sem_drink);
34         pthread_mutex_lock(&fri_lock);
35         printf("Dad comes home.\n");
36         sleep(rand()%2+1);
37         printf("Dad goes to buy milk.\n");
38         *num += 1;
39         if (*num > 2){
40             printf("What a waste of food! The fridge can not hold
41             while(1)printf("TAT~");
42         }
43         printf("Dad puts milk in fridge and leaves.\n");
44         pthread_mutex_unlock(&fri_lock);
45         sem_post(sem_buy);
46     }
47 }

```

```

49 void *grandfather(int *num){
50     for(int i=0;i<10;i++){
51         sem_wait(sem_drink);
52         pthread_mutex_lock(&fri_lock);
53         printf("Grandfather comes home.\n");
54         sleep(rand()%2+1);
55         printf("Grandfather goes to buy milk.\n");
56         *num += 1;
57         if (*num > 2){
58             printf("What a waste of food! The fridge can not hold
59             while(1){
60                 printf("TAT~");
61             }
62         }
63         printf("Grandfather puts milk in fridge and leaves.\n");
64         pthread_mutex_unlock(&fri_lock);
65         sem_post(sem_buy);
66     }
67 }

```

```

69 void *son(int *num){
70     for(int i = 0; i < 30 ; i++){
71         sem_wait(sem_buy);
72         pthread_mutex_lock(&fri_lock);
73         printf("Son comes home.\n");
74         if(*num == 0){
75             printf("The fridge is empty!\n");
76             while(1){
77                 printf("TAT~");
78             }
79         }
80         printf("Son fetches a milk\n");
81         *num -= 1;
82         printf("Son leaves\n");
83         pthread_mutex_unlock(&fri_lock);
84         sem_post(sem_drink);
85     }
86 }

```

```

88  int main(int argc, char * argv[]) {
89      srand(time(0));
90
91      int num_milk = 0;
92      pthread_t p1, p2, p3, p4;
93      pthread_mutex_init(&fri_lock, NULL);
94
95      sem_drink = sem_open("empty", O_CREAT, 0666, 2);
96      sem_buy = sem_open("full", O_CREAT, 0666, 0);
97
98      // Create two threads (both run func)
99      pthread_create(&p1, NULL, mom, &num_milk);
100     pthread_create(&p2, NULL, dad, &num_milk);
101     pthread_create(&p3, NULL, grandfather, &num_milk);
102     pthread_create(&p4, NULL, son, &num_milk);
103
104     // Wait for the threads to end.
105     pthread_join(p1, NULL);
106     pthread_join(p2, NULL);
107     pthread_join(p3, NULL);
108     pthread_join(p4, NULL);
109
110     sem_close(sem_buy);
111     sem_close(sem_drink);
112
113     printf("success!\n");
114 }

```

Result:

```

问题  输出  调试控制台  终端
bash + - [ ] [ ] [ ]
Son leaves
Grandfather comes home.
Grandfather goes to buy milk.
Grandfather puts milk in fridge and leaves.
Son comes home.
Son fetches a milk
Son leaves
success!
ljj11912021@ljj11912021-virtual-machine:~/Desktop/Week12 Ass/Week12 Assignment$

```