

Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What will happen?

```
def outer():
    x = 10

    def inner():
        nonlocal y
        y = 20

    inner()
```

outer()

- A)10
- B)20
- C)SyntaxError
- D)NameError

Q2. Why is

```
try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")
codes's second handler never
reached?
```

- A)Exception is a superclass of ZeroDivisionError
- B)except blocks execute randomly
- C)ZeroDivisionError occurs before Exception
- D)ZeroDivisionError is not an exception

Q3. What is the output?

```
def fun(x):
    return x * 2
```

```
a = fun
print(a(5))
```

- A)10
- B>Error
- C)func(5)
- D)5

Q4. What will be printed?

```
class InvalidAgeError(Exception):
    pass

def check_age(age):
    if age < 18:
        raise InvalidAgeError("Age is
too low")
    return "Allowed"
```

```
try:
    print(check_age(15))
except InvalidAgeError as e:
    print(type(e).__name__)
    print(e)
```

- A)InvalidAgeError
- Age is too low
- B)Exception
- Age is too low
- C)InvalidAgeError
- 15
- D)Nothing, because custom exceptions cannot be caught

Q5. What is the output?

```
def fun(x):
    x += 10
    return x
```

```
x = 5
y = fun(x)
```

print(x, y)

- A)15 5
- B)5 15
- C)15 15
- D)5 5

Q6. What does the following function return?



1
C)0
1
0
2
D)1
2
1
3

Q13. What is the output?

```
try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")
```

A)SyntaxError
B)A
C)B
D)A B

Q14. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

A)A, followed by propagation of the same exception
B)No Output
C)A, and execution ends normally
D)B

Q15. What happens when this function is called?

```
def fun(a=10, b):
    return a + b
```

A)SyntaxError
B)TypeError
C)It executes correctly
D)NameError

Q16. What is the purpose of this statement?

```
if __name__ == "__main__":
```

A)It creates the main function
B)It prevents syntax errors

C)It prevents all imports
D)It identifies code intended to run when the file is executed directly

Q17. Which object keeps track of modules that have already been imported during the current Python process?

A)__module__
B)sys.modules
C)sys.path
D)sys.imports

Q18. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)B
B)Nothing
C)A
D)A and B

Q19. What will be printed?

```
def fun():
    try:
        return 10
    finally:
        print("Finally")
```

```
print(fun())
```

A)Finally followed by 10
B)10 followed by Finally
C)10 only
D)Finally only

Q20. What happens here?

```
class MyError(Exception):
    pass
```

```
def test():
    raise MyError("Something went wrong")
```



```

    numbers
)

print(result)
A)24
B)0
C)10
D)9
Q29. What happens when this code runs?

def first():
    second()

def second():
    third()

def third():
    raise RuntimeError("Failure")

try:
    first()
except RuntimeError:
    print("Handled")
A)Handled
B)NameError
C)TypeError
D)RuntimeError cannot propagate through functions
Q30. What will happen?

def fun(a, b=10):
    return a + b

print(fun(b=5, a=20))
A)SyntaxError
B)TypeError
C)25
D)15
Q31. What is the output?

def fun():
    try:
        return 10
    finally:
        return 20

print(fun())

```

```

A)20
B)RuntimeError
C)10
D)None
Q32. What happens here?

from math import sqrt

print(sqrt(36))
A)NameError
B)6
C)6.0
D)36
Q33. Suppose module_a.py contains:

print("Module loaded")

value = 10

And another file contains:

import module_a
import module_a

print(module_a.value)

Assuming both imports occur in the same Python process, what is normally printed?
A)ImportError
B)Module loaded
Module loaded
10
C)10
10
D)Module loaded
10
Q34. What is the output?

f = lambda x: x + 5

print(f(10))
A>Error
B)10
C)5
D)15
Q35. What is the output?

```



D)A
B
C
D
10

Q40. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(
    map(
        lambda x: x * 2,
        filter(lambda x: x % 2 == 0,
            numbers)
    )
)
```

```
print(result)
```

A)[2, 4]
B)[1, 3, 5]
C)[2, 4, 6, 8, 10]
D)[4, 8]

Q41. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A)sqrt(25)
B)5.0
C)5
D)25

Q42. What is the output?

```
def outer():
    x = 10
```

```
    def inner():
        nonlocal x
        x = x + 5
        return x
```

```
    inner()
    return x
```

```
print(outer())
```

A)15
B)UnboundLocalError
C)10

D)5

Q43. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

A)Python automatically renames the local file
B)The local file can shadow the intended standard-library module
C)random cannot be imported
D)Python will always reject it

Q44. What is the output?

```
def fun(a=10, b=20):
    return a - b
```

```
print(fun(30))
```

A)10
B)-10
C)20
D)30

Q45. What will be printed?

```
x = 10
```

```
def outer():
    x = 20
```

```
    def inner():
        print(x)
```

```
    x = 30
    inner()
```

```
outer()
```

A)NameError
B)20
C)30
D)10

Q46. What will be the output?

```
def fun(x):
    try:
        if x < 0:
            raise ValueError("negative")
        return x
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
def fun(x):
    if x == 0:
        return
    return x + fun(x - 1)
```

print(fun(3))

- A)3
- B)None
- C)5
- D)6

Q2. What will normally happen?

```
import math
import math
```

- A)The module is normally loaded and executed twice
- B)ImportError
- C)SyntaxError
- D)The module is normally loaded once and reused

Q3. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

- A)Nothing
- B)A and B
- C)A
- D)B

Q4. What is the output?

```
def outer():
    x = 10
```

```
def inner():
    return x + 5

return inner
```

```
f = outer()
```

print(f())

- A)10
- B)NameError
- C)None
- D)15

Q5. What will happen?

```
def fun(n):
    if n == 0:
        return 1
    return n * fun(n)
```

print(fun(3))

- A)TypeError
- B)RecursionError
- C)3
- D)6

Q6. What is the output?

```
def fun(a=10, b=20):
    return a - b
```

print(fun(30))

- A)10
- B)30
- C)-10
- D)20

Q7. What happens when this code executes?

```
def fun():
    print(variable)
    variable = 50
```

variable = 10



A)Exception
Age is too low
B)Nothing, because custom exceptions cannot be caught
C)InvalidAgeError
Age is too low
D)InvalidAgeError
15

Q15. What will be the output?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()  
    print(x)
```

```
outer()  
print(x)
```

A)30
20
B)20
10
C)20
30
D)30
30

Q16. What is the output?

```
try:  
    print(10 / 0)  
except Exception:  
    print("A")  
except ZeroDivisionError:  
    print("B")
```

A)A
B)A B
C)SyntaxError
D)B

Q17. Which object keeps track of modules that have already been imported during the current Python process?

A)sys.path
B).__module__
C)sys.imports
D)sys.modules

Q18. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A)sqrt(25)
B)25
C)5
D)5.0

Q19. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():  
    raise MyError("Something went wrong")
```

```
try:  
    test()  
except MyError as e:  
    print(type(e).__name__)
```

A)Something went wrong
B)Exception
C)MyError
D)TypeError

Q20. What will be printed?

```
def make_counter():  
    count = 0
```

```
    def counter():  
        nonlocal count  
        count += 1  
        return count
```

```
    return counter
```

```
a = make_counter()  
b = make_counter()
```

```
print(a())  
print(a())  
print(b())
```



Q27. What will be the output?

```
def fun(x):  
    try:  
        if x < 0:  
            raise ValueError("negative")  
        return x  
    except ValueError:  
        return 100  
    finally:  
        print("cleanup")
```

print(fun(-5))

- A)negative
cleanup
- B)cleanup
100
- C)cleanup
-5
- D)100
cleanup

Q28. What will be printed?

x = 10

f = lambda: x

x = 20

print(f())

- A)None
- B)NameError
- C)20
- D)10

Q29. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

fun()

- A)A B
- B)A
- C)Nothing
- D)B

**Q30. if test.py has
print("A")**

```
if __name__ == "__main__":  
    print("B")
```

**If test.py is executed directly, what
will be printed?**

- A)A followed by B
- B)B
- C)A
- D)Nothing

Q31. What happens here?

```
def fun(a):  
    return a
```

print(fun())

- A)NameError
- B)TypeError
- C)0
- D)None

Q32. What will be printed?

```
try:  
    print(10 / 0)  
except ZeroDivisionError:  
    print("A")  
except Exception:  
    print("B")
```

- A)Nothing
- B)B
- C)A
- D)A B

**Q33. What is the major difference
between the following?**

import math

and

from math import sqrt

- A)There is no difference
- B)First imports only sqrt
- C)First provides the module namespace;
second imports sqrt directly
- D)Both import only sqrt

Q34. What will be printed?

```
try:  
    x = int("10")
```



```
print(a)
```

```
print(b)
```

A)Error

B)[10]

[10]

C)[10, 10]

[10]

D)[10]

[10, 10]

Q40. What is the output?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        nonlocal x
```

```
        x = x + 5
```

```
        return x
```

```
    inner()
```

```
    return x
```

```
print(outer())
```

A)UnboundLocalError

B)10

C)5

D)15

Q41. Suppose sample.py contains:

```
x = 10
```

```
def display():
```

```
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)
```

```
sample.display()
```

A)x

display

B>Error

C)10

Hello

D)Only Hello

Q42. What will be the output?

```
x = 10
```

```
def fun():
```

```
    print(x)
```

```
    x = 20
```

```
fun()
```

A)20

B)NameError

C)10

D)UnboundLocalError

Q43. What happens?

```
def fun(a, b):
```

```
    return a + b
```

```
print(fun(10, a=20))
```

A)30

B)20

C)TypeError

D)SyntaxError

Q44. What will happen?

```
def fun(a, b=10):
```

```
    return a + b
```

```
print(fun(b=5, a=20))
```

A)TypeError

B)SyntaxError

C)25

D)15

Q45. What will be printed?

```
def fun():
```

```
    try:
```

```
        return 10
```

```
    finally:
```

```
        print("Finally")
```

```
print(fun())
```

A)Finally only

B)10 only

C)10 followed by Finally

D)Finally followed by 10

Q46. What is the output?



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What will be printed?

```
def fun(x=[]):
    x.append(10)
    return x
```

```
a = fun()
b = fun()
```

```
print(a)
print(b)
```

- A)Error
- B)[10]
- [10]
- C)[10]
- [10, 10]
- D)[10, 10]
- [10]

Q2. What happens here?

```
class MyError(Exception):
    pass
```

```
def test():
    raise MyError("Something went wrong")
```

```
try:
    test()
except MyError as e:
    print(type(e).__name__)
```

- A)TypeError
- B)Something went wrong
- C)MyError
- D)Exception

Q3. What will happen?

```
def outer():
    x = 10
```

```
    def inner():
        nonlocal y
```

y = 20

```
    inner()
```

```
outer()
```

- A)10
- B)NameError
- C)SyntaxError
- D)20

Q4. What will normally happen?

```
import math
import math
```

- A)SyntaxError
- B)ImportError
- C)The module is normally loaded and executed twice
- D)The module is normally loaded once and reused

Q5. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

- A)B
- B)A, and execution ends normally
- C)A, followed by propagation of the same exception
- D)No Output

Q6. What happens when this function is called?

```
def fun(a=10, b):
    return a + b
```

- A)NameError
- B)It executes correctly
- C)TypeError
- D)SyntaxError

Q7. What does the following function return?



Q13. What is the output?

```
try:
    x = int("abc")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

- A)B
- B)A C
- C)A
- D)B C

Q14. What is the output?

```
def fun(a=10, b=20):
    return a - b
```

```
print(fun(30))
```

- A)10
- B)-10
- C)30
- D)20

Q15. What is the purpose of this statement?

```
if __name__ == "__main__":
```

- A)It prevents all imports
- B)It prevents syntax errors
- C)It identifies code intended to run when the file is executed directly
- D)It creates the main function

Q16. What will be the output?

```
x = 10
```

```
def fun():
    print(x)
    x = 20
```

```
fun()
```

- A)10
- B)UnboundLocalError
- C)NameError
- D)20

Q17. What happens when this code executes?

```
def fun():
    print(variable)
    variable = 50
```

```
variable = 10
```

```
fun()
```

- A)10
- B)NameError
- C)50
- D)UnboundLocalError

Q18. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(
    map(
        lambda x: x * 2,
        filter(lambda x: x % 2 == 0,
            numbers)
    )
)
```

```
print(result)
```

- A)[2, 4]
- B)[1, 3, 5]
- C)[2, 4, 6, 8, 10]
- D)[4, 8]

Q19. What happens here?

```
try:
    raise ValueError("Wrong value")
except ValueError as e:
    print(e)
```

- A)e
- B)Nothing
- C)Wrong Value
- D)ValueError

Q20. if test.py has print("A")

```
if __name__ == "__main__":
    print("B")
```

If test.py is executed directly, what will be printed?

- A)A
- B)B
- C)A followed by B



```
nonlocal x
```

```
x = x + 5
```

```
return x
```

```
inner()
```

```
return x
```

```
print(outer())
```

A)5

B)10

C)15

D)UnboundLocalError

Q27. What is the output?

```
def fun(x):
```

```
    return x * 2
```

```
a = fun
```

```
print(a(5))
```

A)func(5)

B)5

C>Error

D)10

Q28. What happens when this code runs?

```
def first():
```

```
    second()
```

```
def second():
```

```
    third()
```

```
def third():
```

```
    raise RuntimeError("Failure")
```

```
try:
```

```
    first()
```

```
except RuntimeError:
```

```
    print("Handled")
```

A)RuntimeError cannot propagate through functions

B)TypeError

C)Handled

D)NameError

Q29. What is the output?

```
def outer():
```

```
    x = 10
```

```
def inner():
```

```
    return x + 5
```

```
return inner
```

```
f = outer()
```

```
print(f())
```

A)NameError

B)15

C)None

D)10

Q30. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(
```

```
    lambda a, b: a * b,
```

```
    numbers
```

```
)
```

```
print(result)
```

A)10

B)9

C)0

D)24

Q31. What is the output?

```
try:
```

```
    print(10 / 0)
```

```
except Exception:
```

```
    print("A")
```

```
except ZeroDivisionError:
```

```
    print("B")
```

A)A B

B)SyntaxError

C)A

D)B

Q32. What happens here?

```
def fun(a):
```

```
    return a
```

```
print(fun())
```

A)None

B)0



Q40. Suppose sample.py contains:

```
x = 10
```

```
def display():  
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)  
sample.display()
```

A)10

Hello

B)x

display

C)Only Hello

D>Error

Q41. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

```
print(fun(3))
```

A)3

B)RecursionError

C)TypeError

D)6

Q42. Why is

try:

```
    print(10 / 0)
```

except Exception:

```
    print("A")
```

except ZeroDivisionError:

```
    print("B")
```

codes's second handler never reached?

A)ZeroDivisionError occurs before Exception

B)except blocks execute randomly

C)Exception is a superclass of ZeroDivisionError

D)ZeroDivisionError is not an exception

Q43. What is the output?

```
def fun(x):
```

```
    if x == 0:
```

```
        return
```

```
    return x + fun(x - 1)
```

```
print(fun(3))
```

A)6

B)None

C)3

D)5

Q44. What will be printed?

```
def fun():
```

```
    print("A")
```

```
    return
```

```
    print("B")
```

```
fun()
```

A)Nothing

B)B

C)A B

D)A

Q45. What will be printed?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        print(x)
```

```
    x = 30
```

```
    inner()
```

```
outer()
```

A)NameError

B)20

C)30

D)10

Q46. What will be printed?

```
try:
```

```
    print(10 / 0)
```

```
except ZeroDivisionError:
```

```
    print("A")
```

```
except Exception:
```

```
    print("B")
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
try:
    x = int("abc")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

- A)B C
- B)A
- C)A C
- D)B

Q2. What will happen?

```
def fun(n):
    if n == 0:
        return 1
    return n * fun(n)
```

```
print(fun(3))
```

- A)6
- B)3
- C)TypeError
- D)RecursionError

Q3. What happens when this code runs?

```
def first():
    second()
```

```
def second():
    third()
```

```
def third():
    raise RuntimeError("Failure")
```

```
try:
    first()
except RuntimeError:
    print("Handled")
```

- A)Handled
- B)RuntimeError cannot propagate through functions
- C)NameError
- D)TypeError

Q4. What will be printed?

```
x = 10
```

```
def outer():
    x = 20
```

```
    def inner():
        print(x)
```

```
    x = 30
    inner()
```

```
outer()
```

- A)20
- B)NameError
- C)30
- D)10

Q5. What will be printed?

```
def fun():
    try:
        return 10
    finally:
        print("Finally")
```

```
print(fun())
```

- A)Finally only
- B)10 only
- C)Finally followed by 10
- D)10 followed by Finally

Q6. What will be printed?

```
try:
    x = int("10")
except ValueError:
    print("A")
```



D)15

Q13. What happens here?

```
def fun(a):  
    return a
```

```
print(fun())
```

A)None

B)NameError

C)0

D)TypeError

Q14. What is the output?

```
def fun():  
    try:  
        print("A")  
        raise ValueError  
    except ValueError:  
        print("B")  
        return 10  
    else:  
        print("C")  
        return 20  
    finally:  
        print("D")
```

```
print(fun())
```

A)A

C

D

20

B)A

B

10

D

C)A

B

D

10

D)A

B

C

D

10

Q15. What will happen?

```
def outer():
```

x = 10

```
def inner():  
    nonlocal y  
    y = 20
```

```
inner()
```

```
outer()
```

A)SyntaxError

B)10

C)20

D)NameError

Q16. What happens?

```
def fun(a, b):  
    return a + b
```

```
print(fun(10, a=20))
```

A)30

B)TypeError

C)SyntaxError

D)20

Q17. What is the output?

```
def fun(x):  
    return x * 2
```

```
a = fun  
print(a(5))
```

A>Error

B)func(5)

C)10

D)5

Q18. What will be printed?

```
class InvalidAgeError(Exception):  
    pass
```

```
def check_age(age):  
    if age < 18:  
        raise InvalidAgeError("Age is  
too low")  
    return "Allowed"
```

```
try:
```



B)3

C)None

D)6

Q26. What will be the output?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        global x
```

```
        x = 30
```

```
    inner()
```

```
    print(x)
```

```
outer()
```

```
print(x)
```

A)20

10

B)20

30

C)30

30

D)30

20

Q27. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```

```
print(f())
```

A)NameError

B)10

C)20

D)None

Q28. What is the output?

```
try:
```

```
    print(10 / 0)
```

```
except Exception:
```

```
    print("A")
```

```
except ZeroDivisionError:
```

```
    print("B")
```

A)A

B)A B

C)SyntaxError

D)B

Q29. What happens when this code executes?

```
def fun():
```

```
    print(variable)
```

```
    variable = 50
```

```
variable = 10
```

```
fun()
```

A)10

B)NameError

C)UnboundLocalError

D)50

Q30. What will be printed?

```
def fun(a, b):
```

```
    return a + b
```

```
print(fun(10, b=20))
```

A)TypeError

B)SyntaxError

C)30

D)20

Q31. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
```

```
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)B

B)A

C)Nothing

D)A and B

Q32. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(
```



x = 10

```
def inner():  
    nonlocal x  
    x = x + 5  
    return x
```

```
inner()  
return x
```

print(outer())

- A)5
- B)10
- C)15
- D)UnboundLocalError

Q41. What will be the output?

import math

print(math.sqrt(25))

- A)5
- B)sqrt(25)
- C)5.0
- D)25

Q42. What is the output?

```
def fun():  
    try:  
        return 10  
    finally:  
        return 20
```

print(fun())

- A)20
- B)10
- C)None
- D)RuntimeError

**Q43. if test.py has
print("A")**

```
if __name__ == "__main__":  
    print("B")
```

**If test.py is executed directly, what
will be printed?**

- A)Nothing
- B)A followed by B
- C)B
- D)A

Q44. What will be the output?

```
def fun(x):  
    try:  
        if x < 0:  
            raise ValueError("negative")  
        return x  
    except ValueError:  
        return 100  
    finally:  
        print("cleanup")
```

print(fun(-5))

- A)cleanup
100
- B)100
cleanup
- C)cleanup
-5
- D)negative
cleanup

Q45. What will be printed?

```
def make_counter():  
    count = 0  
  
    def counter():  
        nonlocal count  
        count += 1  
        return count
```

return counter

```
a = make_counter()  
b = make_counter()
```

```
print(a())  
print(a())  
print(b())  
print(a())
```

- A)1
2
3
4
- B)1
1
1



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What will be printed?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        print(x)
```

```
    x = 30
```

```
    inner()
```

```
outer()
```

```
A)20
```

```
B)10
```

```
C)30
```

```
D)NameError
```

Q2. What does the following function return?

```
def fun():
```

```
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

```
A>Error
```

```
B>Hello None
```

```
C)None
```

```
D>Hello
```

Q3. What will be the output?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        global x
```

```
        x = 30
```

```
inner()
```

```
print(x)
```

```
outer()
```

```
print(x)
```

```
A)30
```

```
30
```

```
B)20
```

```
10
```

```
C)20
```

```
30
```

```
D)30
```

```
20
```

Q4. What is the output?

```
try:
```

```
    x = int("abc")
```

```
except ValueError:
```

```
    print("A")
```

```
else:
```

```
    print("B")
```

```
finally:
```

```
    print("C")
```

```
A)B
```

```
B)A
```

```
C)A C
```

```
D)B C
```

Q5. Which object keeps track of modules that have already been imported during the current Python process?

```
A)__module__
```

```
B)sys.imports
```

```
C)sys.modules
```

```
D)sys.path
```

Q6. What happens here?

```
class MyError(Exception):
```

```
    pass
```

```
def test():
```

```
    raise MyError("Something went
```



D

Q13. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

fun()

A)A B

B)B

C)A

D)Nothing

Q14. Why is

try:

```
    print(10 / 0)
```

except Exception:

```
    print("A")
```

except ZeroDivisionError:

```
    print("B")
```

codes's second handler never reached?

A)Exception is a superclass of ZeroDivisionError

B)ZeroDivisionError occurs before Exception

C)ZeroDivisionError is not an exception

D)except blocks execute randomly

Q15. if test.py has

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If test.py is executed directly, what will be printed?

A)Nothing

B)A followed by B

C)B

D)A

Q16. What is the output?

```
def fun(x):  
    if x == 0:  
        return  
    return x + fun(x - 1)
```

print(fun(3))

A)3

B)None

C)5

D)6

Q17. What will be printed?

```
def fun(x=[]):  
    x.append(10)  
    return x
```

a = fun()

b = fun()

print(a)

print(b)

A)[10]

[10, 10]

B)[10]

[10]

C)Error

D)[10, 10]

[10]

Q18. What is the output?

def outer():

```
    x = 10
```

def inner():

```
    nonlocal x
```

```
    x = x + 5
```

```
    return x
```

inner()

```
    return x
```

print(outer())

A)5

B)UnboundLocalError

C)15

D)10

Q19. What happens when this function is called?

def fun(a=10, b):

```
    return a + b
```

A)NameError

B)SyntaxError

C)TypeError

D)It executes correctly



C)20

D)NameError

Q27. What will be printed?

try:

```
    print(10 / 0)
```

except ZeroDivisionError:

```
    print("A")
```

except Exception:

```
    print("B")
```

A)A

B)A B

C)Nothing

D)B

Q28. What will happen?

```
def fun(n):
```

```
    if n == 0:
```

```
        return 1
```

```
    return n * fun(n)
```

```
print(fun(3))
```

A)TypeError

B)6

C)3

D)RecursionError

Q29. What happens here?

try:

```
    raise ValueError("Wrong value")
```

except ValueError as e:

```
    print(e)
```

A)Wrong Value

B)ValueError

C)e

D)Nothing

Q30. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A)sqrt(25)

B)5.0

C)5

D)25

Q31. What will be printed?

try:

```
x = int("10")
```

except ValueError:

```
    print("A")
```

else:

```
    print("B")
```

finally:

```
    print("C")
```

A)A

B)B C

C)A C

D)B

Q32. What will be printed?

```
def fun():
```

```
    try:
```

```
        return 10
```

```
    finally:
```

```
        print("Finally")
```

```
print(fun())
```

A)Finally followed by 10

B)10 followed by Finally

C)10 only

D)Finally only

Q33. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(
```

```
    lambda a, b: a * b,
```

```
    numbers
```

```
)
```

```
print(result)
```

A)0

B)10

C)9

D)24

Q34. What is the output?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        return x + 5
```



D)5 5

Q41. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```

```
print(f())
```

- A)None
- B)NameError
- C)10
- D)20

Q42. What will be printed?

```
def fun(a, b):  
    return a + b
```

```
print(fun(10, b=20))
```

- A)SyntaxError
- B)30
- C)TypeError
- D)20

Q43. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```

```
fun()
```

- A)UnboundLocalError
- B)NameError
- C)50
- D)10

Q44. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

- A)First imports only sqrt
- B)Both import only sqrt

C)First provides the module namespace;
second imports sqrt directly

D)There is no difference

Q45. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

- A)Nothing
- B)A and B
- C)B
- D)A

Q46. What is the output?

```
try:  
    print(10 / 0)  
except Exception:  
    print("A")  
except ZeroDivisionError:  
    print("B")
```

- A)SyntaxError
- B)A
- C)B
- D)A B

Q47. What will be the output?

```
def fun(x):  
    try:  
        if x < 0:  
            raise ValueError("negative")  
        return x  
    except ValueError:  
        return 100  
    finally:  
        print("cleanup")
```

```
print(fun(-5))
```

- A)negative
cleanup
- B)100
cleanup



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What happens when this code runs?

```
def first():
    second()

def second():
    third()

def third():
    raise RuntimeError("Failure")
```

```
try:
    first()
except RuntimeError:
    print("Handled")
```

A)Handled
B)NameError
C)RuntimeError cannot propagate through functions
D)TypeError

Q2. What is the output?

```
try:
    x = int("abc")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

A)A
B)B
C)A C
D)B C

Q3. What is the output?

```
def outer():
    x = 10

    def inner():
        return x + 5
```

return inner

```
f = outer()
print(f())
```

A)15
B)NameError
C)10
D)None

Q4. What does the following function return?

```
def fun():
    print("Hello")
```

```
x = fun()

print(x)
```

A)Hello
B>Error
C)Hello None
D)None

Q5. What will happen?

```
def fun(a, b=10):
    return a + b
```

```
print(fun(b=5, a=20))
```

A)TypeError
B)15
C)SyntaxError
D)25

Q6. What will be printed?

```
try:
    print(10 / 0)
except ZeroDivisionError:
    print("A")
except Exception:
    print("B")
```

A)Nothing
B)A



D)B

Q12. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a  
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

A) ImportError

B) 10

10

C) Module loaded

Module loaded

10

D) Module loaded

10

Q13. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```

```
fun()
```

A) 10

B) UnboundLocalError

C) 50

D) NameError

Q14. Suppose sample.py contains:

```
x = 10
```

```
def display():  
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)  
sample.display()
```

A) Only Hello

B) Error

C) x

display

D) 10

Hello

Q15. What happens here?

```
try:
```

```
    raise ValueError("Wrong value")
```

```
except ValueError as e:
```

```
    print(e)
```

A) Nothing

B) Wrong Value

C) e

D) ValueError

Q16. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A) 5

B) 5.0

C) sqrt(25)

D) 25

Q17. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

A) There is no difference

B) First imports only sqrt

C) Both import only sqrt

D) First provides the module namespace; second imports sqrt directly

Q18. What is the output?

```
def fun(x):
```

```
    if x == 0:
```

```
        return
```

```
    return x + fun(x - 1)
```



```
try:
    test()
except MyError as e:
    print(type(e).__name__)
```

- A)TypeError
- B)Something went wrong
- C)Exception
- D)MyError

Q27. What is the output?

```
def fun(a=10, b=20):
    return a - b
```

```
print(fun(30))
```

- A)30
- B)20
- C)-10
- D)10

Q28. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))
```

- A)10
- B>Error
- C)5
- D)15

Q29. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

- A)The local file can shadow the intended standard-library module
- B)random cannot be imported
- C)Python will always reject it
- D)Python automatically renames the local file

Q30. What will be printed?

```
def fun():
    try:
        return 10
    finally:
        print("Finally")
```

```
print(fun())
```

- A)10 followed by Finally
 - B)Finally followed by 10
 - C)10 only
 - D)Finally only
- Q31. What will be printed?**

```
def fun(x=[]):
    x.append(10)
    return x
```

```
a = fun()
b = fun()
```

```
print(a)
```

```
print(b)
```

- A)[10]
- [10]
- B)[10, 10]
- [10]
- C)[10]
- [10, 10]
- D>Error

Q32. What is the output?

```
def fun():
    try:
        print("A")
        raise ValueError
    except ValueError:
        print("B")
        return 10
    else:
        print("C")
        return 20
    finally:
        print("D")
```

```
print(fun())
```

- A)A
- B
- 10
- D
- B)A
- C
- D
- 20



Q39. What is the output?

```
def fun(x):  
    return x * 2
```

```
a = fun  
print(a(5))
```

- A)5
- B)Error
- C)10
- D)func(5)

Q40. What will be the output?

```
x = 10
```

```
def fun():  
    print(x)  
    x = 20
```

```
fun()
```

- A)NameError
- B)20
- C)UnboundLocalError
- D)10

Q41. What will be the output?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()  
    print(x)
```

```
outer()  
print(x)
```

- A)30
- 30
- B)30
- 20
- C)20
- 30
- D)20
- 10

Q42. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

```
fun()
```

- A)B
- B)A B
- C)A
- D)Nothing

Q43. What will be the output?

```
def fun(x):  
    try:  
        if x < 0:  
            raise ValueError("negative")  
        return x  
    except ValueError:  
        return 100  
    finally:  
        print("cleanup")
```

```
print(fun(-5))
```

- A)100
- cleanup
- B)cleanup
- 100
- C)cleanup
- 5
- D)negative
- cleanup

Q44. What happens when this function is called?

```
def fun(a=10, b):  
    return a + b
```

- A)TypeError
- B)NameError
- C)It executes correctly
- D)SyntaxError

Q45. Which object keeps track of modules that have already been imported during the current Python process?

- A)sys.path
- B)sys.imports



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
def fun():
    try:
        return 10
    finally:
        return 20
```

```
print(fun())
```

A)RuntimeError

B)10

C)20

D)None

Q2. What does the following function return?

```
def fun():
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A)Hello

B)None

C>Error

D>Hello None

Q3. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

A)There is no difference

B)First imports only sqrt

C)First provides the module namespace; second imports sqrt directly

D)Both import only sqrt

Q4. What will be printed?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        print(x)
```

```
    x = 30
```

```
    inner()
```

```
outer()
```

A)10

B)NameError

C)20

D)30

Q5. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

A)6

B)6.0

C)36

D)NameError

Q6. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
```

```
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

A)ImportError



```
def fun(a, b):  
    return a + b
```

```
print(fun(10, a=20))
```

- A)SyntaxError
- B)20
- C)TypeError
- D)30

Q14. Which object keeps track of modules that have already been imported during the current Python process?

- A)sys.imports
- B)sys.modules
- C)sys.path
- D).__module__

Q15. What will be printed?

```
def make_counter():  
    count = 0
```

```
    def counter():  
        nonlocal count  
        count += 1  
        return count
```

```
    return counter
```

```
a = make_counter()  
b = make_counter()
```

```
print(a())  
print(a())  
print(b())  
print(a())
```

- A)1
- 1
- 1
- 1
- B)0
- 1
- 0
- 2
- C)1
- 2
- 3
- 4

- D)1
- 2
- 1
- 3

Q16. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

- A)The local file can shadow the intended standard-library module
- B)Python automatically renames the local file
- C)random cannot be imported
- D)Python will always reject it

Q17. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```

```
print(f())
```

- A)20
- B)NameError
- C)None
- D)10

Q18. What is the output?

```
try:  
    x = int("abc")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:  
    print("C")
```

- A)A
- B)A C
- C)B C
- D)B

Q19. What will be printed?

```
def fun():  
    print("A")  
    return
```



```
def fun(a, b=10):  
    return a + b
```

```
print(fun(b=5, a=20))
```

- A)15
- B)SyntaxError
- C)TypeError
- D)25

Q26. What happens here?

```
def fun(a):  
    return a
```

```
print(fun())
```

- A)NameError
- B)0
- C)TypeError
- D)None

Q27. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))
```

- A)15
- B)10
- C>Error
- D)5

Q28. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

- A)Nothing
- B)B
- C)A and B
- D)A

Q29. What is the output?

```
def fun(x):  
    x += 10  
    return x
```

```
x = 5  
y = fun(x)
```

```
print(x, y)
```

- A)5 5
- B)5 15
- C)15 5
- D)15 15

Q30. What is the output?

```
def fun(a=10, b=20):  
    return a - b
```

```
print(fun(30))
```

- A)30
- B)10
- C)20
- D)-10

Q31. What will normally happen?

```
import math  
import math
```

- A)The module is normally loaded once and reused
- B)SyntaxError
- C)ImportError
- D)The module is normally loaded and executed twice

Q32. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(  
    lambda a, b: a * b,  
    numbers  
)
```

```
print(result)
```

- A)9
- B)24
- C)10
- D)0

Q33. What will be the output?

```
import math
```



C)3

D)5

Q40. What happens when this code runs?

```
def first():  
    second()
```

```
def second():  
    third()
```

```
def third():  
    raise RuntimeError("Failure")
```

```
try:  
    first()  
except RuntimeError:  
    print("Handled")
```

A)Handled

B)NameError

C)RuntimeError cannot propagate through functions

D)TypeError

Q41. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

```
print(fun(3))
```

A)TypeError

B)RecursionError

C)3

D)6

Q42. What is the output?

```
try:  
    print(10 / 0)  
except Exception:  
    print("A")  
except ZeroDivisionError:  
    print("B")
```

A)B

B)A

C)SyntaxError

D)A B

Q43. Suppose sample.py contains:

```
x = 10
```

```
def display():  
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)  
sample.display()
```

A)Only Hello

B)x

display

C)10

Hello

D>Error

Q44. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```

```
fun()
```

A)UnboundLocalError

B)10

C)NameError

D)50

Q45. What will be the output?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()  
    print(x)
```

```
outer()  
print(x)
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")
```

- A)A
- B)SyntaxError
- C)A B
- D)B

Q2. What will be printed?

```
try:
    print(10 / 0)
except ZeroDivisionError:
    print("A")
except Exception:
    print("B")
```

- A)A B
- B)A
- C)B
- D)Nothing

Q3. What will be the output?

```
x = 10

def outer():
    x = 20

    def inner():
        global x
        x = 30

    inner()
    print(x)
```

```
outer()
print(x)
A)20
10
```

- B)30
- 30
- C)30
- 20
- D)20
- 30

**Q4. if test.py has
print("A")**

```
if __name__ == "__main__":
    print("B")
```

**If test.py is executed directly, what
will be printed?**

- A)A followed by B
- B)Nothing
- C)B
- D)A

**Q5. What does the following
function return?**

```
def fun():
    print("Hello")
```

```
x = fun()
```

```
print(x)
A)Hello
B)None
C>Error
D>Hello None
```

Q6. What is the output?

```
def outer():
    x = 10

    def inner():
        return x + 5

    return inner
```

```
f = outer()
print(f())
```



- A)10 only
- B)Finally only
- C)10 followed by Finally
- D)Finally followed by 10

Q14. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(
    map(
        lambda x: x * 2,
        filter(lambda x: x % 2 == 0,
            numbers)
    )
)
```

```
print(result)
```

- A)[2, 4, 6, 8, 10]
- B)[1, 3, 5]
- C)[2, 4]
- D)[4, 8]

Q15. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)6.0
- B)36
- C)6
- D)NameError

Q16. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

- A)random cannot be imported
- B)Python will always reject it
- C)The local file can shadow the intended standard-library module
- D)Python automatically renames the local file

Q17. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(
    lambda a, b: a * b,
    numbers
)
```

```
print(result)
```

- A)0
- B)24
- C)10
- D)9

Q18. What will be the output?

```
def fun(x):
```

```
    try:
```

```
        if x < 0:
```

```
            raise ValueError("negative")
```

```
        return x
```

```
    except ValueError:
```

```
        return 100
```

```
    finally:
```

```
        print("cleanup")
```

```
print(fun(-5))
```

- A)cleanup
- 5
- B)100
- cleanup
- C)negative
- cleanup
- D)cleanup
- 100

Q19. What is the output?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        nonlocal x
```

```
        x = x + 5
```

```
        return x
```

```
    inner()
```

```
    return x
```

```
print(outer())
```

- A)5
- B)15
- C)UnboundLocalError



B)A

C

D

20

C)A

B

10

D

D)A

B

D

10

Q26. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

print(fun(3))

A)TypeError

B)3

C)6

D)RecursionError

Q27. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

variable = 10

fun()

A)10

B)NameError

C)50

D)UnboundLocalError

Q28. What is the output?

```
def fun(x):  
    return x * 2
```

a = fun

print(a(5))

A)10

B)5

C)func(5)

D>Error

Q29. Which object keeps track of modules that have already been imported during the current Python process?

A)sys.modules

B)sys.imports

C)sys.path

D).__module__

Q30. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():  
    raise MyError("Something went wrong")
```

```
try:  
    test()  
except MyError as e:  
    print(type(e).__name__)
```

A)TypeError

B)MyError

C)Exception

D)Something went wrong

Q31. What is the output?

```
def fun(x):  
    if x == 0:  
        return  
    return x + fun(x - 1)
```

print(fun(3))

A)3

B)6

C)5

D)None

Q32. What is the purpose of this statement?

```
if __name__ == "__main__":
```

A)It prevents all imports

B)It creates the main function

C)It prevents syntax errors

D)It identifies code intended to run when the file is executed directly

Q33. What will be printed?



D)[10]

[10]

Q40. What will be printed?

```
try:
    x = int("10")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

A)B

B)A

C)B C

D)A C

Q41. What will be printed?

```
def fun():
    print("A")
    return
    print("B")
```

fun()

A)Nothing

B)A B

C)A

D)B

Q42. What happens when this code runs?

```
def first():
    second()
```

```
def second():
    third()
```

```
def third():
    raise RuntimeError("Failure")
```

```
try:
    first()
except RuntimeError:
    print("Handled")
```

A)RuntimeError cannot propagate through functions

B)TypeError

C)Handled

D)NameError

Q43. What will be printed?

```
def make_counter():
    count = 0
```

```
    def counter():
        nonlocal count
        count += 1
        return count
```

```
    return counter
```

```
a = make_counter()
```

```
b = make_counter()
```

```
print(a())
```

```
print(a())
```

```
print(b())
```

```
print(a())
```

A)1

2

1

3

B)0

1

0

2

C)1

2

3

4

D)1

1

1

1

Q44. What happens when this function is called?

```
def fun(a=10, b):
    return a + b
```

A)TypeError

B)It executes correctly

C)NameError

D)SyntaxError

Q45. What is the output?

```
f = lambda x: x + 5
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What happens when this code runs?

```
def first():
    second()
```

```
def second():
    third()
```

```
def third():
    raise RuntimeError("Failure")
```

```
try:
    first()
except RuntimeError:
    print("Handled")
```

- A)NameError
- B)Handled
- C)TypeError
- D)RuntimeError cannot propagate through functions

Q2. What happens when this function is called?

```
def fun(a=10, b):
    return a + b
```

- A)TypeError
- B)It executes correctly
- C)NameError
- D)SyntaxError

Q3. Suppose sample.py contains:

```
x = 10
```

```
def display():
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)
```

```
sample.display()
```

- A)Error
- B)x
- display
- C)10
- Hello
- D)Only Hello

Q4. What will be printed?

```
def fun():
    try:
        return 10
    finally:
        print("Finally")
```

```
print(fun())
```

- A)10 followed by Finally
- B)Finally followed by 10
- C)Finally only
- D)10 only

Q5. What happens here?

```
try:
    raise ValueError("Wrong value")
except ValueError as e:
    print(e)
```

- A)Wrong Value
- B)e
- C)ValueError
- D)Nothing

Q6. What is the output?

```
def fun():
    try:
        print("A")
        raise ValueError
    except ValueError:
        print("B")
        return 10
    else:
        print("C")
        return 20
```



```
def inner():  
    print(x)
```

```
x = 30  
inner()
```

outer()

- A)10
- B)30
- C)20
- D)NameError

Q12. What happens here?

```
def fun(a):  
    return a
```

print(fun())

- A)NameError
- B)TypeError
- C)None
- D)0

Q13. What will be the output?

```
import math
```

print(math.sqrt(25))

- A)5.0
- B)sqrt(25)
- C)5
- D)25

Q14. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(  
    map(  
        lambda x: x * 2,  
        filter(lambda x: x % 2 == 0,  
            numbers)  
    )  
)
```

print(result)

- A)[2, 4]
- B)[2, 4, 6, 8, 10]
- C)[1, 3, 5]
- D)[4, 8]

Q15. What will be printed?

```
try:  
    print(10 / 0)  
except ZeroDivisionError:  
    print("A")  
except Exception:  
    print("B")
```

- A)Nothing
- B)B
- C)A B
- D)A

Q16. What is the output?

```
f = lambda x: x + 5
```

print(f(10))

- A)5
- B>Error
- C)10
- D)15

Q17. What is the output?

```
def outer():  
    x = 10
```

```
    def inner():  
        nonlocal x  
        x = x + 5  
        return x
```

```
    inner()  
    return x
```

print(outer())

- A)10
- B)UnboundLocalError
- C)15
- D)5

Q18. What will be printed?

```
def make_counter():  
    count = 0
```

```
    def counter():  
        nonlocal count  
        count += 1  
        return count
```



```
if __name__ == "__main__":
```

- A) It identifies code intended to run when the file is executed directly
- B) It prevents syntax errors
- C) It creates the main function
- D) It prevents all imports

Q25. What will be the output?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        global x
```

```
        x = 30
```

```
    inner()
```

```
    print(x)
```

```
outer()
```

```
print(x)
```

A) 20

30

B) 20

10

C) 30

30

D) 30

20

Q26. What is the output?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        return x + 5
```

```
    return inner
```

```
f = outer()
```

```
print(f())
```

A) None

B) 15

C) 10

D) NameError

Q27. What is the output?

```
try:
```

```
    raise ValueError
```

```
except ValueError:
```

```
    print("A")
```

```
    raise
```

A) B

B) No Output

C) A, and execution ends normally

D) A, followed by propagation of the same exception

Q28. What will be printed?

```
def fun(x=[]):
```

```
    x.append(10)
```

```
    return x
```

```
a = fun()
```

```
b = fun()
```

```
print(a)
```

```
print(b)
```

A) [10]

[10, 10]

B) Error

C) [10, 10]

[10]

D) [10]

[10]

Q29. What will be printed?

```
try:
```

```
    x = int("10")
```

```
except ValueError:
```

```
    print("A")
```

```
else:
```

```
    print("B")
```

```
finally:
```

```
    print("C")
```

A) A C

B) B C

C) B

D) A

Q30. What is the major difference between the following?

```
import math
```

```
and
```



A)SyntaxError

B)A B

C)B

D)A

Q38. What is the output?

```
def fun():  
    try:  
        return 10  
    finally:  
        return 20
```

print(fun())

A)10

B)20

C)None

D)RuntimeError

Q39. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)Nothing

B)A and B

C)A

D)B

Q40. What will happen?

```
def outer():  
    x = 10  
  
    def inner():  
        nonlocal x  
        x = 20  
  
    inner()
```

outer()

A)NameError

B)20

C)10

D)SyntaxError

Q41. What will normally happen?

```
import math
```

```
import math
```

A)The module is normally loaded once and reused

B)The module is normally loaded and executed twice

C)SyntaxError

D)ImportError

Q42. What happens here?

```
from math import sqrt
```

print(sqrt(36))

A)NameError

B)6

C)36

D)6.0

Q43. What will happen?

```
def fun(a, b=10):  
    return a + b
```

print(fun(b=5, a=20))

A)15

B)25

C)TypeError

D)SyntaxError

Q44. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

A)The local file can shadow the intended standard-library module

B)Python will always reject it

C)random cannot be imported

D)Python automatically renames the local file

Q45. What is the output?

```
def fun(x):  
    if x == 0:  
        return  
    return x + fun(x - 1)
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the purpose of this statement?

```
if __name__ == "__main__":
```

- A)It identifies code intended to run when the file is executed directly
- B)It creates the main function
- C)It prevents all imports
- D)It prevents syntax errors

Q2. What is the output?

```
def fun(a=10, b=20):
    return a - b
```

```
print(fun(30))
```

- A)-10
- B)30
- C)10
- D)20

Q3. What is the output?

```
try:
    x = int("abc")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

- A)A
- B)A C
- C)B C
- D)B

Q4. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

- A)First provides the module namespace; second imports sqrt directly
- B)First imports only sqrt
- C)Both import only sqrt
- D)There is no difference

Q5. What is the output?

```
def fun(x):
    x += 10
    return x
```

```
x = 5
y = fun(x)
```

```
print(x, y)
```

- A)5 5
- B)15 15
- C)5 15
- D)15 5

Q6. What will be the output?

```
x = 10
```

```
def fun():
    print(x)
    x = 20
```

```
fun()
```

- A)10
- B)NameError
- C)20
- D)UnboundLocalError

Q7. Which object keeps track of modules that have already been imported during the current Python process?

- A)sys.imports
- B)sys.modules
- C)__module__
- D)sys.path

Q8. What happens when this code runs?



Q14. What is the output?

```
def fun(x):  
    return x * 2
```

```
a = fun  
print(a(5))
```

- A)5
- B)Error
- C)func(5)
- D)10

Q15. Why is

try:

```
    print(10 / 0)
```

except Exception:

```
    print("A")
```

except ZeroDivisionError:

```
    print("B")
```

codes's second handler never reached?

- A)ZeroDivisionError occurs before Exception
- B)Exception is a superclass of ZeroDivisionError
- C)except blocks execute randomly
- D)ZeroDivisionError is not an exception

Q16. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

fun()

- A)A B
- B)Nothing
- C)A
- D)B

Q17. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```

```
fun()
```

- A)50

B)UnboundLocalError

C)10

D)NameError

Q18. What is the output?

```
def outer():  
    x = 10
```

```
    def inner():  
        return x + 5
```

```
    return inner
```

```
f = outer()
```

```
print(f())
```

- A)None
- B)NameError
- C)10
- D)15

Q19. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(  
    map(  
        lambda x: x * 2,  
        filter(lambda x: x % 2 == 0,  
            numbers)  
    )  
)
```

```
print(result)
```

- A)[1, 3, 5]
- B)[2, 4]
- C)[2, 4, 6, 8, 10]
- D)[4, 8]

Q20. What happens here?

```
def fun(a):  
    return a
```

```
print(fun())
```

- A)0
- B)NameError
- C)TypeError
- D)None

Q21. What will be printed?



```

    print("C")
    return 20
finally:
    print("D")

```

```
print(fun())
```

A)A

B

D

10

B)A

C

D

20

C)A

B

C

D

10

D)A

B

10

D

Q29. What happens when this function is called?

```

def fun(a=10, b):
    return a + b

```

A)It executes correctly

B)TypeError

C)SyntaxError

D)NameError

Q30. What happens here?

```

class MyError(Exception):
    pass

```

```

def test():
    raise MyError("Something went wrong")

```

```

try:
    test()
except MyError as e:
    print(type(e).__name__)

```

A)Exception

B)TypeError

C)MyError

D)Something went wrong

Q31. What will be printed?

```

def fun(a, b):
    return a + b

```

```
print(fun(10, b=20))
```

A)30

B)SyntaxError

C)TypeError

D)20

Q32. What will be printed?

```

def make_counter():
    count = 0

```

```

    def counter():
        nonlocal count
        count += 1
        return count

```

```
    return counter
```

```

a = make_counter()
b = make_counter()

```

```

print(a())
print(a())
print(b())
print(a())

```

A)0

1

0

2

B)1

1

1

1

C)1

2

3

4

D)1

2

1

3



```

    raise ValueError("negative")
    return x
except ValueError:
    return 100
finally:
    print("cleanup")

```

print(fun(-5))

- A)cleanup
- 100
- B)cleanup
- 5
- C)negative
- cleanup
- D)100
- cleanup

Q41. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

- A)Module loaded
- Module loaded
- 10
- B)10
- 10
- C)ImportError
- D)Module loaded
- 10

Q42. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

- A)The local file can shadow the intended standard-library module

B)Python automatically renames the local file

C)random cannot be imported

D)Python will always reject it

Q43. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)NameError
- B)36
- C)6.0
- D)6

Q44. What will be printed?

```
def fun(x=[]):
    x.append(10)
    return x
```

```
a = fun()
```

```
b = fun()
```

```
print(a)
```

```
print(b)
```

- A)[10]
- [10, 10]
- B)[10, 10]
- [10]
- C)[10]
- [10]
- D>Error

Q45. What will be printed?

```
def fun():
    try:
        return 10
    finally:
        print("Finally")
```

```
print(fun())
```

- A)Finally only
- B)10 followed by Finally
- C)10 only
- D)Finally followed by 10

Q46. What will be printed?

```
try:
    x = int("10")
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What happens when this code executes?

```
def fun():
    print(variable)
    variable = 50
```

```
variable = 10
```

```
fun()
```

A)NameError

B)10

C)50

D)UnboundLocalError

Q2. What is the purpose of this statement?

```
if __name__ == "__main__":
```

A)It creates the main function

B)It prevents all imports

C)It prevents syntax errors

D)It identifies code intended to run when the file is executed directly

Q3. What will be printed?

```
try:
```

```
    print(10 / 0)
```

```
except ZeroDivisionError:
```

```
    print("A")
```

```
except Exception:
```

```
    print("B")
```

A)A B

B)B

C)A

D)Nothing

Q4. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

A)6.0

B)6

C)36

D)NameError

Q5. What is the output?

```
def fun(x):
```

```
    if x == 0:
```

```
        return
```

```
    return x + fun(x - 1)
```

```
print(fun(3))
```

A)5

B)6

C)None

D)3

Q6. What will be the output?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        global x
```

```
        x = 30
```

```
    inner()
```

```
    print(x)
```

```
outer()
```

```
print(x)
```

A)20

10

B)30

20

C)30

30

D)20

30

Q7. What is the output?

```
def fun(a=10, b=20):
```

```
    return a - b
```



```
def fun():
    print("A")
    return
    print("B")
```

fun()

A)Nothing

B)A

C)B

D)A B

Q15. What will happen?

```
def fun(a, b=10):
    return a + b
```

```
print(fun(b=5, a=20))
```

A)25

B)15

C)SyntaxError

D)TypeError

Q16. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)B

B)Nothing

C)A and B

D)A

Q17. What is the output?

```
def fun(x):
    x += 10
    return x
```

```
x = 5
```

```
y = fun(x)
```

```
print(x, y)
```

A)5 15

B)5 5

C)15 15

D)15 5

Q18. What will normally happen?

```
import math
```

```
import math
```

A)The module is normally loaded and executed twice

B)The module is normally loaded once and reused

C)SyntaxError

D)ImportError

Q19. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
```

```
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

A)ImportError

B)10

10

C)Module loaded

Module loaded

10

D)Module loaded

10

Q20. What is the major difference between the following?

```
import math
```

and

```
from math import sqrt
```

A)First provides the module namespace; second imports sqrt directly

B)First imports only sqrt

C)There is no difference



A)1

1

1

1

B)1

2

1

3

C)0

1

0

2

D)1

2

3

4

Q27. What happens?

```
def fun(a, b):  
    return a + b
```

```
print(fun(10, a=20))
```

A)30

B)SyntaxError

C)TypeError

D)20

Q28. What is the output?

```
try:  
    print(10 / 0)  
except Exception:  
    print("A")  
except ZeroDivisionError:  
    print("B")
```

A)A

B)SyntaxError

C)A B

D)B

Q29. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))
```

A)15

B)5

C>Error

D)10

Q30. What happens when this code runs?

```
def first():  
    second()
```

```
def second():  
    third()
```

```
def third():  
    raise RuntimeError("Failure")
```

```
try:  
    first()  
except RuntimeError:  
    print("Handled")
```

A)Handled

B)RuntimeError cannot propagate through functions

C)NameError

D)TypeError

Q31. What is the output?

```
def fun(x):  
    return x * 2
```

```
a = fun  
print(a(5))
```

A>Error

B)10

C)5

D)func(5)

Q32. Why is

```
try:  
    print(10 / 0)  
except Exception:  
    print("A")  
except ZeroDivisionError:  
    print("B")  
codes's second handler never reached?
```

A)ZeroDivisionError occurs before Exception

B)except blocks execute randomly

C)ZeroDivisionError is not an exception

D)Exception is a superclass of ZeroDivisionError

C)x
display
D)Error

Q40. What does the following function return?

```
def fun():  
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A)None
B)Hello None
C)Error
D)Hello

Q41. What happens when this function is called?

```
def fun(a=10, b):  
    return a + b
```

A)SyntaxError
B)NameError
C)TypeError
D)It executes correctly

Q42. What is the output?

```
def fun():  
    try:  
        print("A")  
        raise ValueError  
    except ValueError:  
        print("B")  
        return 10  
    else:  
        print("C")  
        return 20  
    finally:  
        print("D")
```

```
print(fun())
```

A)A
B
C
D
10

B)A
B
D
10
C)A
C
D
20
D)A
B
10
D

Q43. What is the output?

```
try:  
    x = int("abc")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:  
    print("C")
```

A)A
B)B C
C)B
D)A C

Q44. What happens here?

```
try:  
    raise ValueError("Wrong value")  
except ValueError as e:  
    print(e)
```

A)ValueError
B)Nothing
C)Wrong Value
D)e

Q45. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():  
    raise MyError("Something went wrong")
```

```
try:  
    test()  
except MyError as e:
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

- A)Python automatically renames the local file
- B)random cannot be imported
- C)Python will always reject it
- D)The local file can shadow the intended standard-library module

Q2. What will be printed?

```
class InvalidAgeError(Exception):
    pass
```

```
def check_age(age):
    if age < 18:
        raise InvalidAgeError("Age is
too low")
    return "Allowed"
```

```
try:
    print(check_age(15))
except InvalidAgeError as e:
    print(type(e).__name__)
    print(e)
```

- A)InvalidAgeError
- 15
- B)InvalidAgeError
- Age is too low
- C)Nothing, because custom exceptions cannot be caught
- D)Exception
- Age is too low

Q3. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

- A)ImportError
- B)10
- 10
- C)Module loaded
- 10
- D)Module loaded
- Module loaded
- 10

Q4. What happens here?

```
class MyError(Exception):
    pass
```

```
def test():
    raise MyError("Something went
wrong")
```

```
try:
    test()
except MyError as e:
    print(type(e).__name__)
```

- A)MyError
- B)Exception
- C)Something went wrong
- D)TypeError

Q5. What will happen?

```
def fun(a, b=10):
    return a + b
```



```
result = reduce(
    lambda a, b: a * b,
    numbers
)
```

```
print(result)
```

A)24

B)0

C)9

D)10

Q13. What happens here?

```
def fun(a):
    return a
```

```
print(fun())
```

A)TypeError

B)None

C)0

D)NameError

Q14. What will be printed?

```
try:
    print(10 / 0)
except ZeroDivisionError:
    print("A")
except Exception:
    print("B")
```

A)A B

B)A

C)B

D)Nothing

Q15. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)B

B)A and B

C)Nothing

D)A

Q16. What will be the output?

```
x = 10
```

```
def outer():
    x = 20
```

```
def inner():
    global x
    x = 30
```

```
inner()
print(x)
```

```
outer()
print(x)
```

A)30

30

B)20

30

C)20

10

D)30

20

Q17. What is the output?

```
try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")
```

A)B

B)A B

C)A

D)SyntaxError

Q18. What happens when this code runs?

```
def first():
    second()
```

```
def second():
    third()
```

```
def third():
    raise RuntimeError("Failure")
```



C)[10, 10]

[10]

D)[10]

[10, 10]

Q24. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A)5

B)25

C)5.0

D)sqrt(25)

Q25. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))
```

A)5

B)10

C>Error

D)15

Q26. Why is

```
try:
```

```
    print(10 / 0)
```

```
except Exception:
```

```
    print("A")
```

```
except ZeroDivisionError:
```

```
    print("B")
```

codes's second handler never reached?

A)except blocks execute randomly

B)ZeroDivisionError occurs before Exception

C)ZeroDivisionError is not an exception

D)Exception is a superclass of ZeroDivisionError

Q27. What will be printed?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        print(x)
```

```
    x = 30
```

```
inner()
```

```
outer()
```

A)30

B)10

C)NameError

D)20

Q28. What is the output?

```
def fun():
```

```
    try:
```

```
        print("A")
```

```
        raise ValueError
```

```
    except ValueError:
```

```
        print("B")
```

```
        return 10
```

```
    else:
```

```
        print("C")
```

```
        return 20
```

```
    finally:
```

```
        print("D")
```

```
print(fun())
```

A)A

B

C

D

10

B)A

C

D

20

C)A

B

10

D

D)A

B

D

10

Q29. What is the output?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        return x + 5
```



print(fun(3))

- A)None
- B)6
- C)3
- D)5

Q37. What is the output?

```
def fun(x):  
    return x * 2
```

```
a = fun  
print(a(5))
```

- A)Error
- B)10
- C)func(5)
- D)5

Q38. What will happen?

```
def outer():  
    x = 10  
  
    def inner():  
        nonlocal y  
        y = 20
```

```
    inner()
```

```
outer()  
A)NameError  
B)SyntaxError  
C)20  
D)10
```

Q39. What is the output?

```
def fun(a=10, b=20):  
    return a - b
```

```
print(fun(30))  
A)20  
B)30  
C)10  
D)-10
```

Q40. What is the purpose of this statement?

```
if __name__ == "__main__":  
A)It prevents syntax errors
```

- B)It creates the main function
- C)It identifies code intended to run when the file is executed directly
- D)It prevents all imports

Q41. What happens here?

```
try:  
    raise ValueError("Wrong value")  
except ValueError as e:  
    print(e)
```

- A)ValueError
- B)Nothing
- C)Wrong Value
- D)e

Q42. What happens when this function is called?

```
def fun(a=10, b):  
    return a + b
```

- A)SyntaxError
- B)It executes correctly
- C)NameError
- D)TypeError

Q43. What will be printed?

```
try:  
    x = int("10")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:  
    print("C")
```

- A)B C
- B)B
- C)A C
- D)A

Q44. What is the output?

```
def fun(x):  
    x += 10  
    return x
```

```
x = 5  
y = fun(x)
```

```
print(x, y)  
A)15 5
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
def fun():
    try:
        return 10
    finally:
        return 20
```

```
print(fun())
```

- A)20
- B)None
- C)RuntimeError
- D)10

**Q2. if test.py has
print("A")**

```
if __name__ == "__main__":
    print("B")
```

**If test.py is executed directly, what
will be printed?**

- A)B
- B)A followed by B
- C)Nothing
- D)A

Q3. What is the output?

```
def fun(x):
    x += 10
    return x
```

```
x = 5
y = fun(x)
```

```
print(x, y)
```

- A)15 5
- B)5 5
- C)15 15
- D)5 15

**Q4. What happens when this
function is called?**

```
def fun(a=10, b):
```

```
    return a + b
```

- A)SyntaxError
- B)NameError
- C)TypeError
- D)It executes correctly

Q5. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

- A)No Output
- B)A, followed by propagation of the same exception
- C)B
- D)A, and execution ends normally

Q6. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)36
- B)6
- C)6.0
- D)NameError

**Q7. What is the purpose of this
statement?**

```
if __name__ == "__main__":
```

- A)It prevents all imports
- B)It creates the main function
- C)It identifies code intended to run when the file is executed directly
- D)It prevents syntax errors

**Q8. What is the major difference
between the following?**

```
import math
```

```
and
```



```

if x < 0:
    raise ValueError("negative")
return x
except ValueError:
    return 100
finally:
    print("cleanup")

```

print(fun(-5))

- A)cleanup
- 100
- B)negative
- cleanup
- C)100
- cleanup
- D)cleanup
- 5

Q16. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(
    lambda a, b: a * b,
    numbers
)
```

print(result)

- A)24
- B)0
- C)10
- D)9

Q17. What is the output?

```
f = lambda x: x + 5
```

print(f(10))

- A)15
- B)5
- C)10
- D>Error

Q18. What will be printed?

```
try:
    x = int("10")
except ValueError:
    print("A")

```

```

else:
    print("B")
finally:
    print("C")

```

- A)B
- B)B C
- C)A
- D)A C

Q19. What will be printed?

```

try:
    print(10 / 0)
except ZeroDivisionError:
    print("A")
except Exception:
    print("B")

```

- A)A
- B)A B
- C)B
- D)Nothing

Q20. What will be printed?

```

def fun():
    try:
        return 10
    finally:
        print("Finally")

```

print(fun())

- A)Finally only
- B)10 only
- C)10 followed by Finally
- D)Finally followed by 10

Q21. What is the output?

```

try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")

```

- A)B
- B)SyntaxError
- C)A
- D)A B

Q22. What happens here?

```
def fun(a):
```



D)10

Q28. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():  
    raise MyError("Something went  
wrong")
```

```
try:  
    test()  
except MyError as e:  
    print(type(e).__name__)
```

- A)MyError
- B)Something went wrong
- C)Exception
- D)TypeError

Q29. What happens?

```
def fun(a, b):  
    return a + b
```

```
print(fun(10, a=20))
```

- A)SyntaxError
- B)30
- C)TypeError
- D)20

Q30. What will be printed?

```
def fun(x=[]):  
    x.append(10)  
    return x
```

```
a = fun()  
b = fun()
```

```
print(a)  
print(b)
```

- A)[10, 10]
- [10]
- B)[10]
- [10]
- C>Error
- D)[10]
- [10, 10]

Q31. What happens here?

try:

```
    raise ValueError("Wrong value")  
except ValueError as e:  
    print(e)
```

- A)Wrong Value
- B)e
- C)Nothing
- D)ValueError

Q32. What is the output?

```
def fun(a=10, b=20):  
    return a - b
```

```
print(fun(30))
```

- A)30
- B)10
- C)-10
- D)20

Q33. What is the output?

```
def fun(x):  
    if x == 0:  
        return  
    return x + fun(x - 1)
```

```
print(fun(3))
```

- A)3
- B)None
- C)5
- D)6

Q34. What will happen?

```
def fun(a, b=10):  
    return a + b
```

```
print(fun(b=5, a=20))
```

- A)SyntaxError
- B)TypeError
- C)15
- D)25

Q35. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```



print(a(5))

A)func(5)

B)5

C)10

D>Error

Q42. What will be printed?

```
def make_counter():
```

```
    count = 0
```

```
    def counter():
```

```
        nonlocal count
```

```
        count += 1
```

```
        return count
```

```
    return counter
```

```
a = make_counter()
```

```
b = make_counter()
```

```
print(a())
```

```
print(a())
```

```
print(b())
```

```
print(a())
```

A)1

2

3

4

B)1

1

1

1

C)1

2

1

3

D)0

1

0

2

Q43. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A)sqrt(25)

B)5.0

C)5

D)25

Q44. Which object keeps track of modules that have already been imported during the current Python process?

A)sys.modules

B)sys.imports

C).__module__

D)sys.path

Q45. What will be printed?

```
def fun(a, b):
```

```
    return a + b
```

```
print(fun(10, b=20))
```

A)30

B)20

C)TypeError

D)SyntaxError

Q46. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```

```
print(f())
```

A)None

B)NameError

C)20

D)10

Q47. What will be printed?

```
def fun():
```

```
    print("A")
```

```
    return
```

```
    print("B")
```

```
fun()
```

A)A

B)Nothing

C)A B

D)B

Q48. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the major difference between the following?

```
import math
```

and

```
from math import sqrt
```

A)First provides the module namespace; second imports sqrt directly

B)There is no difference

C)Both import only sqrt

D)First imports only sqrt

Q2. What will be the output?

```
x = 10
```

```
def fun():
    print(x)
    x = 20
```

```
fun()
```

A)20

B)UnboundLocalError

C)NameError

D)10

Q3. What will normally happen?

```
import math
```

```
import math
```

A)The module is normally loaded and executed twice

B)SyntaxError

C)ImportError

D)The module is normally loaded once and reused

Q4. What will be printed?

```
try:
    x = int("10")
except ValueError:
    print("A")
```

```
else:
    print("B")
finally:
    print("C")
```

A)B

B)A C

C)B C

D)A

Q5. What is the output?

```
def fun(x):
    if x == 0:
        return
    return x + fun(x - 1)
```

```
print(fun(3))
```

A)6

B)3

C)5

D)None

Q6. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)Nothing

B)A and B

C)B

D)A

Q7. What is the output?

```
def fun(x):
    return x * 2
```

```
a = fun
```



Q13. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)6.0
- B)NameError
- C)6
- D)36

Q14. What happens when this code runs?

```
def first():  
    second()
```

```
def second():  
    third()
```

```
def third():  
    raise RuntimeError("Failure")
```

```
try:  
    first()  
except RuntimeError:  
    print("Handled")
```

- A)Handled
- B)RuntimeError cannot propagate through functions
- C)TypeError
- D)NameError

Q15. What is the output?

```
try:  
    print(10 / 0)  
except Exception:  
    print("A")  
except ZeroDivisionError:  
    print("B")
```

- A)A
- B)A B
- C)B
- D)SyntaxError

Q16. What will be printed?

```
def fun(x=[]):  
    x.append(10)  
    return x
```

```
a = fun()  
b = fun()
```

```
print(a)  
print(b)  
A)[10, 10]  
[10]  
B)Error  
C)[10]  
[10, 10]  
D)[10]  
[10]
```

Q17. What will be the output?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()  
    print(x)
```

```
outer()  
print(x)
```

- A)30
- 20
- B)20
- 30
- C)30
- 30
- D)20
- 10

Q18. What is the output?

```
def outer():  
    x = 10
```

```
    def inner():  
        return x + 5
```

```
    return inner
```

```
f = outer()  
print(f())
```



print(x)

- A)Hello None
- B)None
- C)Hello
- D)Error

Q26. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(
    map(
        lambda x: x * 2,
        filter(lambda x: x % 2 == 0,
numbers)
    )
)
```

print(result)

- A)[4, 8]
- B)[1, 3, 5]
- C)[2, 4, 6, 8, 10]
- D)[2, 4]

Q27. Which object keeps track of modules that have already been imported during the current Python process?

- A)__module__
- B)sys.path
- C)sys.modules
- D)sys.imports

Q28. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

- A)B
- B)No Output
- C)A, followed by propagation of the same exception
- D)A, and execution ends normally

Q29. What will be printed?

```
x = 10
```

```
def outer():
```

```
x = 20
```

```
def inner():
    print(x)
```

```
x = 30
inner()
```

outer()

- A)NameError
- B)30
- C)20
- D)10

Q30. What happens when this function is called?

```
def fun(a=10, b):
    return a + b
```

- A)SyntaxError
- B)TypeError
- C)NameError
- D)It executes correctly

Q31. What will be printed?

```
class InvalidAgeError(Exception):
    pass
```

```
def check_age(age):
    if age < 18:
        raise InvalidAgeError("Age is
too low")
    return "Allowed"
```

```
try:
    print(check_age(15))
except InvalidAgeError as e:
    print(type(e).__name__)
    print(e)
```

- A)InvalidAgeError
- Age is too low
- B)InvalidAgeError
- 15
- C)Exception
- Age is too low
- D)Nothing, because custom exceptions cannot be caught



B)10

10

C)Module loaded

Module loaded

10

D)Module loaded

10

Q39. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

variable = 10

fun()

A)10

B)UnboundLocalError

C)50

D)NameError

Q40. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(  
    lambda a, b: a * b,  
    numbers  
)
```

```
print(result)
```

A)10

B)0

C)24

D)9

Q41. What will be printed?

```
def fun():  
    try:  
        return 10  
    finally:  
        print("Finally")
```

```
print(fun())
```

A)10 only

B)10 followed by Finally

C)Finally followed by 10

D)Finally only

Q42. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():  
    raise MyError("Something went  
wrong")
```

```
try:  
    test()  
except MyError as e:  
    print(type(e).__name__)
```

A)Something went wrong

B)MyError

C)TypeError

D)Exception

Q43. Why is

```
try:  
    print(10 / 0)  
except Exception:  
    print("A")  
except ZeroDivisionError:  
    print("B")  
codes's second handler never  
reached?
```

A)ZeroDivisionError occurs before
Exception

B)Exception is a superclass of
ZeroDivisionError

C)except blocks execute randomly

D)ZeroDivisionError is not an exception

Q44. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

```
print(fun(3))
```

A)TypeError

B)RecursionError

C)6

D)3

Q45. What is the output?

```
def fun(x):
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A)5

B)5.0

C)25

D)sqrt(25)

Q2. What will be printed?

```
def fun(x=[]):
    x.append(10)
    return x
```

```
a = fun()
```

```
b = fun()
```

```
print(a)
```

```
print(b)
```

A)[10]

[10]

B)[10, 10]

[10]

C)Error

D)[10]

[10, 10]

Q3. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(
    lambda a, b: a * b,
    numbers
)
```

```
print(result)
```

A)24

B)10

C)0

D)9

Q4. What will be printed?

```
def make_counter():
    count = 0
```

```
def counter():
    nonlocal count
    count += 1
    return count
```

```
return counter
```

```
a = make_counter()
```

```
b = make_counter()
```

```
print(a())
```

```
print(a())
```

```
print(b())
```

```
print(a())
```

A)1

1

1

1

B)1

2

1

3

C)1

2

3

4

D)0

1

0

2

Q5. What happens when this function is called?

```
def fun(a=10, b):
    return a + b
```

A)TypeError



```
print("A")
else:
    print("B")
finally:
    print("C")
```

- A)B C
- B)B
- C)A
- D)A C

Q14. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

- A)B
- B)A, and execution ends normally
- C)No Output
- D)A, followed by propagation of the same exception

Q15. What will be printed?

```
try:
    x = int("10")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

- A)B C
- B)A C
- C)B
- D)A

Q16. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)6.0
- B)36
- C)6
- D)NameError

Q17. What will be printed?

```
try:
    print(10 / 0)
```

```
except ZeroDivisionError:
    print("A")
except Exception:
    print("B")
```

- A)A
- B)A B
- C)Nothing
- D)B

Q18. if test.py has print("A")

```
if __name__ == "__main__":
    print("B")
```

If test.py is executed directly, what will be printed?

- A)A followed by B
- B)A
- C)B
- D)Nothing

Q19. What is the output?

```
def fun(x):
    x += 10
    return x
```

```
x = 5
y = fun(x)
```

```
print(x, y)
```

- A)15 15
- B)5 15
- C)15 5
- D)5 5

Q20. What will be the output?

```
x = 10
```

```
def outer():
    x = 20
```

```
    def inner():
        global x
        x = 30
```

```
    inner()
    print(x)
```

```
outer()
```



B)30

C)TypeError

D)SyntaxError

Q27. What will be the output?

```
x = 10
```

```
def fun():  
    print(x)  
    x = 20
```

```
fun()
```

A)20

B)NameError

C)10

D)UnboundLocalError

Q28. What is the output?

```
def outer():  
    x = 10
```

```
    def inner():  
        nonlocal x  
        x = x + 5  
        return x
```

```
    inner()  
    return x
```

```
print(outer())
```

A)5

B)15

C)10

D)UnboundLocalError

Q29. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

A)Python will always reject it

B)Python automatically renames the local file

C)The local file can shadow the intended standard-library module

D)random cannot be imported

Q30. What does the following function return?

```
def fun():  
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A)None

B>Error

C>Hello None

D>Hello

Q31. What will happen?

```
def outer():  
    x = 10
```

```
    def inner():  
        nonlocal y  
        y = 20
```

```
    inner()
```

```
outer()
```

A)SyntaxError

B)NameError

C)10

D)20

Q32. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

```
print(fun(3))
```

A)RecursionError

B)3

C)TypeError

D)6

Q33. What is the output?

```
def outer():  
    x = 10
```

```
    def inner():  
        return x + 5
```

```
    return inner
```



imported during the current Python process?

- A)sys.imports
- B)sys.modules
- C)__module__
- D)sys.path

Q40. What is the output?

```
def fun(a=10, b=20):  
    return a - b
```

```
print(fun(30))
```

- A)20
- B)-10
- C)30
- D)10

Q41. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

- A)B
- B)A
- C)Nothing
- D)A and B

Q42. What will normally happen?

```
import math
```

```
import math
```

- A)The module is normally loaded and executed twice
- B)ImportError
- C)The module is normally loaded once and reused
- D)SyntaxError

Q43. What will be printed?

```
def fun():  
    try:  
        return 10  
    finally:
```

```
print("Finally")
```

```
print(fun())
```

- A)10 followed by Finally
- B)10 only
- C)Finally followed by 10
- D)Finally only

Q44. Suppose sample.py contains:

```
x = 10
```

```
def display():  
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)  
sample.display()
```

- A)Only Hello
- B>Error
- C)x
- display
- D)10
- Hello

Q45. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a  
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

- A)10
- 10
- B)ImportError
- C)Module loaded
- Module loaded
- 10



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. Suppose sample.py contains:

```
x = 10
```

```
def display():
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)
sample.display()
```

A)10

Hello

B)x

display

C)Only Hello

D)Error

Q2. What will be printed?

```
def fun(a, b):
    return a + b
```

```
print(fun(10, b=20))
```

A)TypeError

B)20

C)30

D)SyntaxError

Q3. What will be printed?

```
try:
```

```
    x = int("10")
```

```
except ValueError:
```

```
    print("A")
```

```
else:
```

```
    print("B")
```

```
finally:
```

```
    print("C")
```

A)B

B)A C

C)B C

D)A

Q4. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)Nothing

B)A

C)B

D)A and B

Q5. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```

```
print(f())
```

A)20

B)NameError

C)None

D)10

Q6. What happens here?

```
try:
```

```
    raise ValueError("Wrong value")
```

```
except ValueError as e:
```

```
    print(e)
```

A)ValueError

B)Nothing

C)e

D)Wrong Value

Q7. Which object keeps track of modules that have already been



C)NameError

D)None

Q15. What does the following function return?

```
def fun():  
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A)Hello

B>Error

C)Hello None

D)None

Q16. What will be printed?

```
def make_counter():  
    count = 0
```

```
    def counter():  
        nonlocal count  
        count += 1  
        return count
```

```
    return counter
```

```
a = make_counter()
```

```
b = make_counter()
```

```
print(a())
```

```
print(a())
```

```
print(b())
```

```
print(a())
```

A)1

2

1

3

B)1

2

3

4

C)1

1

1

1

D)0

1

0

2

Q17. What happens?

```
def fun(a, b):  
    return a + b
```

```
print(fun(10, a=20))
```

A)20

B)30

C)TypeError

D)SyntaxError

Q18. Why is

try:

```
    print(10 / 0)
```

except Exception:

```
    print("A")
```

except ZeroDivisionError:

```
    print("B")
```

codes's second handler never reached?

A)except blocks execute randomly

B)ZeroDivisionError is not an exception

C)Exception is a superclass of ZeroDivisionError

D)ZeroDivisionError occurs before Exception

Q19. What is the output?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        return x + 5
```

```
    return inner
```

```
f = outer()
```

```
print(f())
```

A)None

B)15

C)10

D)NameError

Q20. What is the output?

```
def outer():
```

```
    x = 10
```



C)A
B
C
D
10
D)A
B
10
D

Q26. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

fun()

A)B
B)A B
C)Nothing
D)A

Q27. What happens when this function is called?

```
def fun(a=10, b):  
    return a + b
```

A)It executes correctly
B)TypeError
C)SyntaxError
D)NameError

Q28. What is the output?

```
def fun():  
    try:  
        return 10  
    finally:  
        return 20
```

print(fun())

A)RuntimeError
B)20
C)10
D)None

**Q29. if test.py has
print("A")**

```
if __name__ == "__main__":  
    print("B")
```

If test.py is executed directly, what will be printed?

A)B
B)Nothing
C)A
D)A followed by B

Q30. What is the output?

```
try:  
    x = int("abc")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:  
    print("C")
```

A)A C
B)A
C)B
D)B C

Q31. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(  
    lambda a, b: a * b,  
    numbers  
)
```

print(result)

A)9
B)10
C)24
D)0

Q32. What will be the output?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()
```



Q37. What will be printed?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        print(x)
```

```
    x = 30
```

```
    inner()
```

```
outer()
```

A)20

B)10

C)30

D)NameError

Q38. What is the output?

```
def fun(x):
```

```
    return x * 2
```

```
a = fun
```

```
print(a(5))
```

A)Error

B)10

C)func(5)

D)5

Q39. What is the output?

```
def fun(a=10, b=20):
```

```
    return a - b
```

```
print(fun(30))
```

A)30

B)10

C)20

D)-10

Q40. What is the output?

```
try:
```

```
    raise ValueError
```

```
except ValueError:
```

```
    print("A")
```

```
    raise
```

A)A, followed by propagation of the same exception

B)No Output

C)B

D)A, and execution ends normally

Q41. What is the output?

```
try:
```

```
    print(10 / 0)
```

```
except Exception:
```

```
    print("A")
```

```
except ZeroDivisionError:
```

```
    print("B")
```

A)A B

B)A

C)SyntaxError

D)B

Q42. What will happen?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        nonlocal y
```

```
        y = 20
```

```
    inner()
```

```
outer()
```

A)SyntaxError

B)20

C)NameError

D)10

Q43. What will happen?

```
def fun(n):
```

```
    if n == 0:
```

```
        return 1
```

```
    return n * fun(n)
```

```
print(fun(3))
```

A)3

B)TypeError

C)6

D)RecursionError

Q44. What will happen?

```
def fun(a, b=10):
```

```
    return a + b
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What will be printed?

```
x = 10
```

```
def outer():
    x = 20
```

```
    def inner():
        print(x)
```

```
    x = 30
    inner()
```

```
outer()
```

- A)30
- B)10
- C)NameError
- D)20

Q2. What is the output?

```
def fun(x):
    x += 10
    return x
```

```
x = 5
y = fun(x)
```

```
print(x, y)
```

- A)15 5
- B)5 5
- C)15 15
- D)5 15

Q3. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random
```

- A)The local file can shadow the intended standard-library module
- B)Python automatically renames the local file

- C)Python will always reject it
- D)random cannot be imported

Q4. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```

```
print(f())
```

- A)20
- B)None
- C)NameError
- D)10

Q5. What is the output?

```
def outer():
    x = 10
```

```
    def inner():
        nonlocal x
        x = x + 5
        return x
```

```
    inner()
    return x
```

```
print(outer())
```

- A)10
- B)5
- C)UnboundLocalError
- D)15

Q6. What happens when this function is called?

```
def fun(a=10, b):
    return a + b
```

- A)TypeError
- B)NameError
- C)It executes correctly
- D)SyntaxError



```
def display():  
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)  
sample.display()
```

A)Only Hello

B>Error

C)10

Hello

D)x

display

Q15. What happens?

```
def fun(a, b):  
    return a + b
```

```
print(fun(10, a=20))
```

A)SyntaxError

B)30

C)TypeError

D)20

Q16. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

A)Both import only sqrt

B)First imports only sqrt

C)First provides the module namespace; second imports sqrt directly

D)There is no difference

Q17. What is the output?

```
def fun(a=10, b=20):  
    return a - b
```

```
print(fun(30))
```

A)30

B)-10

C)20

D)10

Q18. What will be printed?

```
class InvalidAgeError(Exception):  
    pass
```

```
def check_age(age):  
    if age < 18:  
        raise InvalidAgeError("Age is too low")  
    return "Allowed"
```

```
try:  
    print(check_age(15))  
except InvalidAgeError as e:  
    print(type(e).__name__)  
    print(e)
```

A)Nothing, because custom exceptions cannot be caught

B)InvalidAgeError

15

C)InvalidAgeError

Age is too low

D)Exception

Age is too low

Q19. What is the output?

```
def fun(x):  
    if x == 0:  
        return  
    return x + fun(x - 1)
```

```
print(fun(3))
```

A)3

B)6

C)5

D)None

Q20. What will be printed?

```
try:  
    x = int("10")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:
```



Q28. What will be printed?

```
def fun(x=[]):  
    x.append(10)  
    return x
```

```
a = fun()  
b = fun()
```

```
print(a)  
print(b)
```

- A)Error
- B)[10]
- [10, 10]
- C)[10]
- [10]
- D)[10, 10]
- [10]

Q29. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)6.0
- B)NameError
- C)6
- D)36

Q30. What will be the output?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()  
    print(x)
```

```
outer()  
print(x)
```

- A)20
- 10
- B)30
- 20

C)20

30

D)30

30

Q31. Which object keeps track of modules that have already been imported during the current Python process?

A)__module__

B)sys.path

C)sys.modules

D)sys.imports

Q32. What will happen?

```
def outer():  
    x = 10
```

```
    def inner():  
        nonlocal y  
        y = 20
```

```
    inner()
```

```
outer()
```

A)SyntaxError

B)NameError

C)20

D)10

Q33. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():  
    raise MyError("Something went wrong")
```

```
try:  
    test()  
except MyError as e:  
    print(type(e).__name__)
```

A)TypeError

B)Exception

C)Something went wrong

D)MyError

Q34. What will happen?

```
def fun(n):
```



D)A

B

D

10

Q40. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
```

```
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

A)ImportError

B)Module loaded

10

C)10

10

D)Module loaded

Module loaded

10

Q41. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```

```
fun()
```

A)UnboundLocalError

B)50

C)10

D)NameError

Q42. What is the output?

```
def fun(x):  
    return x * 2
```

```
a = fun  
print(a(5))
```

A)10

B)5

C)func(5)

D>Error

Q43. Why is

try:

```
    print(10 / 0)
```

except Exception:

```
    print("A")
```

except ZeroDivisionError:

```
    print("B")
```

codes's second handler never reached?

A)ZeroDivisionError occurs before Exception

B)except blocks execute randomly

C)ZeroDivisionError is not an exception

D)Exception is a superclass of ZeroDivisionError

Q44. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
```

```
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)A and B

B)B

C)Nothing

D)A

Q45. What will be printed?

try:

```
    print(10 / 0)
```

except ZeroDivisionError:

```
    print("A")
```

except Exception:

```
    print("B")
```

A)Nothing

B)A B

C)A

D)B



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

- A) ImportError
- B) Module loaded
- 10
- C) Module loaded
- Module loaded
- 10
- D) 10
- 10

Q2. What will happen?

```
def fun(a, b=10):
    return a + b
```

```
print(fun(b=5, a=20))
```

- A) TypeError
- B) 15
- C) SyntaxError
- D) 25

Q3. What is the output?

```
def fun(x):
    x += 10
    return x
```

```
x = 5
y = fun(x)
```

```
print(x, y)
```

- A) 5 5
- B) 5 15
- C) 15 15
- D) 15 5

Q4. What is the output?

```
def fun():
    try:
        return 10
    finally:
        return 20
```

```
print(fun())
```

- A) RuntimeError
- B) 10
- C) 20
- D) None

Q5. What will be the output?

```
x = 10
```

```
def outer():
    x = 20
```

```
    def inner():
        global x
        x = 30
```

```
    inner()
    print(x)
```

```
outer()
print(x)
```

- A) 20
- 30
- B) 30
- 20
- C) 20
- 10



C)NameError

D)10

Q14. What will be printed?

```
def fun(a, b):  
    return a + b
```

```
print(fun(10, b=20))
```

A)SyntaxError

B)20

C)30

D)TypeError

Q15. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A)5

B)25

C)5.0

D)sqrt(25)

Q16. Why is

try:

```
    print(10 / 0)
```

except Exception:

```
    print("A")
```

except ZeroDivisionError:

```
    print("B")
```

codes's second handler never reached?

A)ZeroDivisionError is not an exception

B)Exception is a superclass of

ZeroDivisionError

C)except blocks execute randomly

D)ZeroDivisionError occurs before

Exception

Q17. What is the output?

```
def fun():
```

```
    try:
```

```
        print("A")
```

```
        raise ValueError
```

```
    except ValueError:
```

```
        print("B")
```

```
        return 10
```

```
    else:
```

```
        print("C")
```

```
        return 20
```

finally:

```
    print("D")
```

```
print(fun())
```

A)A

B

D

10

B)A

B

C

D

10

C)A

B

10

D

D)A

C

D

20

Q18. What will be the output?

```
def fun(x):
```

```
    try:
```

```
        if x < 0:
```

```
            raise ValueError("negative")
```

```
        return x
```

```
    except ValueError:
```

```
        return 100
```

```
    finally:
```

```
        print("cleanup")
```

```
print(fun(-5))
```

A)negative

cleanup

B)cleanup

-5

C)100

cleanup

D)cleanup

100

Q19. What will be printed?

```
class InvalidAgeError(Exception):
```

```
    pass
```



Q25. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(  
    lambda a, b: a * b,  
    numbers  
)
```

```
print(result)
```

A)24

B)0

C)9

D)10

Q26. What will be printed?

```
def fun():  
    try:  
        return 10  
    finally:  
        print("Finally")
```

```
print(fun())
```

A)10 followed by Finally

B)10 only

C)Finally only

D)Finally followed by 10

Q27. What happens here?

```
def fun(a):  
    return a
```

```
print(fun())
```

A)0

B)None

C)TypeError

D)NameError

Q28. What is the output?

```
try:  
    raise ValueError  
except ValueError:  
    print("A")  
    raise
```

A)A, and execution ends normally

B)B

C)No Output

D)A, followed by propagation of the same exception

Q29. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

```
print(fun(3))
```

A)TypeError

B)RecursionError

C)6

D)3

Q30. What does the following function return?

```
def fun():  
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A>Hello None

B>Error

C)None

D>Hello

Q31. What is the output?

```
def fun(a=10, b=20):  
    return a - b
```

```
print(fun(30))
```

A)20

B)30

C)-10

D)10

Q32. What will be printed?

```
try:  
    x = int("10")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:  
    print("C")
```

Q38. Which object keeps track of modules that have already been imported during the current Python process?

- A) `__module__`
- B) `sys.imports`
- C) `sys.path`
- D) `sys.modules`

Q39. What will normally happen?

```
import math
import math
```

- A) `SyntaxError`
- B) The module is normally loaded and executed twice
- C) The module is normally loaded once and reused
- D) `ImportError`

Q40. What will be printed?

```
def fun(x=[]):
    x.append(10)
    return x
```

```
a = fun()
b = fun()
```

```
print(a)
print(b)
```

- A) `[10]`
- `[10]`
- B) `Error`
- C) `[10]`
- `[10, 10]`
- D) `[10, 10]`
- `[10]`

Q41. if test.py has
`print("A")`

```
if __name__ == "__main__":
    print("B")
```

If test.py is executed directly, what will be printed?

- A) Nothing
- B) B
- C) A followed by B
- D) A

Q42. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))
```

- A) 15
- B) `Error`
- C) 10
- D) 5

Q43. What happens here?

```
class MyError(Exception):
    pass
```

```
def test():
    raise MyError("Something went wrong")
```

```
try:
    test()
except MyError as e:
    print(type(e).__name__)
```

- A) `MyError`
- B) `TypeError`
- C) `Something went wrong`
- D) `Exception`

Q44. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

- A) B
- B) A
- C) A and B
- D) Nothing

Q45. What is the output?

```
def fun(x):
    if x == 0:
        return
    return x + fun(x - 1)
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. Why is

try:

```
print(10 / 0)
```

except Exception:

```
print("A")
```

except ZeroDivisionError:

```
print("B")
```

codes's second handler never reached?

A)ZeroDivisionError occurs before Exception

B)Exception is a superclass of ZeroDivisionError

C)ZeroDivisionError is not an exception

D)except blocks execute randomly

Q2. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
```

```
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

A)ImportError

B)Module loaded

10

C)10

10

D)Module loaded

Module loaded

10

Q3. What is the output?

try:

```
x = int("abc")
```

except ValueError:

```
print("A")
```

else:

```
print("B")
```

finally:

```
print("C")
```

A)A

B)B C

C)B

D)A C

Q4. What will be the output?

def fun(x):

try:

if x < 0:

```
raise ValueError("negative")
```

```
return x
```

except ValueError:

```
return 100
```

finally:

```
print("cleanup")
```

```
print(fun(-5))
```

A)negative

cleanup

B)cleanup

-5

C)cleanup

100

D)100

cleanup

Q5. What happens here?

class MyError(Exception):

```
pass
```

def test():

```
raise MyError("Something went wrong")
```

try:



- A)B
- B)A and B
- C)Nothing
- D)A

Q13. What will be the output?

```
x = 10
```

```
def fun():
    print(x)
    x = 20
```

fun()

- A)20
- B)UnboundLocalError
- C)NameError
- D)10

Q14. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

- A)25
- B)5
- C)sqrt(25)
- D)5.0

Q15. Which object keeps track of modules that have already been imported during the current Python process?

- A)__module__
- B)sys.path
- C)sys.imports
- D)sys.modules

Q16. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))
```

- A)10
- B)15
- C>Error
- D)5

Q17. What will be printed?

```
def make_counter():
    count = 0
```

```
def counter():
    nonlocal count
    count += 1
    return count
```

```
return counter
```

```
a = make_counter()
b = make_counter()
```

```
print(a())
print(a())
print(b())
print(a())
```

A)1

1

1

1

B)0

1

0

2

C)1

2

3

4

D)1

2

1

3

Q18. What is the output?

```
def outer():
    x = 10
```

```
def inner():
    nonlocal x
    x = x + 5
    return x
```

```
inner()
return x
```

```
print(outer())
```

A)5

B)15

C)10

D)UnboundLocalError



If test.py is executed directly, what will be printed?

- A)A followed by B
- B)B
- C)Nothing
- D)A

Q27. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

print(fun(3))

- A)TypeError
- B)6
- C)3
- D)RecursionError

Q28. What is the purpose of this statement?

```
if __name__ == "__main__":
```

- A)It prevents syntax errors
- B)It identifies code intended to run when the file is executed directly
- C)It creates the main function
- D)It prevents all imports

Q29. What happens?

```
def fun(a, b):  
    return a + b
```

print(fun(10, a=20))

- A)30
- B)TypeError
- C)20
- D)SyntaxError

Q30. What is the output?

```
def fun():  
    try:  
        print("A")  
        raise ValueError  
    except ValueError:  
        print("B")  
        return 10  
    else:  
        print("C")
```

```
    return 20  
finally:  
    print("D")
```

print(fun())

- A)A
- B
- D
- 10
- B)A
- B
- 10
- D
- C)A
- B
- C
- D
- 10
- D)A
- C
- D
- 20

Q31. What will be printed?

```
class InvalidAgeError(Exception):  
    pass
```

```
def check_age(age):  
    if age < 18:  
        raise InvalidAgeError("Age is too low")  
    return "Allowed"
```

```
try:  
    print(check_age(15))  
except InvalidAgeError as e:  
    print(type(e).__name__)  
    print(e)
```

- A)InvalidAgeError
- Age is too low
- B)Exception
- Age is too low
- C)Nothing, because custom exceptions cannot be caught



Q39. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

fun()

- A)A
- B)Nothing
- C)A B
- D)B

Q40. What happens here?

```
try:  
    raise ValueError("Wrong value")  
except ValueError as e:  
    print(e)
```

- A)ValueError
- B)e
- C)Wrong Value
- D)Nothing

Q41. What will be printed?

```
try:  
    print(10 / 0)  
except ZeroDivisionError:  
    print("A")  
except Exception:  
    print("B")
```

- A)Nothing
- B)A B
- C)A
- D)B

Q42. What will be the output?

x = 10

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()  
    print(x)
```

```
outer()  
print(x)
```

- A)20
- 10
- B)30
- 20
- C)20
- 30
- D)30
- 30

Q43. What does the following function return?

```
def fun():  
    print("Hello")
```

x = fun()

print(x)

- A>Error
- B>Hello
- C>Hello None
- D)None

Q44. What will be printed?

x = 10

```
def outer():  
    x = 20
```

```
    def inner():  
        print(x)
```

```
    x = 30  
    inner()
```

outer()

- A)10
- B)30
- C)20
- D)NameError

Q45. What will be printed?

```
def fun(x=[]):  
    x.append(10)  
    return x
```

a = fun()



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the major difference between the following?

```
import math
```

and

```
from math import sqrt
```

- A)Both import only sqrt
- B)First provides the module namespace; second imports sqrt directly
- C)There is no difference
- D)First imports only sqrt

Q2. What is the output?

```
def fun(x):
    return x * 2
```

```
a = fun
print(a(5))
```

- A)func(5)
- B)5
- C)10
- D>Error

Q3. Why is

```
try:
```

```
    print(10 / 0)
```

```
except Exception:
```

```
    print("A")
```

```
except ZeroDivisionError:
```

```
    print("B")
```

codes's second handler never reached?

- A)except blocks execute randomly
- B)ZeroDivisionError is not an exception
- C)ZeroDivisionError occurs before Exception
- D)Exception is a superclass of ZeroDivisionError

Q4. What happens here?

```
class MyError(Exception):
```

```
    pass
```

```
def test():
```

```
    raise MyError("Something went wrong")
```

```
try:
```

```
    test()
```

```
except MyError as e:
```

```
    print(type(e).__name__)
```

- A)Exception
- B)Something went wrong
- C)MyError
- D)TypeError

Q5. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)36
- B)NameError
- C)6.0
- D)6

Q6. What is the purpose of this statement?

```
if __name__ == "__main__":
```

- A)It identifies code intended to run when the file is executed directly
- B)It creates the main function
- C)It prevents all imports
- D)It prevents syntax errors

Q7. What is the output?

```
def fun(x):
```

```
    x += 10
```

```
    return x
```

```
x = 5
```

```
y = fun(x)
```

```
print(x, y)
```



print(fun())

A)NameError

B)TypeError

C)0

D)None

Q16. What will be printed?

try:

print(10 / 0)

except ZeroDivisionError:

print("A")

except Exception:

print("B")

A)A B

B)Nothing

C)B

D)A

Q17. What happens?

def fun(a, b):

return a + b

print(fun(10, a=20))

A)30

B)SyntaxError

C)20

D)TypeError

Q18. What will be the output?

x = 10

def fun():

print(x)

x = 20

fun()

A)10

B)20

C)NameError

D)UnboundLocalError

Q19. Suppose test.py contains:

print("A")

if __name__ == "__main__":

print("B")

If another Python program executes:

import test

what will normally be printed?

A)A and B

B)Nothing

C)A

D)B

Q20. What will be printed?

class InvalidAgeError(Exception):

pass

def check_age(age):

if age < 18:

raise InvalidAgeError("Age is too low")

return "Allowed"

try:

print(check_age(15))

except InvalidAgeError as e:

print(type(e).__name__)

print(e)

A)Exception

Age is too low

B)InvalidAgeError

Age is too low

C)InvalidAgeError

15

D)Nothing, because custom exceptions cannot be caught

Q21. What is the output?

def fun():

try:

return 10

finally:

return 20

print(fun())

A)20

B)10

C)RuntimeError

D)None



```
try:
    x = int("abc")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

A)B C
B)A
C)B
D)A C

Q29. What is the output?

```
def outer():
    x = 10

    def inner():
        nonlocal x
        x = x + 5
        return x

    inner()
    return x

print(outer())
```

A)5
B)15
C)10
D)UnboundLocalError

Q30. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

A)A, followed by propagation of the same exception
B)B
C)A, and execution ends normally
D)No Output

Q31. What is the output?

```
try:
    print(10 / 0)
except Exception:
    print("A")
```

```
except ZeroDivisionError:
    print("B")
```

A)A B
B)B
C)SyntaxError
D)A

Q32. Which object keeps track of modules that have already been imported during the current Python process?

A)sys.imports
B)sys.modules
C)sys.path
D).__module__

Q33. What will be printed?

```
x = 10

f = lambda: x

x = 20

print(f())
```

A)20
B)10
C)None
D)NameError

Q34. What is the output?

```
numbers = [1, 2, 3, 4, 5]

result = list(
    map(
        lambda x: x * 2,
        filter(lambda x: x % 2 == 0,
            numbers)
    )
)

print(result)
```

A)[2, 4]
B)[1, 3, 5]
C)[4, 8]
D)[2, 4, 6, 8, 10]

Q35. What is the output?

```
def fun(x):
    if x == 0:
```



```
finally:  
    print("cleanup")
```

```
print(fun(-5))
```

- A)100
- cleanup
- B)cleanup
- 5
- C)cleanup
- 100
- D)negative
- cleanup

Q40. What happens here?

```
try:  
    raise ValueError("Wrong value")  
except ValueError as e:  
    print(e)
```

- A)e
- B)ValueError
- C)Wrong Value
- D)Nothing

Q41. What will happen?

```
def fun(a, b=10):  
    return a + b
```

```
print(fun(b=5, a=20))
```

- A)SyntaxError
- B)15
- C)25
- D)TypeError

Q42. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a  
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

- A)Module loaded
- 10
- B)ImportError
- C)10
- 10
- D)Module loaded
- Module loaded
- 10

Q43. What will normally happen?

```
import math  
import math
```

- A)SyntaxError
- B)The module is normally loaded and executed twice
- C)The module is normally loaded once and reused
- D)ImportError

Q44. What does the following function return?

```
def fun():  
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

- A>Hello None
- B>Error
- C)None
- D>Hello

Q45. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```

```
fun()
```

- A)50
- B)10
- C)NameError
- D)UnboundLocalError

Q46. What happens when this code runs?

```
def first():
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(
    map(
        lambda x: x * 2,
        filter(lambda x: x % 2 == 0,
            numbers)
    )
)
```

```
print(result)
```

- A)[1, 3, 5]
- B)[4, 8]
- C)[2, 4, 6, 8, 10]
- D)[2, 4]

Q2. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)6.0
- B)36
- C)NameError
- D)6

Q3. What happens when this code executes?

```
def fun():
    print(variable)
    variable = 50
```

```
variable = 10
```

```
fun()
```

- A)UnboundLocalError
- B)10
- C)NameError
- D)50

Q4. What happens here?

```
try:
```

```
    raise ValueError("Wrong value")
except ValueError as e:
    print(e)
```

- A)ValueError
- B)e
- C)Wrong Value
- D)Nothing

Q5. What is the output?

```
def fun():
    try:
        return 10
    finally:
        return 20
```

```
print(fun())
```

- A)20
- B)10
- C)RuntimeError
- D)None

Q6. What is the output?

```
try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")
```

- A)A
- B)A B
- C)B
- D)SyntaxError

Q7. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

- A)5
- B)5.0
- C)25
- D)sqrt(25)



Q14. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(  
    lambda a, b: a * b,  
    numbers  
)
```

```
print(result)
```

- A)9
- B)24
- C)10
- D)0

Q15. What will be printed?

```
def fun(x=[]):  
    x.append(10)  
    return x
```

```
a = fun()  
b = fun()
```

```
print(a)  
print(b)
```

- A)[10, 10]
- [10]
- B)[10]
- [10, 10]
- C)[10]
- [10]
- D)Error

Q16. if test.py has

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If test.py is executed directly, what will be printed?

- A)Nothing
- B)A followed by B
- C)A
- D)B

Q17. What is the output?

```
def fun(x):
```

```
    x += 10  
    return x
```

```
x = 5  
y = fun(x)
```

```
print(x, y)
```

- A)5 5
- B)5 15
- C)15 5
- D)15 15

Q18. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

- A)Both import only sqrt
- B)First provides the module namespace; second imports sqrt directly
- C)First imports only sqrt
- D)There is no difference

Q19. What happens?

```
def fun(a, b):  
    return a + b
```

```
print(fun(10, a=20))
```

- A)20
- B)SyntaxError
- C)30
- D)TypeError

Q20. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))
```

- A)5
- B)15
- C>Error
- D)10

Q21. What is the output?

```
def fun(x):  
    return x * 2
```



D)10 followed by Finally

Q29. What will be the output?

```
def fun(x):  
    try:  
        if x < 0:  
            raise ValueError("negative")  
        return x  
    except ValueError:  
        return 100  
    finally:  
        print("cleanup")
```

print(fun(-5))

A)negative

cleanup

B)cleanup

100

C)100

cleanup

D)cleanup

-5

Q30. What will be printed?

x = 10

f = lambda: x

x = 20

print(f())

A)None

B)20

C)NameError

D)10

Q31. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

fun()

A)Nothing

B)B

C)A

D)A B

Q32. What will be the output?

x = 10

```
def fun():  
    print(x)  
    x = 20
```

fun()

A)UnboundLocalError

B)20

C)NameError

D)10

Q33. What will be printed?

```
def make_counter():  
    count = 0
```

```
    def counter():  
        nonlocal count  
        count += 1  
        return count
```

return counter

a = make_counter()

b = make_counter()

print(a())

print(a())

print(b())

print(a())

A)0

1

0

2

B)1

2

1

3

C)1

2

3

4

D)1

1

1

1



A)20
10
B)20
30
C)30
20
D)30
30

Q41. Why is

try:

```
    print(10 / 0)
```

except Exception:

```
    print("A")
```

except ZeroDivisionError:

```
    print("B")
```

codes's second handler never reached?

- A)ZeroDivisionError occurs before Exception
- B)ZeroDivisionError is not an exception
- C)except blocks execute randomly
- D)Exception is a superclass of ZeroDivisionError

Q42. Suppose sample.py contains:

```
x = 10
```

```
def display():
```

```
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)
```

```
sample.display()
```

- A)x
- display
- B)Only Hello
- C)10
- Hello
- D>Error

Q43. What is the purpose of this statement?

```
if __name__ == "__main__":
```

- A)It prevents syntax errors
- B)It creates the main function

C)It prevents all imports

D)It identifies code intended to run when the file is executed directly

Q44. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():
```

```
    raise MyError("Something went wrong")
```

```
try:
```

```
    test()
```

```
except MyError as e:
```

```
    print(type(e).__name__)
```

- A)Something went wrong
- B)Exception
- C)TypeError
- D)MyError

Q45. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
```

```
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

- A)ImportError
- B)Module loaded
- Module loaded
- 10
- C)10
- 10
- D)Module loaded
- 10

Q46. What is the output?

```
def fun():
```

```
    try:
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What will happen?

```
def fun(n):
    if n == 0:
        return 1
    return n * fun(n)
```

```
print(fun(3))
```

- A)3
- B)RecursionError
- C)6
- D)TypeError

Q2. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(
    lambda a, b: a * b,
    numbers
)
```

```
print(result)
```

- A)24
- B)0
- C)9
- D)10

Q3. What is the output?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        return x + 5
```

```
    return inner
```

```
f = outer()
```

```
print(f())
```

- A)None
- B)15

C)10

D)NameError

Q4. What will happen?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        nonlocal y
```

```
        y = 20
```

```
    inner()
```

```
outer()
```

- A)10
- B)NameError
- C)20
- D)SyntaxError

Q5. Why is

```
try:
```

```
    print(10 / 0)
```

```
except Exception:
```

```
    print("A")
```

```
except ZeroDivisionError:
```

```
    print("B")
```

codes's second handler never reached?

- A)ZeroDivisionError is not an exception
- B)Exception is a superclass of ZeroDivisionError
- C)ZeroDivisionError occurs before Exception
- D)except blocks execute randomly

Q6. What will be printed?

```
def fun(a, b):
```

```
    return a + b
```

```
print(fun(10, b=20))
```

- A)TypeError
- B)20
- C)SyntaxError



```
print(type(e).__name__)
print(e)
```

A) Nothing, because custom exceptions cannot be caught

B) InvalidAgeError

15

C) Exception

Age is too low

D) InvalidAgeError

Age is too low

Q12. What will be printed?

```
try:
```

```
    print(10 / 0)
```

```
except ZeroDivisionError:
```

```
    print("A")
```

```
except Exception:
```

```
    print("B")
```

A) A B

B) Nothing

C) B

D) A

Q13. What happens here?

```
try:
```

```
    raise ValueError("Wrong value")
```

```
except ValueError as e:
```

```
    print(e)
```

A) Wrong Value

B) Nothing

C) ValueError

D) e

Q14. What is the output?

```
def fun(x):
```

```
    x += 10
```

```
    return x
```

```
x = 5
```

```
y = fun(x)
```

```
print(x, y)
```

A) 15 5

B) 5 5

C) 15 15

D) 5 15

Q15. What is the output?

```
def fun(x):
```

```
    if x == 0:
```

```
        return
```

```
    return x + fun(x - 1)
```

```
print(fun(3))
```

A) 3

B) 5

C) None

D) 6

Q16. What happens when this code executes?

```
def fun():
```

```
    print(variable)
```

```
    variable = 50
```

```
variable = 10
```

```
fun()
```

A) UnboundLocalError

B) 10

C) NameError

D) 50

Q17. What is the output?

```
try:
```

```
    x = int("abc")
```

```
except ValueError:
```

```
    print("A")
```

```
else:
```

```
    print("B")
```

```
finally:
```

```
    print("C")
```

A) A C

B) B C

C) B

D) A

Q18. What will happen?

```
def fun(a, b=10):
```

```
    return a + b
```

```
print(fun(b=5, a=20))
```

A) 15

B) TypeError

C) SyntaxError

D) 25



- A)15
- B)Error
- C)5
- D)10

Q27. What will be printed?

```
x = 10
```

```
def outer():  
    x = 20  
  
    def inner():  
        print(x)  
  
    x = 30  
    inner()
```

outer()

- A)10
- B)NameError
- C)30
- D)20

Q28. Suppose sample.py contains:

```
x = 10
```

```
def display():  
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)  
sample.display()
```

- A)10
- Hello
- B)x
- display
- C)Error
- D)Only Hello

Q29. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

- A)Nothing
- B)A and B
- C)A
- D)B

Q30. Which object keeps track of modules that have already been imported during the current Python process?

- A)sys.imports
- B).__module__
- C)sys.path
- D)sys.modules

Q31. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

fun()

- A)B
- B)A
- C)Nothing
- D)A B

Q32. What will normally happen?

```
import math  
import math
```

- A)ImportError
- B)The module is normally loaded and executed twice
- C)The module is normally loaded once and reused
- D)SyntaxError

Q33. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)6.0
- B)6
- C)36
- D)NameError



```
return x * 2
```

```
a = fun  
print(a(5))
```

- A)10
- B)Error
- C)func(5)
- D)5

Q41. What will be printed?

```
try:  
    x = int("10")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:  
    print("C")
```

- A)B C
- B)A C
- C)A
- D)B

Q42. What will be the output?

```
x = 10
```

```
def fun():  
    print(x)  
    x = 20
```

```
fun()
```

- A)UnboundLocalError
- B)10
- C)20
- D)NameError

Q43. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

- A)First provides the module namespace; second imports sqrt directly
- B)There is no difference
- C)First imports only sqrt
- D)Both import only sqrt

Q44. What is the output?

```
def fun(a=10, b=20):  
    return a - b
```

```
print(fun(30))
```

- A)10
- B)20
- C)30
- D)-10

Q45. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(  
    map(  
        lambda x: x * 2,  
        filter(lambda x: x % 2 == 0,  
            numbers)  
    )  
)
```

```
print(result)
```

- A)[2, 4]
- B)[4, 8]
- C)[1, 3, 5]
- D)[2, 4, 6, 8, 10]

Q46. What will be the output?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()  
    print(x)
```

```
outer()  
print(x)
```

- A)30
- 30
- B)20
- 10



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What will be printed?

```
def make_counter():
    count = 0
```

```
    def counter():
        nonlocal count
        count += 1
        return count
```

```
    return counter
```

```
a = make_counter()
b = make_counter()
```

```
print(a())
print(a())
print(b())
print(a())
```

A)1

1

1

1

B)1

2

1

3

C)0

1

0

2

D)1

2

3

4

Q2. What happens when this code runs?

```
def first():
    second()
```

```
def second():
```

```
third()
```

```
def third():
    raise RuntimeError("Failure")
```

```
try:
    first()
except RuntimeError:
    print("Handled")
```

A)NameError

B)Handled

C)TypeError

D)RuntimeError cannot propagate through functions

Q3. What does the following function return?

```
def fun():
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A)Hello

B>Error

C)Hello None

D)None

Q4. What will happen?

```
def fun(a, b=10):
    return a + b
```

```
print(fun(b=5, a=20))
```

A)25

B)SyntaxError

C)15

D)TypeError

Q5. What is the output?

```
def fun():
    try:
        print("A")
```



```
print("A")
except Exception:
    print("B")
```

- A) A B
- B) Nothing
- C) A
- D) B

Q12. What is the major difference between the following?

```
import math
```

and

```
from math import sqrt
```

- A) First provides the module namespace; second imports sqrt directly
- B) There is no difference
- C) First imports only sqrt
- D) Both import only sqrt

Q13. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))
```

- A) 15
- B) 5
- C) 10
- D) Error

Q14. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```

```
print(f())
```

- A) NameError
- B) 10
- C) 20
- D) None

Q15. What is the output?

```
def fun():
    try:
        return 10
    finally:
```

```
return 20
```

```
print(fun())
```

- A) 20
- B) RuntimeError
- C) None
- D) 10

Q16. What happens here?

```
try:
    raise ValueError("Wrong value")
except ValueError as e:
    print(e)
```

- A) Wrong Value
- B) Nothing
- C) e
- D) ValueError

Q17. What is the output?

```
def outer():
    x = 10

    def inner():
        return x + 5

    return inner
```

```
f = outer()
print(f())
```

- A) None
- B) 15
- C) NameError
- D) 10

Q18. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is

If another Python program executes:

```
import test
```

what will normally be printed?

- A)A
- B)Nothing
- C)B
- D)A and B

Q26. What is the output?

```
def fun(x):  
    if x == 0:  
        return  
    return x + fun(x - 1)
```

```
print(fun(3))
```

- A)None
- B)6
- C)3
- D)5

Q27. What is the output?

```
try:  
    x = int("abc")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:  
    print("C")
```

- A)A C
- B)A
- C)B C
- D)B

Q28. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

```
fun()
```

- A)A B
- B)Nothing
- C)A
- D)B

Q29. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(  
    map(  
        lambda x: x * 2,  
        filter(lambda x: x % 2 == 0,  
            numbers)  
    )  
)
```

```
print(result)
```

- A)[4, 8]
- B)[1, 3, 5]
- C)[2, 4, 6, 8, 10]
- D)[2, 4]

Q30. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```

```
fun()
```

- A)50
- B)NameError
- C)UnboundLocalError
- D)10

Q31. What will be printed?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        print(x)
```

```
    x = 30  
    inner()
```

```
outer()
```

- A)10
- B)30
- C)20
- D)NameError



print(fun(3))

A)RecursionError

B)3

C)TypeError

D)6

Q40. What happens here?

```
def fun(a):  
    return a
```

print(fun())

A)None

B)NameError

C)TypeError

D)0

Q41. What is the output?

```
def outer():  
    x = 10
```

```
    def inner():  
        nonlocal x  
        x = x + 5  
        return x
```

```
    inner()  
    return x
```

print(outer())

A)15

B)UnboundLocalError

C)10

D)5

Q42. What will be the output?

import math

print(math.sqrt(25))

A)5.0

B)sqrt(25)

C)5

D)25

Q43. What will be the output?

x = 10

```
def fun():  
    print(x)
```

x = 20

fun()

A)UnboundLocalError

B)10

C)20

D)NameError

Q44. What will be printed?

```
class InvalidAgeError(Exception):  
    pass
```

```
def check_age(age):
```

```
    if age < 18:
```

```
        raise InvalidAgeError("Age is  
too low")
```

```
    return "Allowed"
```

```
try:
```

```
    print(check_age(15))
```

```
except InvalidAgeError as e:
```

```
    print(type(e).__name__)
```

```
    print(e)
```

A)Nothing, because custom exceptions cannot be caught

B)InvalidAgeError

15

C)InvalidAgeError

Age is too low

D)Exception

Age is too low

Q45. What will be printed?

from functools import reduce

numbers = [1, 2, 3, 4]

result = reduce(

lambda a, b: a * b,

numbers

)

print(result)

A)24

B)0

C)9



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

- A)No Output
- B)A, followed by propagation of the same exception
- C)A, and execution ends normally
- D)B

Q2. What is the output?

```
def fun():
    try:
        print("A")
        raise ValueError
    except ValueError:
        print("B")
        return 10
    else:
        print("C")
        return 20
    finally:
        print("D")
```

```
print(fun())
```

- A)A
- C
- D
- 20
- B)A
- B
- 10
- D
- C)A
- B
- D
- 10

D)A

B

C

D

10

Q3. What is the output?

```
def fun(x):
    if x == 0:
        return
    return x + fun(x - 1)
```

```
print(fun(3))
```

- A)3
- B)6
- C)5
- D)None

Q4. What happens here?

```
def fun(a):
    return a
```

```
print(fun())
```

- A)0
- B)TypeError
- C)NameError
- D)None

Q5. Suppose sample.py contains:

```
x = 10
```

```
def display():
    print("Hello")
```

What will this print?

```
import sample
```

```
print(sample.x)
sample.display()
```

- A>Error



```
def first():
    second()

def second():
    third()

def third():
    raise RuntimeError("Failure")
```

```
try:
    first()
except RuntimeError:
    print("Handled")
```

A)NameError
B)Handled
C)RuntimeError cannot propagate through functions
D)TypeError

Q13. What is the output?

```
def outer():
    x = 10

    def inner():
        return x + 5

    return inner
```

```
f = outer()
print(f())
```

A)10
B)NameError
C)None
D)15

Q14. What happens here?

```
try:
    raise ValueError("Wrong value")
except ValueError as e:
    print(e)
```

A)Nothing
B)ValueError
C)e
D)Wrong Value

Q15. What is the output?

```
def fun(x):
```

```
x += 10
return x
```

```
x = 5
y = fun(x)
```

```
print(x, y)
```

A)5 5
B)15 5
C)15 15
D)5 15

Q16. What will be printed?

```
def fun(x=[]):
    x.append(10)
    return x
```

```
a = fun()
b = fun()
```

```
print(a)
print(b)
```

A)[10]
[10]
B)[10, 10]
[10]
C)[10]
[10, 10]
D>Error

Q17. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

A)There is no difference
B)First imports only sqrt
C)First provides the module namespace; second imports sqrt directly
D)Both import only sqrt

Q18. What will normally happen?

```
import math
import math
```

A)ImportError



- A)10
- B)15
- C)Error
- D)5

Q26. What will be the output?

```
def fun(x):
    try:
        if x < 0:
            raise ValueError("negative")
        return x
    except ValueError:
        return 100
    finally:
        print("cleanup")
```

print(fun(-5))

- A)cleanup
- 5
- B)100
- cleanup
- C)negative
- cleanup
- D)cleanup
- 100

Q27. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

- A)Module loaded
- 10
- B)ImportError
- C)Module loaded
- Module loaded
- 10

- D)10
- 10

Q28. What will be printed?

```
def fun(a, b):
    return a + b
```

print(fun(10, b=20))

- A)TypeError
- B)30
- C)SyntaxError
- D)20

Q29. if test.py has
print("A")

```
if __name__ == "__main__":
    print("B")
```

If test.py is executed directly, what will be printed?

- A)A
- B)A followed by B
- C)B
- D)Nothing

Q30. What is the output?

```
def fun(x):
    return x * 2
```

```
a = fun
print(a(5))
```

- A>Error
- B)10
- C)5
- D)func(5)

Q31. What will be the output?

```
x = 10
```

```
def outer():
    x = 20
```

```
    def inner():
        global x
        x = 30
```

```
    inner()
    print(x)
```



```
def fun(n):
    if n == 0:
        return 1
    return n * fun(n)
```

print(fun(3))

A) RecursionError

B) 6

C) TypeError

D) 3

Q39. What will be printed?

```
try:
```

```
    print(10 / 0)
```

```
except ZeroDivisionError:
```

```
    print("A")
```

```
except Exception:
```

```
    print("B")
```

A) A

B) A B

C) Nothing

D) B

Q40. What will be printed?

```
class InvalidAgeError(Exception):
    pass
```

```
def check_age(age):
```

```
    if age < 18:
```

```
        raise InvalidAgeError("Age is
too low")
```

```
    return "Allowed"
```

```
try:
```

```
    print(check_age(15))
```

```
except InvalidAgeError as e:
```

```
    print(type(e).__name__)
```

```
    print(e)
```

A) Nothing, because custom exceptions cannot be caught

B) InvalidAgeError

15

C) Exception

Age is too low

D) InvalidAgeError

Age is too low

Q41. What does the following function return?

```
def fun():
```

```
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A) Error

B) Hello None

C) Hello

D) None

Q42. Which object keeps track of modules that have already been imported during the current Python process?

A) sys.imports

B) sys.path

C) __module__

D) sys.modules

Q43. What will be printed?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        print(x)
```

```
    x = 30
```

```
    inner()
```

```
outer()
```

A) 20

B) NameError

C) 30

D) 10

Q44. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A) sqrt(25)

B) 25

C) 5

D) 5.0



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

- A)B
- B)A and B
- C)Nothing
- D)A

Q2. What is the output?

```
def fun(x):
    return x * 2
```

```
a = fun
print(a(5))
```

- A)func(5)
- B)5
- C>Error
- D)10

Q3. What is the purpose of this statement?

```
if __name__ == "__main__":
```

- A)It prevents syntax errors
- B)It creates the main function
- C)It prevents all imports
- D)It identifies code intended to run when the file is executed directly

Q4. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(
    lambda a, b: a * b,
    numbers
)
```

```
print(result)
```

- A)24
- B)0
- C)10
- D)9

Q5. What will be printed?

```
def fun():
    print("A")
    return
    print("B")
```

```
fun()
```

- A)A B
- B)A
- C)B
- D)Nothing

Q6. What is the output?

```
try:
    x = int("abc")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

- A)A
- B)A C
- C)B
- D)B C

Q7. What is the output?

```
try:
    print(10 / 0)
except Exception:
    print("A")
```



return inner

**f = outer()
print(f())**

- A)10
- B)NameError
- C)None
- D)15

Q16. What will be the output?

x = 10

**def fun():
 print(x)
 x = 20**

- fun()**
- A)20
 - B)NameError
 - C)10
 - D)UnboundLocalError

Q17. What will be printed?

**class InvalidAgeError(Exception):
 pass**

**def check_age(age):
 if age < 18:
 raise InvalidAgeError("Age is too low")
 return "Allowed"**

**try:
 print(check_age(15))
except InvalidAgeError as e:
 print(type(e).__name__)
 print(e)**

- A)Nothing, because custom exceptions cannot be caught
- B)InvalidAgeError
- 15
- C)Exception
- Age is too low
- D)InvalidAgeError
- Age is too low

Q18. What happens here?

**try:
 raise ValueError("Wrong value")
except ValueError as e:
 print(e)**

- A)e
- B)ValueError
- C)Nothing
- D)Wrong Value

Q19. What will normally happen?

**import math
import math**

- A)SyntaxError
- B)ImportError
- C)The module is normally loaded once and reused
- D)The module is normally loaded and executed twice

Q20. What will be the output?

**def fun(x):
 try:
 if x < 0:
 raise ValueError("negative")
 return x
 except ValueError:
 return 100
 finally:
 print("cleanup")**

print(fun(-5))

- A)cleanup
- 5
- B)negative
- cleanup
- C)cleanup
- 100
- D)100
- cleanup

Q21. What will be the output?

x = 10

**def outer():
 x = 20**



Q27. What will be printed?

try:

```
    print(10 / 0)
```

except ZeroDivisionError:

```
    print("A")
```

except Exception:

```
    print("B")
```

A)Nothing

B)A B

C)A

D)B

Q28. What is the major difference between the following?

```
import math
```

and

```
from math import sqrt
```

A)Both import only sqrt

B)There is no difference

C)First provides the module namespace; second imports sqrt directly

D)First imports only sqrt

Q29. What happens when this code executes?

```
def fun():
```

```
    print(variable)
```

```
    variable = 50
```

```
variable = 10
```

```
fun()
```

A)NameError

B)10

C)UnboundLocalError

D)50

Q30. What will be printed?

try:

```
    x = int("10")
```

except ValueError:

```
    print("A")
```

else:

```
    print("B")
```

finally:

```
    print("C")
```

A)A

B)B C

C)B

D)A C

Q31. What will happen?

```
def fun(n):
```

```
    if n == 0:
```

```
        return 1
```

```
    return n * fun(n)
```

```
print(fun(3))
```

A)3

B)RecursionError

C)TypeError

D)6

Q32. What does the following function return?

```
def fun():
```

```
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A)None

B>Hello

C>Error

D>Hello None

Q33. What is the output?

```
def fun():
```

```
    try:
```

```
        print("A")
```

```
        raise ValueError
```

```
    except ValueError:
```

```
        print("B")
```

```
        return 10
```

```
    else:
```

```
        print("C")
```

```
        return 20
```

```
    finally:
```

```
        print("D")
```

```
print(fun())
```

A)A

B



```
print("B")
```

If test.py is executed directly, what will be printed?

- A)Nothing
- B)B
- C)A followed by B
- D)A

Q40. What happens when this function is called?

```
def fun(a=10, b):  
    return a + b
```

- A)NameError
- B)It executes correctly
- C)SyntaxError
- D)TypeError

Q41. What will happen?

```
def outer():  
    x = 10  
  
    def inner():  
        nonlocal y  
        y = 20  
  
    inner()
```

```
outer()  
A)20  
B)NameError  
C)SyntaxError  
D)10
```

Q42. What will be printed?

```
x = 10  
  
def outer():  
    x = 20  
  
    def inner():  
        print(x)  
  
    x = 30  
    inner()
```

```
outer()  
A)20  
B)30
```

- C)10
- D)NameError

Q43. What will be printed?

```
x = 10  
  
f = lambda: x  
  
x = 20
```

```
print(f())  
A)NameError  
B)10  
C)None  
D)20
```

Q44. Suppose module_a.py contains:

```
print("Module loaded")  
  
value = 10
```

And another file contains:

```
import module_a  
import module_a  
  
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

- A)Module loaded
- 10
- B)ImportError
- C)10
- 10
- D)Module loaded
- Module loaded
- 10

Q45. Suppose the current directory contains a file named random.py. What potential problem can occur with:

```
import random  
A)Python automatically renames the local file  
B)random cannot be imported
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What happens?

```
def fun(a, b):
    return a + b
```

```
print(fun(10, a=20))
```

- A)TypeError
- B)30
- C)20
- D)SyntaxError

Q2. What is the output?

```
def outer():
    x = 10
```

```
    def inner():
        return x + 5
```

```
    return inner
```

```
f = outer()
```

```
print(f())
```

- A)NameError
- B)15
- C)None
- D)10

Q3. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)36
- B)NameError
- C)6
- D)6.0

Q4. What is the output?

```
def fun():
```

```
    try:
```

```
        print("A")
```

```
        raise ValueError
```

```
    except ValueError:
```

```
        print("B")
```

```
        return 10
```

```
    else:
```

```
        print("C")
```

```
        return 20
```

```
    finally:
```

```
        print("D")
```

```
print(fun())
```

```
A)A
```

```
C
```

```
D
```

```
20
```

```
B)A
```

```
B
```

```
10
```

```
D
```

```
C)A
```

```
B
```

```
C
```

```
D
```

```
10
```

```
D)A
```

```
B
```

```
D
```

```
10
```

Q5. What will be the output?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        global x
```

```
        x = 30
```

```
    inner()
```

```
    print(x)
```

```
outer()
```



```
import math
```

```
import math
```

A)The module is normally loaded once and reused

B)ImportError

C)SyntaxError

D)The module is normally loaded and executed twice

Q13. What is the output?

```
def fun():
```

```
    try:
```

```
        return 10
```

```
    finally:
```

```
        return 20
```

```
print(fun())
```

A)20

B)10

C)None

D)RuntimeError

Q14. What will be the output?

```
x = 10
```

```
def fun():
```

```
    print(x)
```

```
    x = 20
```

```
fun()
```

A)UnboundLocalError

B)NameError

C)20

D)10

Q15. What will be printed?

```
def fun():
```

```
    try:
```

```
        return 10
```

```
    finally:
```

```
        print("Finally")
```

```
print(fun())
```

A)10 followed by Finally

B)Finally only

C)Finally followed by 10

D)10 only

Q16. What does the following function return?

```
def fun():
```

```
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

A>Error

B>Hello None

C)None

D>Hello

Q17. Why is

```
try:
```

```
    print(10 / 0)
```

```
except Exception:
```

```
    print("A")
```

```
except ZeroDivisionError:
```

```
    print("B")
```

codes's second handler never reached?

A)except blocks execute randomly

B)ZeroDivisionError is not an exception

C)ZeroDivisionError occurs before Exception

D)Exception is a superclass of ZeroDivisionError

Q18. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(
```

```
    map(
```

```
        lambda x: x * 2,
```

```
        filter(lambda x: x % 2 == 0,
```

```
numbers)
```

```
    )
```

```
)
```

```
print(result)
```

A)[1, 3, 5]

B)[4, 8]

C)[2, 4]

D)[2, 4, 6, 8, 10]

Q19. What will be the output?

```
def fun(x):
```



```
try:
    raise ValueError("Wrong value")
except ValueError as e:
    print(e)
```

- A) ValueError
- B) Wrong Value
- C) e
- D) Nothing

Q27. What is the major difference between the following?

```
import math
```

and

```
from math import sqrt
```

- A) First imports only sqrt
- B) First provides the module namespace; second imports sqrt directly
- C) There is no difference
- D) Both import only sqrt

Q28. What will be printed?

```
try:
    x = int("10")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

- A) B
- B) A
- C) A C
- D) B C

Q29. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

- A) No Output
- B) B
- C) A, and execution ends normally
- D) A, followed by propagation of the same exception

Q30. What is the output?

```
try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")
```

- A) SyntaxError
- B) A
- C) A B
- D) B

Q31. What is the output?

```
def outer():
    x = 10

    def inner():
        nonlocal x
        x = x + 5
        return x
```

```
    inner()
    return x
```

```
print(outer())
```

- A) 15
- B) UnboundLocalError
- C) 5
- D) 10

Q32. What will be printed?

```
def fun():
    print("A")
    return
    print("B")
```

```
fun()
```

- A) B
- B) Nothing
- C) A
- D) A B

Q33. What happens when this code executes?

```
def fun():
    print(variable)
    variable = 50
```



```
def counter():
    nonlocal count
    count += 1
    return count
```

```
return counter
```

```
a = make_counter()
b = make_counter()
```

```
print(a())
print(a())
print(b())
print(a())
```

A)1

2

3

4

B)1

1

1

1

C)0

1

0

2

D)1

2

1

3

Q41. What is the output?

```
def fun(x):
    x += 10
    return x
```

```
x = 5
y = fun(x)
```

```
print(x, y)
```

A)15 15

B)5 5

C)5 15

D)15 5

Q42. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]
```

```
result = reduce(
    lambda a, b: a * b,
    numbers
)
```

```
print(result)
```

A)9

B)24

C)0

D)10

Q43. What will be printed?

```
x = 10
```

```
def outer():
    x = 20
```

```
    def inner():
        print(x)
```

```
    x = 30
    inner()
```

```
outer()
```

A)10

B)NameError

C)30

D)20

Q44. What is the purpose of this statement?

```
if __name__ == "__main__":
```

A)It prevents syntax errors

B)It prevents all imports

C)It identifies code intended to run when the file is executed directly

D)It creates the main function

Q45. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a
```



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
try:
    x = int("abc")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

- A)A C
- B)A
- C)B
- D)B C

Q2. What will be printed?

```
class InvalidAgeError(Exception):
    pass

def check_age(age):
    if age < 18:
        raise InvalidAgeError("Age is
too low")
    return "Allowed"
```

```
try:
    print(check_age(15))
except InvalidAgeError as e:
    print(type(e).__name__)
    print(e)
```

A)InvalidAgeError
15
B)InvalidAgeError
Age is too low
C)Nothing, because custom exceptions
cannot be caught
D)Exception
Age is too low

Q3. What will be printed?

```
from functools import reduce
```

```
numbers = [1, 2, 3, 4]

result = reduce(
    lambda a, b: a * b,
    numbers
)
```

```
print(result)
```

- A)10
- B)24
- C)0
- D)9

Q4. What is the output?

```
def fun(x):
    if x == 0:
        return
    return x + fun(x - 1)
```

```
print(fun(3))
```

- A)5
- B)None
- C)6
- D)3

Q5. What is the output?

```
def fun():
    try:
        return 10
    finally:
        return 20
```

```
print(fun())
```

- A)10
- B)RuntimeError
- C)20
- D)None

Q6. What will be printed?

```
x = 10
```



10
D
B)A
B
D
10
C)A
B
C
D
10
D)A
C
D
20

Q13. What will be printed?

```
def fun(x=[]):  
    x.append(10)  
    return x
```

```
a = fun()  
b = fun()
```

```
print(a)  
print(b)
```

A)Error
B)[10]
[10, 10]
C)[10, 10]
[10]
D)[10]
[10]

Q14. What will happen?

```
def outer():  
    x = 10
```

```
    def inner():  
        nonlocal y  
        y = 20
```

```
    inner()
```

```
outer()  
A)SyntaxError  
B)NameError  
C)10
```

D)20

Q15. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():  
    raise MyError("Something went  
wrong")
```

```
try:  
    test()  
except MyError as e:  
    print(type(e).__name__)
```

A)TypeError

B)MyError

C)Something went wrong

D)Exception

Q16. What will be printed?

```
def fun():  
    try:  
        return 10  
    finally:  
        print("Finally")
```

```
print(fun())
```

A)Finally only

B)10 only

C)Finally followed by 10

D)10 followed by Finally

Q17. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

A)5.0

B)5

C)sqrt(25)

D)25

Q18. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(  
    map(  
        lambda x: x * 2,  
        filter(lambda x: x % 2 == 0,
```



D)10

Q25. What happens here?

```
try:  
    raise ValueError("Wrong value")  
except ValueError as e:  
    print(e)
```

A)Wrong Value

B)e

C)ValueError

D)Nothing

Q26. What is the output?

```
def fun(x):  
    x += 10  
    return x
```

x = 5

y = fun(x)

print(x, y)

A)5 15

B)15 15

C)15 5

D)5 5

Q27. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

variable = 10

fun()

A)10

B)NameError

C)50

D)UnboundLocalError

Q28. Suppose module_a.py contains:

```
print("Module loaded")
```

value = 10

And another file contains:

```
import module_a  
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

A)Module loaded

10

B)10

10

C)Module loaded

Module loaded

10

D)ImportError

Q29. What happens?

```
def fun(a, b):  
    return a + b
```

print(fun(10, a=20))

A)20

B)SyntaxError

C)TypeError

D)30

Q30. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

print(fun(3))

A)TypeError

B)3

C)RecursionError

D)6

Q31. What does the following function return?

```
def fun():  
    print("Hello")
```

x = fun()

print(x)

A)None

B>Hello None

C>Hello



D)B

Q37. What is the output?

try:

print(10 / 0)

except Exception:

print("A")

except ZeroDivisionError:

print("B")

A)A

B)SyntaxError

C)A B

D)B

Q38. if test.py has

print("A")

if __name__ == "__main__":

print("B")

If test.py is executed directly, what will be printed?

A)Nothing

B)B

C)A

D)A followed by B

Q39. What will normally happen?

import math

import math

A)The module is normally loaded once and reused

B)ImportError

C)SyntaxError

D)The module is normally loaded and executed twice

Q40. What is the output?

f = lambda x: x + 5

print(f(10))

A>Error

B)5

C)15

D)10

Q41. Suppose sample.py contains:

x = 10

def display():

print("Hello")

What will this print?

import sample

print(sample.x)

sample.display()

A)10

Hello

B)Only Hello

C)x

display

D>Error

Q42. What will be printed?

x = 10

f = lambda: x

x = 20

print(f())

A)20

B)None

C)NameError

D)10

Q43. Which object keeps track of modules that have already been imported during the current Python process?

A)sys.path

B)sys.modules

C)sys.imports

D)__module__

Q44. What will be printed?

try:

x = int("10")

except ValueError:

print("A")

else:

print("B")

finally:

print("C")

A)B C

B)A C

C)B



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What happens when this code runs?

```
def first():
    second()
```

```
def second():
    third()
```

```
def third():
    raise RuntimeError("Failure")
```

```
try:
    first()
except RuntimeError:
    print("Handled")
```

- A)Handled
- B)TypeError
- C)NameError
- D)RuntimeError cannot propagate through functions

Q2. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

- A)B
- B)A, and execution ends normally
- C)No Output
- D)A, followed by propagation of the same exception

Q3. What will be printed?

```
def fun():
    try:
        return 10
    finally:
        print("Finally")
```

```
print(fun())
```

- A)10 only
 - B)10 followed by Finally
 - C)Finally only
 - D)Finally followed by 10
- Q4. What is the output?**

```
def outer():
    x = 10

    def inner():
        return x + 5
```

```
    return inner
```

```
f = outer()
print(f())
```

- A)NameError
- B)None
- C)15
- D)10

Q5. What is the output?

```
try:
    x = int("abc")
except ValueError:
    print("A")
else:
    print("B")
finally:
    print("C")
```

- A)B C
- B)B
- C)A
- D)A C

Q6. Why is

```
try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")
codes's second handler never
```



```
return x
```

```
x = 5  
y = fun(x)
```

```
print(x, y)
```

A)15 15

B)15 5

C)5 5

D)5 15

Q13. What will be printed?

```
class InvalidAgeError(Exception):  
    pass
```

```
def check_age(age):  
    if age < 18:  
        raise InvalidAgeError("Age is  
too low")  
    return "Allowed"
```

```
try:  
    print(check_age(15))  
except InvalidAgeError as e:  
    print(type(e).__name__)  
    print(e)
```

A)Nothing, because custom exceptions cannot be caught

B)InvalidAgeError

Age is too low

C)InvalidAgeError

15

D)Exception

Age is too low

Q14. What will happen?

```
def fun(n):  
    if n == 0:  
        return 1  
    return n * fun(n)
```

```
print(fun(3))
```

A)RecursionError

B)6

C)3

D)TypeError

Q15. What is the output?

```
def fun(x):  
    return x * 2
```

```
a = fun
```

```
print(a(5))
```

A)5

B>Error

C)10

D)func(5)

Q16. What happens when this code executes?

```
def fun():  
    print(variable)  
    variable = 50
```

```
variable = 10
```

```
fun()
```

A)UnboundLocalError

B)50

C)NameError

D)10

Q17. What will happen?

```
def outer():  
    x = 10
```

```
    def inner():  
        nonlocal y  
        y = 20
```

```
    inner()
```

```
outer()
```

A)20

B)NameError

C)10

D)SyntaxError

Q18. What happens here?

```
def fun(a):  
    return a
```

```
print(fun())
```

A)0

B)TypeError



Q26. Which object keeps track of modules that have already been imported during the current Python process?

- A) `__module__`
- B) `sys.imports`
- C) `sys.modules`
- D) `sys.path`

Q27. What will be printed?

```
def make_counter():  
    count = 0  
  
    def counter():  
        nonlocal count  
        count += 1  
        return count  
  
    return counter
```

```
a = make_counter()  
b = make_counter()
```

```
print(a())  
print(a())  
print(b())  
print(a())
```

A) 1

2

1

3

B) 1

2

3

4

C) 0

1

0

2

D) 1

1

1

1

Q28. What is the output?

```
def fun():  
    try:  
        return 10
```

finally:
return 20

print(fun())

A) None

B) 10

C) 20

D) RuntimeError

Q29. What will be the output?

```
def fun(x):  
    try:  
        if x < 0:  
            raise ValueError("negative")  
        return x  
    except ValueError:  
        return 100  
    finally:  
        print("cleanup")
```

print(fun(-5))

A) cleanup

-5

B) cleanup

100

C) negative

cleanup

D) 100

cleanup

Q30. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A) B

B) A

C) Nothing

D) A and B

Q31. What is the output?

```
try:
```



Q38. What will normally happen?

```
import math
```

```
import math
```

A)SyntaxError

B)The module is normally loaded once and reused

C)The module is normally loaded and executed twice

D)ImportError

Q39. if test.py has

```
print("A")
```

```
if __name__ == "__main__":
```

```
    print("B")
```

If test.py is executed directly, what will be printed?

A)B

B)Nothing

C)A

D)A followed by B

Q40. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

A)First imports only sqrt

B)Both import only sqrt

C)There is no difference

D)First provides the module namespace; second imports sqrt directly

Q41. What will be the output?

```
x = 10
```

```
def fun():
```

```
    print(x)
```

```
    x = 20
```

```
fun()
```

A)UnboundLocalError

B)20

C)10

D)NameError

Q42. What is the output?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        nonlocal x
```

```
        x = x + 5
```

```
    return x
```

```
inner()
```

```
return x
```

```
print(outer())
```

A)10

B)UnboundLocalError

C)15

D)5

Q43. What will be printed?

```
def fun():
```

```
    print("A")
```

```
    return
```

```
    print("B")
```

```
fun()
```

A)B

B)A

C)A B

D)Nothing

Q44. What will be printed?

```
x = 10
```

```
def outer():
```

```
    x = 20
```

```
    def inner():
```

```
        print(x)
```

```
    x = 30
```

```
    inner()
```

```
outer()
```

A)20

B)30

C)10

D)NameError



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What is the output?

```
try:
    raise ValueError
except ValueError:
    print("A")
    raise
```

- A)No Output
- B)B
- C)A, followed by propagation of the same exception
- D)A, and execution ends normally

Q2. What is the output?

```
def fun(x):
    if x == 0:
        return
    return x + fun(x - 1)
```

```
print(fun(3))
```

- A)6
- B)3
- C)None
- D)5

Q3. What happens here?

```
try:
    raise ValueError("Wrong value")
except ValueError as e:
    print(e)
```

- A)ValueError
- B)Wrong Value
- C)Nothing
- D)e

Q4. What will be the output?

```
x = 10
```

```
def outer():
    x = 20
```

```
    def inner():
```

```
    global x
    x = 30
```

```
    inner()
    print(x)
```

```
outer()
print(x)
```

- A)30
- 30
- B)20
- 30
- C)20
- 10
- D)30
- 20

Q5. What is the output?

```
def outer():
    x = 10
```

```
    def inner():
        return x + 5
```

```
    return inner
```

```
f = outer()
print(f())
```

- A)NameError
- B)10
- C)None
- D)15

Q6. What will be the output?

```
def fun(x):
    try:
        if x < 0:
            raise ValueError("negative")
        return x
    except ValueError:
        return 100
    finally:
```



Q13. What happens here?

```
class MyError(Exception):  
    pass
```

```
def test():  
    raise MyError("Something went  
wrong")
```

```
try:  
    test()  
except MyError as e:  
    print(type(e).__name__)
```

- A)MyError
- B)Exception
- C)TypeError
- D)Something went wrong

Q14. What is the output?

```
def fun():  
    try:  
        return 10  
    finally:  
        return 20
```

```
print(fun())  
A)RuntimeError  
B)10  
C)None  
D)20
```

Q15. What is the output?

```
f = lambda x: x + 5
```

```
print(f(10))  
A)15  
B>Error  
C)10  
D)5
```

Q16. What is the output?

```
numbers = [1, 2, 3, 4, 5]  
  
result = list(  
    map(  
        lambda x: x * 2,  
        filter(lambda x: x % 2 == 0,  
numbers)
```

```
)  
)  
  
print(result)
```

- A)[1, 3, 5]
- B)[4, 8]
- C)[2, 4]
- D)[2, 4, 6, 8, 10]

Q17. What will be printed?

```
try:  
    print(10 / 0)  
except ZeroDivisionError:  
    print("A")  
except Exception:  
    print("B")
```

- A)A B
- B)B
- C)Nothing
- D)A

Q18. What happens when this code runs?

```
def first():  
    second()
```

```
def second():  
    third()
```

```
def third():  
    raise RuntimeError("Failure")
```

```
try:  
    first()  
except RuntimeError:  
    print("Handled")  
A)Handled  
B)RuntimeError cannot propagate through  
functions  
C)TypeError  
D)NameError
```

Q19. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```



```
def counter():
    nonlocal count
    count += 1
    return count
```

```
return counter
```

```
a = make_counter()
b = make_counter()
```

```
print(a())
print(a())
print(b())
print(a())
```

A)1

1

1

1

B)1

2

3

4

C)0

1

0

2

D)1

2

1

3

Q27. What will be printed?

```
def fun(x=[]):
    x.append(10)
    return x
```

```
a = fun()
b = fun()
```

```
print(a)
print(b)
```

A)[10, 10]

[10]

B>Error

C)[10]

[10]

D)[10]

[10, 10]

Q28. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

A)6.0

B)NameError

C)36

D)6

Q29. What will be printed?

```
class InvalidAgeError(Exception):
    pass
```

```
def check_age(age):
```

```
    if age < 18:
```

```
        raise InvalidAgeError("Age is
too low")
```

```
    return "Allowed"
```

```
try:
```

```
    print(check_age(15))
```

```
except InvalidAgeError as e:
```

```
    print(type(e).__name__)
```

```
    print(e)
```

A)Nothing, because custom exceptions cannot be caught

B)Exception

Age is too low

C)InvalidAgeError

Age is too low

D)InvalidAgeError

15

Q30. if test.py has

```
print("A")
```

```
if __name__ == "__main__":
```

```
    print("B")
```

If test.py is executed directly, what will be printed?

A)A followed by B

B)A

C)Nothing

D)B



```
def fun(x):
```

```
    x += 10
```

```
    return x
```

```
x = 5
```

```
y = fun(x)
```

```
print(x, y)
```

A)15 5

B)15 15

C)5 5

D)5 15

Q38. Suppose the current directory contains a file named random.py.

What potential problem can occur with:

```
import random
```

A)Python will always reject it

B)The local file can shadow the intended standard-library module

C)random cannot be imported

D)Python automatically renames the local file

Q39. What is the output?

```
try:
```

```
    print(10 / 0)
```

```
except Exception:
```

```
    print("A")
```

```
except ZeroDivisionError:
```

```
    print("B")
```

A)SyntaxError

B)A B

C)B

D)A

Q40. What will be printed?

```
try:
```

```
    x = int("10")
```

```
except ValueError:
```

```
    print("A")
```

```
else:
```

```
    print("B")
```

```
finally:
```

```
    print("C")
```

A)B C

B)A

C)B

D)A C

Q41. What happens?

```
def fun(a, b):
```

```
    return a + b
```

```
print(fun(10, a=20))
```

A)30

B)20

C)TypeError

D)SyntaxError

Q42. What will happen?

```
def fun(a, b=10):
```

```
    return a + b
```

```
print(fun(b=5, a=20))
```

A)25

B)15

C)TypeError

D)SyntaxError

Q43. What will be printed?

```
def fun(a, b):
```

```
    return a + b
```

```
print(fun(10, b=20))
```

A)SyntaxError

B)20

C)TypeError

D)30

Q44. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":
```

```
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)Nothing

B)A and B

C)B

D)A



Full Marks:50

SET:A

Time: 1Hour 10Minutes

Q1. What will normally happen?

```
import math
import math
```

- A)The module is normally loaded and executed twice
- B)The module is normally loaded once and reused
- C)SyntaxError
- D)ImportError

Q2. What happens here?

```
from math import sqrt
```

```
print(sqrt(36))
```

- A)36
- B)6.0
- C)6
- D)NameError

Q3. What happens here?

```
class MyError(Exception):
    pass
```

```
def test():
    raise MyError("Something went wrong")
```

```
try:
    test()
except MyError as e:
    print(type(e).__name__)
```

- A)Exception
- B)TypeError
- C)Something went wrong
- D)MyError

Q4. What is the output?

```
try:
    x = int("abc")
except ValueError:
    print("A")
```

```
else:
    print("B")
finally:
    print("C")
```

- A)B
- B)A
- C)A C
- D)B C

Q5. Why is

```
try:
    print(10 / 0)
except Exception:
    print("A")
except ZeroDivisionError:
    print("B")
codes's second handler never reached?
```

- A)ZeroDivisionError occurs before Exception
- B)except blocks execute randomly
- C)Exception is a superclass of ZeroDivisionError
- D)ZeroDivisionError is not an exception

Q6. What will happen?

```
def fun(a, b=10):
    return a + b
```

```
print(fun(b=5, a=20))
```

- A)TypeError
- B)25
- C)15
- D)SyntaxError

Q7. if test.py has
print("A")

```
if __name__ == "__main__":
    print("B")
```

If test.py is executed directly, what will be printed?

- A)A followed by B
- B)B



Q15. What will be the output?

```
import math
```

```
print(math.sqrt(25))
```

- A) sqrt(25)
- B) 5.0
- C) 5
- D) 25

Q16. What will be printed?

```
x = 10
```

```
f = lambda: x
```

```
x = 20
```

```
print(f())
```

- A) None
- B) 10
- C) NameError
- D) 20

Q17. What will be printed?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        print(x)
```

```
    x = 30  
    inner()
```

```
outer()
```

- A) 20
- B) NameError
- C) 10
- D) 30

Q18. What will be printed?

```
def fun():  
    print("A")  
    return  
    print("B")
```

```
fun()
```

- A) B
- B) Nothing
- C) A B
- D) A

Q19. What will be the output?

```
x = 10
```

```
def outer():  
    x = 20
```

```
    def inner():  
        global x  
        x = 30
```

```
    inner()  
    print(x)
```

```
outer()  
print(x)
```

- A) 30
- 30
- B) 20
- 10
- C) 30
- 20
- D) 20
- 30

Q20. What is the output?

```
numbers = [1, 2, 3, 4, 5]
```

```
result = list(  
    map(  
        lambda x: x * 2,  
        filter(lambda x: x % 2 == 0,  
            numbers)  
    )  
)
```

```
print(result)
```

- A) [1, 3, 5]
- B) [2, 4]
- C) [4, 8]
- D) [2, 4, 6, 8, 10]

Q21. What is the output?

```
try:
```



```
return n * fun(n)
```

```
print(fun(3))
```

- A)TypeError
- B)3
- C)RecursionError
- D)6

Q28. What will happen?

```
def outer():
```

```
    x = 10
```

```
    def inner():
```

```
        nonlocal y
```

```
        y = 20
```

```
    inner()
```

```
outer()
```

- A)NameError
- B)SyntaxError
- C)20
- D)10

Q29. What does the following function return?

```
def fun():
```

```
    print("Hello")
```

```
x = fun()
```

```
print(x)
```

- A>Error
- B>Hello None
- C)None
- D>Hello

Q30. What happens?

```
def fun(a, b):
```

```
    return a + b
```

```
print(fun(10, a=20))
```

- A)SyntaxError
- B)20
- C)30
- D)TypeError

Q31. What is the output?

```
def fun(x):
```

```
    x += 10
```

```
    return x
```

```
x = 5
```

```
y = fun(x)
```

```
print(x, y)
```

- A)15 5
- B)5 5
- C)5 15
- D)15 15

Q32. What is the major difference between the following?

```
import math
```

```
and
```

```
from math import sqrt
```

- A)First provides the module namespace; second imports sqrt directly
- B)Both import only sqrt
- C)First imports only sqrt
- D)There is no difference

Q33. What will be printed?

```
class InvalidAgeError(Exception):
```

```
    pass
```

```
def check_age(age):
```

```
    if age < 18:
```

```
        raise InvalidAgeError("Age is too low")
    return "Allowed"
```

```
try:
```

```
    print(check_age(15))
```

```
except InvalidAgeError as e:
```

```
    print(type(e).__name__)
```

```
    print(e)
```

- A)Exception
- Age is too low
- B)InvalidAgeError
- 15



B)50

C)NameError

D)10

Q41. What is the output?

```
def fun(x):  
    if x == 0:  
        return  
    return x + fun(x - 1)
```

```
print(fun(3))
```

A)6

B)3

C)None

D)5

Q42. What will be printed?

```
try:  
    x = int("10")  
except ValueError:  
    print("A")  
else:  
    print("B")  
finally:  
    print("C")
```

A)A C

B)B

C)A

D)B C

Q43. Suppose test.py contains:

```
print("A")
```

```
if __name__ == "__main__":  
    print("B")
```

If another Python program executes:

```
import test
```

what will normally be printed?

A)Nothing

B)A and B

C)A

D)B

Q44. Suppose module_a.py contains:

```
print("Module loaded")
```

```
value = 10
```

And another file contains:

```
import module_a  
import module_a
```

```
print(module_a.value)
```

Assuming both imports occur in the same Python process, what is normally printed?

A)Module loaded

Module loaded

10

B)ImportError

C)10

10

D)Module loaded

10

Q45. What happens when this code runs?

```
def first():  
    second()
```

```
def second():  
    third()
```

```
def third():  
    raise RuntimeError("Failure")
```

```
try:  
    first()  
except RuntimeError:  
    print("Handled")
```

A)Handled

B)NameError

C)RuntimeError cannot propagate through functions

D)TypeError

Q46. Which object keeps track of modules that have already been imported during the current Python process?

A)sys.path

B).__module__

