spec-kit-skills
Technical Reference Manual

Version 0.2.0

Harness Engineering for AI Coding Agents

Jihoon Choi

March 2026

https://github.com/coolhero/spec-kit-skills

Built with Claude Code — the same tool this project is designed for.

Contents

I Vision and Philosophy **3**

1 The Problem Space **5**
1.1 Why Agents Need Harnesses, Not Just Prompts . . . 5
1.2 The Gap Between Capable and Controllable . . . 5
1.3 Real Failure Stories . . . 6
1.3.1 The "Build Passes" Trap . . . 6
1.3.2 The Context Compression Disaster . . . 6
1.3.3 The Cross-Feature Integration Failure . . . 6
1.3.4 The Silent SDK Failure . . . 6
1.4 Why This Matters More as Agents Get Smarter . . . 6
1.5 Defining the Field: Software Engineering for Agents . . . 7
1.6 The Four Skills at a Glance . . . 7
1.7 Terminology . . . 7

2 Three Foundational Principles **9**
2.1 P1: Context Continuity . . . 9
2.1.1 P1-a: Domain Profile as First-Class Citizen . . . 9
2.1.2 P1-b: Artifact Separation (Source Code Fidelity) . . . 10
2.1.3 P1-c: Cross-Feature Memory (GEL) . . . 11
2.1.4 Context Reset Protocol . . . 11
2.2 P2: Enforce, Don't Reference . . . 11
2.2.1 Five Evasion Patterns . . . 11
2.2.2 The Three-Generation Evolution . . . 12
2.2.3 The Three-Layer Enforcement Pattern . . . 12
2.2.4 The Inverse Proximity Law . . . 13
2.3 P3: File over Memory . . . 13

3 The Honest Assessment **15**
3.1 Strengths . . . 15
3.1.1 First Serious Attempt at Agent Harness Engineering . . . 15
3.1.2 Real Failure Catalog . . . 15
3.1.3 Engineering Depth . . . 15
3.1.4 Composability . . . 15
3.2 Limitations . . . 15
3.2.1 Production Validation Gap . . . 15
3.2.2 Complexity Risk . . . 16
3.2.3 Model Evolution Dependency . . . 16
3.2.4 Single-Agent Assumption . . . 16

3.3 The Broader Perspective . . . 16
3.4 Future Directions . . . 16
3.5 Open Questions . . . 17
3.6 Application Checklist . . . 17
3.6.1 P2 Corollary: Delegate, Don't Skip . . . 18

II Architecture **19**

4 5-Axis Domain Profile **21**
4.1 Axis 1: Interface . . . 21
4.2 Axis 2: Concern . . . 22
4.3 Axis 3: Archetype . . . 22
4.4 Axis 4: Foundation . . . 23
4.5 Axis 5: Context . . . 23
4.6 How Axes Compose: Cross-Concern Integration . . . 24
4.7 Composition Example: Full Walkthrough . . . 24
4.8 Profiling Framework vs. Profiling Result . . . 25
4.9 Evolution History . . . 25

5 Section System **27**
5.1 S-Family: Pipeline Execution Rules (S0–S9) . . . 27
5.2 A-Family: Archetype Philosophy (A0–A5) . . . 27
5.3 R-Family: Reverse-Spec Analysis (R1–R5) . . . 28
5.4 F-Family: Foundation Platform (F0–F8) . . . 28
5.5 The Philosophy Behind the Division . . . 28

6 Module Loading and Context Injection **31**
6.1 The 8-Step Loading Order . . . 31
6.2 Per-Step Injection Maps . . . 31
6.3 Context Budget Mathematics . . . 32
6.4 Merge Semantics . . . 32
6.5 Graceful Degradation . . . 32

7 Pipeline Integrity Guards **33**
7.1 Guard 1: Guideline to Gate Escalation . . . 33
7.2 Guard 2: Static Is Not Runtime Verification . . . 33
7.3 Guard 3: Cross-Stage Trust Breakers . . . 33
7.4 Guard 4: Granularity Alignment . . . 34
7.5 Guard 5: Environment Parity . . . 34
7.6 Guard 6: Cross-Feature Interface Verification . . . 34
7.7 Guard 7: Rebuild Fidelity Chain . . . 34
7.8 Using the Guards . . . 34
7.8.1 Guard Interaction Example . . . 34
7.9 Bug Fix Severity System . . . 35

8 Global Evolution Layer **37**
8.1 Core Artifacts . . . 37
8.2 Data Flow Example: F001 to F003 . . . 37
8.3 The State Machine: sdd-state.md . . . 38
8.3.1 State Validation . . . 39
8.3.2 Rebuild Configuration . . . 39
8.4 Context Injection Rules . . . 39

8.4.1 Shared Patterns . . . 39
8.4.2 Per-Command Injection Files . . . 40
8.4.3 What Happens During Context Assembly . . . 40
8.4.4 Scale Modifier Enforcement . . . 40

III Skills Reference **43**

9 code-explore **45**
9.1 Commands . . . 45
9.2 Orient: Structured Project Scan . . . 45
9.3 Five Trace Strategies . . . 45
9.4 Synthesis: From Understanding to Action . . . 46
9.5 Context-Aware Mode . . . 46
9.6 Entity Conflict Resolution . . . 46
9.7 Software Catalog . . . 47
9.8 Practical Tips for Effective Exploration . . . 47

10 reverse-spec **49**
10.1 Five Phases . . . 49
10.2 Source Behavior Inventory (SBI) . . . 49
10.3 spec-draft Generation . . . 50
10.4 The –from-explore Mode . . . 50
10.5 When to Use code-explore vs. reverse-spec . . . 50
10.6 Adoption Mode . . . 50
10.7 Runtime Exploration (Phase 1.5) . . . 50
10.8 Handling Large Codebases . . . 51

11 smart-sdd **53**
11.1 Full Pipeline . . . 53
11.2 The 4-Step Common Protocol . . . 53
11.3 The Brief: 6-Perspective Validation . . . 54
11.4 The 4-Phase Verify . . . 54
11.5 SC Preservation (add –to) . . . 54
11.6 Pipeline Step Detail . . . 54
11.6.1 Constitution . . . 54
11.6.2 Specify . . . 55
11.6.3 Plan . . . 55
11.6.4 Tasks . . . 55
11.6.5 Analyze . . . 55
11.6.6 Implement . . . 55
11.6.7 Verify . . . 55
11.6.8 Merge . . . 55
11.7 Step-Back Navigation . . . 56
11.8 Adopt Pipeline . . . 56

12 domain-extend **57**
12.1 Six Commands . . . 57
12.2 Module Creation Workflow . . . 57
12.3 Convention Hierarchy . . . 57

IV Domain Module System 59

13 Module Architecture 61
13.1 Triple Structure: Shared, Reverse-Spec, Smart-SDD . . . 61
13.2 Key System Files . . . 61
13.3 Convention over Configuration . . . 61
13.4 Module Validation . . . 62
13.5 Module Lifecycle . . . 62

14 Complete Module Inventory 63
14.1 Interfaces (10 modules) . . . 63
14.2 Concerns (48 modules) . . . 63
14.3 Archetypes (15 modules) . . . 64
14.4 Context Modes (4 modules) . . . 64
14.5 Context Modifiers (extensible) . . . 64
14.6 Foundations (40+ modules) . . . 64

15 Cross-Concern Integration 65
15.1 Rule Structure . . . 65
15.2 Selected Integration Rules . . . 65
15.3 Scale Modifier Effects . . . 66

V Failure Patterns and Lessons 67

16 19 Gap Patterns 69
16.1 G1: Build Pass Does Not Mean Feature Works . . . 69
16.2 G2: Foundation Absence . . . 69
16.3 G3: Source Information Gap . . . 69
16.4 G4: Async/Temporal Pattern Omission . . . 69
16.5 G5: Context Compaction Procedure Loss . . . 70
16.6 G6: Runtime Behavior Verification Gap . . . 70
16.7 G7: Cross-Feature Integration Contract Gap . . . 70
16.8 G8: i18n Key Coverage Gap . . . 70
16.9 G9: SDK API Contract Gap . . . 70
16.10 G10: UI Interaction Over-exposure . . . 70
16.11 G11: Verify Checks Code Existence, Not Runtime Behavior . . . 70
16.12 G12: Ad-hoc Domain Philosophy . . . 70
16.13 G13: Framework Philosophy vs. Operational Checklists . . . 70
16.14 G14: Metrics-Only Reports Miss the "Why" . . . 71
16.15 G15: Skill Tool Return Overrides Pipeline Instructions . . . 71
16.16 G16: Path Ambiguity in Multi-Directory Operations . . . 71
16.17 G17: Context Continuity Failure . . . 71
16.18 G18: Enforce, Don't Reference . . . 71
16.19 G19: Domain Profile Set-and-Forget . . . 71
16.20 Coverage Summary . . . 72
16.21 Countermeasure Evolution Timeline . . . 72

17 Key Lessons 75
17.1 Theme A: How Agents Interpret Instructions . . . 75
17.2 Theme B: Context Window and Instruction Placement . . . 75
17.3 Theme C: Build and Verification Traps . . . 75
17.4 Theme D: Cross-System Coordination . . . 76

17.5 Theme E: Pipeline Architecture . . . 76
17.6 Theme F: Verification Completeness . . . 76
17.7 Theme G: Pipeline Architecture Patterns . . . 76
17.8 Theme H: Context Efficiency . . . 76

18 Agent Behavioral Patterns **79**
18.1 Five Evasion Patterns (Detailed) . . . 79
18.2 Pipeline Completion Bias . . . 79
18.3 The "Helpful but Wrong" Problem . . . 79
18.4 Why Stronger Language Does Not Help . . . 79
18.5 The Sub-Skill Trap . . . 80
18.6 Practical Mitigation Strategies . . . 80
18.7 The Paradox of Agent Skill Design . . . 80
18.8 Countermeasure Design Patterns . . . 81
18.8.1 The Output Verification Pattern . . . 81
18.8.2 The State Recovery Pattern . . . 81
18.8.3 The Catch-All Fallback Pattern . . . 81
18.8.4 The Inline Duplication Pattern . . . 82

VI Practical Guide **83**

19 Getting Started **85**
19.1 Prerequisites . . . 85
19.2 Installation . . . 85
19.3 First Project Walkthrough: Greenfield . . . 85
19.4 Decision Tree: Which Command Should I Use? . . . 86
19.5 Understanding the Output Structure . . . 86
19.6 CLI Reference . . . 87

20 Scenario Walkthroughs **89**
20.1 Scenario 1: Greenfield Idea . . . 89
20.2 Scenario 2: Brownfield Rebuild . . . 89
20.3 Scenario 3: Adoption . . . 89
20.4 Scenario 4: Exploration to Build . . . 90
20.5 Scenario 5: Mid-Pipeline Investigation . . . 90
20.6 Scenario 6: Domain Customization . . . 90

21 Advanced Topics **91**
21.1 Context Reset Protocol . . . 91
21.2 Mid-Pipeline Step-Back . . . 91
21.3 Cross-Feature Impact Analysis . . . 91
21.4 Multi-Ecosystem Support . . . 92
21.5 Skill Development Guidelines . . . 92
21.5.1 Skill Structure . . . 92
21.5.2 Enforcement Checklist . . . 92
21.5.3 State Management . . . 92
21.5.4 Testing Protocol . . . 92
21.6 Comparison with Other Approaches . . . 93
21.6.1 Prompt Libraries . . . 93
21.6.2 Workflow Automation (n8n, Zapier) . . . 93
21.6.3 Custom Agent Frameworks (LangChain, AutoGPT) . . . 93

21.6.4 IDE AI Features (Cursor, Copilot Workspace) 93

A Complete File Inventory **95**
A.1 Root Files 95
A.2 Complete Concern Inventory 95
A.3 Skill File Counts 97

B Scenario Catalog **99**
B.1 A: Understand Code (5 scenarios) 99
B.2 B: Start New Project (5 scenarios) 99
B.3 C: Apply SDD to Existing Code (5 scenarios) 99
B.4 D: Rewrite from Scratch (3 scenarios) 100
B.5 E: Revise and Iterate (6 scenarios) 100
B.6 F: Manage Multiple Features (2 scenarios) 100
B.7 G: Check Status (2 scenarios) 100
B.8 H: Advanced and Customization (10 scenarios) 100
B.9 Scenario Summary by Entry Point 101

C Quick Reference Card **103**
C.1 Essential Commands 103
C.2 Common Flags 104

D Glossary **105**

E Detailed Injection Map Reference **111**
E.1 specify Injection 111
E.2 plan Injection 112
E.3 implement Injection 112
E.4 verify Injection 113

F Design Decision History (Selected) **115**
F.1 Context Optimization Phase 1 (2026-03-23) 115
F.2 Architectural Rename: Scenario to Context (2026-03-23) 115
F.3 Simulation-Driven Gap Fixes (2026-03-23) 115
F.4 3-Axis to 5-Axis Evolution 116

Colophon **117**

List of Tables

1.1 Skill comparison . . . 7

3.1 Foundational principle checklist . . . 18

4.1 Interface modules and their primary contributions . . . 22
4.2 Selected Cross-Concern Integration Rules . . . 24

5.1 S-Family section definitions . . . 27
5.2 A-Family section definitions . . . 28
5.3 R-Family section definitions . . . 28
5.4 F-Family section definitions . . . 28

6.1 Per-command section loading . . . 31
6.2 Graceful degradation rules . . . 32

7.1 Bug Fix Severity Classification . . . 35

8.1 Rebuild configuration parameters . . . 39
8.2 Injection file mapping . . . 40
8.3 Scale adjustment examples . . . 41

10.1 Choosing between code-explore and reverse-spec . . . 50

16.1 Gap pattern coverage estimates . . . 72

19.1 Command reference . . . 87

B.1 Scenario distribution . . . 101

Part I

Vision and Philosophy

Chapter 1

The Problem Space

1.1 Why Agents Need Harnesses, Not Just Prompts

Here is a scenario every developer using AI coding tools has experienced: you ask your AI agent to add user authentication. It generates four hundred lines of code in thirty seconds. You review it. It looks reasonable. You merge it.

Three weeks later, you discover that it used JWT when your team standardized on sessions, that it stored tokens in `localStorage` (exposing you to XSS attacks), that it created a `User` model that conflicts with the one Feature 2 already defined, and that the error handling covers the happy path and literally nothing else.

The code *worked*. It even had tests. But it was not *your* code—it was code that happened to be in your repository.

This is the gap between AI capability and developer control. A prompt is a one-shot instruction. It carries no memory of what Feature 1 decided, no awareness of your team's architectural patterns, no understanding that your project is an Electron app (not a web app) and that this changes how state management works.

What you actually need is not a better prompt but a **system** that:

1. **Remembers** across Features—Feature 3 knows Feature 1's data models.
2. **Adapts** to your project type—an Electron app gets different rules than a REST API.
3. **Enforces** quality gates—the agent cannot skip verification just because the build passed.
4. **Documents** decisions in files, not in the agent's memory—which evaporates between sessions.

This is what we call **Harness Engineering**—building structured systems that channel AI agent behavior toward reliable outcomes.

1.2 The Gap Between Capable and Controllable

Agentic coding tools have crossed a threshold. Claude Code, Cursor, Copilot Workspace, Devin—they do not just autocomplete lines; they plan, implement, test, and iterate across entire Features.

But the smarter the agent, the more damage it can do unsupervised. A basic autocomplete suggestion is easy to review—it is one line. An agentic workflow that scaffolds an entire

authentication system across twelve files requires a different kind of review. You need to trust the *process* that generated it, not just the output.

This is where the industry is heading. Not "AI replaces developers" but "developers build harnesses for AI." The value shifts from *writing code* to *designing the system that writes code*.

1.3 Real Failure Stories

The failures that motivated `spec-kit-skills` are not hypothetical. Each emerged from real pipeline runs during the project's development—over 500 commits across three weeks, cataloging 19 recurring failure patterns and 50+ specific incidents.

1.3.1 The "Build Passes" Trap

The build passed. TypeScript was clean. Tests were green. And the app was completely unusable—infinite re-renders caused by a state selector creating new object references every frame, scroll broken during streaming, the UI locked in a death spiral.

A Zustand state selector created new array/object references on every render. Build tools check syntax and types. Tests check isolated units. Neither checks runtime state behavior, animation timing, or interaction between live components.

1.3.2 The Context Compression Disaster

After five Features were correctly verified with full Playwright UI checks, Feature 6's verification skipped Playwright entirely. Context compression had eaten the verification instructions. Same agent, same skill, same pipeline—just a longer conversation. The agent ran `npm run build`, saw zero errors, reported "verify complete," and moved on. Four phases of verification were silently skipped.

1.3.3 The Cross-Feature Integration Failure

Feature A expected `{mcpMode, mcpServers}` on an object. Feature B stored `{mcpEnabled, servers}`. Different names, different structure. The spec did not define the contract, the implementation did not build a bridge, and verification did not check compatibility.

1.3.4 The Silent SDK Failure

An AI SDK's `tool()` function expects `{execute: async () => {...}}`. The agent passed `{type: "mcp", serverId: "xxx"}`—metadata only, no execute function. The SDK silently accepted it. The AI responded without tool access. Everything "worked"—except the tools.

1.4 Why This Matters More as Agents Get Smarter

A more capable agent without guardrails produces more *impressive-looking* output that is *harder to review*. When the agent generates twelve files of authentication code in thirty seconds, you cannot review each line. You have to trust the process. And the process is only trustworthy if it has structural guarantees—gates that block, registries that remember, state machines that track.

1.5 Defining the Field: Software Engineering for Agents

spec-kit-skills represents one of the first serious attempts at what might be called **software engineering for agents**—not the software agents write, but the software that governs *how* agents write software. The distinction is important:

- Traditional software engineering focuses on code quality, architecture, testing, deployment.
- Agent software engineering focuses on behavioral control, context management, enforcement mechanisms, and failure pattern catalogs.

The skills, patterns, and failure catalogs documented in this manual are the raw material for this emerging discipline. They answer questions that did not exist three years ago: How do you enforce a rule when the enforcer is an LLM that optimizes for completion? How do you maintain cross-session memory when your runtime has no persistent state? How do you verify behavioral compliance when your "compiler" is a language model?

1.6 The Four Skills at a Glance

Before diving into principles and architecture, here is a functional overview of the four skills and how they connect:

```
UNDERSTAND:  /code-explore   orient -> trace -> synthesis
ANALYZE:     /reverse-spec   scan -> classify -> extract -> generate
BUILD:       /smart-sdd      init -> add -> specify -> plan -> tasks
                              -> analyze -> implement -> verify -> merge
EXTEND:      /domain-extend  browse -> detect -> extend -> validate
```

The Four Skills Pipeline

The first three skills form a sequential pipeline. The fourth skill (`/domain-extend`) wraps around the pipeline—it enriches the domain vocabulary that the other three skills draw from.

Table 1.1: Skill comparison

Skill	Input	Output	Style
code-explore	Source code path	Architecture maps, traces, Feature candidates	Interactive
reverse-spec	Source code path	GEL artifacts (roadmap, registries, spec-drafts)	Automated
smart-sdd	Idea, PRD, or GEL artifacts	Working code with specs and plans	Pipeline
domain-extend	Gaps, ADRs, style guides	New domain modules	Toolkit

1.7 Terminology

Key terms used throughout this manual:

Feature A self-contained unit of functionality (e.g., authentication, task CRUD, dashboard). Each Feature is independently specifiable, implementable, and verifiable.

Pipeline The sequential execution of steps for one Feature: specify → plan → tasks → implement → verify.

GEL Global Evolution Layer—project-wide artifacts that carry information across Features.

Domain Profile The 5-axis type system that captures a project's characteristics.

Brief The structured output of the `add` consultation that defines a Feature.

HARD STOP A blocking checkpoint requiring explicit user approval.

SC Success Criterion—a measurable condition for Feature completion.

SBI Source Behavior Inventory—a catalog of behaviors in existing code.

Chapter 2

Three Foundational Principles

Every design decision in spec-kit-skills traces back to three principles. They were not designed upfront—they were discovered through hundreds of failed pipeline runs. They apply to any system where an LLM is the execution engine and natural language is the instruction set.

```
        P1. Context Continuity (what to protect)
       /          |           \
Domain Profile  Source Code   Cross-Feature
full pipeline   preservation  GEL memory
      \           |           /
     P2. Enforce, Don't Reference (how to protect)
                 |
     P3. File over Memory (where to store)
```

Principle Hierarchy

2.1 P1: Context Continuity

> *Information must flow continuously through every pipeline stage. Nothing gets lost at transitions.*

This sounds obvious until you realize what "transitions" means for an AI agent: between Features (Feature 3 starts with a clean context), between pipeline stages (specify to plan may lose detail), and between sessions (the user closes their laptop overnight). Each transition is a potential information loss point.

2.1.1 P1-a: Domain Profile as First-Class Citizen

The Domain Profile (5 axes: Interface, Concern, Archetype, Foundation, Context) is not a one-time configuration. It actively shapes every pipeline stage—which probes get asked during `add`, which rules activate during `specify`, which verification steps run during `verify`.

If the profile says `gui + realtime`, then `specify` generates Success Criteria for optimistic UI updates and reconnection handling. If it says `cli + resilience`, completely different SCs emerge. The Domain Profile is a living context that influences behavior at every step.

The Section System — How Domain Knowledge Becomes Pipeline Rules

Each domain module is divided into **numbered sections**, and each section feeds a specific pipeline stage. Think of it like a recipe card with labeled tabs — the "ingredients" tab is read when shopping, the "cooking steps" tab is read when cooking, not before.

- **S0** (Signal Keywords) — "How do I detect this domain?" Read at `init`.
- **S1** (SC Generation Rules) — "What scenarios must be tested?" Read at `specify`.
- **S5** (Elaboration Probes) — "What should I ask the user?" Read at `add` (Brief).
- **S7** (Bug Prevention) — "What mistakes are common here?" Read at `implement/verify`.

Archetypes use A-sections (A0–A5) instead, and reverse-spec uses R-sections (R1–R5). The full schema is in Chapter 5. For now, just remember: **the number tells you when it's used in the pipeline**.

This design emerged from a practical problem: early versions loaded entire module files at every stage, wasting 60% of the context window on irrelevant content. Splitting modules into numbered sections enabled *lazy loading* — each stage reads only the tabs it needs. The numbering was not pre-planned from a theoretical framework; it grew organically as new pipeline stages needed new rule types.

The mechanism is concrete: domain modules have standardized sections (S1 for SC generation rules, S5 for elaboration probes, S7 for bug prevention). When the pipeline runs, the injection file loads relevant modules and merges their sections. An `ai-assistant` archetype adds A2 (SC extensions for token management). A `gui` interface adds S6 (UI testing integration). They accumulate.

The real power emerges when modules *combine*. The resolver detects specific combinations and activates Cross-Concern Integration Rules—62 combination patterns defined in `_resolver.md`. When a project includes both `gui` and `realtime`, the resolver triggers emergent rules that neither module alone contains: optimistic update patterns, reconnection UI states, and "stale UI after reconnect" prevention.

Failure Without P1-a

Project had `gui + realtime` active, triggering Cross-Concern Integration Rules for optimistic update + reconnection UI. But `specify` never loaded the combined rules. `plan` never referenced them. `implement` never saw the streaming-specific requirements. The Domain Profile was correctly detected but never actually influenced behavior.

2.1.2 P1-b: Artifact Separation (Source Code Fidelity)

In one rebuild, the source application had a `ModelSelector` component—a dropdown that let users pick an AI model, with embedding dimensions auto-calculated based on the selection. The Source Behavior Inventory correctly recorded this. But by the time the pipeline reached `implement`—several hundred messages after the initial code analysis—all the rich detail about UI controls had been compressed away. Three plain text inputs appeared in the implementation. No dropdown, no auto-calculation.

The fix was twofold:

1. Specs describe *what to build*, never *where it came from*. Source analysis stays in reverse-spec artifacts (`pre-context.md`). Smart-sdd specs (`spec.md`) are source-agnostic.
2. A **Source Code Reference Injection** at the implement stage—a BLOCKING gate that forces the agent to re-read `pre-context.md` before writing any code.

The spec says "user selects a model and provides embedding dimensions." The pre-context says "source used dropdown with auto-calculated dimensions." When implement reads both, it builds a dropdown with auto-calculation while remaining free to change the underlying architecture.

2.1.3 P1-c: Cross-Feature Memory (GEL)

The Global Evolution Layer consists of files that carry information across Features:

- `entity-registry.md`—all data models with fields, types, relationships
- `api-registry.md`—all endpoints with contracts
- `sdd-state.md`—project state machine
- `roadmap.md`—Feature dependency graph
- `pre-context.md` (per Feature)—detailed requirements context

Without GEL, in one early pipeline run, Feature 1 defined a User entity with `id, email, displayName, role`. Feature 3 invented its own: `userId, name, userType`. Feature 5 referenced yet another with `username, permissions`. Integration became a week-long renaming exercise.

2.1.4 Context Reset Protocol

Counterintuitively, if everything is in files, you should periodically *throw away* the conversation context. After completing a Feature, the agent's context window is filled with conversation history. Starting the next Feature with all that baggage means less room for new injection and review.

The protocol: clear context between Features. The agent re-reads `sdd-state.md`, loads updated registries, and starts fresh. Nothing is lost because everything was written to files.

When NOT to Reset

Never reset mid-Feature (between specify and plan). Inter-step continuity requires unbroken flow. Reset only at Feature boundaries, skill transitions, or after context compaction warnings.

2.2 P2: Enforce, Don't Reference

> *"See X for details" has zero enforcement power. Rules must be enforced at the point of execution, not referenced from a distance.*

In normal software, you write a function once and call it from everywhere. DRY—Don't Repeat Yourself. But in agent skills, **DRY kills compliance**.

When the agent sees "See verify-phases.md for the full verification protocol," it processes this as "there's more info available, but I have enough context to proceed." It runs build + TypeScript, reports "verify complete," and moves on.

2.2.1 Five Evasion Patterns

Agents do not just ignore rules—they *rationalize* around them:

1. **The fabricated excuse**: "Health check passed, so HARD STOP verification is not needed for this Feature." The agent invented a concept ("health check") that existed nowhere in the skill files.
2. **The keyword downgrade**: Rules marked `MANDATORY` were treated as strong suggestions and skipped under context pressure.
3. **The explicit ignore**: "Do NOT skip under any circumstances" was skipped when context compression reduced it to a summary.
4. **The premature completion**: After implementing 5 of 7 tasks, the agent declared "implementation complete"—the remaining 2 tasks had vanished from compressed context.
5. **The silent substitution**: Instead of executing the required 4-phase verification protocol, the agent substituted a simpler version: "build passes, TypeScript passes, therefore verified." It never announced the substitution. The user saw "verify complete" with a checkmark.

2.2.2 The Three-Generation Evolution

The fix evolved through three generations, each prompted by a real failure:

Generation 1: Guidelines. "You should verify all phases." Compliance: approximately 70%.

Generation 2: Warnings. "WARNING: Skipping verification will result in bugs." Compliance: approximately 85%.

Generation 3: BLOCKING gates. Structural barriers where the agent literally cannot produce the next output without completing the current step. Compliance: effectively 100%.

2.2.3 The Three-Layer Enforcement Pattern

Every critical rule in spec-kit-skills requires three layers:

1. **Inline instruction**—the rule appears directly at the execution point, not in a referenced file.
2. **Blocking gate**—not a warning ("you should verify") but a blocker ("BLOCKING: verification incomplete. Cannot proceed to merge.").
3. **Anti-pattern examples**—explicit **WRONG** and **RIGHT** patterns.

```
WRONG: Run build+TS, display "verify complete", proceed to merge
   -> 10 SCs unverified. Feature unreachable from UI.

RIGHT: Read verify-phases.md -> execute Phase 0-4 ->
   show SC coverage matrix -> AskUserQuestion
```

Anti-Pattern Example

This is why spec-kit-skills has what looks like redundant text. The HARD STOP re-ask instruction appears 30+ times across different files. Each occurrence is at a different execution point. Extracting it to a shared file would be "cleaner" code—and would be ignored by the agent.

2.2.4 The Inverse Proximity Law

The probability of an agent following an instruction is inversely proportional to its distance from the execution point. Rules at the top of a file are "documentation" by the time execution happens 200 lines later. Rules adjacent to the execution point are "working memory."

Implication: place rules where they will be executed, not where they are organizationally tidy. In agent skills, 30 inline repetitions beat 1 beautifully organized reference.

2.3 P3: File over Memory

> *Every intermediate artifact and state goes into a file. Never rely on agent memory.*

Three properties of the agent's context window make it unreliable for state:

- **Limited**—it gets compressed as the conversation grows. After 50 messages, early context is summarized or dropped.
- **Session-scoped**—when the session ends, everything is gone.
- **Non-inspectable**—you cannot see what the agent remembers. There is no `console.log(agent.memory`

Files have none of these problems. They are persistent, diffable (`git diff` shows exactly what changed), editable (you can manually fix a spec and re-run), and shareable (another agent or human can continue).

This is why `sdd-state.md` exists as a state machine file. When the agent resumes after compression or a new session, it reads the file, sees "F003 is at step implement, task 4/7," and continues.

Auditability Bonus

Because every state change is recorded in a file tracked by git, you get a complete audit trail for free. You can answer: "When was this entity changed? Which Feature introduced this API endpoint?" All answerable through `git log`.

Chapter 3

The Honest Assessment

3.1 Strengths

3.1.1 First Serious Attempt at Agent Harness Engineering

spec-kit-skills is not a prompt library or a workflow template. It is a **behavioral control system** for AI coding agents, built on three engineering principles and validated through 500+ commits of real pipeline runs. The distinction matters: prompt libraries optimize for capability; harness engineering optimizes for controllability.

3.1.2 Real Failure Catalog

The project includes 19 gap patterns and 57 specific lessons, each traced to a real incident. This is not theoretical—every countermeasure was motivated by an observed failure. The catalog itself is a contribution: these patterns apply to anyone building AI agent workflows, regardless of tooling.

3.1.3 Engineering Depth

The module system (48 concerns, 15 archetypes, 10 interfaces, 40+ foundations, 62 cross-concern integration rules) represents genuine domain engineering. Each module encodes expert knowledge about what matters for a specific project type—knowledge that would otherwise exist only in senior engineers' heads.

3.1.4 Composability

The four skills work independently or together. Use `/code-explore` alone to study a codebase. Use `/smart-sdd` alone for greenfield. Use all four for a full rebuild. Each produces persistent file artifacts. The pipeline reads files, not agent memory.

3.2 Limitations

3.2.1 Production Validation Gap

The system has been developed and tested through the process of building itself and through simulated pipelines on reference projects. It has not yet been validated on production codebases with real development teams over extended periods. The failure patterns and countermeasures are real, but the coverage claims need production confirmation.

3.2.2 Complexity Risk

Over 400 markdown files. The context budget analysis shows that a project with 5+ active concerns could exhaust 70%+ of context before project-specific content loads. The lazy-loading optimization (Section 6.2) mitigates this, but the fundamental tension between comprehensiveness and context efficiency remains.

3.2.3 Model Evolution Dependency

The enforcement mechanisms (inline repetition, blocking gates, anti-pattern examples) are calibrated for current-generation LLMs. As models improve at following instructions, some of these mechanisms may become unnecessary overhead. Conversely, as models become more capable at rationalization, new evasion patterns may emerge that require new countermeasures.

3.2.4 Single-Agent Assumption

The current architecture assumes a single agent executing the pipeline. Multi-agent scenarios (one agent for specify, another for implement) are not formally supported, though the file-based architecture (P3) provides a natural coordination mechanism.

3.3 The Broader Perspective

Throughout this project, a persistent tension emerges: AI agents are getting smarter every month, yet the need for structured control is not decreasing—it is increasing.

Why? Because a more capable agent without guardrails produces more *impressive-looking* output that is *harder to review*. When the agent generates 12 files in 30 seconds, you cannot review each line. You must trust the process. And the process is only trustworthy if it has structural guarantees.

This is the future of software development with AI: not "prompting better" but **harness engineering**. The developers who thrive in the age of agentic coding will not be the ones who write the best prompts. They will be the ones who build the best harnesses—the systems that channel AI capability toward reliable, reviewable, controllable outcomes.

The four principles that emerged from this project:

1. **Context Continuity**—information must flow forward without loss.
2. **Enforce, Don't Reference**—structural barriers, not suggestions.
3. **File over Memory**—persistent state, not ephemeral context.
4. **Delegate, Don't Skip**—when automation fails, ask the user.

These principles are not specific to spec-kit-skills. They apply to anyone building AI agent workflows, regardless of the tool, the model, or the domain.

3.4 Future Directions

1. **Production validation**—Real-team deployments with metrics on defect rates, rework frequency, and developer satisfaction. The most critical next step.

2. **Model-adaptive enforcement**—Dynamically adjusting enforcement intensity based on observed agent compliance rates. As models improve, some inline repetitions may become unnecessary overhead.

3. **Multi-agent support**—Formal handoff protocols when different agents handle different pipeline stages. The file-based architecture (P3) provides a natural coordination mechanism.

4. **Automated regression testing**—CI pipelines that verify agent behavioral compliance against the failure pattern catalog. Currently, behavioral testing requires manual pipeline execution.

5. **Community module ecosystem**—A registry where teams share domain modules, cross-concern rules, and org conventions. The convention-over-configuration architecture makes this feasible.

6. **Metrics and observability**—Pipeline-level metrics (SC coverage, verify depth, context budget utilization) to track harness effectiveness over time.

7. **Cross-model portability**—Testing the same skill files with different LLM providers to understand which enforcement mechanisms are model-specific vs. universal.

3.5 Open Questions

Several questions remain unanswered by the current project:

1. **Optimal enforcement intensity**: How much inline repetition is enough? At what point does adding more enforcement text become counterproductive (consuming context budget that could be used for project-specific content)?

2. **Generational stability**: Will the enforcement mechanisms calibrated for current models (Claude Opus 4.6) remain effective for future models? Or will new evasion patterns emerge?

3. **Team dynamics**: How does the Brief consultation work with teams of different sizes and expertise levels? Does the structured intake help junior developers or frustrate senior ones?

4. **Domain module completeness**: At what point does the module library reach "good enough" coverage? The current 48 concerns and 15 archetypes cover many common patterns, but every real project discovers gaps.

5. **Cost of comprehensiveness**: The 400+ file framework has a real context budget cost. Is there a simpler architecture that achieves 80% of the benefit at 20% of the complexity?

3.6 Application Checklist

When adding any new rule, gate, command, or skill to spec-kit-skills, the following questions must be answered:

Table 3.1: Foundational principle checklist

#	Principle	Question to Answer
1	P1-a	Is this rule conditionally activated by a Domain Profile axis? Or is it universal?
2	P1-b, P1-c	When this information passes to the next pipeline stage, is any detail lost?
3	P2	Does this rule have a BLOCKING gate + inline instruction + anti-pattern?
4	P3	Is the rule's result/state recorded in a file, or does it exist only in agent memory?
5	P2-delegate	If the agent cannot automate part of this, is the user explicitly asked?

3.6.1 P2 Corollary: Delegate, Don't Skip

When the agent encounters a verification it cannot automate (OS-native features, external API keys, hardware dependencies), the correct response is not "skip" but rather a specific request to the user:

```
WRONG: "Playwright limitation -> drag-and-drop skip"
  -> Untested. Bug ships silently.

RIGHT: AskUserQuestion "Please drag a file onto the upload zone.
       Does the status change from 'idle' to 'processing'?"
  -> User verifies. Result documented.

WRONG: "API key absent -> external-dep -> skip"
  -> Feature untested in real conditions.

RIGHT: AskUserQuestion "Please set your API key in Settings > Provider.
       After setup, I will auto-test embedding generation."
  -> User provides key. Agent tests. Real verification.
```

Delegation Examples

The difference: skipping is invisible technical debt that accumulates silently. Delegation is documented verification with a clear owner. Every verification item must end in one of three states: machine-verified, user-verified, or explicitly acknowledged as unverifiable. "Skipped because no automation path" is not a valid state.

Part II

Architecture

Chapter 4

5-Axis Domain Profile

The Domain Profile is the compositional type system of spec-kit-skills. It captures the fundamental characteristics of a project across five independent axes, each contributing rules that shape how the pipeline operates.

```
              Domain Profile
              |
INTERFACE --| What does the app expose?    -> gui, http-api, cli, ...
CONCERN ----| What cross-cutting patterns? -> auth, async-state, ipc, ...
ARCHETYPE --| What domain philosophy?      -> ai-assistant, microservice, ...
FOUNDATION -| What framework constraints?  -> React, Electron, Go, ...
CONTEXT ----| What project situation?       -> Mode + Scale + Modifiers
```

Domain Profile Structure

4.1 Axis 1: Interface

Definition: The surface through which users or systems interact with the application.

Available values: `gui`, `http-api`, `cli`, `tui`, `data-io`, `mobile`, `library`, `embedded`, `grpc`, `k8s-api`.

Detection: During `/smart-sdd init`, semantic keywords from user description are matched against S0 signal keywords. During `/reverse-spec`, R1 code pattern keywords identify interfaces from imports and file structures.

Pipeline impact: Interface determines SC generation patterns (S1), parity dimensions (S2), elaboration probes (S5), bug prevention rules (S7), and runtime verification strategy (S8).

Table 4.1: Interface modules and their primary contributions

Interface	What it contributes
gui	Form validation feedback SCs, navigation route guards, hover states, loading indicators, empty states. S8: Playwright browser or Electron launch.
http-api	Status code + response shape SCs, endpoint contract verification. S8: curl/httpie verification.
cli	Exit code + stdout/stderr SCs, flag validation, interactive prompt handling. S8: shell-based verification.
tui	Terminal rendering SCs, key binding verification.
data-io	Pipeline stage SCs, data quality assertions.
mobile	Touch interaction SCs, orientation handling, push notification.
grpc	Protobuf contract SCs, streaming deadline management.
embedded	Memory constraint SCs, interrupt handling, watchdog patterns.

4.2 Axis 2: Concern

Definition: Cross-cutting patterns that span multiple Features. A concern is a *mechanism*—it defines *what* pattern to handle.

Available values: 48 concern modules organized into five categories:

Core
auth, authorization, async-state, audit-logging, i18n, ipc, offline-sync, realtime, graceful-lifecycle, observability

Integration
external-sdk, message-queue, task-worker, plugin-system, connection-pool, push-notification

Code
codegen, polyglot, multi-tenancy, infra-as-code, compliance

Protocol
protocol-integration, llm-agents, hardware-io, webrtc, tls-management, schema-registry, cryptography, udp-transport, iot-protocol

Domain
cqrs-eventsourcing, distributed-consensus, dag-orchestration, ecs, wire-protocol, k8s-operator, gpu-compute, resilience, content-moderation, geospatial, media-streaming, payment-processing, scheduling-algorithm, search-engine, simulation-engine, speech-processing, stream-processing

Each concern module contributes S1 (SC generation rules), S3 (verify steps), S5 (elaboration probes for the Brief), and S7 (bug prevention rules).

4.3 Axis 3: Archetype

Definition: Domain philosophy—*why* certain decisions matter more than others.

Available values: 15 archetype modules: ai-assistant, public-api, microservice, sdk-framework, database-engine, network-server, message-broker, game-engine, browser-extension, infra-tool, cache-server, compiler, inference-server, media-server, workflow-engine.

Archetype vs. Concern: Archetypes and Concerns occupy different abstraction levels. A Concern defines *what* pattern to handle (`realtime` produces WebSocket reconnection rules). An Archetype defines *why* it matters more (`ai-assistant` produces "streaming is non-negotiable because LLM responses are inherently streaming").

Archetypes **extend** Concern rules via A2 (SC extensions) and A3 (probes). They do not duplicate them.

4.4 Axis 4: Foundation

Definition: Framework-specific constraints and toolchain rules.

The Foundation axis contains 40+ framework files covering React, Next.js, Electron, Tauri, Express, NestJS, FastAPI, Django, Flask, Go, Rust, Python, Erlang/OTP, and many more.

Foundation rules are expressed as universal principles with framework-specific examples:

```
# Universal principle
"Isolate side effects from render logic"

# Framework examples
React:   useEffect for side effects
Vue:     watch/watchEffect
Django:  signals or middleware
Go:      goroutine with context.Context
```

Foundation Rule Pattern

Anti-pattern

A foundation file that says "use `useEffect` for side effects" is React-coupled and useless for other frameworks. Foundation rules must always be universal principles with framework-specific implementations as examples.

4.5 Axis 5: Context

Context is a **composite axis** with three components:

Mode (exactly one): `greenfield`, `rebuild`, `incremental`, `adoption`. Determines which pipeline steps run and how.

Scale (product of two dimensions): project_maturity (`prototype`, `mvp`, `production`) × team_context (`solo`, `small-team`, `large-team`). Adjusts enforcement depth.

Modifiers (zero or more): `+migration`, `+compliance`, etc. Add situational rules regardless of mode or scale.

Key distinction: Mode determines *what* the pipeline does. Scale determines *how deeply* rules are enforced. Modifiers add *situational rules*.

A `prototype + solo` project gets functional-only SCs with optional tests. A `production + large-team` project gets mandatory observability, code ownership, and full edge-case coverage.

4.6 How Axes Compose: Cross-Concern Integration

When multiple concerns are active, emergent patterns arise that neither module produces alone. These 62 rules are defined in `_resolver.md` Step 3.5:

Table 4.2: Selected Cross-Concern Integration Rules

Active Combination	Emergent Pattern
gui + realtime	Optimistic update + reconnection UI + stale-data prevention
gui + async-state + realtime	Live state synchronization with conflict resolution
gui + ipc	IPC bridge health check + renderer crash recovery UI
http-api + auth	Token refresh on 401 + auth header injection
microservice + message-queue	Message contract versioning + dead-letter handling
ai-assistant + realtime	Stream interruption + partial response display + token budget
resilience + connection-pool	Pool health monitoring + circuit breaker on pool exhaustion

4.7 Composition Example: Full Walkthrough

Consider an AI-powered desktop app being rebuilt from an existing codebase (MVP stage, solo developer):

```
Profile:     desktop-app
Interfaces:  [gui]                    <- Axis 1
Concerns:    [async-state, ipc, external-sdk, realtime]  <- Axis 2
Archetype:   ai-assistant             <- Axis 3
Foundation:  electron                 <- Axis 4
Context:     rebuild / mvp / solo     <- Axis 5 (mode / scale)
```

Domain Profile Example

This profile loads the following modules (8 file reads, cached for session):

1. `_core.md` — universal baseline rules
2. `interfaces/gui.md` — form validation, navigation, loading states
3. `concerns/async-state.md` — reactive state management patterns
4. `concerns/ipc.md` — inter-process communication for Electron
5. `concerns/external-sdk.md` — third-party API integration
6. `concerns/realtime.md` — WebSocket/SSE/streaming patterns
7. `archetypes/ai-assistant.md` — Streaming-First, Model Agnosticism, Token Awareness
8. `foundations/electron.md` — process model, IPC patterns, security boundaries
9. `contexts/modes/rebuild.md` — preservation rules, SBI tracking, source fidelity gates

Then cross-concern rules activate for the following combinations:

- gui + realtime → optimistic update + reconnection UI
- gui + async-state → loading/error/empty state management
- gui + ipc → IPC bridge health check + renderer crash recovery
- gui + async-state + ipc → Electron main-renderer state sync
- ai-assistant + realtime → stream interruption + token budget

The Context Scale (mvp × solo) then adjusts: MVP means full SC coverage for critical paths but optional for edge cases. Solo means no code review requirements or team collaboration probes.

4.8 Profiling Framework vs. Profiling Result

An important architectural distinction: the Domain Profile *framework* (the 5-axis module system with S0–S9 sections) is the profiling **tool**. The Domain Profile *Instance* (stored in `domain-profile-instance.md`) is the profiling **result**.

The Questionnaire Analogy

Domain Profile modules are the questionnaire template—they define what questions to ask about auth, what SC patterns to generate for realtime, what bugs to prevent for GUI apps. The Domain Profile Instance is the filled-out form—"this project uses JWT + OAuth2, decided during F001 Brief."
The separation matters because Feature 3 can query Feature 1's auth decisions programmatically by reading the Instance file, instead of parsing prose scattered across spec and plan documents.

The Instance file (`specs/_global/domain-profile-instance.md`) contains:

Per-Concern Decisions S5 probe answers with timestamps and Feature IDs

Per-Archetype Decisions A3 probe answers

Cross-Concern Integrations Applied Which resolver rules were activated and when

Per-Feature Domain Summary Active modules, key decisions, inherited constraints

Lifecycle: Created during the first `/add` Brief (Phase 1c). Updated at each Feature's specify Post-Step Update. Read during subsequent Features' `/add` and `/specify` Assemble stages.

4.9 Evolution History

The Domain Profile model evolved through three generations:

3-Axis Model (v0.1) Interface × Concern × Scenario. Lacked structured domain philosophy. Principles like "Streaming-First" were generated ad-hoc by the agent's training data, producing inconsistent results across sessions.

4-Axis Model (v0.1.5) Added Archetype axis. Standardized domain philosophies into reusable, versionable module files. However, Foundation was operating as a de facto axis without formal recognition.

5-Axis + Modifier Model (v0.2) Promoted Foundation to a full axis. Unified the 5th axis from "Scenario" to "Context" with three components (Mode + Scale + Modifiers). The separate Scale modifier was absorbed into Context as a subcomponent.

Chapter 5

Section System

Every domain module in spec-kit-skills uses standardized section numbering across four families. This is not arbitrary—each family serves a different purpose, and each section maps to exactly one pipeline stage. This mapping enables lazy loading: each pipeline step loads only the sections it needs.

5.1 S-Family: Pipeline Execution Rules (S0–S9)

S-sections tell smart-sdd how to *build* projects for this domain.

Table 5.1: S-Family section definitions

ID	Name	Pipeline Stage / Purpose
S0	Signal Keywords	`init`: profile detection via semantic keyword matching
S1	SC Generation Rules	`specify`: required SC patterns, anti-patterns, measurability criteria
S2	Parity Dimensions	`parity`: additional structural/logic comparison dimensions
S3	Verify Steps	`verify`: additional verification steps when this module is active
S4	(Reserved)	—
S5	Elaboration Probes	`add` (Brief): domain-specific questions to ask the user
S6	Pattern Rules	`plan/implement`: pattern constraints and idioms
S7	Bug Prevention	`plan/implement/verify`: known anti-patterns for this domain
S8	Runtime Verification Strategy	`verify`: how to launch and verify the running application
S9	Brief Completion Criteria	`add`: what makes a Feature definition "complete" for this module

5.2 A-Family: Archetype Philosophy (A0–A5)

A-sections tell smart-sdd *why* certain decisions matter—philosophy principles, not just checklists.

Table 5.2: A-Family section definitions

ID	Name	Purpose
A0	Signal Keywords	Profile detection for archetypes
A1	Philosophy	Core domain principles (e.g., Streaming-First, Model Agnosticism)
A2	SC Extensions	Additional SC rules that extend Concern S1 rules
A3	Elaboration Probes	Domain-philosophy-specific questions for the Brief
A4	Constitution Injection	Principles to inject into the project constitution
A5	Brief Completion	Archetype-specific completeness criteria

5.3 R-Family: Reverse-Spec Analysis (R1–R5)

R-sections tell reverse-spec how to *read* existing code for this pattern.

Table 5.3: R-Family section definitions

ID	Name	Purpose
R1	Code Pattern Keywords	Source code signals (imports, annotations, file patterns)
R2	Project Type Classification	How to classify the project type from code evidence
R3	Analysis Axes	Specific analysis dimensions for this module
R4	Data Flow Rules	Entity and API extraction rules specific to this module
R5	Feature Boundary Heuristics	How to identify Feature boundaries in code

5.4 F-Family: Foundation Platform (F0–F8)

F-sections define framework-specific platform rules.

Table 5.4: F-Family section definitions

ID	Name	Purpose
F0	Detection	Framework identification signals
F1	(Reserved)	—
F2	Specify-time Items	Framework constraints that affect spec generation
F3	Implement-time Rules	Framework idioms, anti-patterns, toolchain setup
F7	Philosophy	Framework-endorsed principles (distinct from operational checklists)
F8	Toolchain Commands	Build, test, lint commands for this framework
F9	Scan Targets	Directories and files to scan during analysis

5.5 The Philosophy Behind the Division

The four families exist because of three design requirements:

1. **Pipeline-stage mapping**: Each section maps to exactly one pipeline stage. `specify` loads S1; `implement` loads S7. This enables per-command lazy loading—55–70% of

module content is skipped per command.

2. **Independent extension**: You can create a new module by filling S5 (elaboration probes) without knowing S7 (bug patterns yet). Add S7 later as failure modes are discovered. Each section is independently valuable.

3. **Skill separation**: S-sections drive smart-sdd (building). R-sections drive reverse-spec (reading). A-sections add philosophy. F-sections add platform constraints. No skill needs to load another skill's sections.

Chapter 6

Module Loading and Context Injection

6.1 The 8-Step Loading Order

When the pipeline runs, modules load in a defined order. Each layer can extend the previous:

1. `_core.md`—Universal rules that apply to every project.
2. `interfaces/{name}.md`—For each active Interface (Axis 1).
3. `concerns/{name}.md`—For each active Concern (Axis 2).
4. `archetypes/{name}.md`—For each active Archetype (Axis 3).
5. `foundations/{framework}.md`—Framework-specific rules (Axis 4).
6. `org-convention.md`—Organization-wide rules (optional).
7. `contexts/modes/{mode}.md`—Lifecycle rules (Axis 5 Mode).
8. `domain-custom.md`—Project-level overrides (optional).

Three levels of customization: Skill (steps 1–5), Org (step 6), Project (step 8). Later levels can override earlier ones, but the override semantics differ by purpose.

6.2 Per-Step Injection Maps

Each pipeline command loads only the S-sections it needs. This is the lazy-loading optimization that reduces context consumption by 40–95% per command:

Table 6.1: Per-command section loading

Command	Sections Loaded
specify	S0, S1, S5, S9, A2, A3, A5, F2
plan	S6, S7, A2, F2, F3
tasks	S7 (Bug Prevention subset B-3)
implement	S7 (B-3), S6, F3, F8
verify	S1 (for SC compliance check), S3, S7, S8, F8, F9
add (Brief)	S5, S9, A3, A5
constitution	A4, F7
analyze	S1, S7

6.3 Context Budget Mathematics

Here is the math for a typical pipeline step:

- **Always loaded**: ∼200 lines (SKILL.md with routing + mandatory rules)
- **Per-command**: ∼500 lines (the specific command file)
- **Per-domain**: ∼400 lines (3–5 modules × ∼100 lines each)
- **Per-Feature**: ∼200 lines (pre-context + current spec)
- **Total**: ∼1,300 lines in working context

Compare to loading everything: ∼15,000+ lines. The agent would spend its context budget reading instructions instead of doing work. Selective loading means the agent reads 1,300 lines of highly relevant context instead of 15,000 lines of mostly irrelevant rules.

6.4 Merge Semantics

When multiple modules are active, their sections merge via **append** semantics: `gui.md`'s S1 accumulates with `realtime.md`'s S1 and `ai-assistant`'s A2.

Why append instead of override? Because domain modules address orthogonal concerns. A `gui` SC rule about hover states does not conflict with a `realtime` SC rule about completion indicators.

The exception: the **convention hierarchy** (project overriding org) uses override semantics, because the intent is explicitly "I know the org rule, and I am choosing to do something different."

6.5 Graceful Degradation

When optional artifacts are missing, the pipeline degrades gracefully rather than failing:

Table 6.2: Graceful degradation rules

Missing Artifact	Behavior
org-convention.md	Skip org rules, proceed with skill defaults
domain-custom.md	Skip project overrides
pre-context.md	Generate from Brief only (no source context)
entity-registry.md	Treat all entities as new (no cross-Feature references)
spec-draft.md	Generate spec from scratch (no reverse-spec refinement)
constitution.md	Use default project principles

Chapter 7

Pipeline Integrity Guards

Seven generalized guard patterns extracted from 44 field-discovered failure cases (SKF-001 through SKF-044). Each guard addresses a *class* of pipeline failure—not a single instance.

7.1 Guard 1: Guideline to Gate Escalation

Root cause: Rules written as "should" or "recommended" get skipped by agents under context pressure.

Pattern: Any rule whose violation causes Major+ quality regression MUST be a BLOCKING gate, not a guideline. A BLOCKING gate requires agent action (AskUserQuestion, file read, or assertion) before proceeding.

Escalation mechanism: New rules default to WARNING. After first documented violation (SKF entry), automatically promote to BLOCKING.

7.2 Guard 2: Static Is Not Runtime Verification

Root cause: Build/TypeScript/lint pass while runtime behavior is broken.

Verification chain (each level includes all previous):

```
Level 0: Build + TS + Lint          (syntax/type errors)
Level 1: + App launches without crash (import/config errors)
Level 2: + UI elements render        (CSS/template errors)
Level 3: + Interactions correct state (logic errors)
Level 4: + Data persists across restart (round-trip errors)
```

Verification Levels

7.3 Guard 3: Cross-Stage Trust Breakers

Root cause: Pipeline stages blindly trust previous stage output. A wrong assumption at stage N propagates unchanged through N+6.

Pattern: Critical assumptions need independent verification at 2+ pipeline stages (circuit breakers). Three gate positions for rebuild + GUI projects: specify entry, implement entry, verify Phase 3e.

7.4 Guard 4: Granularity Alignment

Root cause: Analysis operates at file/function level, but bugs occur at UI control level. A settings page with 15 toggles gets one SBI entry, causing 14 to be missed.

Pattern: When a source file contains 5+ form control elements, each control becomes an individual SBI entry. The threshold is configurable.

7.5 Guard 5: Environment Parity

Root cause: Playwright creates a clean-state environment. Tests pass in clean state but fail with persisted data, non-default settings, or stale localStorage.

Pattern: Dual-mode verification—both clean environment (baseline) and real environment simulation must pass.

7.6 Guard 6: Cross-Feature Interface Verification

Root cause: Feature A verified in isolation, but its interface to Feature B is broken.

Three mechanisms: Provides Interface Verification (verify Phase 2), Interaction Surface Inventory (implement to verify), Dependency Stub Resolution.

7.7 Guard 7: Rebuild Fidelity Chain

Root cause: Rebuild projects produce UI that looks nothing like the source app because source structure is captured once then ignored.

Pattern: Source app structure must be a first-class artifact referenced at every pipeline stage. The chain flows: reverse-spec (Component Tree) → specify (FR references) → plan (Source Mapping, BLOCKING) → tasks (per-task refs) → implement (Source-First gate) → verify (Source Comparison, BLOCKING).

7.8 Using the Guards

When a new pipeline failure is discovered:

1. **Classify** it under one of the 7 guards. If it does not fit, it is either a guard extension or a candidate for Guard 8.
2. **Add the specific rule** to the relevant injection/command file, cross-referencing the guard.
3. **Verify coverage**: Each guard should have references in at least 3 pipeline files. Use: `grep -c "Guard [1-7]" injection/*.md verify-phases.md pipeline.md`

7.8.1 Guard Interaction Example

During a rebuild of an Electron AI assistant app, a single Feature (Settings page with 15 toggles) triggered five guards simultaneously:

- **Guard 2**: Build passed but CSS was unstyled (Tailwind plugin not registered).

- **Guard 4**: The 15 toggles were captured as a single SBI entry ("renders settings page"). 14 toggles missed downstream.
- **Guard 5**: Tests passed in clean state but failed with persisted user preferences (fontSize 22 broke layout).
- **Guard 6**: Feature A's settings affected Feature B's behavior, but the interface was never verified from Feature B's perspective.
- **Guard 7**: Source app had opt-in model management; rebuild implemented opt-out. Structurally correct but behaviorally wrong.

This illustrates why guards are needed as a *system*, not individually. A single-guard approach would have caught one or two issues. The full guard system caught all five.

7.9 Bug Fix Severity System

Bugs discovered during verify are classified into four tiers:

Table 7.1: Bug Fix Severity Classification

Severity	Action	Criteria
Minor	Fix in verify	Typo, missing label, off-by-one
Major-Implement	Return to implement	Logic error, missing feature behavior
Major-Plan	Return to plan	Architectural flaw, wrong component structure
Major-Spec	Return to specify	Missing requirement, wrong scope definition

Chapter 8

Global Evolution Layer

The Global Evolution Layer (GEL) is the set of project-wide artifacts that carry information across Features. It is the implementation of P1-c (Cross-Feature Memory).

8.1 Core Artifacts

entity-registry.md
: All data models with fields, types, relationships, and validation rules. Each entity records which Feature introduced it and which Features reference it.

api-registry.md
: All endpoints with methods, paths, request/response schemas, auth requirements, and error responses.

sdd-state.md
: The project state machine. Tracks Domain Profile (all 5 axes), Feature progress table, constitution version, rebuild configuration, and environment bootstrap status.

roadmap.md
: Feature dependency graph with execution ordering. Groups Features into tiers for phased delivery.

constitution.md
: Project-wide architectural principles. Seeded by reverse-spec or generated during init. Influences every subsequent pipeline step.

pre-context.md
: (per Feature) What each Feature needs to know about the rest of the project, including source analysis details, cross-Feature dependencies, and augmented requirements.

`domain-profile-instance.md`
: Records profiling *results*—the concrete domain decisions made for this project. S5 probe answers, cross-concern integration activations, and per-Feature domain summaries. Written during `/add` Brief and `/specify` Post-Update. The 4th GEL registry alongside entity-registry, api-registry, and sdd-state.

8.2 Data Flow Example: F001 to F003

```
F001 (Auth):
```

```
  specify -> entity-registry += User{id, email, displayName, role}
  specify -> api-registry += POST /api/auth/login {...}
  implement -> code written

F002 (Task CRUD):
  specify -> reads entity-registry -> sees User entity
  specify -> SC: "task.owner references User.id" (not a new User)
  specify -> api-registry += GET /api/tasks {...}
  implement -> imports User type from F001

F003 (Dashboard):
  specify -> reads both registries
  specify -> SC: "dashboard displays User.displayName"
  specify -> SC: "dashboard lists tasks via GET /api/tasks"
  plan -> Integration Contract: consumes User from F001, Tasks from F002
  implement -> references both existing APIs
  verify -> Phase 4 (cross-Feature): dashboard + auth + tasks together
```

Cross-Feature Data Flow

Each Feature builds on the accumulated knowledge of all previous Features. The registries grow richer with each Feature, creating a compounding advantage.

8.3 The State Machine: sdd-state.md

`sdd-state.md` is the central state file. Its structure:

```
# SDD State

**Project**: My Knowledge Base App
**Origin**: rebuild
**Domain Profile**: desktop-app
**Interfaces**: gui
**Concerns**: async-state, ipc, external-sdk, realtime
**Archetype**: ai-assistant
**Framework**: electron
**Context Mode**: rebuild
**Context Scale**: mvp x solo
**Context Modifiers**: none
**Artifact Language**: en
**Source Path**: /Users/dev/original-app
**Scope**: core
**Active Tiers**: T1
**Constitution Version**: 1.0
**State Schema Version**: 2.0
```

sdd-state.md Header Structure

Below the header, the Feature Progress Table tracks every Feature's current step:

```
| FID   | Name             | Step       | Status     | Branch             |
|------|-----------------|-----------|-----------|-------------------|
| F001 | Auth             | verify     | active     | 001-auth           |
| F002 | Knowledge Base   | specify    | queued     | ---                |
| F003 | Chat             | ---        | planned    | ---                |
```

Feature Progress Table

8.3.1 State Validation

At pipeline start, the state file is validated:

1. File exists and is valid markdown
2. State Schema Version field present
3. Required header fields present (Project, Origin, Domain Profile)
4. Feature Progress table has correct column count
5. All Feature IDs in progress table match Feature Mapping table
6. No duplicate Feature IDs

If validation fails, the agent presents repair options via AskUserQuestion.

8.3.2 Rebuild Configuration

For rebuild projects, additional configuration is stored:

Table 8.1: Rebuild configuration parameters

Parameter	Description
change_scope	What is changing: stack, platform, framework, language, architecture, vendor
preservation_level	How closely to match source: exact, equivalent, functional
source_available	Source app accessibility: running, code-only, docs-only
migration_strategy	Approach: big-bang, incremental, strangler-fig

8.4 Context Injection Rules

The context injection system is the architectural heart of spec-kit-skills. Each pipeline step has an injection file (`reference/injection/{command}.md`) that orchestrates context assembly.

8.4.1 Shared Patterns

All injection files follow these patterns:

HARD STOP pattern Every Review ends with AskUserQuestion. The loop/re-ask/empty-response handling is standard across all steps.

Files You Can Edit block Every Review includes paths to the artifact files, allowing the user to edit externally.

Post-Execution Output Suppression After any spec-kit command, suppress all navigation messages. The user sees the Review, not spec-kit's next-step guidance.

Fallback message If context prevents Review display: `Type "continue" to review the results.`

8.4.2 Per-Command Injection Files

Table 8.2: Injection file mapping

Command	Injection File
constitution	`injection/constitution.md`
specify + clarify	`injection/specify.md`
plan	`injection/plan.md`
tasks	`injection/tasks.md`
analyze	`injection/analyze.md`
implement	`injection/implement.md`
verify	`injection/verify.md`
parity	`injection/parity.md`
adopt (specify)	`injection/adopt-specify.md`
adopt (plan)	`injection/adopt-plan.md`
adopt (verify)	`injection/adopt-verify.md`

8.4.3 What Happens During Context Assembly

Using the `specify` step as an example for an ai-assistant + gui + realtime project:

1. Load Domain Module Loading Protocol (read sdd-state.md header, resolve 5 axes).
2. Load `_core.md` S1—universal SC generation rules.
3. Load `gui.md` S1—"Every form needs validation feedback SC."
4. Load `realtime.md` S1—"Every streaming display needs start/progress/completion/error/reconnection."
5. Load `ai-assistant` A2—"Provider abstraction requires multi-provider SC, rate limit SC, token budget SC."
6. Apply Cross-Concern Integration (Step 3.5): gui + realtime → optimistic update rules.
7. Apply Scale adjustment: mvp → full critical paths, optional edge cases.
8. Filter to specify-relevant sections only (S0, S1, S5, S9, A2, A3, A5).
9. Include GEL context: entity-registry.md, api-registry.md.
10. Include Feature context: pre-context.md for this Feature.
11. For rebuild: include spec-draft.md from reverse-spec.

The result: `speckit-specify` receives a tailored context that reflects this specific project's needs. A different project (cli + resilience + microservice) would receive completely different rules through the same mechanism.

8.4.4 Scale Modifier Enforcement

After module loading, Scale adjusts enforcement depth. This is BLOCKING—not optional:

Table 8.3: Scale adjustment examples

Section	**prototype + solo**	**production + large-team**
S1 (SC Rules)	Functional-only SCs	Full edge-case coverage
S5 (Probes)	Basic completeness	+ collaboration, ownership probes
S7 (Bug Prevention)	Disabled (speed over safety)	All patterns + observability
S3 (Verify Steps)	Build + smoke test	Full 4-phase verification

Part III

Skills Reference

Chapter 9

code-explore

`/code-explore` is the understanding skill—interactive, human-guided source code exploration that produces persistent, structured documentation.

9.1 Commands

orient Scan a project to generate an architecture map, module discovery, Domain Profile detection.

trace End-to-end flow tracing for a specific topic.

synthesis Aggregate all traces into Feature candidates and consolidated maps.

status Exploration coverage summary.

9.2 Orient: Structured Project Scan

When you run `/code-explore /path/to/project`, the agent performs a systematic analysis:

- **Language and framework** from project markers (`package.json`, `go.mod`, `Cargo.toml`, etc.)
- **Project type**—TCP servers, UDP servers, gRPC services, message consumers, API gateways, WebSocket servers, TUI applications, embedded firmware, and more
- **Entry points**—server-specific patterns like accept loops, listener bindings, event handlers, `@KafkaListener`, `.proto` service definitions
- **Concurrency model**—async/await, goroutines, thread pools, actor models, event loops
- **Module map** with file counts, import relationships, inferred purposes
- **Domain Profile** across all 5 axes

Output: `specs/explore/orientation.md`.

9.3 Five Trace Strategies

Not all code flows linearly. The agent selects the appropriate strategy:

1. **Sequential flow**: Request → handler → service → repository → response. For REST APIs, CLI commands.

2. **Connection Lifecycle**: Accept → handshake → read → parse → dispatch → handle → write → close. For TCP/WebSocket/gRPC servers.
3. **State Machine**: States + transitions mapped to source code. For presence systems, reconciler loops, workflow engines.
4. **Pub/Sub Fan-out**: Both publish path and consume/delivery path with fan-out visualized. For message brokers, event systems.
5. **Concurrent Actors**: Per-goroutine/task annotation with parallel participants and handoff points.

Each trace produces: summary, Mermaid sequence diagram, flow table with source references, entities discovered, APIs discovered, business rules, and categorized observations.

9.4 Synthesis: From Understanding to Action

After 3–5 traces, synthesis aggregates into:

- **Consolidated Entity Map**—entities merged across traces with conflict flags
- **Consolidated API Map**—dependency graph of API calls
- **Server Component Map**—layer-based architectural view (for server projects)
- **Feature Candidates**—grouped by module clustering, ready for `/smart-sdd add --from-explore`

9.5 Context-Aware Mode

When SDD artifacts already exist in the project (`specs/` directory), code-explore activates Context-Aware mode automatically. Analysis cross-references existing specs, registries, and Feature definitions, producing enriched output that shows how discovered code maps to existing SDD documentation.

This mode is particularly useful for:

- Investigating bugs in already-specified Features: the trace shows which SCs are relevant to the traced flow.
- Discovering undocumented behavior: code that does not map to any existing SC is flagged.
- Planning augmentation: gaps between code behavior and spec coverage suggest requirements for `add --to`.

9.6 Entity Conflict Resolution

When multiple traces discover entities with the same name but different fields, synthesis performs conflict resolution:

1. **Union merge**: Fields from all traces are combined. `User{id, email}` from trace 1 and `User{id, role}` from trace 3 become `User{id, email, role}`.
2. **Type conflict flagging**: If the same field has different types across traces, the conflict is flagged for user resolution.

3. **Source attribution**: Each field records which trace(s) discovered it, providing traceability.

9.7 Software Catalog

After synthesis, code-explore can produce a Software Catalog—a structured inventory of the studied codebase's technical components:

- **Languages and frameworks**: with version information where detectable
- **External dependencies**: categorized by purpose (database, messaging, API, etc.)
- **Internal modules**: with estimated complexity and coupling metrics
- **Infrastructure patterns**: deployment, CI/CD, monitoring (detected from config files)

The Software Catalog feeds into reverse-spec for foundation detection and into smart-sdd init for Domain Profile inference.

9.8 Practical Tips for Effective Exploration

Exploration Best Practices

1. Start with orient to get the big picture. Read the orientation output before tracing.
2. Choose 3–5 trace topics that cover the core business logic, not infrastructure.
3. Use the observation icons: tag findings with the appropriate icon during traces. These accumulate in synthesis.
4. Do not trace everything. Exploration has diminishing returns after 5–7 traces. Move to synthesis.
5. For rebuild projects, focus traces on the flows you plan to change. The source fidelity for unchanged flows comes from reverse-spec.

Chapter 10

reverse-spec

`/reverse-spec` is the automated extraction skill—a systematic audit that produces the Global Evolution Layer from existing source code.

10.1 Five Phases

Phase 0: Strategy User answers scope (core/full), stack (same/new), naming questions.

Phase 1: Code Pattern Analysis File structure scan, dependency graphs, architectural pattern identification. Produces structural map.

Phase 1.5: Runtime Exploration Launches the source app, captures real UI flows. Required for rebuild mode. Produces screenshots and interaction recordings.

Phase 2: Source Behavior Inventory (SBI) Catalogs every user-facing behavior as B### entries mapped to source code locations.

Phase 3: Entity and API Extraction Produces `entity-registry.md` and `api-registry.md` in the same formats smart-sdd uses.

Phase 4: Roadmap Construction Groups behaviors into Features ordered by dependency. Produces `roadmap.md`.

Phase 5: Constitution Seed Extracts architectural principles. Produces `constitution-seed.md`.

10.2 Source Behavior Inventory (SBI)

The SBI is reverse-spec's unique contribution. It catalogs not just "the auth module exists" but specific behaviors:

```
B001: User can log in with email and password
B002: Failed login shows inline error message after 1 second
B003: 3 failed attempts triggers 15-minute lockout
B004: Session token stored in httpOnly cookie, expires in 24h
```

SBI Example

For rebuild projects, the SBI ensures nothing gets lost. If the source has 47 behaviors, the rebuild should cover all 47—or explicitly document which are intentionally dropped.

10.3 spec-draft Generation

Phase 4 converts SBI entries into per-Feature `spec-draft.md` files containing Feature Requirements (FRs) and Success Criteria (SCs) that preserve UI control types, interaction patterns, and error handling. The pipeline's `specify` step refines this draft rather than generating from scratch.

10.4 The –from-explore Mode

When code-explore artifacts exist, `reverse-spec --from-explore` enriches analysis with pre-validated human understanding: Domain Profile hypothesis, entity/API pre-validation, and Feature boundary seeding.

10.5 When to Use code-explore vs. reverse-spec

Table 10.1: Choosing between code-explore and reverse-spec

Criterion	code-explore	reverse-spec
Goal	Build intuition and understanding	Comprehensive artifact extraction
Style	Interactive, human-guided	Automated, systematic
Scope	Selective (you choose what to trace)	Exhaustive (catalogs everything)
Depth	Deep on chosen topics	Broad across entire codebase
Output	Learning documentation	Pipeline-ready GEL artifacts
When	Unfamiliar codebase	Ready for rebuild/adopt

They chain well: `/code-explore` first to understand, then `/reverse-spec --from-explore` to extract with human insights.

10.6 Adoption Mode

When invoked with `--adopt`, reverse-spec adjusts its behavior:

- Forces `--scope full` (document everything, not just core)
- Forces `--stack same` (no tech stack change)
- Skips renaming question (documenting in-place)
- Output feeds directly into `/smart-sdd adopt`

The adoption output preserves existing code structure. Specs describe what the code *does*, not what it *should* do. This makes adoption specs useful as onboarding documentation.

10.7 Runtime Exploration (Phase 1.5)

For GUI applications, Phase 1.5 launches the source app and captures actual UI flows:

1. Launch the application using the detected start command or Playwright Electron protocol.
2. Navigate through each major user flow.

3. Capture screenshots, form fields, dropdown options, error messages, loading states.
4. Record exact interaction patterns: what auto-fills, what validates inline, what submits to server.

This phase is required for rebuild mode because static code analysis cannot capture UI interaction details reliably. A dropdown in source code might appear as a generic `<select>` element—Phase 1.5 captures that it contains model names, that selecting a model auto-fills dimension fields, and that the auto-fill triggers a re-calculation.

Without Phase 1.5, the information loss pattern from G17 (Context Continuity Failure) becomes almost inevitable: the dropdown becomes "text input" by the time implementation runs.

10.8 Handling Large Codebases

For projects with 1000+ files:

1. Phase 1 uses file structure heuristics to identify high-value directories (not an exhaustive scan).
2. Phase 2 prioritizes files with the most imports/exports (hub files).
3. SBI extraction focuses on user-facing modules first, then internal services.
4. The `--scope core` flag limits extraction to Features in the critical dependency path.

Chapter 11

smart-sdd

`/smart-sdd` is the main pipeline skill—the full Specification-Driven Development workflow with cross-Feature memory.

11.1 Full Pipeline

```
init -> add -> constitution -> specify -> plan -> tasks
     -> analyze -> implement -> verify -> merge
```

Pipeline Steps

11.2 The 4-Step Common Protocol

Every pipeline step follows the same protocol:

1. **Assemble**: Load Domain Profile modules, GEL artifacts, pre-context. This is where cross-Feature memory activates.
2. **Checkpoint (HARD STOP)**: Show assembled context. Wait for user approval.
3. **Execute + Review**: Run the spec-kit command with injected context. Suppress raw output. Read generated artifact. Display formatted review. Call AskUserQuestion (HARD STOP).
4. **Update**: Register new entities/APIs in GEL. Update `sdd-state.md`.

Mandatory Rules

Three mandatory rules are always loaded in SKILL.md:
Rule 1: Every HARD STOP uses AskUserQuestion. Empty response = re-ask. Never treat silence as approval.
Rule 2: Demos must be executable scripts that launch the real Feature, not test suites.
Rule 3: After any spec-kit command: suppress raw output, read artifact, display review, call AskUserQuestion.

11.3 The Brief: 6-Perspective Validation

The `add` command implements a structured consultation:

1. **Parse input**—text, files, or both.
2. **Identify perspective gaps**—actors? Error paths? Data model? Dependencies?
3. **Elaborate via domain-specific probes**—loaded from S5 sections based on Domain Profile.
4. **Draft Brief**—scope, actors, entities, interaction patterns, error scenarios, cross-Feature dependencies.
5. **Review HARD STOP**—user approves or modifies the Brief.
6. **Create artifacts**—pre-context generated, Feature registered in sdd-state.md.

11.4 The 4-Phase Verify

Phase 0: Preflight Playwright availability check (CLI probe → library import → MCP probe).

Phase 1: Build + TypeScript + Lint Baseline static checks.

Phase 2: Automated Tests Unit + integration. Fix code, not tests.

Phase 3: UI/Runtime Verification Launch application via Playwright. Verify each SC against running UI. Delegate to user if Playwright unavailable—never skip.

Phase 4: Cross-Feature Integration Verify Features work together.

11.5 SC Preservation (add –to)

When augmenting an existing Feature, SC Preservation ensures existing approved SCs are not lost:

- Existing SCs get `[preserved]` tags—cannot be removed or modified.
- New SCs get `[new]` tags.
- Contradictions get `[updated]` with explanation.
- Post-check: SC count did not decrease, preserved SCs match originals, every augmented requirement has at least one new SC.

11.6 Pipeline Step Detail

11.6.1 Constitution

The constitution defines project-wide architectural principles. For greenfield projects, it is generated from the Domain Profile's A4 (Constitution Injection) sections. For rebuild projects, it is seeded from reverse-spec Phase 5 analysis.

The constitution influences every subsequent pipeline step. For example, if the constitution declares "Provider Agnosticism," then every Feature's spec must include SCs for multi-provider support.

11.6.2 Specify

Transforms the Brief into a formal specification with Feature Requirements (FRs) and Success Criteria (SCs). Domain module S1 rules shape what SCs are generated:

- `gui` S1: "Every form needs validation feedback SC, every navigation needs route guard SC"
- `realtime` S1: "Every streaming display needs start indicator, progress update, completion signal, error fallback, reconnection logic"
- `ai-assistant` A2: "Provider abstraction requires multi-provider SC, rate limit handling SC, token budget management SC"

For rebuild projects, specify refines the `spec-draft.md` (generated by reverse-spec Phase 4) rather than generating from scratch. A Brief-to-Spec alignment check verifies that the generated spec faithfully reflects the approved Brief.

11.6.3 Plan

Breaks the spec into an architecture with components, data flow, and API contracts. For rebuild projects, plan includes Source Component Mapping (BLOCKING: every source component must map to a target component or be explicitly dropped).

11.6.4 Tasks

Creates implementation tasks ordered by dependency. Each task references specific FRs and SCs. For GUI projects with rebuild mode, each UI task references source component(s) per Guard 7 (Fidelity Chain).

11.6.5 Analyze

Performs static analysis of the task breakdown: coverage validation (every FR has tasks), dependency cycle detection, and complexity estimation. The analyze step uses S1 rules for SC compliance checking and S7 rules for anti-pattern detection.

11.6.6 Implement

Executes tasks sequentially. Each task follows a protocol: read task specification, read relevant source files (BLOCKING for rebuild), implement, run build check, verify task completion. Domain module S7 (Bug Prevention) rules are active—known anti-patterns trigger warnings or blocks.

11.6.7 Verify

The most complex pipeline step, split into 4 phases (described in Section **??**).

11.6.8 Merge

After verify passes, the Feature is merged to main. Entity and API registries are updated. Feature status in `sdd-state.md` changes to "completed." Interaction Surface Inventory is generated for cross-Feature verification.

11.7 Step-Back Navigation

At any HARD STOP, the user can choose to go back to a previous step. The pipeline supports arbitrary step-back: from verify back to plan, from implement back to specify. State in `sdd-state.md` is updated accordingly.

Common step-back patterns:

- **During plan review**: "The component structure is wrong" → back to specify to add missing FRs.
- **During implement**: "This approach will not work" → back to plan for architectural change.
- **During verify**: "The spec missed a requirement" → back to specify (Major-Spec severity).

11.8 Adopt Pipeline

`/smart-sdd adopt` wraps existing code with SDD documentation without rewriting. It auto-chains reverse-spec if artifacts do not exist, then runs a lighter consultation for each Feature.

Chapter 12

domain-extend

`/domain-extend` is the meta-tool that grows the domain vocabulary.

12.1 Six Commands

browse Explore what exists—system overview, module lists, keyword search, active modules.

detect Find gaps—profile gap analysis, codebase scanning, cross-reference with explore artifacts.

extend Create new modules—concern, archetype, foundation, or context modifier.

import Convert internal documentation (ADRs, style guides, postmortems) into module format.

customize Create org-level or project-level convention overlays.

validate Check all modules for schema compliance, taxonomy sync, cross-concern rule coverage.

12.2 Module Creation Workflow

When creating a new concern module (e.g., `rate-limiting`):

1. Create three files: `shared/domains/concerns/rate-limiting.md` (S0/R1 keywords), `reverse-spec/domains/concerns/rate-limiting.md` (R3–R5), `smart-sdd/domains/concerns/rate-` (S1–S8).
2. Update `_taxonomy.md` with the new module entry.
3. Optionally add cross-concern integration rules to `_resolver.md` Step 3.5.

The module is immediately available to all pipelines. No code changes, no registration step, no config file update.

12.3 Convention Hierarchy

Three levels of customization, where later levels override earlier ones:

1. **Skill-level**: Built-in domain modules (shipped with spec-kit-skills).

2. **Org-level**: `org-convention.md`—shared across all projects in an organization.
3. **Project-level**: `domain-custom.md`—specific to one project.

Part IV

Domain Module System

Chapter 13

Module Architecture

13.1 Triple Structure: Shared, Reverse-Spec, Smart-SDD

Most module types exist in **three locations** (exception: Foundations exist only in reverse-spec, as they provide framework detection rules rather than pipeline execution rules):

1. `shared/domains/{axis}/{name}.md`—Signal keywords (S0/A0 semantic + R1 code patterns). Single source of truth for detection.
2. `reverse-spec/domains/{axis}/{name}.md`—Analysis rules (R3–R5) for extracting information from existing code.
3. `smart-sdd/domains/{axis}/{name}.md`—Pipeline execution rules (S1–S9) for building new code.

Why three copies: Each skill has different section schemas. reverse-spec needs R3 (analysis axes) which smart-sdd does not use. smart-sdd needs S7 (bug prevention) which reverse-spec does not use. Shared keywords avoid duplication where the content is identical.

Each skill-local module replaces its S0/R1 section with a cross-reference to the shared file, ensuring a single source of truth for keywords.

13.2 Key System Files

_core.md Universal rules loaded for ALL projects. Contains baseline SC patterns, verification requirements, and anti-patterns that are domain-independent.

_resolver.md The 7-step module loading protocol including cross-concern integration (Step 3.5, 62 rules), scale adjustment (Step 4), and lazy-loading section tables (Step 5).

_taxonomy.md Single source of truth for all available modules. Referenced by the resolver and by domain-extend for validation.

_schema.md Section schema definitions. Documents what each S/A/R/F section should contain. Serves as both specification and contributor template.

13.3 Convention over Configuration

The module system follows a "convention over configuration" approach: put a file in the right directory with the right section numbers, and the system picks it up. No registration,

no config file updates, no code changes.

This is analogous to Ruby on Rails' auto-loading: "put a model in `app/models/` and it's auto-loaded." In spec-kit-skills: "put a concern module in `domains/concerns/` with S0–S9 sections and it's auto-activated."

The schema files (`_schema.md`) serve as both specification and contributor template. Want to create a new concern? Read `_schema.md` for section definitions, look at `auth.md` as an example, and create your file.

13.4 Module Validation

`/domain-extend validate` checks all modules for:

1. **Schema compliance**: Are section numbers correct? Are required fields present?
2. **Taxonomy sync**: Does every file in `domains/` have a corresponding entry in `_taxonomy.md`?
3. **Triple-file consistency**: For each module, do shared, reverse-spec, and smart-sdd files all exist?
4. **Cross-reference integrity**: Do shared file cross-references point to existing files?
5. **Cross-concern coverage**: For common module combinations, are integration rules defined in `_resolver.md`?

13.5 Module Lifecycle

A typical module goes through these stages:

1. **Detection-only**: Signal keywords exist (S0/R1). The module can be auto-detected but has no pipeline rules.
2. **Minimal**: S1 (SC rules) and S5 (probes) are populated. The module shapes `specify` and Brief consultation.
3. **Complete**: S7 (bug prevention), S3 (verify steps), and S8 (runtime verification) are populated. The module shapes the full pipeline.
4. **Integrated**: Cross-concern rules with commonly co-occurring modules are defined in `_resolver.md`.

New modules can start at any stage and grow incrementally. A detection-only module is still useful—it ensures the project's Domain Profile accurately reflects its patterns.

Chapter 14

Complete Module Inventory

14.1 Interfaces (10 modules)

Module	Description
gui	GUI windows, web pages, visual UI. Pairs with async-state, ipc.
http-api	REST/GraphQL endpoints, HTTP servers. Pairs with auth, authorization.
cli	Command-line tools, shell commands.
tui	Terminal UI (Ink, Bubble Tea, Ratatui).
data-io	Data pipelines, ETL, batch/stream processing. Pairs with dag-orchestration.
mobile	Mobile apps (iOS, Android, cross-platform). Pairs with auth, async-state, realtime.
library	Libraries/SDKs consumed via import/linking. Pairs with plugin-system.
embedded	Embedded systems, firmware, IoT, RTOS. Pairs with hardware-io, wire-protocol.
grpc	gRPC/RPC services (Protobuf, Connect, Twirp). Pairs with auth, resilience.
k8s-api	Kubernetes CRD spec/status reconciliation. Pairs with k8s-operator.

14.2 Concerns (48 modules)

The full list of concerns is organized into five categories. Each module provides S0 (signal keywords), S1 (SC rules), S5 (elaboration probes), and S7 (bug prevention). For the complete list with descriptions and common pairings, see Table A.2 in Appendix A.

Selected highlights:

- **auth**: Authentication flows (JWT, OAuth, session). High-confidence signal keywords: login, signup, password, token.
- **realtime**: WebSocket, SSE, live updates. S7 includes reconnection handling, message ordering, stale-data prevention.

- **llm-agents**: Multi-agent coordination, non-deterministic outputs. Cross-concern with ai-assistant archetype.
- **distributed-consensus**: Raft, Paxos, gossip, leader election. Pairs with database-engine and message-broker archetypes.
- **wire-protocol**: Binary protocols (MQTT, AMQP, RESP, WebRTC, RTMP). Pairs with network-server.

14.3 Archetypes (15 modules)

Each archetype defines domain philosophy (A1), SC extensions (A2), probes (A3), constitution principles (A4), and Brief completion criteria (A5).

Module	Philosophy Highlights
ai-assistant	Streaming-First, Model Agnosticism, Token Awareness.
public-api	Backward Compatibility, Rate Limiting by Design, Documentation as Contract.
microservice	Service Boundary, Failure Isolation, Independent Deployability.
database-engine	Durability First, WAL Before Data, Crash Recovery.
network-server	Connection Lifecycle, Backpressure, Zero-Copy Where Possible.
compiler	Correctness Before Performance, Error Recovery, Incremental Processing.
game-engine	Frame Budget, ECS Composition, Deterministic Replay.

14.4 Context Modes (4 modules)

greenfield Pipeline runs from scratch. No preservation rules.

rebuild Adds preservation rules, SBI tracking, source fidelity gates.

incremental For subsequent Features after initial setup.

adoption Documents existing code without rewriting.

14.5 Context Modifiers (extensible)

Currently one built-in modifier: `+migration` (adds M0–M4 migration framework gates). Additional modifiers (`+compliance`, etc.) can be created via `/domain-extend`.

14.6 Foundations (40+ modules)

Framework-specific rules covering major ecosystems: React, Next.js, Electron, Tauri, Express, NestJS, FastAPI, Django, Flask, Go, Rust/Cargo, Python, Erlang/OTP, TypeScript, Vite, and many more.

Chapter 15

Cross-Concern Integration

The resolver (`_resolver.md` Step 3.5) defines 62 cross-concern integration rules that activate when specific combinations of modules are loaded together. These rules produce emergent behavior that no individual module contains.

15.1 Rule Structure

Each rule specifies:

- **Trigger**: Which modules must be simultaneously active.
- **Emergent pattern**: What additional SCs, probes, or verification steps are generated.
- **Pipeline stage**: Where the rule applies (specify, plan, implement, verify).

15.2 Selected Integration Rules

- **gui + auth**: Login form validation UI, session expiry notification, redirect-after-login state management.
- **gui + realtime**: Optimistic update patterns, reconnection banner UI, stale-data indicators after reconnect.
- **gui + async-state + ipc**: Electron-specific: main process state synchronization with renderer, IPC error recovery UI.
- **http-api + auth**: Token refresh on 401, auth header injection middleware, rate limit response handling.
- **microservice + message-queue**: Message contract versioning, dead-letter queue handling, idempotency keys.
- **ai-assistant + realtime**: Stream interruption UX, partial response display, token budget mid-stream.
- **resilience + connection-pool**: Pool health monitoring, circuit breaker triggered by pool exhaustion.
- **k8s-operator + resilience**: Reconciliation retry with exponential backoff, status condition degradation.

15.3 Scale Modifier Effects

The Context Scale adjusts how deeply cross-concern rules are enforced:

- `prototype + solo`: Cross-concern rules generate recommendations, not blocking gates.
- `mvp + small-team`: Error-path cross-concern rules are blocking; edge-case rules are recommended.
- `production + large-team`: All cross-concern rules are blocking. Observability cross-concerns are mandatory.

Part V

Failure Patterns and Lessons

Chapter 16

19 Gap Patterns

Each gap pattern represents a *class* of bugs that traditional software checks (build, test, lint) do not catch.

16.1 G1: Build Pass Does Not Mean Feature Works

Trap: Build succeeds, tests pass, linter is clean—but the feature does not work at runtime.

Real example: Zustand state selectors created new object references every render, causing infinite re-renders and broken scroll during streaming. Build and TypeScript saw nothing wrong.

Countermeasure: Per-task runtime verification, pattern compliance scanning for known anti-patterns (selector instability, stale closures), runtime error zero-tolerance gate.

16.2 G2: Foundation Absence

Trap: The same infrastructure bug appears in every Feature because nobody verified the foundation.

Countermeasure: Foundation Gate runs once before the first business Feature—verifies build toolchain, framework plugins, IPC bridges, layout structure. Results cached for subsequent Features.

16.3 G3: Source Information Gap

Trap: Agent guesses values it could have looked up in source code.

Real example: Agent guessed CSS color tokens instead of reading them from source theme file.

Countermeasure: Source Reference Active Read (read actual source files for each SBI entry), SBI Accuracy Cross-Check.

16.4 G4: Async/Temporal Pattern Omission

Trap: Only synchronous happy-path flows documented. Async state transitions, error recovery, and cleanup missing.

16.5 G5: Context Compaction Procedure Loss

Trap: Context window compacts mid-session—agent forgets verification phases, skips or repeats them.

Countermeasure: Verify progress written to `sdd-state.md` at every phase boundary. Resumption protocol reads persisted state.

16.6 G6: Runtime Behavior Verification Gap

Trap: Verify does static checks but never runs the feature. SC verification covered 1 of 10 success criteria.

16.7 G7: Cross-Feature Integration Contract Gap

Trap: Features work alone but break together because nobody defined data shapes at boundaries.

16.8 G8: i18n Key Coverage Gap

Trap: Components use `t('key')` but keys are missing from translation files. i18next silently falls back to raw key strings.

16.9 G9: SDK API Contract Gap

Trap: Code passes metadata-only objects to SDK functions expecting callable objects. SDK silently ignores them.

16.10 G10: UI Interaction Over-exposure

Trap: Hover/click interactions on overly broad DOM areas cause flickering and cascading re-renders.

16.11 G11: Verify Checks Code Existence, Not Runtime Behavior

Trap: Verify uses `grep` to confirm code patterns exist—but the code does not run correctly. Empty state treated as PASS.

16.12 G12: Ad-hoc Domain Philosophy

Trap: Domain principles generated ad-hoc by agent's general knowledge. Different sessions produce different principles for the same domain.

16.13 G13: Framework Philosophy vs. Operational Checklists

Trap: Philosophical principles diluted among checklist items. "Main process must survive renderer crashes" looks identical to "CORS policy: config."

16.14 G14: Metrics-Only Reports Miss the "Why"

Trap: Reports show what was built but not why decisions were made.

16.15 G15: Skill Tool Return Overrides Pipeline Instructions

Trap: Sub-skill's completion message becomes the agent's final response, bypassing all post-execution steps.

16.16 G16: Path Ambiguity in Multi-Directory Operations

Trap: "Write to target directory" is ambiguous when source and build directories coexist.

16.17 G17: Context Continuity Failure

Trap: Each stage abstracts previous output more compactly. UI control details lost through 4 stages of summarization.

16.18 G18: Enforce, Don't Reference

Trap: Detailed rule in reference file. "See X for details" treated as optional reading. 400 lines of verification never executed.

16.19 G19: Domain Profile Set-and-Forget

Trap: Domain Profile detected during init but never actually loaded at individual pipeline steps.

Real example: Project had `gui + realtime` active. But specify never loaded the combined rules. Plan never referenced them. Implement never saw streaming requirements. The Domain Profile was documented, not operationalized.

Countermeasure: Domain Module Loading Protocol as a shared reference, Domain Profile display in status commands, per-step section-to-pipeline mapping.

16.20 Coverage Summary

Table 16.1: Gap pattern coverage estimates

Pattern	Coverage	Remaining Gap
G1: Build ≠ Feature	∼80%	Drops to build-only when Playwright unavailable
G2: Foundation Absence	∼90%	Most robust pattern
G3: Source Information Gap	∼85%	Weakens when runtime exploration skipped
G4: Async/Temporal Omission	∼70%	Most recently added
G5: Context Compaction	∼85%	File-based recovery effective
G6: Runtime Behavior Gap	∼75%	External service SCs need manual verify
G7: Cross-Feature Integration	∼80%	Catches structural, not all semantic issues
G8: i18n Key Coverage	∼95%	Dynamic keys not caught
G9: SDK Contract Gap	∼70%	Complex contracts need runtime verify
G10: UI Over-exposure	∼60%	Requires judgment
G11: Existence ≠ Behavior	∼85%	External dependencies need manual verify
G12: Ad-hoc Philosophy	∼90%	Robust for domains with archetype modules
G13: Philosophy vs. Checklists	∼85%	Effective for 21 frameworks with F7 sections
G14: Metrics-Only Reports	∼75%	Implicit decisions harder to capture
G15: Skill Tool Boundary	∼85%	Multi-layer defense effective
G16: Path Ambiguity	∼95%	Highly effective with CWD annotations
G17: Context Continuity Failure	∼70%	Better for rebuild; greenfield has no source
G18: Enforce, Don't Reference	∼85%	High when all 3 layers present
G19: Domain Profile Set-and-Forget	∼75%	Weakest in implicit situations

16.21 Countermeasure Evolution Timeline

The defenses were not designed upfront. Each layer was triggered by a specific failure:

```
Phase 1 (Week 1): SC verification -> Foundation Gate -> Source Reference
Phase 2 (Week 1-2): SBI Cross-Check -> Playwright fallback chain
Phase 3 (Week 2): UX Contract -> Verify Progress -> SC Matrix
Phase 4 (Week 2-3): i18n Lint -> SDK Contract -> Type Trust
Phase 5 (Week 3): BLOCKING gates -> Inline Execution -> Stop Hook
Phase 6 (Post-release): Context Budget -> Lazy Loading -> Reset Protocol
Phase 7 (Ongoing): 3 Principles -> Domain Module Loading Protocol
```

Defense Evolution

Each phase added approximately 5–10 countermeasures. The total system represents over

40 individual countermeasures organized under 7 guards and 3 principles.

Chapter 17

Key Lessons

Organized by theme, with selected highlights from the 57 lessons.

17.1 Theme A: How Agents Interpret Instructions

L1: Agents Fabricate Excuses. Agent auto-skipped HARD STOP checkpoints, citing "health check passed." The only defense is inline repetition at every violation point.

L10: "MANDATORY" Is a Suggestion. A step marked `MANDATORY---You MUST NOT skip it` was skipped twice. Only BLOCKING gates (downstream output verification) work.

L14: Sub-Skill Calls Break Orchestration. The Skill tool creates a response boundary. Post-execution review becomes structurally impossible. Use inline execution instead.

17.2 Theme B: Context Window and Instruction Placement

L21: Instruction Proximity Determines Compliance. The probability of following an instruction is inversely proportional to its distance from execution. File-top instructions are "documentation" by execution time.

L53: Context Saturation Across Work Units. After 3+ Features in a single session, later Features show degraded quality. Reset context at work unit boundaries.

L54: Specification Without Enforcement Is Decoration. A well-designed lazy-loading table sat in a reference file for months. No injection file referenced it. Agents loaded full modules every time.

17.3 Theme C: Build and Verification Traps

L5: State Selector Instability. Build passes, runtime loops. Zustand selectors creating new references per render are invisible to static analysis.

L33: Structure Fidelity vs. Behavioral Fidelity. Source app's model management was opt-in (user explicitly adds). Rebuild implemented opt-out (all auto-enabled). Structurally correct but behaviorally wrong.

17.4 Theme D: Cross-System Coordination

L34: Data Lifecycle Paradigms Are Invisible. How entities enter, activate, and exit a system is orthogonal to component structure and must be captured separately.

17.5 Theme E: Pipeline Architecture

L29: Ad-hoc Rules Don't Scale. Over 5 Features, 44 individual failure reports accumulated. Extract Guard Patterns when rules exceed ∼20 for the same failure class.

L30: Single-Direction Trust Kills Pipelines. A wrong runtime default (`navbarPosition: 'left'` instead of `'top'`) was inferred via static code analysis at reverse-spec. This wrong assumption propagated unchanged through specify, plan, tasks, implement, and verify—6 stages, 27 files, 3 user feedback rounds to discover. No stage independently verified the assumption. Insert circuit breakers—independent verification at 2+ stages.

17.6 Theme F: Verification Completeness

L23: Automation-Impossible Does Not Mean Skip. Manual SCs and manual-only test plan items were silently skipped during verify. The agent treated "can't automate" as "doesn't need verification." Every verification item must end in one of three states: machine-verified, user-verified, or explicitly acknowledged as unverifiable.

L24: Test State Isolation. Tests passed because previous runs left data in persistent storage. The feature appeared to work by reading stale data. Fix: 3-tier isolation (clean data directory, reset API state, read-before-act pattern).

L25: Feature Reachability. A feature was fully implemented and tests passed, but users could not reach it—no navigation path from the home screen. For GUI features, verify the navigation path from entry point to feature.

17.7 Theme G: Pipeline Architecture Patterns

L31: Granularity Mismatch. SBI extraction operated at file level. FR-to-task mapping at FR level. But actual bugs occurred at control level. 14 controls on a settings page became 1 SBI entry, losing 13 controls. The granularity of analysis must match the granularity of the problem domain.

L32: Test Environment vs. User Environment. Playwright tested in clean state (no persisted data, default settings). User's app had fontSize 22, dark theme, API keys saved—UI was broken. Automated tests prove the feature works *in the test environment*, not the user's.

L38: Simulation-Driven Gap Detection. A systematic review audit (11-point protocol) found 17 issues. But simulating the pipeline on a real project found 6 entirely new gap categories that reviews could not discover. Always validate framework changes through end-to-end simulation, not just code review.

17.8 Theme H: Context Efficiency

L37: Context Budget Is a Hard Ceiling. After 65+ SKF items, the framework grew to 174 files / 27,574 lines. The 2 largest files alone consume 40% of typical context budget. Framework designers must track instruction size like engineers track memory usage.

Specific techniques for managing context budget:

- Lazy section loading: load only S-sections needed per command (40% reduction).
- Per-phase file reading: for files over 2000 lines, read only the relevant phase section.
- Deduplication monitoring: track inline duplication growth across locations.

Chapter 18

Agent Behavioral Patterns

18.1 Five Evasion Patterns (Detailed)

Agent evasion is not defiance—it is optimization. When context is compressed and the full protocol is unavailable, the agent fills gaps with what seems reasonable. The five patterns (fabricated excuse, keyword downgrade, explicit ignore, premature completion, silent substitution) share a root cause: the agent optimizes for completion, not compliance.

The Most Dangerous Pattern

Silent substitution: the agent produces output that *looks correct*. It does not say "I skipped verification." It says "verification complete"—confidently, with a checkmark. Only manual inspection reveals that 80% of the protocol was silently dropped.

18.2 Pipeline Completion Bias

Agents exhibit strong completion bias—they want to finish the pipeline. This manifests as:

- Declaring tasks "done" when 5 of 7 are complete (the remaining 2 were compressed out of context).
- Skipping HARD STOPs to maintain "momentum."
- Substituting simpler verification (build-only) when full verification instructions are no longer in context.

18.3 The "Helpful but Wrong" Problem

Agents are trained to be helpful. When they cannot do what was asked (instructions compressed out of context), they do something related rather than stopping to ask. This is more dangerous than refusing—refusal is visible; helpful-but-wrong is silent.

18.4 Why Stronger Language Does Not Help

"MANDATORY," "CRITICAL," "DO NOT SKIP UNDER ANY CIRCUMSTANCES"—these are adjectives in natural language. They do not create structural constraints. Only blocking

gates (the agent physically cannot produce the next output without completing the step) create true enforcement.

18.5 The Sub-Skill Trap

When an orchestrator calls a sub-skill via the Skill tool, the sub-skill's completion message becomes the final response. The orchestrator loses control. Post-execution review, user approval, and state updates become structurally impossible. The fix: inline execution—read the sub-skill's instructions and execute them within the orchestrator's turn.

18.6 Practical Mitigation Strategies

Based on the behavioral patterns above, here is a checklist for building reliable agent skills:

1. **Assume instructions will be compressed.** Place critical rules at every execution point, not just at the file top.
2. **Use output verification, not input instruction.** Instead of "you must do X," check "did the output contain evidence of X?"
3. **Model state as a file-based state machine.** The agent can always read the file, even if it forgot the instructions.
4. **Never use the Skill tool for sub-skills that need post-processing.** Inline execution preserves control flow.
5. **Define safety nets as invariants, not conditions.** "Every response must end with user interaction" catches all failure modes. "If context limit prevents review, show fallback" catches only one.
6. **Test with 50+ message conversations.** Short tests miss compression-induced failures.
7. **After every rule change, re-execute.** Reading the rule looks correct. Only execution reveals whether the agent actually follows it.
8. **Track violations in a history file.** When deciding "is this rule still needed?" the history tells you what breaks if you remove it.

18.7 The Paradox of Agent Skill Design

Building tools for AI agents has a fundamental paradox: the agent is both your user and your runtime. When you write a React component, React runs it. When you write a Claude Code skill, Claude *reads* it as markdown and decides how to behave.

This means:

- Your "code" is natural language.
- Your "compiler" is an LLM.
- Your "bugs" are behavioral—the agent does the wrong thing because it misunderstood, not because of a syntax error.
- You cannot debug with stack traces, breakpoints, or unit tests.
- Your only testing method: run the pipeline, watch what happens, iterate.

And there is the context window constraint: the rule you wrote at the top of your file may be compressed to a summary after 50 messages—or dropped entirely. Your engineering challenge is building rules that resist compression, that work not because the agent remembers them but because the pipeline structure makes it impossible to proceed without following them.

18.8 Countermeasure Design Patterns

Several reusable patterns emerged from building spec-kit-skills:

18.8.1 The Output Verification Pattern

Instead of telling the agent what to do (input), verify what was done (output).

```
# Input instruction (weak):
"You must verify all 4 phases before merge."

# Output verification (strong):
"Read sdd-state.md verify_progress. If any phase != complete,
 BLOCKING: 'Verify incomplete. Complete phases before merge.'"
```

Output Verification Example

18.8.2 The State Recovery Pattern

Write progress to files so the agent can recover after context loss.

```
# After each verify phase:
Write to sdd-state.md:
  phase_0_preflight: complete
  phase_1_build: complete
  phase_2_ui: in_progress (SC-003 remaining)
  phase_3_regression: pending

# On resume: read file, continue from SC-003
```

State Recovery Example

18.8.3 The Catch-All Fallback Pattern

Every possible exit path ends with user interaction or a recovery message.

```
# Normal exit: AskUserQuestion with review
# Abnormal exit (any reason):
"[command] executed for [FID].
 Type 'continue' to review the results."

# Never: silent exit with no user guidance
```

Catch-All Pattern

18.8.4 The Inline Duplication Pattern

Critical rules repeated at every execution point, not extracted to shared files.

```
# In pipeline.md specify section:
"HARD STOP: AskUserQuestion. If response empty -> re-ask."

# In pipeline.md plan section:
"HARD STOP: AskUserQuestion. If response empty -> re-ask."

# In pipeline.md tasks section:
"HARD STOP: AskUserQuestion. If response empty -> re-ask."

# Same text 30+ times. Intentional. Not a code smell.
```

Inline Duplication Example

Part VI

Practical Guide

Chapter 19

Getting Started

19.1 Prerequisites

- **Claude Code** CLI—the AI coding agent that runs these skills.
- **spec-kit**—the SDD pipeline engine (required for `/smart-sdd`).
- **Playwright**—for runtime verification. Optional but strongly recommended.

19.2 Installation

```
git clone https://github.com/coolhero/spec-kit-skills.git
cd spec-kit-skills
./install.sh      # creates symlinks -> ~/.claude/skills/
```

Verify installation:

```
/reverse-spec --help     # Should show command help
/smart-sdd status        # Should show status or ask to init
/domain-extend browse    # Should show domain module overview
```

19.3 First Project Walkthrough: Greenfield

```
# 1. Initialize project
/smart-sdd init "AI-powered knowledge base with provider abstraction"

# 2. Define first Feature
/smart-sdd add "knowledge base CRUD with file upload"
# -> 6-step Brief consultation
# -> Review and approve

# 3. Run pipeline
/smart-sdd pipeline F001
# -> constitution -> specify -> plan -> tasks
# -> implement -> verify (4 phases)
# -> At each step: review and approve
```

```
# 4. Add more Features
/smart-sdd add "multi-provider chat with streaming"
/smart-sdd pipeline F002
# F002 automatically sees F001's entities and APIs
```

From Idea to Working App

19.4 Decision Tree: Which Command Should I Use?

```
Have existing code?
  No  -> /smart-sdd init -> add -> pipeline        (New Project)
  Yes -> What is your goal?
         Understand only    -> /code-explore          (Explore)
         Document only      -> /smart-sdd adopt       (Adoption)
         Add features       -> adopt -> add -> pipeline (Extend)
         Rebuild (same stack) -> /reverse-spec -> pipeline (Rebuild)
         Rebuild (new stack)  -> /reverse-spec --stack new (Migrate)

Need custom domain modules?
  -> /domain-extend detect -> extend
```

Command Selection Decision Tree

Every journey converges to incremental mode (`/smart-sdd add` → `pipeline`) as the steady state. The entry points differ, but the pipeline is always the same.

19.5 Understanding the Output Structure

After running the pipeline, your project directory contains:

```
my-project/
  specs/
    _global/
      roadmap.md              <- Feature dependency graph
      entity-registry.md      <- All data models
      api-registry.md         <- All API contracts
      sdd-state.md            <- Pipeline state + Domain Profile
      constitution-seed.md    <- Project principles
    explore/                  <- code-explore output
      orientation.md
      traces/
    001-auth/                 <- Per-Feature artifacts
      pre-context.md          <- Context from analysis
      spec-draft.md           <- Initial spec (from reverse-spec)
      spec.md                 <- Final spec
      plan.md                 <- Architecture
      tasks.md                <- Implementation tasks
    002-task-crud/
      ...
  .specify/
    memory/
      constitution.md         <- Active constitution
```

Output Directory Structure

19.6 CLI Reference

Table 19.1: Command reference

Command	Description
`/code-explore [path]`	Scan project, generate architecture map
`/code-explore trace "topic"`	End-to-end flow tracing
`/code-explore synthesis`	Aggregate traces into Feature candidates
`/reverse-spec [path]`	Extract GEL from existing code
`/smart-sdd init`	Initialize new project
`/smart-sdd add`	Define new Feature(s)
`/smart-sdd pipeline [FID]`	Run SDD pipeline
`/smart-sdd adopt`	Document existing code
`/smart-sdd status`	Check progress
`/smart-sdd reset [FID]`	Reset Feature or pipeline
`/domain-extend browse`	Explore modules
`/domain-extend detect`	Find coverage gaps
`/domain-extend extend`	Create new modules
`/domain-extend validate`	Schema compliance check

Chapter 20

Scenario Walkthroughs

20.1 Scenario 1: Greenfield Idea

You have an idea and no code.

```
/smart-sdd init "AI-powered knowledge base with provider abstraction"
/smart-sdd add "knowledge base CRUD"
/smart-sdd pipeline F001
/smart-sdd add "multi-provider chat with streaming"
/smart-sdd pipeline F002
```

At each pipeline step, Domain Profile modules load context-appropriate rules. Cross-Feature memory ensures F002 references F001's entities.

20.2 Scenario 2: Brownfield Rebuild

You have a working app that needs rewriting with a new tech stack.

```
/reverse-spec /path/to/legacy-app
/smart-sdd init --from-reverse-spec
/smart-sdd pipeline F001
# ... continue in dependency order
```

The SBI ensures no behavior is lost. The Artifact Separation principle keeps specs clean while preserving source fidelity in pre-contexts.

20.3 Scenario 3: Adoption

You have working code and want SDD documentation without rewriting.

```
/smart-sdd adopt /path/to/existing-app
```

Auto-chains reverse-spec if needed. Each Feature goes through scope confirmation. Specs describe existing behavior as-is.

20.4 Scenario 4: Exploration to Build

You have a reference project and want to build something similar but better.

```
/code-explore /path/to/reference
/code-explore trace "how does context management work"
/code-explore trace "how does provider abstraction work"
/code-explore synthesis
/smart-sdd init --from-explore
/smart-sdd add --from-explore C001
/smart-sdd pipeline F001
```

Traces produce entities, APIs, and observations. Synthesis generates Feature candidates. The pipeline builds your improved design.

20.5 Scenario 5: Mid-Pipeline Investigation

You are in the middle of building Feature 3, and the implementation is stuck because you do not understand how the source handles a specific edge case.

```
# Step out of the pipeline temporarily
/code-explore . --no-branch
/code-explore trace "how does the original handle concurrent file uploads"
# -> Trace reveals: source uses a queue with deduplication

# Return to the pipeline with this understanding
/smart-sdd pipeline F003 --continue
```

The key design: code-explore runs without disturbing pipeline state. It produces persistent file artifacts. The pipeline reads files, not agent memory. You can interrupt, explore, and resume without losing state.

20.6 Scenario 6: Domain Customization

Your project uses a pattern no existing module covers.

```
/domain-extend detect /path/to/code
# -> "Detected uncovered pattern: video-encoding"
/domain-extend extend concerns/video-encoding
# -> Creates 3-file module set
/domain-extend validate
# -> Schema compliance check passes
```

The new module is immediately available. Future Features in this domain automatically inherit its SC rules, bug prevention patterns, and elaboration probes.

Chapter 21

Advanced Topics

21.1 Context Reset Protocol

When to reset: Between Features (after merge), between skill transitions (reverse-spec to pipeline), after context compaction warnings.

When NOT to reset: Never mid-Feature (between specify and plan). Inter-step continuity requires unbroken flow.

How: `/clear` then re-invoke. The agent re-reads `sdd-state.md`, loads updated registries, starts fresh.

Why it is safe: P3 (File over Memory) guarantees nothing is lost. Every decision, artifact, and status update lives in files.

21.2 Mid-Pipeline Step-Back

At any HARD STOP, the user can choose to return to an earlier step. Common patterns:

- During plan review: "Back to specify"—rework the spec before planning.
- During verify: "Back to implement"—fix code issues.
- During verify: "Back to specify"—the spec was fundamentally wrong.

`sdd-state.md` tracks the current step. Step-back updates the state and re-runs from the target step.

21.3 Cross-Feature Impact Analysis

When augmenting a Feature (`add --to`), the pipeline performs impact analysis:

1. Read entity-registry and api-registry for cross-Feature references.
2. Identify which existing Features reference the augmented Feature's entities/APIs.
3. Generate warnings if augmentation could break existing contracts.
4. Post-augmentation: verify cross-Feature integration (Guard 6).

21.4 Multi-Ecosystem Support

For projects spanning multiple frameworks (e.g., React frontend + FastAPI backend), the Foundation axis accepts comma-separated values. Each framework's rules are loaded independently and applied to the relevant parts of the codebase.

```
Framework: react, fastapi
```

Multi-Framework Domain Profile

This loads both `foundations/react.md` and `foundations/fastapi.md`. Each foundation's F2 (specify-time) and F3 (implement-time) rules apply to their respective parts of the codebase. The pipeline does not attempt to merge conflicting foundation rules—they operate on different file sets.

21.5 Skill Development Guidelines

For developers building their own Claude Code skills (not necessarily using spec-kit-skills), the following principles from this project apply universally:

21.5.1 Skill Structure

```
SKILL.md        <- Always loaded (~200 lines): routing + mandatory rules
commands/       <- Loaded on-demand (only the invoked command)
reference/      <- Supporting rules and schemas
domains/        <- Modular expertise (loaded per profile)
```

Recommended Skill Structure

SKILL.md is prime real estate—always in context. Keep it under 300 lines. Everything else loads on demand.

21.5.2 Enforcement Checklist

Every critical rule needs:

1. Inline instruction at the execution point
2. BLOCKING gate (not a warning)
3. Anti-pattern examples (**WRONG** then **RIGHT**)

21.5.3 State Management

- All pipeline state in files (never agent memory)
- State machine file with valid transitions
- After context compression: recover by reading state file

21.5.4 Testing Protocol

1. Test with 50+ message conversations (compression scenario)
2. Test with interrupted sessions (resume from file state)

3. Test anti-patterns (verify agent avoids **WRONG** patterns)
4. After rule changes, re-execute the pipeline (reading is not validating)

21.6 Comparison with Other Approaches

21.6.1 Prompt Libraries

Prompt libraries (awesome-chatgpt-prompts, etc.) provide one-shot instructions. They carry no memory, no state, no enforcement. They optimize for the first message; spec-kit-skills optimizes for the 50th.

21.6.2 Workflow Automation (n8n, Zapier)

Workflow tools chain API calls with deterministic logic. They work well for fixed pipelines but cannot adapt to the semantic complexity of software development—where each step's output determines the next step's context.

21.6.3 Custom Agent Frameworks (LangChain, AutoGPT)

Agent frameworks provide building blocks for tool use and memory. They operate at a lower abstraction level—you build the pipeline from primitives. spec-kit-skills operates at the domain level—the pipeline is pre-built with software engineering semantics.

21.6.4 IDE AI Features (Cursor, Copilot Workspace)

IDE-integrated AI focuses on code generation within an editor context. They are excellent for individual file operations but do not provide cross-Feature memory, domain-adapted rules, or pipeline-level quality gates.

Appendix A

Complete File Inventory

The project contains approximately 400+ markdown files organized across four skills and one shared module. The complete inventory is maintained in `FILE-MAP.md`.

A.1 Root Files

- `README.md` / `README.ko.md`—Project overview (English/Korean)
- `ARCHITECTURE-EXTENSIBILITY.md` / `.ko.md`—Detailed extensibility guide
- `SCENARIO-CATALOG.md` / `.ko.md`—All 38 scenarios
- `FILE-MAP.md`—This inventory
- `CLAUDE.md`—Project rules for Claude Code
- `history.md`—Design decision history
- `lessons-learned.md`—19 gap patterns + 57 lessons
- `PLAYWRIGHT-GUIDE.md`—Playwright setup for Electron

A.2 Complete Concern Inventory

Module	Description
async-state	Reactive state management patterns (Zustand, Redux, MobX).
auth	Authentication flows: JWT, OAuth, session, API key.
authorization	Permission models: RBAC, ABAC, ACL, policy engines.
audit-logging	Immutable audit trails, tamper-proof event logging.
codegen	Generated/templated code from IDL, schema, or template.
compliance	Regulatory frameworks: HIPAA, PCI-DSS, GDPR, SOX.
connection-pool	Connection/resource pool management (DB, HTTP, gRPC).
content-moderation	Text/image/video moderation, review queues, appeals.

Module	Description
cqrs-eventsourcing	CQRS + Event Sourcing (Axon, EventStoreDB).
cryptography	Cryptographic primitives: key exchange, encryption, signatures.
dag-orchestration	DAG workflows (Airflow, Prefect, Dagster, dbt).
distributed-consensus	Raft, Paxos, gossip, leader election.
ecs	Entity-Component-System, data-oriented design.
external-sdk	Third-party API/SDK integrations.
geospatial	Spatial indexing, geo-fencing, map tiles, geocoding.
gpu-compute	GPU/accelerator programming (CUDA, compute shaders).
graceful-lifecycle	Server lifecycle: health checks, graceful shutdown, draining.
hardware-io	Hardware I/O: ioctl, mmap, serial, USB, GPIO, KVM.
i18n	Internationalization and localization.
infra-as-code	Infrastructure definitions (Terraform, Helm, K8s manifests).
iot-protocol	MQTT/CoAP/LwM2M, device management, telemetry.
ipc	Inter-process communication (Electron, Workers).
k8s-operator	Kubernetes reconciliation loop, CRD, controller-runtime.
llm-agents	LLM-based agents, multi-agent coordination.
media-streaming	HLS/DASH adaptive streaming, transcoding, RTMP.
message-queue	Async messaging (RabbitMQ, Kafka, BullMQ).
multi-tenancy	Tenant isolation, per-tenant config.
observability	Structured logging, metrics, distributed tracing.
offline-sync	Offline-first storage, sync queues, conflict resolution.
payment-processing	Payment gateway integration, idempotency, refunds.
plugin-system	Dynamic loading, extension points.
polyglot	Multi-language codebases with cross-language bridges.
protocol-integration	Bidirectional protocols (LSP, MCP).
push-notification	FCM/APNS/WNS, topic subscription, delivery tracking.
realtime	WebSocket, SSE, live updates.
resilience	Retry, circuit breaker, backpressure, timeout.
scheduling-algorithm	Task scheduling, resource allocation, constraint solving.
schema-registry	Schema evolution and registry (Protobuf, Avro).
search-engine	Full-text search, inverted indexes, relevance scoring.
simulation-engine	Physics/DES, time-stepping, deterministic replay.
speech-processing	STT/TTS, VAD, speaker diarization.
stream-processing	Windowing, watermarks, exactly-once, checkpointing.
task-worker	Background jobs, scheduled tasks.
tls-management	TLS/mTLS certificate lifecycle (ACME, rotation, SNI).
udp-transport	UDP datagram networking (DNS, QUIC, game net).
webrtc	WebRTC protocol suite (ICE, DTLS-SRTP, SDP).
wire-protocol	Binary protocols (MQTT, AMQP, RESP, RTMP).

A.3 Skill File Counts

Skill/Module	File Count
shared/ (domains + runtime + reference)	∼80
reverse-spec/ (SKILL + commands + domains + templates)	∼100
smart-sdd/ (SKILL + commands + domains + reference + scripts)	∼120
code-explore/ (SKILL + commands)	∼5
domain-extend/ (SKILL + commands + reference + templates)	∼16
Total	**∼400+**

Appendix B

Scenario Catalog

All 38 scenarios organized by category. Each entry shows when to use it, the command flow, and expected output.

B.1 A: Understand Code (5 scenarios)

SA01 Full architecture understanding: `code-explore [path]` → `trace` → `synthesis`

SA02 Focused area analysis: `code-explore --scope src/auth`

SA03 Compare two projects: `code-explore A` then `code-explore B`

SA04 Deeper analysis with existing SDD docs: `code-explore .` (Context-Aware mode)

SA05 Security/performance audit: `code-explore .` with observation icons

B.2 B: Start New Project (5 scenarios)

SB01 From just an idea: `init "..."` → `add` → `pipeline`

SB02 Inspired by reference: `code-explore` first → `init --from-explore`

SB03 From requirements doc: `init spec.md` or `add requirements.md`

SB04 Build specific Features: `pipeline F003` or `pipeline --tier 1`

SB05 Resume or restart: `pipeline --continue` or delete specs/ → `init`

B.3 C: Apply SDD to Existing Code (5 scenarios)

SC01 Document existing code: `adopt`

SC02 Add features after documenting: `adopt` → `add` → `pipeline`

SC03 Fix bugs systematically: `adopt` → `pipeline`

SC04 Document one service in monorepo: `adopt --scope services/api`

SC05 Modernize legacy code: `adopt` → `pipeline --migration`

B.4 D: Rewrite from Scratch (3 scenarios)

SD01 Full rewrite: `reverse-spec` → `init --from-reverse-spec` → `pipeline`

SD02 Study before rewriting: `code-explore` → `reverse-spec --from-explore`

SD03 Selective rewrite: `reverse-spec` → `pipeline --tier 1`

B.5 E: Revise and Iterate (6 scenarios)

SE01 Step back: At any HARD STOP, choose "Reject" or "back to ..."

SE02 Re-verify after bug fix: `pipeline F001 --start verify`

SE03 Reopen completed Feature: `pipeline F001 --step specify`

SE04 Augment existing Feature: `add --to F001 "add OAuth"`

SE05 Split or merge Features: During `add` or `pipeline merge`

SE06 Specs/plans only: `pipeline F001 --step specify,plan`

B.6 F: Manage Multiple Features (2 scenarios)

SF01 Handle dependencies: `pipeline F001` first, then `pipeline F002`

SF02 Revisit earlier Feature: `pipeline F001 --step specify`

B.7 G: Check Status (2 scenarios)

SG01 Overall progress: `status`

SG02 Spec-code alignment: `parity` or `coverage`

B.8 H: Advanced and Customization (10 scenarios)

SH01 Build a plugin or extension: `init --profile sdk-library` → add → pipeline

SH02 Modernize legacy code: `adopt` → `pipeline --migration`

SH03 Generate artifacts in specific language: `init --lang ko` or `adopt --lang ja`

SH04 Apply SDD per service in monorepo: `adopt --scope services/api` per service

SH05 Browse available modules: `domain-extend browse` or `browse concerns`

SH06 Project uses uncovered pattern: `domain-extend detect` → `extend concern "video-encoding"`

SH07 Import team ADRs: `domain-extend import ./docs/adr/`

SH08 Set org-wide conventions: `domain-extend customize org`

SH09 code-explore found uncovered patterns: `domain-extend detect --from-explore`

SH10 Validate custom modules: `domain-extend validate`

B.9 Scenario Summary by Entry Point

Table B.1: Scenario distribution

Category	Count
A: Understand Code	5
B: Start New Project	5
C: Apply SDD to Existing Code	5
D: Rewrite from Scratch	3
E: Revise and Iterate	6
F: Manage Multiple Features	2
G: Check Status	2
H: Advanced and Customization	10
Total	**38**

Appendix C

Quick Reference Card

C.1 Essential Commands

```
/smart-sdd init "project description"
/smart-sdd add "Feature description"
/smart-sdd pipeline F001
```

Greenfield Workflow

```
/reverse-spec /path/to/source
/smart-sdd init --from-reverse-spec
/smart-sdd pipeline F001
```

Rebuild Workflow

```
/code-explore /path/to/project
/code-explore trace "topic"
/code-explore synthesis
/smart-sdd init --from-explore
```

Exploration Workflow

```
/domain-extend browse
/domain-extend detect /path/to/code
/domain-extend extend concerns/new-pattern
```

Domain Extension

C.2 Common Flags

Flag	Description
`--lang ko|en|ja`	Set artifact language
`--scope core|full`	Limit analysis scope
`--from-explore path`	Use code-explore artifacts
`--from-reverse-spec`	Initialize from reverse-spec output
`--start step`	Resume pipeline from specific step
`--to FID`	Augment existing Feature
`--tier N`	Build specific tier only
`--all`	Batch mode (all eligible Features)
`--adopt`	Adoption mode for reverse-spec
`--no-branch`	Skip branch creation in code-explore

Appendix D

Glossary

Brief
A structured Feature intake process that normalizes any input into a consistently complete Feature definition. Not the same as a PRD—a Brief is the *output* of the consultation, validated for completeness and accuracy.

BLOCKING gate
A structural barrier that prevents the pipeline from proceeding. Unlike a warning or guideline, the agent physically cannot produce the next output without completing the gated step.

Context Injection
The process of assembling relevant domain modules, GEL artifacts, and Feature context before each pipeline step. The architectural heart of spec-kit-skills.

Cross-Concern Integration Rules
Emergent patterns that activate when multiple domain modules are loaded simultaneously. Defined in `_resolver.md` Step 3.5.

Domain Profile
A 5-axis type system that captures project characteristics: Interface, Concern, Archetype, Foundation, Context.

Domain Profile Instance
The concrete, project-specific values assigned to the 5 Domain Profile axes, plus per-Feature domain decisions recorded in `domain-profile-instance.md`. Contrasts with the Domain Profile *framework* (the module system that defines what to ask). The Instance is the "filled-out form"; the framework is the "questionnaire template."

Feature
A self-contained unit of functionality that is independently specifiable, implementable, and verifiable. Each Feature gets exactly one spec, one plan, one implementation cycle.

GEL (Global Evolution Layer)
The set of project-wide artifacts (registries, state, roadmap, constitution, pre-contexts) that carry information across Features.

Guard
A generalized pipeline integrity pattern that addresses a class of failure. Seven guards are defined, extracted from 44 field-discovered incidents.

HARD STOP
A point in the pipeline where execution pauses and requires explicit user input via AskUserQuestion. The agent cannot proceed without a response.

Harness Engineering
The discipline of building structured systems that channel AI agent behavior toward reliable outcomes. The central thesis of spec-kit-skills.

Inline Execution
Executing a sub-skill's instructions within the orchestrator's turn (by reading and following SKILL.md directly) rather than calling it via the Skill tool. Preserves control flow continuity.

Lazy Loading
Loading only the S-sections relevant to the current pipeline command, reducing context consumption by 40–95%.

Module
A markdown file containing domain-specific rules organized by standardized section numbers (S0–S9, A0–A5, R1–R5, F0–F8).

Pre-context
A per-Feature file containing what that Feature needs to know about the project, source analysis, cross-Feature dependencies, and augmented requirements.

Resolver
The module loading protocol (`_resolver.md`) that reads the Domain Profile and loads modules in a defined 8-step order, applying cross-concern rules and scale adjustments.

SBI (Source Behavior Inventory)
A catalog of every user-facing behavior in an existing codebase, produced by reverse-spec Phase 2. Each entry has a B### identifier and maps to source code locations.

SC (Success Criterion)
A measurable condition that defines when a feature requirement is met. Generated during `specify` based on domain module S1 rules.

SDD (Specification-Driven Development)
An approach where each Feature gets a spec defining what it does before any code is written. The spec drives the implementation pipeline.

spec-kit
GitHub's SDD tool that provides the underlying specify/plan/tasks/implement commands. spec-kit-skills wraps spec-kit with cross-Feature awareness and domain expertise.

SKF (Skill Feedback)
A documented failure incident with a unique identifier (SKF-001 through SKF-044+). Each SKF records what happened, why it happened, and how it was fixed. SKFs are the raw material from which gap patterns and guards are extracted.

Tier A grouping of Features by priority. Tier 1 contains core Features that must be built first. Tier 2 and Tier 3 contain progressively less critical Features. The `--tier` flag controls which tiers are active.

Augmentation
The process of adding new requirements to an existing Feature via `add --to`. Triggers SC Preservation to protect previously approved Success Criteria.

Foundation Gate
A one-time verification that runs before the first business Feature. Checks build toolchain, framework plugins, IPC bridges, and layout structure. Results are cached so subsequent Features skip it.

Integration Contract
An explicit definition of the data shapes at Feature boundaries. Specifies what Feature A provides and what Feature B consumes, including exact field names and types.

Interaction Surface Inventory
A list of all user-facing interaction points (drag regions, window controls, keyboard shortcuts, theme toggles) generated after implementation. Used by subsequent Features to avoid breaking existing interactions.

Stub Registry
A record of behaviors stubbed during implementation due to future Feature dependencies. When the dependency Feature starts, the stub list is injected into its context to ensure stubs are resolved.

Clarity Index
A score (0–100%) measuring how completely the user's initial project description covers the key dimensions needed for Domain Profile detection. Low-confidence dimensions trigger targeted questions during `init`.

Fidelity Chain
The mechanism (Guard 7) that ensures source app structure is referenced at every pipeline stage during rebuild. Flows from reverse-spec Component Tree through specify, plan, tasks, implement, and verify.

Data Lifecycle Paradigm
How entities enter, activate, and exit a system (opt-in, opt-out, curated, import-driven). Orthogonal to component structure and must be captured separately to avoid behavioral fidelity failures.

Context Budget
The finite amount of text an agent can hold in its context window at any given time. Managing this budget through lazy loading, per-phase reading, and context resets is essential for pipeline quality.

ADR (Architecture Decision Record)
A document that captures an important architectural decision along with its context and consequences. Teams use ADRs to record why specific technology choices were made. domain-extend's `import` command can convert ADRs into domain module rules.

PRD (Product Requirements Document)
A document describing what a product should do, from the user's perspective. spec-kit-skills can ingest PRDs via `init --prd` to extract Feature candidates and Domain Profile signals.

FR (Functional Requirement)
A specific behavior a Feature must exhibit, identified by a FR-### number. Generated during the `specify` step from Brief inputs and domain module S1 rules.

P1, P2, P3
The three foundational design principles. P1: Context Continuity (information survives transitions). P2: Enforce, Don't Reference (rules must be structurally enforced,

not merely referenced). P3: File over Memory (all state persisted to files, never relying on agent memory).

IPC (Inter-Process Communication)
Communication between separate processes in the same application (e.g., Electron's main process to renderer process). Relevant for desktop app architectures where multiple processes share state.

CDP (Chrome DevTools Protocol)
The protocol used by Playwright and other tools to control Chromium-based browsers. Used in verify phases for runtime UI testing and screenshot capture.

Playwright
A browser automation framework by Microsoft used for end-to-end testing. spec-kit-skills uses Playwright during verify Phase 3 for runtime SC verification, including UI interaction, screenshot capture, and accessibility checks.

Mermaid
A text-based diagram language that renders flowcharts, sequence diagrams, and entity-relationship diagrams from markdown. Used by code-explore's `trace` command to produce visual flow documentation.

JWT (JSON Web Token)
A compact, URL-safe token format for representing claims between two parties. Commonly used for stateless authentication in web APIs.

REST (Representational State Transfer)
An architectural style for web APIs using HTTP methods (GET, POST, PUT, DELETE) and resource-oriented URLs.

gRPC
A high-performance RPC framework by Google using Protocol Buffers for serialization and HTTP/2 for transport. An interface type in the Domain Profile system.

WebSocket
A protocol providing full-duplex communication channels over a single TCP connection. Used for real-time features like chat, live updates, and collaborative editing.

CORS (Cross-Origin Resource Sharing)
A browser security mechanism that controls which domains can access an API. A common source of bugs in web applications with separate frontend and backend.

CI/CD (Continuous Integration / Continuous Deployment)
Automated build, test, and deployment pipelines. Referenced as a signal for `production` maturity level in the Scale system.

DRY (Don't Repeat Yourself)
A software principle that each piece of knowledge should have a single representation. Notably, P2 (Enforce, Don't Reference) intentionally violates DRY because inline repetition is more reliable than cross-references for AI agents.

CQRS (Command Query Responsibility Segregation)
A pattern that separates read operations from write operations, using different models for each. A concern module in the Domain Profile system.

DAG (Directed Acyclic Graph)
A graph with directed edges and no cycles. Used in workflow orchestration, build systems, and data pipeline tools like Airflow.

ETL (Extract, Transform, Load)
A data integration pattern that extracts data from sources, transforms it, and loads it into a destination. An archetype in the Domain Profile system.

ECS (Entity Component System)
A software architecture pattern used primarily in game engines where entities are composed of reusable components processed by systems. A concern module in the Domain Profile system.

LSP (Language Server Protocol)
A protocol for communication between code editors and language servers, providing features like auto-completion, go-to-definition, and diagnostics.

ICE (Interactive Connectivity Establishment)
A framework used by WebRTC to find the best path for peer-to-peer connections, using STUN and TURN servers.

RBAC / ABAC
Role-Based Access Control and Attribute-Based Access Control. Two authorization models for determining user permissions.

AST (Abstract Syntax Tree)
A tree representation of source code structure used by compilers, linters, and formatters. Central to the compiler archetype.

IR (Intermediate Representation)
A data structure used by compilers between parsing and code generation. Enables optimization passes independent of source and target languages.

HLS / DASH
HTTP Live Streaming (Apple) and Dynamic Adaptive Streaming over HTTP (MPEG). Protocols for adaptive bitrate video streaming.

Appendix E

Detailed Injection Map Reference

This appendix documents exactly what context each pipeline step receives, serving as a reference for understanding and debugging pipeline behavior.

E.1 specify Injection

```
Read targets:
  1. specs/_global/entity-registry.md
  2. specs/_global/api-registry.md
  3. specs/{FID}/pre-context.md
  4. specs/{FID}/spec-draft.md (rebuild only)
  5. .specify/memory/constitution.md

Domain sections loaded: S0, S1, S5, S9, A2, A3, A5, F2
Sections discarded: S2, S3, S4, S6, S7, S8, F0, F1, F3-F9

Injected content:
  - Brief-to-SC mapping instructions
  - SC numbering convention
  - Measurability criteria from S1
  - Cross-concern emergent rules (from Step 3.5)
  - Scale-adjusted SC depth

Checkpoint display:
  - Feature name and ID
  - Loaded domain modules with section counts
  - Entity/API registry summary (N entities, M endpoints)
  - Pre-context summary (key requirements)

Review display:
  - Generated FRs with SC counts
  - SC measurability assessment
  - Brief-to-SC coverage (every Brief item -> at least 1 SC)
  - Entity references (new vs existing)
  - AskUserQuestion: Approve / Request modifications
```

specify Context Assembly

E.2 plan Injection

```
Read targets:
  1. specs/{FID}/spec.md
  2. specs/_global/entity-registry.md
  3. specs/_global/api-registry.md
  4. specs/{FID}/pre-context.md (for source component mapping)

Domain sections loaded: S6, S7, A2, F2, F3
Sections discarded: S0, S1, S2, S3, S4, S5, S8, S9

Injected content:
  - Pattern constraints from S6
  - Bug prevention from S7 (plan-relevant subset)
  - Source Component Mapping instructions (rebuild only)
  - Integration Contract template

Review display:
  - Architecture summary (components, data flow)
  - API contracts
  - Integration Contracts (if cross-Feature dependencies)
  - Source Component Mapping (rebuild only, BLOCKING)
  - AskUserQuestion: Approve / Request modifications
```

plan Context Assembly

E.3 implement Injection

```
Read targets:
  1. specs/{FID}/tasks.md
  2. specs/{FID}/plan.md
  3. specs/{FID}/pre-context.md (BLOCKING for rebuild)
  4. Preceding Features' interaction-surfaces.md

Domain sections loaded: S7 (B-3 subset), S6, F3, F8
Sections discarded: S0, S1, S2, S3, S4, S5, S8, S9

Injected content:
  - Per-task bug prevention anti-patterns from S7
  - Framework idioms from F3
  - Toolchain commands from F8
  - Source Reference Injection (BLOCKING for rebuild+GUI)
  - Visual Reference Checkpoint (BLOCKING for first UI task)
  - Interaction Surface Preservation (read inventory before
    modifying shared components)

Post-step update:
  - New entities -> entity-registry.md
  - New API endpoints -> api-registry.md
  - Interaction surfaces -> specs/{FID}/interaction-surfaces.md
```

implement Context Assembly

E.4 verify Injection

```
Read targets:
  1. specs/{FID}/spec.md (for SC list)
  2. specs/{FID}/plan.md (for Integration Contracts)
  3. verify-phases.md (Phase 0-4 protocol)
  4. sdd-state.md verify_progress (for resume)

Domain sections loaded: S1, S3, S7, S8, F8, F9
Sections discarded: S0, S2, S4, S5, S6

Injected content:
  - SC verification checklist from S1
  - Additional verify steps from S3
  - Runtime verification strategy from S8
  - Bug regression patterns from S7
  - Toolchain commands from F8
  - Scan targets from F9

Phase structure:
  Phase 0: Playwright preflight
  Phase 1: Build + typecheck + lint (F8 commands)
  Phase 2: Automated tests
  Phase 3: UI/Runtime verification (S8 strategy)
    3a: Launch application
    3b: SC-by-SC verification against running UI
    3c: Regression checks (previous Features still work)
    3d: Source app comparison (rebuild only, Guard 7)
    3e: User-assisted verification (if Playwright unavailable)
    3f: SC Evidence Gate (all SCs must have evidence)
  Phase 4: Cross-Feature integration (Guard 6)
```

verify Context Assembly

Appendix F

Design Decision History (Selected)

Key architectural decisions that shaped the project, extracted from `history.md`.

F.1 Context Optimization Phase 1 (2026-03-23)

Added "Domain Module Filtering" sections to all 9 injection files, enforcing the lazy-loading table that had been specified but never enforced. The gap was pure P2 violation: the optimization existed on paper (in `_resolver.md` Step 5) but no injection file referenced it.

Decision: Enforce existing spec, do not redesign. Add inline filtering directives to each injection file. Fallback is "load everything" (previous behavior). Zero risk of breaking existing pipelines.

Impact: specify—55% domain context reduction. implement—70% reduction. verify—40% reduction.

F.2 Architectural Rename: Scenario to Context (2026-03-23)

Unified the 5th axis from "Scenario" to "Context", absorbing the separate Scale modifier into a single coherent axis with three components (Mode + Scale + Modifiers).

Rationale: The "5 axes + 1 modifier" model was confusing. Scale was operating as a modifier on the 5th axis but was not formally part of it. Unification made the model cleaner and the resolver logic simpler.

F.3 Simulation-Driven Gap Fixes (2026-03-23)

Ran virtual pipeline simulations on 6 representative project types across rebuild and adoption scenarios. Fixed all HIGH/MEDIUM issues discovered, including:

- Missing TypeScript Foundation stub (Network SDK had no Foundation support)
- Missing desktop-app verify strategy (Electron had no archetype-specific verify)
- 10 new cross-concern integration rules for previously untested combinations
- Missing Foundation F8 in adopt-verify injection

Key insight: Systematic review audits found 17 issues. Simulation on real projects found 6 entirely new gap categories. Reviews are necessary but insufficient; simulation-driven testing is the gold standard for framework validation.

F.4 3-Axis to 5-Axis Evolution

The Domain Profile evolved through three generations:

3-Axis (original) Interface × Concern × Scenario. Adequate for simple projects. Failed when domain philosophy needed to be captured (Gap G12: Ad-hoc Domain Philosophy).

4-Axis (+Archetype) Added archetype axis for domain philosophy. Solved G12 but Foundation was operating as a de facto axis without recognition.

5-Axis (+Foundation, Context restructure) Promoted Foundation. Restructured Scenario into Context with Mode + Scale + Modifiers. The complete model.

Each evolution was triggered by a specific failure pattern. The model will likely continue to evolve as new project types expose gaps.

Colophon

This document was authored in March 2026 using Claude Code (Claude Opus 4.6). The entire spec-kit-skills project, including this manual, was developed through human-AI collaboration—the human designs the harness, the AI operates within it.

The source files for this document and the project it describes are available at:

https://github.com/coolhero/spec-kit-skills

Typeset with XeLaTeX using TeX Gyre Pagella. Code listings in Menlo.
Cover design: none (content over form).
Licensed under the project license.