

Product: RTL8811C/RTL8821C USB Software Package - Linux Driver

Version: v5.8.1_34171.20190628_COEX20190509-4141

Release History:

new ETSI spec. (CE-RED)
)
ility - key reinstallation
mity key remstantation
171114-2525
rs to 0x48
S to OA TO
2
not sniffer Beacon pkt
n TIM IE
ΓS/VTS testing
SA action frame
use power index issue
some AP IOT issue
en kernel version less than 3.0
wakeup can not control GPIO 6, 7
180712-3232
rs to 0x49
4.16
A connected issue
re
190509-4141
rs to 0x54
ersonal)
P connect fail issue



Description:

Realtek provides the solution for WLAN in hardware and software. The software package could be adopted for Realtek RTL8811C/RTL8821C USB WLAN series hardware on Linux based platforms.

Software Version:

RTL8811C/RTL8821C USB Linux Driver Version: v5.8.1_34171.20190628_COEX20190509-4141

Hardware Supported:

- RTL8811CU
- RTL8821CU

Software Package Feature:

- IEEE 802.11 b/g/n/ac WiFi compliant
- 802.1x, WEP, WPA TKIP and WPA2 AES/Mixed mode for PSK and TLS (Radius)
- WPA3-SAE (Personal)
- WPS PIN and PBC Methods
- IEEE 802.11b/g/n/ac Client mode
 - Support wireless security for WEP, WPA TKIP and WPA2 AES PSK
 - Support site survey scan and manual connect
 - Support WPA/WPA2 TLS client
 - Support power saving mode
- Soft AP mode
- WiFi-Direct
- Miracast
- MU-MIMO
- BT-COEXist
- Mesh
- Wake on WLAN

Platform Supported:

- \blacksquare Linux (kernel 2.6.18 ~ 5.x)
- Android $1.6 \sim 2.3, 4.0 \sim 9.x$

CPU supported:

- x86
- ARM
- **■** MIPS