♣ TEXAS INSTRUMENTS Bill of Materials 11 DESIGNS

		1			Manufacturer
Reference	Qty	Value	Part Description	Manufacturer	Part Number
A1	1	DNM	MECHANIC, 2.4GHz INVERTED F ANTENNA, SMD	TEXAS INSTRUMENTS	DN007
ANT1 ANT4	2	2nH	INDUCTOR, CHIP, 2nH, -0.3nH/ +0.3nH, 0.3A, -55DEGC/+125DEGC, 0402, SMD	MURATA	LQG15HS2N0S02D
ANT2 C17 C18 C31	4	DNM	CAPACITOR, CERAMIC, N/A VALUE, -55DEGC/+125DEGC, 0402, SMD	MANUFACTURER SELECTION	CAPACITOR_0402_DNM_N/A_M
ANT3 C11 C13	3	1pF	CAPACITOR, CERAMIC COG/NP0, 1pF, 50V, -0.25pF/ +0.25pF, -55DEGC/+125DEGC, 0402, SMD	MURATA	GRM1555C1H1R0CA01D
ANT5 R12 R26	3	0	RESISTOR, THICK FILM, 0, -5%/+5%, 0.063W, 50V, -55DEGC/+155DEGC, 0402, SMD	MANUFACTURER SELECTION	RESISTOR_0402_0_+/-5%_50V_0.063W_M_+/-200PPM
ANT6	1	0.5pF	CAPACITOR, CERAMIC COG/NP0, 0.5pF, 50V, -0.1pF/+0.1pF, -55DEGC/+125DEGC, 0402, SMD	MURATA	GRM1555C1HR50BA01D
BAT+	1	DNM	NON COMPONENT, BATTERY + PAD, SMD		
BAT-	1	DNM	NON COMPONENT, BATTERY - PAD, SMD		
BT1	1	BAT-HLD-001	BATTERY, HOLDER FOR CR2032 AND CR2025 BATTERIES, SMD	LINX	BAT-HLD-001
BZ1	1	HCS0503B	ACOUSTIC, BUZZER, 3V, -40DEGC/+85DEGC, SMD	CHANGZHOU TIANYIN	HCS0503B
C1	1	DNM	CAPACITOR, CERAMIC X5R, 2.2uf, 10V, -20%/+20%, -55DEGC/+85DEGC, 0603, SMD	MURATA	GRM188R61A225ME34D
2 C3 C4 C6 C8 C9 C12	7	100nF	CAPACITOR, CERAMIC X7R, 100nF, 6.3V, -10%/+10%, -55DEGC/+125DEGC, 0402, SMD	MURATA	GRM155R70J104KA01D
C5	1	22uF	CAPACITOR, CERAMIC X5R, 22uF, 4V, -20%/+20%, -55DEGC/+85DEGC, 0603, SMD	MURATA	GRM188R60G226MEA0D
C7	1	10uF	CAPACITOR, CERAMIC XSR, 10uF, 6.3V, -20%/+20%, -55DEGC/+85DEGC, 0603, SMD	MURATA	GRM188R60J106ME47D
C14 C15	2	12pF	CAPACITOR, CERAMIC COG/NPO, 12pF, 50V, -5%/+5%, -55DEGC/+125DEGC, 0402, SMD	MURATA	GRM1555C1H120JA01D
C16	1	1uF	CAPACITOR, CERAMIC X5R, 1uF, 10V, -10%/+10%, -55DEGC/+85DEGC, 0402, SMD	MURATA	GRM155R61A105KE15D
21 C22 C23 C24 C25 C27 C28	9 C1	100nF	CAPACITOR, CERAMIC XSR, 100nF, 10V, -10%/+10%, -55DEGC/+85DEGC, 0201, SMD	MANUFACTURER SELECTION	CAPACITOR 0201 100nF X5R I +/-10% 10V
C26	1	10nF	CAPACITOR, CERAMIC XSR, 10nF, 10V, -10%/+10%, -55DEGC/+125DEGC, 0201, SMD	MURATA	GRM033R71A103KA01D
C29	1	DNM	CAPACITOR, DO NOT MOUNT	DO NOT MOUNT	DNM
C32 C33	2	15pF	CAPACITOR, CERAMIC, 15pf, 50V, -5%/-5%, -55DEGC/+125DEGC, 0201, SMD	MURATA	GRM0332C1H150JA01D
CR1	1	LS L296-P2Q2-1	OPTO, LED, SUPER RED COLOR, 630nm, 1.8V TO 2.3V, 0.06A, 0603, SMD	OSRAM	LS L296-P2Q2-1-Z
CR3	1	LPL296-J2L2-25	OPTO, LED, GERN COLOR, 562nm, 0.02A, 0.08W, 0.003, 5MD	OSRAM	LP L296-J2L2-25
J2 FIDU3 FIDU4 FIDU5 FIDU6		DNM	FIDUCIAL MARK, ROUND 1.27MM	OSIGNI	Lr L250-3212-25
FL1	1	BLM18HE152SN1	FILTER, EM, 1500@100MHz, -55DEGC, 1603, SMD	MURATA	BLM18HE152SN1D
J1	1	MS-156HF	FILTER, CRIN, 1300@100WINE, 33DEGL/TEJDEGL, 0005, NID CONNECTOR COAX RF, STRAIGHT, FEMALE, SMD	HIROSE	MS-156HF
J2	1	LSS-110-01-F-DV-A-TR		SAMTEC	
L1	1	10uH	CONNECTOR, HEADER, HI-SPEED SOCKET, FEMALE, STRAIGHT, 2 ROWS, 20 PINS, PITCH 0.635mm, SMD INDUCTOR. CHIP. 10uH20%/+20%. 0.11a40DEGC/+85DEGC. 0805. SMD	TAIYO YUDEN	LSS-110-01-F-DV-A-TR CKS2125100M-T
L2 L3	2	2.4nH	INDUCTOR, CHIP, J. JUNI, -2009/1-2008, U. 1143, -40DESC/+85DESC, 0805, SMID INDUCTOR, CHIP, 2.4nH, -0, 3nH/40.3nH, 4, -55DESC/+125DESC, 0402, SMD	MURATA	LQG15HS2N4S02D
P1 01	1	BB02-BS101-KA8-025B00 BC846B	CONNECTOR, HEADER, MALE, 2 ROWS, 10 PINS, PITCH 1.27mm, SMD	GRADCONN	BB02-BS101-KA8-025B00
			TRANSISTOR, BIPOLAR NPN, 65V, 0.1A, 0.25W, SOT-23, SMD	NXP	BC846B,215
R1	1	100k	RESISTOR, THICK FILM, 100k, -5%/+5%, 0.063W, 50V, -55DEGC/+155DEGC, 0402, SMD	MANUFACTURER SELECTION	RESISTOR_0402_100k_+/-5%_50V_0.063W_M_+/-200PPM
R3 R4 R5 R7 R17 R18	7	10k	RESISTOR, THICK FILM, 10K, -5%/+5%, 0.05W, 30V, -55DEGC/+125DEGC, 0201, SMD	MANUFACTURER SELECTION	RESISTOR_0201_10k_+/-5%_30V_0.05W_M_+/-200ppm
R6	1	200k	RESISTOR, THICK FILM, 200K, -1%/+1%, 0.05W, 30V, -55DEGC/+125DEGC, 0201, SMD	VISHAY DALE	CRCW0201200KFKED
R8	1	5.1	RESISTOR, THICK FILM, 5R1, -5%/+5%, 0.05W, 25V, -55DEGC/+125DEGC, 0201, SMD	KAMAYA	RMC1/205R1JPA
R9	1	2Meg	RESISTOR, THICK FILM, 2M, -1%/+1%, 0.063W, 50V, -55DEGC/+155DEGC, 0402, SMD	YAGEO	RC0402FR-072ML
R10	1	680	RESISTOR, THICK FILM, 680, -5%/+5%, 0.063W, 50V, -55DEGC/+155DEGC, 0402, SMD	MANUFACTURER SELECTION	RESISTOR_0402_680_+/-5%_50V_0.063W_M_+/-200PPM
R11 R31 R32	3	0	RESISTOR, THICK FILM, 0, -1%/+1%, 0.05W, 30V, -55DEGC/+155DEGC, 0201, SMD	Manufacturer selection	RESISTOR_0201_0_+/-1%_30V_0.05W_M_+/-100PPM
R16 R50	2	2.2k	RESISTOR, THICK FILM, 2K2, -5%/+5%, 0.05W, 30V, -55DEGC/+125DEGC, 0201, SMD	VISHAY	CRCW02012K20JNED
R21 R22	2	270	RESISTOR, THIN FILM, 270, -5%/+5%, 0.0625W, 50V, -55DEGC/+125DEGCC, 0402, SMD	MANUFACTURER SELECTION	RESISTOR_0402_270_+/-1%_50V_0.063W_M_+/-200PPM
R23	1	DNM	RESISTOR, DO NOT MOUNT, 0402, SMD	DO NOT MOUNT	DNM
R27	1	150	RESISTOR, THICK FILM, 150, -5%/+5%, 0.063W, 50V, -55DEGC/+155DEGC, 0402, SMD	MANUFACTURER SELECTION	RESISTOR_0402_150_+/-5%_50V_0.063W_M_+/-200PPM
SW1 SW2	2	MTA2-WNC	SWITCH, TACT SWITCH, RIGHT ANGLE, 0.05A@12VDC, SMD	DIPTRONICS	MTA2-WNC-V-T/R
SW3	1	MK24-A	SWITCH, OTHER, REED SENSOR, SPST-NO, PULL-IN:23AT TO 50AT, 0.3A@60V, 0.3A, 60V, SMD	MEDER	MK24-A-3
U1	1	CC26xx-7x7	IC, DIGITAL, TEXAS INSTRUMENTS CUSTOM 26xx, QFN48, SMD	TEXAS INSTRUMENTS	CC26xx_7x7_QFN48
U2	1	TS5A3159AYZPR	IC, ANALOG, SPDT SWITCH SINGLE CHANNEL 2:1 MULTIPLEXER/DEMULTIPLEXER, 4.5V TO 5.5V, DSBGA6, SMD	TEXAS INSTRUMENTS	TS5A3159AYZPR
U3	1	BMP280	IC, TRANSDUCER PRESSURE, 300 to 110 hPa, 1.71V TO 3.6V, LGA8, SMD	BOSCH	BMP280
U4	1	TMP007	IC, TRANSDUCER, INFRARED THERMOPILE SENSOR, 2.5V TO 5.5V, DSBGA8, SMD	TEXAS INSTRUMENTS	TMP007AIYZFR
U6	1	SPH0641LU4H	IC, DIGITAL, MICROPHONE WITH MULTIPLE PERFORMANCE MODE, 1.62V TO 3.6V, SMD	KNOWLES	SPH0641LU4H
U7	1	OPT3001	IC, ANALOG, OPT3001, SON6, SMD	TEXAS INSTRUMENTS	OPT3001
U8	1	MPU-9250	IC, TRANSDUCER, 3-AXIS ACCELEROMETER, 3-AXIS GYROSCOPE, 2.4V TO 3.6V, QFN24, SMD	INVENSENSE	MPU-9250
U9	1	HDC1000YPA	IC, TRANSDUCER, LOW POWER, HIGH ACCURACY DIGITAL HUMIDITY SENSOR WITH INTEGRATED TEMPERATURE SENSOR, 2.7V TO 5.5V, DSBGA8, SMD	TEXAS INSTRUMENTS	HDC1000YPAR
U10	1	W25X40CLUXIG	IC, MEMORY, 4M-BIT SERIAL FLASH MEMORY, 2.3V TO 3.6V, USON8, SMD	WINBOND	W25X40CLUXIG
					DNM
	1				FC-135 32.7680KA-AG0
					TSX-3225 24.0000MF15X-AC3
V11 Y1 Y2	1		DNM 32.768kHz 24MHz	DNM IC, DO NOT MOUNT 32.768kHz CRYSTAL, RESONATOR, 32.768kHz, -20PPM/+20PPM, -40DEGC/+85DEGC, SMD	DNM IC, DO NOT MOUNT DO NOT MOUNT 32.768kHz CRYSTAL, RESONATOR, 32.768kHz, -20PPM/-40DEGC/+85DEGC, SMD EPSON

IMPORTANT NOTICE FOR TI REFERENCE DESIGNS

Texas Instruments Incorporated ("TI") reference designs are solely intended to assist designers ("Buyers") who are developing systems that incorporate TI semiconductor products (also referred to herein as "components"). Buyer understands and agrees that Buyer remains responsible for using its independent analysis, evaluation and judgment in designing Buyer's systems and products.

TI reference designs have been created using standard laboratory conditions and engineering practices. TI has not conducted any testing other than that specifically described in the published documentation for a particular reference design. TI may make corrections, enhancements, improvements and other changes to its reference designs.

Buyers are authorized to use TI reference designs with the TI component(s) identified in each particular reference design and to modify the reference design in the development of their end products. HOWEVER, NO OTHER LICENSE, EXPRESS OR IMPLIED, BY ESTOPPEL OR OTHERWISE TO ANY OTHER TI INTELLECTUAL PROPERTY RIGHT, AND NO LICENSE TO ANY THIRD PARTY TECHNOLOGY OR INTELLECTUAL PROPERTY RIGHT, IS GRANTED HEREIN, including but not limited to any patent right, copyright, mask work right, or other intellectual property right relating to any combination, machine, or process in which TI components or services are used. Information published by TI regarding third-party products or services does not constitute a license to use such products or services, or a warranty or endorsement thereof. Use of such information may require a license from a third party under the patents or other intellectual property of the third party, or a license from TI under the patents or other intellectual property of TI.

TI REFERENCE DESIGNS ARE PROVIDED "AS IS". TI MAKES NO WARRANTIES OR REPRESENTATIONS WITH REGARD TO THE REFERENCE DESIGNS OR USE OF THE REFERENCE DESIGNS, EXPRESS, IMPLIED OR STATUTORY, INCLUDING ACCURACY OR COMPLETENESS. TI DISCLAIMS ANY WARRANTY OF TITLE AND ANY IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, QUIET ENJOYMENT, QUIET POSSESSION, AND NON-INFRINGEMENT OF ANY THIRD PARTY INTELLECTUAL PROPERTY RIGHTS WITH REGARD TO TI REFERENCE DESIGNS OR USE THEREOF. TI SHALL NOT BE LIABLE FOR AND SHALL NOT DEFEND OR INDEMNIFY BUYERS AGAINST ANY THIRD PARTY INFRINGEMENT CLAIM THAT RELATES TO OR IS BASED ON A COMBINATION OF COMPONENTS PROVIDED IN A TI REFERENCE DESIGN. IN NO EVENT SHALL TI BE LIABLE FOR ANY ACTUAL, SPECIAL, INCIDENTAL, CONSEQUENTIAL OR INDIRECT DAMAGES, HOWEVER CAUSED, ON ANY THEORY OF LIABILITY AND WHETHER OR NOT TI HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES, ARISING IN ANY WAY OUT OF TI REFERENCE DESIGNS OR BUYER'S USE OF TI REFERENCE DESIGNS.

TI reserves the right to make corrections, enhancements, improvements and other changes to its semiconductor products and services per JESD46, latest issue, and to discontinue any product or service per JESD48, latest issue. Buyers should obtain the latest relevant information before placing orders and should verify that such information is current and complete. All semiconductor products are sold subject to TI's terms and conditions of sale supplied at the time of order acknowledgment.

TI warrants performance of its components to the specifications applicable at the time of sale, in accordance with the warranty in TI's terms and conditions of sale of semiconductor products. Testing and other quality control techniques for TI components are used to the extent TI deems necessary to support this warranty. Except where mandated by applicable law, testing of all parameters of each component is not necessarily performed.

TI assumes no liability for applications assistance or the design of Buyers' products. Buyers are responsible for their products and applications using TI components. To minimize the risks associated with Buyers' products and applications, Buyers should provide adequate design and operating safeguards.

Reproduction of significant portions of TI information in TI data books, data sheets or reference designs is permissible only if reproduction is without alteration and is accompanied by all associated warranties, conditions, limitations, and notices. TI is not responsible or liable for such altered documentation. Information of third parties may be subject to additional restrictions.

Buyer acknowledges and agrees that it is solely responsible for compliance with all legal, regulatory and safety-related requirements concerning its products, and any use of TI components in its applications, notwithstanding any applications-related information or support that may be provided by TI. Buyer represents and agrees that it has all the necessary expertise to create and implement safeguards that anticipate dangerous failures, monitor failures and their consequences, lessen the likelihood of dangerous failures and take appropriate remedial actions. Buyer will fully indemnify TI and its representatives against any damages arising out of the use of any TI components in Buyer's safety-critical applications.

In some cases, TI components may be promoted specifically to facilitate safety-related applications. With such components, TI's goal is to help enable customers to design and create their own end-product solutions that meet applicable functional safety standards and requirements. Nonetheless, such components are subject to these terms.

No TI components are authorized for use in FDA Class III (or similar life-critical medical equipment) unless authorized officers of the parties have executed an agreement specifically governing such use.

Only those TI components that TI has specifically designated as military grade or "enhanced plastic" are designed and intended for use in military/aerospace applications or environments. Buyer acknowledges and agrees that any military or aerospace use of TI components that have *not* been so designated is solely at Buyer's risk, and Buyer is solely responsible for compliance with all legal and regulatory requirements in connection with such use.

TI has specifically designated certain components as meeting ISO/TS16949 requirements, mainly for automotive use. In any case of use of non-designated products, TI will not be responsible for any failure to meet ISO/TS16949.