

Spike Train Analysis: Estimating the firing rate of a simple model neuron from its spike train

Cathal Cooney

School of Maths, Trinity College Dublin

2nd April 2015

Overview

- 1 Introduction
 - Computational Neuroscience
 - Spike Trains
- 2 Neuron Model
 - Definition
 - Markov Chains
 - Firing Rate
 - ISI distribution
- 3 Testing on data
- 4 Conclusion

Introduction to Computational Neuroscience

- Neural data is highly temporal, and data sets can be very large.

Introduction to Computational Neuroscience

- Neural data is highly temporal, and data sets can be very large.
- Computers are therefore widely used to aid the analysis of neural data.

Introduction to Computational Neuroscience

- Neural data is highly temporal, and data sets can be very large.
- Computers are therefore widely used to aid the analysis of neural data.
- Mathematicians, physicists and engineers have looked to use their skills to analyse data and model phenomena.

Spikes

- Spikes are the electrical signals that propagate through the brain.

Spikes

- Spikes are the electrical signals that propagate through the brain.
- They consist of a rapid depolarisation and subsequent hyper-polarisation of the membrane potential.


Spikes

- Spikes are the electrical signals that propagate through the brain.
- They consist of a rapid depolarisation and subsequent hyper-polarisation of the membrane potential.
- A neuron either spikes or it doesn't, there are no fractional spikes.

Spikes

- Spikes are the electrical signals that propagate through the brain.
- They consist of a rapid depolarisation and subsequent hyper-polarisation of the membrane potential.
- A neuron either spikes or it doesn't, there are no fractional spikes.
- A neuron's spikes tend to have a typical voltage profile.

Example spike



Spike Trains

- Spike trains can be described by just their times.

Spike Trains

- Spike trains can be described by just their times.
- So, if a neuron has n spikes at times $t_i, i = 1, \dots, n$.

Spike Trains

- Spike trains can be described by just their times.
- So, if a neuron has n spikes at times $t_i, i = 1, \dots, n$.

$$X = x(t) = \sum_{i=1}^n \delta(t - t_i)$$

Spike Trains

- Spike trains can be described by just their times.
- So, if a neuron has n spikes at times t_i , $i = 1, \dots, n$.

$$X = x(t) = \sum_{i=1}^n \delta(t - t_i)$$

Spike trains are typically treated as point processes in computational neuroscience.

Motivation and assumptions

- It has been observed that some neurons spike at a much higher rate when specific features are present in the stimuli.

Motivation and assumptions

- It has been observed that some neurons spike at a much higher rate when specific features are present in the stimuli.
(eg. grandmother/Jennifer Aniston neuron)

Motivation and assumptions

- It has been observed that some neurons spike at a much higher rate when specific features are present in the stimuli. (eg. grandmother/Jennifer Aniston neuron)
- A simple neuron model is proposed, where a ‘neuron’ is said to either be in an ‘up-state’ or an ‘down-state’.


Motivation and assumptions

- It has been observed that some neurons spike at a much higher rate when specific features are present in the stimuli. (eg. grandmother/Jennifer Aniston neuron)
- A simple neuron model is proposed, where a ‘neuron’ is said to either be in an ‘up-state’ or an ‘down-state’.
- It is assumed that the features are very specific, so most neurons would be ‘down’ more than they are ‘up’.

Motivation and assumptions


- It has been observed that some neurons spike at a much higher rate when specific features are present in the stimuli. (eg. grandmother/Jennifer Aniston neuron)
- A simple neuron model is proposed, where a ‘neuron’ is said to either be in an ‘up-state’ or an ‘down-state’.
- It is assumed that the features are very specific, so most neurons would be ‘down’ more than they are ‘up’.
- This is typical of *sparse coding*, which has been shown to be an energy-efficient coding scheme in the brain.

The Model



The model assumes that the neuron is a bimodal Poisson process, with constant firing rates λ_u and λ_d .

The Model



The model assumes that the neuron is a bimodal Poisson process, with constant firing rates λ_u and λ_d . The ‘switching rates’, u and d , are also assumed to be constant Poisson rates.

Markov Chains

- The on/off - states form a *Markov chain*; there is no extra information to be gained by knowing the history of the process.

$$P(x(t_0 + h) = A | x(t), t \leq t_0) = P(x(t_0 + h) = A | x(t_0))$$

Markov Chains

- The on/off - states form a *Markov chain*; there is no extra information to be gained by knowing the history of the process.

$$P(x(t_0 + h) = A | x(t), t \leq t_0) = P(x(t_0 + h) = A | x(t_0))$$

For the up/down-states, the Markov chain is described as:

$$P'(t) = P(t)Q, \text{ where } Q = \begin{pmatrix} -d & d \\ u & -u \end{pmatrix}$$

Markov Chains

So, if the probability, $p_u(t_0)$, of being in the up-state is known at a time t_0 , then:

$$P(t) = P(t_0)e^{(t-t_0)Q}$$

and

$$p_u(t) = \frac{u}{u+d} \left(1 - e^{-(u+d)(t-t_0)} \right) + p_u(t_0)e^{-(u+d)(t-t_0)}$$

Markov Chains

So, if the probability, $p_u(t_0)$, of being in the up-state is known at a time t_0 , then:

$$P(t) = P(t_0)e^{(t-t_0)Q}$$

and

$$p_u(t) = \frac{u}{u+d} \left(1 - e^{-(u+d)(t-t_0)} \right) + p_u(t_0)e^{-(u+d)(t-t_0)}$$

However, this ignores the differing spiking rates of the two states.

Absorption State

- By restricting the viewpoint to between any two spikes, a new Markov chain is formed.

Absorption State

- By restricting the viewpoint to between any two spikes, a new Markov chain is formed.
- The state of spiking is introduced as an ‘absorption state’ to the previous Markov chain.

Absorption State


- By restricting the viewpoint to between any two spikes, a new Markov chain is formed.
- The state of spiking is introduced as an ‘absorption state’ to the previous Markov chain.
- That is, there is no return possible to the up/down - states having spiked.


Absorption State

- By restricting the viewpoint to between any two spikes, a new Markov chain is formed.
- The state of spiking is introduced as an ‘absorption state’ to the previous Markov chain.
- That is, there is no return possible to the up/down - states having spiked.

This has transition matrix Q_s :

$$Q_s = \begin{pmatrix} -d - \lambda_u & d & \lambda_u \\ u & -u - \lambda_d & \lambda_d \\ 0 & 0 & 0 \end{pmatrix}$$





Between any two spikes, this Markov chain determines the probability of being in the up-state or the down-state. By setting $t_0 = 0$, this has solution:

$$P(t) = P(0)e^{tQ_s}$$

Estimated Firing Rate

Then the firing rate is calculated as:

$$r(t) = \lambda_u p_u(t) + \lambda_d (1 - p_u(t)) = (\lambda_u - \lambda_d) p_u(t) + \lambda_d$$

Estimated Firing Rate

Then the firing rate is calculated as:

$$r(t) = \lambda_u p_u(t) + \lambda_d (1 - p_u(t)) = (\lambda_u - \lambda_d) p_u(t) + \lambda_d$$

If the firing rate at $t = 0$ is r_0 , then this has the very nice form:

$$r(t) = \frac{\alpha (\beta - r_0) e^{-\alpha t} + \beta (r_0 - \alpha) e^{-\beta t}}{(\beta - r_0) e^{-\alpha t} + (r_0 - \alpha) e^{-\beta t}} \quad (1)$$

where $-\alpha, -\beta$ are the non-zero eigenvalues of Q_s .

What about spikes?

What about spikes?

- The firing rate is now known between any two spikes, provided it can be re-calculated at the arrival of each spike.

What about spikes?

- The firing rate is now known between any two spikes, provided it can be re-calculated at the arrival of each spike.
- Use Bayes' theorem to calculate the change at the arrival of each spike.

$$\begin{aligned} P(\text{up-state}|\text{spike}) &= \frac{P(\text{spike}|\text{up-state})P(\text{up-state})}{P(\text{spike})} \\ &= \frac{\lambda_u p_u(t)}{(\lambda_u - \lambda_d)p_u(t) + \lambda_d} \end{aligned}$$

What about spikes?


- The firing rate is now known between any two spikes, provided it can be re-calculated at the arrival of each spike.
- Use Bayes' theorem to calculate the change at the arrival of each spike.

$$\begin{aligned} P(\text{up-state}|\text{spike}) &= \frac{P(\text{spike}|\text{up-state})P(\text{up-state})}{P(\text{spike})} \\ &= \frac{\lambda_u p_u(t)}{(\lambda_u - \lambda_d)p_u(t) + \lambda_d} \end{aligned}$$

In term of the firing rate, get:

$$r(t) \mapsto (\lambda_u + \lambda_d) - \frac{\lambda_u \lambda_d}{r(t)} \quad (2)$$

Firing Rate Estimate



Inter-Spike Interval Distribution

- The firing rate of neurons in-vivo can only be estimated, not measured directly.

Inter-Spike Interval Distribution

- The firing rate of neurons in-vivo can only be estimated, not measured directly.
- Instead, the *inter-spike interval* (ISI) distribution can be measured.

Inter-Spike Interval Distribution

- The firing rate of neurons in-vivo can only be estimated, not measured directly.
- Instead, the *inter-spike interval* (ISI) distribution can be measured.

Given an inhomogeneous Poisson rate $f(t)$, the probability density function (pdf) of the associated ISI distribution can be calculated:

$$p_{ISI}(t) = f(t)e^{\int_0^t f(s) ds}$$

With the rate function $r(t)$ as above, get:

$$p_{ISI}(t) = \rho e^{-\alpha t} + (1 - \rho)e^{-\beta t} \quad (3)$$

This is the pdf of the hyper-exponential distribution H_2 .

Zebra Finch Data



$\times 20$

⋮




⋮

G



M



P



20 conspecific songs.
Each is played ten times.

The electrode is in the area L1.

The output is recorded.

Notes on Data

- Due to the refractory period, this model will not be observed in a single neuron's response.


Notes on Data

- Due to the refractory period, this model will not be observed in a single neuron's response.
- Instead, the ten presentations of each stimulus are superimposed to get an 'average response'.

Notes on Data

- Due to the refractory period, this model will not be observed in a single neuron's response.
- Instead, the ten presentations of each stimulus are superimposed to get an 'average response'.
- The data is trained on 16 of the songs and tested on the remaining four songs.

Results



Conclusions

- There appears to be evidence of bimodality in the ISI distributions.

Conclusions

- There appears to be evidence of bimodality in the ISI distributions.
- This would suggest a bimodality in the firing rate.

Conclusions

- There appears to be evidence of bimodality in the ISI distributions.
- This would suggest a bimodality in the firing rate.
- Evidence of sparse coding in the auditory forebrain of zebra finches.

Thanks

Special thanks to:

my supervisor Dr. Conor Houghton,

Thanks

Special thanks to:

my supervisor Dr. Conor Houghton,

the School of Maths here in TCD,

Thanks

Special thanks to:

my supervisor Dr. Conor Houghton,

the School of Maths here in TCD,

and the University of Bristol.

Questions?

Thank you for listening!

Any questions?