

# ARM® and Thumb®-2 Instruction Set

## Quick Reference Card

Key to Tables			
Rm {, <opsh>}	See Table <b>Register, optionally shifted by constant</b>	<reglist>	A comma-separated list of registers, enclosed in braces { and }.
<Operand2>	See Table <b>Flexible Operand 2</b> . Shift and rotate are only available as part of Operand2.	<reglist-PC>	As <reglist>, must not include the PC.
<fields>	See Table <b>PSR fields</b> .	<reglist+PC>	As <reglist>, including the PC.
<PSR>	APSR (Application Program Status Register), CPSR (Current Processor Status Register), or SPSR (Saved Processor Status Register)	<flags>	Either nzcvcq (ALU flags PSR[31:27]) or g (SIMD GE flags PSR[19:16])
C*, V*	Flag is unpredictable in Architecture v4 and earlier, unchanged in Architecture v5 and later.	\$	See Table <b>ARM architecture versions</b> .
<Rs sh>	Can be Rs or an immediate shift value. The values allowed for each shift type are the same as those shown in Table <b>Register, optionally shifted by constant</b> .	+/-	+ or -. (+ may be omitted.)
x,y	B meaning half-register [15:0], or T meaning [31:16].	<iflags>	Interrupt flags. One or more of a, i, f (abort, interrupt, fast interrupt).
<imm8m>	ARM: a 32-bit constant, formed by right-rotating an 8-bit value by an even number of bits. Thumb: a 32-bit constant, formed by left-shifting an 8-bit value by any number of bits, or a bit pattern of one of the forms 0xXYXYXYXY, 0x00XY00XY or 0xXY00XY00.	<p_mode>	See Table <b>Processor Modes</b>
<prefix>	See Table <b>Prefixes for Parallel instructions</b>	SPm	SP for the processor mode specified by <p_mode>
{IA IB DA DB}	Increment After, Increment Before, Decrement After, or Decrement Before. IB and DA are not available in Thumb state. If omitted, defaults to IA.	<lsb>	Least significant bit of bitfield.
<size>	B, SB, H, or SH, meaning Byte, Halfword, and Signed Halfword respectively. SB and SH are not available in STR instructions.	<width>	Width of bitfield. <width> + <lsb> must be <= 32.
		{X}	RsX is Rs rotated 16 bits if X present. Otherwise, RsX is Rs.
		{!}	Updates base register after data transfer if ! present (pre-indexed).
		{S}	Updates condition flags if S present.
		{T}	User mode privilege if T present.
		{R}	Rounds result to nearest if R present, otherwise truncates result.

Operation		\$	Assembler	S updates	Action	Notes
<b>Add</b>	Add		ADD{S} Rd, Rn, <Operand2>	N Z C V	Rd := Rn + Operand2	N
	with carry		ADC{S} Rd, Rn, <Operand2>	N Z C V	Rd := Rn + Operand2 + Carry	N
	wide	T2	ADD Rd, Rn, #<imm12>		Rd := Rn + imm12, imm12 range 0-4095	T, P
	saturating {doubled}	5E	Q{D}ADD Rd, Rm, Rn		Rd := SAT(Rm + Rn) doubled: Rd := SAT(Rm + SAT(Rn * 2))	Q
<b>Address</b>	Form PC-relative address		ADR Rd, <label>		Rd := <label>, for <label> range from current instruction see Note L	N, L
<b>Subtract</b>	Subtract		SUB{S} Rd, Rn, <Operand2>	N Z C V	Rd := Rn - Operand2	N
	with carry		SBC{S} Rd, Rn, <Operand2>	N Z C V	Rd := Rn - Operand2 - NOT(Carry)	N
	wide	T2	SUB Rd, Rn, #<imm12>		Rd := Rn - imm12, imm12 range 0-4095	T, P
	reverse subtract		RSB{S} Rd, Rn, <Operand2>	N Z C V	Rd := Operand2 - Rn	N
	reverse subtract with carry		RSC{S} Rd, Rn, <Operand2>	N Z C V	Rd := Operand2 - Rn - NOT(Carry)	A
	saturating {doubled}	5E	Q{D}SUB Rd, Rm, Rn		Rd := SAT(Rm - Rn) doubled: Rd := SAT(Rm - SAT(Rn * 2))	Q
	Exception return without stack		SUBS PC, LR, #<imm8>	N Z C V	PC = LR - imm8, CPSR = SPSR(current mode), imm8 range 0-255.	
<b>Parallel arithmetic</b>	Halfword-wise addition	6	<prefix>ADD16 Rd, Rn, Rm		Rd[31:16] := Rn[31:16] + Rm[31:16], Rd[15:0] := Rn[15:0] + Rm[15:0]	G
	Halfword-wise subtraction	6	<prefix>SUB16 Rd, Rn, Rm		Rd[31:16] := Rn[31:16] - Rm[31:16], Rd[15:0] := Rn[15:0] - Rm[15:0]	G
	Byte-wise addition	6	<prefix>ADD8 Rd, Rn, Rm		Rd[31:24] := Rn[31:24] + Rm[31:24], Rd[23:16] := Rn[23:16] + Rm[23:16], Rd[15:8] := Rn[15:8] + Rm[15:8], Rd[7:0] := Rn[7:0] + Rm[7:0]	G
	Byte-wise subtraction	6	<prefix>SUB8 Rd, Rn, Rm		Rd[31:24] := Rn[31:24] - Rm[31:24], Rd[23:16] := Rn[23:16] - Rm[23:16], Rd[15:8] := Rn[15:8] - Rm[15:8], Rd[7:0] := Rn[7:0] - Rm[7:0]	G
	Halfword-wise exchange, add, subtract	6	<prefix>ASX Rd, Rn, Rm		Rd[31:16] := Rn[31:16] + Rm[15:0], Rd[15:0] := Rn[15:0] - Rm[31:16]	G
	Halfword-wise exchange, subtract, add	6	<prefix>SAX Rd, Rn, Rm		Rd[31:16] := Rn[31:16] - Rm[15:0], Rd[15:0] := Rn[15:0] + Rm[31:16]	G
	Unsigned sum of absolute differences	6	USAD8 Rd, Rm, Rs		Rd := Abs(Rm[31:24] - Rs[31:24]) + Abs(Rm[23:16] - Rs[23:16]) + Abs(Rm[15:8] - Rs[15:8]) + Abs(Rm[7:0] - Rs[7:0])	
	and accumulate	6	USADA8 Rd, Rm, Rs, Rn		Rd := Rn + Abs(Rm[31:24] - Rs[31:24]) + Abs(Rm[23:16] - Rs[23:16]) + Abs(Rm[15:8] - Rs[15:8]) + Abs(Rm[7:0] - Rs[7:0])	
<b>Saturate</b>	Signed saturate word, right shift	6	SSAT Rd, #<sat>, Rm{, ASR <sh>}		Rd := SignedSat((Rm ASR sh), sat). <sat> range 1-32, <sh> range 1-31.	Q, R
	Signed saturate word, left shift	6	SSAT Rd, #<sat>, Rm{, LSL <sh>}		Rd := SignedSat((Rm LSL sh), sat). <sat> range 1-32, <sh> range 0-31.	Q
	Signed saturate two halfwords	6	SSAT16 Rd, #<sat>, Rm		Rd[31:16] := SignedSat(Rm[31:16], sat), Rd[15:0] := SignedSat(Rm[15:0], sat). <sat> range 1-16.	Q
	Unsigned saturate word, right shift	6	USAT Rd, #<sat>, Rm{, ASR <sh>}		Rd := UnsignedSat((Rm ASR sh), sat). <sat> range 0-31, <sh> range 1-31.	Q, R
	Unsigned saturate word, left shift	6	USAT Rd, #<sat>, Rm{, LSL <sh>}		Rd := UnsignedSat((Rm LSL sh), sat). <sat> range 0-31, <sh> range 0-31.	Q
	Unsigned saturate two halfwords	6	USAT16 Rd, #<sat>, Rm		Rd[31:16] := UnsignedSat(Rm[31:16], sat), Rd[15:0] := UnsignedSat(Rm[15:0], sat). <sat> range 0-15.	Q

# ARM and Thumb-2 Instruction Set

## Quick Reference Card

Operation		§	Assembler	S updates	Action	Notes
<b>Multiply</b>	Multiply		MUL{S} Rd, Rm, Rs	N Z C*	Rd := (Rm * Rs)[31:0] (If Rs is Rd, S can be used in Thumb-2)	N, S
	and accumulate		MLA{S} Rd, Rm, Rs, Rn	N Z C*	Rd := (Rn + (Rm * Rs))[31:0]	S
	and subtract	T2	MLS Rd, Rm, Rs, Rn		Rd := (Rn - (Rm * Rs))[31:0]	
	unsigned long		UMULL{S} RdLo, RdHi, Rm, Rs	N Z C* V*	RdHi, RdLo := unsigned(Rm * Rs)	S
	unsigned accumulate long		UMLAL{S} RdLo, RdHi, Rm, Rs	N Z C* V*	RdHi, RdLo := unsigned(RdHi, RdLo + Rm * Rs)	S
	unsigned double accumulate long	6	UMAAL RdLo, RdHi, Rm, Rs		RdHi, RdLo := unsigned(RdHi + RdLo + Rm * Rs)	
	Signed multiply long		SMULL{S} RdLo, RdHi, Rm, Rs	N Z C* V*	RdHi, RdLo := signed(Rm * Rs)	S
	and accumulate long		SMLAL{S} RdLo, RdHi, Rm, Rs	N Z C* V*	RdHi, RdLo := signed(RdHi, RdLo + Rm * Rs)	S
	16 * 16 bit	5E	SMULxy Rd, Rm, Rs		Rd := Rm[x] * Rs[y]	
	32 * 16 bit	5E	SMULWy Rd, Rm, Rs		Rd := (Rm * Rs[y])[47:16]	
	16 * 16 bit and accumulate	5E	SMLAxy Rd, Rm, Rs, Rn		Rd := Rn + Rm[x] * Rs[y]	Q
	32 * 16 bit and accumulate	5E	SMLAWy Rd, Rm, Rs, Rn		Rd := Rn + (Rm * Rs[y])[47:16]	Q
	16 * 16 bit and accumulate long	5E	SMLALxy RdLo, RdHi, Rm, Rs		RdHi, RdLo := RdHi, RdLo + Rm[x] * Rs[y]	
	Dual signed multiply, add	6	SMUAD{X} Rd, Rm, Rs		Rd := Rm[15:0] * RsX[15:0] + Rm[31:16] * RsX[31:16]	Q
	and accumulate	6	SMLAD{X} Rd, Rm, Rs, Rn		Rd := Rn + Rm[15:0] * RsX[15:0] + Rm[31:16] * RsX[31:16]	Q
	and accumulate long	6	SMLALD{X} RdLo, RdHi, Rm, Rs		RdHi, RdLo := RdHi, RdLo + Rm[15:0] * RsX[15:0] + Rm[31:16] * RsX[31:16]	
	Dual signed multiply, subtract	6	SMUSD{X} Rd, Rm, Rs		Rd := Rm[15:0] * RsX[15:0] - Rm[31:16] * RsX[31:16]	Q
	and accumulate	6	SMLSd{X} Rd, Rm, Rs, Rn		Rd := Rn + Rm[15:0] * RsX[15:0] - Rm[31:16] * RsX[31:16]	Q
	and accumulate long	6	SMLSd{X} RdLo, RdHi, Rm, Rs		RdHi, RdLo := RdHi, RdLo + Rm[15:0] * RsX[15:0] - Rm[31:16] * RsX[31:16]	
	Signed top word multiply	6	SMMUL{R} Rd, Rm, Rs		Rd := (Rm * Rs)[63:32]	
	and accumulate	6	SMMLA{R} Rd, Rm, Rs, Rn		Rd := Rn + (Rm * Rs)[63:32]	
	and subtract	6	SMMLS{R} Rd, Rm, Rs, Rn		Rd := Rn - (Rm * Rs)[63:32]	
<b>Divide</b>	with internal 40-bit accumulate	XS	MIA Ac, Rm, Rs		Ac := Ac + Rm * Rs	
	packed halfword	XS	MIAPH Ac, Rm, Rs		Ac := Ac + Rm[15:0] * Rs[15:0] + Rm[31:16] * Rs[31:16]	
	halfword	XS	MIAXy Ac, Rm, Rs		Ac := Ac + Rm[x] * Rs[y]	
<b>Divide</b>	Signed or Unsigned	RM	<op> Rd, Rn, Rm		Rd := Rn / Rm <op> is SDIV (signed) or UDIV (unsigned)	T
<b>Move data</b>	Move		MOV{S} Rd, <Operand2>	N Z C	Rd := Operand2 See also Shift instructions	N
	not		MVN{S} Rd, <Operand2>	N Z C	Rd := 0xFFFFFFFF EOR Operand2	N
	top	T2	MOVT Rd, #<imm16>		Rd[31:16] := imm16, Rd[15:0] unaffected, imm16 range 0-65535	
	wide	T2	MOV Rd, #<imm16>		Rd[15:0] := imm16, Rd[31:16] = 0, imm16 range 0-65535	
	40-bit accumulator to register	XS	MRA RdLo, RdHi, Ac		RdLo := Ac[31:0], RdHi := Ac[39:32]	
	register to 40-bit accumulator	XS	MAR Ac, RdLo, RdHi		Ac[31:0] := RdLo, Ac[39:32] := RdHi[7:0]	
<b>Shift</b>	Arithmetic shift right		ASR{S} Rd, Rm, <Rs sh>	N Z C	Rd := ASR(Rm, Rslsh) Same as MOV{S} Rd, Rm, ASR <Rs sh>	N
	Logical shift left		LSL{S} Rd, Rm, <Rs sh>	N Z C	Rd := LSL(Rm, Rslsh) Same as MOV{S} Rd, Rm, LSL <Rs sh>	N
	Logical shift right		LSR{S} Rd, Rm, <Rs sh>	N Z C	Rd := LSR(Rm, Rslsh) Same as MOV{S} Rd, Rm, LSR <Rs sh>	N
	Rotate right		ROR{S} Rd, Rm, <Rs sh>	N Z C	Rd := ROR(Rm, Rslsh) Same as MOV{S} Rd, Rm, ROR <Rs sh>	N
	Rotate right with extend		RRX{S} Rd, Rm	N Z C	Rd := RRX(Rm) Same as MOV{S} Rd, Rm, RRX	
<b>Count leading zeros</b>		5	CLZ Rd, Rm		Rd := number of leading zeros in Rm	
<b>Compare</b>	Compare		CMP Rn, <Operand2>	N Z C V	Update CPSR flags on Rn - Operand2	N
	negative		CMN Rn, <Operand2>	N Z C V	Update CPSR flags on Rn + Operand2	N
<b>Logical</b>	Test		TST Rn, <Operand2>	N Z C	Update CPSR flags on Rn AND Operand2	N
	Test equivalence		TEQ Rn, <Operand2>	N Z C	Update CPSR flags on Rn EOR Operand2	
	AND		AND{S} Rd, Rn, <Operand2>	N Z C	Rd := Rn AND Operand2	N
	EOR		EOR{S} Rd, Rn, <Operand2>	N Z C	Rd := Rn EOR Operand2	N
	ORR		ORR{S} Rd, Rn, <Operand2>	N Z C	Rd := Rn OR Operand2	N
	ORN	T2	ORN{S} Rd, Rn, <Operand2>	N Z C	Rd := Rn OR NOT Operand2	T
	Bit Clear		BIC{S} Rd, Rn, <Operand2>	N Z C	Rd := Rn AND NOT Operand2	N

# ARM and Thumb-2 Instruction Set

## Quick Reference Card

Operation		§	Assembler	Action	Notes
Bit field	Bit Field Clear	T2	BFC Rd, #<lsb>, #<width>	Rd[(width+lsb-1):lsb] := 0, other bits of Rd unaffected	
	Bit Field Insert	T2	BFI Rd, Rn, #<lsb>, #<width>	Rd[(width+lsb-1):lsb] := Rn[(width-1):0], other bits of Rd unaffected	
	Signed Bit Field Extract	T2	SBFX Rd, Rn, #<lsb>, #<width>	Rd[(width-1):0] = Rn[(width+lsb-1):lsb], Rd[31:width] = Replicate( Rn[width+lsb-1] )	
	Unsigned Bit Field Extract	T2	UBFX Rd, Rn, #<lsb>, #<width>	Rd[(width-1):0] = Rn[(width+lsb-1):lsb], Rd[31:width] = Replicate( 0 )	
Pack	Pack halfword bottom + top	6	PKHBT Rd, Rn, Rm{, LSL #<sh>}	Rd[15:0] := Rn[15:0], Rd[31:16] := (Rm LSL sh)[31:16]. sh 0-31.	
	Pack halfword top + bottom	6	PKHTB Rd, Rn, Rm{, ASR #<sh>}	Rd[31:16] := Rn[31:16], Rd[15:0] := (Rm ASR sh)[15:0]. sh 1-32.	
Signed extend	Halfword to word	6	SXTH Rd, Rm{, ROR #<sh>}	Rd[31:0] := SignExtend((Rm ROR (8 * sh))[15:0]). sh 0-3.	N
	Two bytes to halfwords	6	SXTB16 Rd, Rm{, ROR #<sh>}	Rd[31:16] := SignExtend((Rm ROR (8 * sh))[23:16]), Rd[15:0] := SignExtend((Rm ROR (8 * sh))[7:0]). sh 0-3.	
	Byte to word	6	SXTB Rd, Rm{, ROR #<sh>}	Rd[31:0] := SignExtend((Rm ROR (8 * sh))[7:0]). sh 0-3.	N
Unsigned extend	Halfword to word	6	UXTH Rd, Rm{, ROR #<sh>}	Rd[31:0] := ZeroExtend((Rm ROR (8 * sh))[15:0]). sh 0-3.	N
	Two bytes to halfwords	6	UXTB16 Rd, Rm{, ROR #<sh>}	Rd[31:16] := ZeroExtend((Rm ROR (8 * sh))[23:16]), Rd[15:0] := ZeroExtend((Rm ROR (8 * sh))[7:0]). sh 0-3.	
	Byte to word	6	UXTB Rd, Rm{, ROR #<sh>}	Rd[31:0] := ZeroExtend((Rm ROR (8 * sh))[7:0]). sh 0-3.	N
Signed extend with add	Halfword to word, add	6	SXTAH Rd, Rn, Rm{, ROR #<sh>}	Rd[31:0] := Rn[31:0] + SignExtend((Rm ROR (8 * sh))[15:0]). sh 0-3.	
	Two bytes to halfwords, add	6	SXTAB16 Rd, Rn, Rm{, ROR #<sh>}	Rd[31:16] := Rn[31:16] + SignExtend((Rm ROR (8 * sh))[23:16]), Rd[15:0] := Rn[15:0] + SignExtend((Rm ROR (8 * sh))[7:0]). sh 0-3.	
	Byte to word, add	6	SXTAB Rd, Rn, Rm{, ROR #<sh>}	Rd[31:0] := Rn[31:0] + SignExtend((Rm ROR (8 * sh))[7:0]). sh 0-3.	
Unsigned extend with add	Halfword to word, add	6	UXTAH Rd, Rn, Rm{, ROR #<sh>}	Rd[31:0] := Rn[31:0] + ZeroExtend((Rm ROR (8 * sh))[15:0]). sh 0-3.	
	Two bytes to halfwords, add	6	UXTAB16 Rd, Rn, Rm{, ROR #<sh>}	Rd[31:16] := Rn[31:16] + ZeroExtend((Rm ROR (8 * sh))[23:16]), Rd[15:0] := Rn[15:0] + ZeroExtend((Rm ROR (8 * sh))[7:0]). sh 0-3.	
	Byte to word, add	6	UXTAB Rd, Rn, Rm{, ROR #<sh>}	Rd[31:0] := Rn[31:0] + ZeroExtend((Rm ROR (8 * sh))[7:0]). sh 0-3.	
Reverse	Bits in word	T2	RBIT Rd, Rm	For (i = 0; i < 32; i++) : Rd[i] = Rm[31 - i]	
	Bytes in word	6	REV Rd, Rm	Rd[31:24] := Rm[7:0], Rd[23:16] := Rm[15:8], Rd[15:8] := Rm[23:16], Rd[7:0] := Rm[31:24]	N
	Bytes in both halfwords	6	REV16 Rd, Rm	Rd[15:8] := Rm[7:0], Rd[7:0] := Rm[15:8], Rd[31:24] := Rm[23:16], Rd[23:16] := Rm[31:24]	N
	Bytes in low halfword, sign extend	6	REVSH Rd, Rm	Rd[15:8] := Rm[7:0], Rd[7:0] := Rm[15:8], Rd[31:16] := Rm[7] * &FFFF	N
Select	Select bytes	6	SEL Rd, Rn, Rm	Rd[7:0] := Rn[7:0] if GE[0] = 1, else Rd[7:0] := Rm[7:0] Bits[15:8], [23:16], [31:24] selected similarly by GE[1], GE[2], GE[3]	
If-Then	If-Then	T2	IT{pattern} {cond}	Makes up to four following instructions conditional, according to pattern. pattern is a string of up to three letters. Each letter can be T (Then) or E (Else). The first instruction after IT has condition cond. The following instructions have condition cond if the corresponding letter is T, or the inverse of cond if the corresponding letter is E. See Table <b>Condition Field</b> for available condition codes.	T, U
Branch	Branch		B <label>	PC := label. label is this instruction ±32MB (T2: ±16MB, T: -252 - +256B)	N, B
	with link		BL <label>	LR := address of next instruction, PC := label. label is this instruction ±32MB (T2: ±16MB).	
	and exchange	4T	BX Rm	PC := Rm. Target is Thumb if Rm[0] is 1, ARM if Rm[0] is 0.	N
	with link and exchange (1)	5T	BLX <label>	LR := address of next instruction, PC := label, Change instruction set. label is this instruction ±32MB (T2: ±16MB).	C
	with link and exchange (2)	5	BLX Rm	LR := address of next instruction, PC := Rm[31:1]. Change to Thumb if Rm[0] is 1, to ARM if Rm[0] is 0.	N
	and change to Jazelle state	5J	CBXJ Rm	Change to Jazelle state if available	
	Compare, branch if (non) zero	T2	CB{N}Z Rn, <label>	If Rn {== or !=} 0 then PC := label. label is (this instruction + 4-130).	N,T,U
Move to or from PSR	Table Branch Byte	T2	TBB [Rn, Rm]	PC = PC + ZeroExtend( Memory( Rn + Rm, 1) << 1). Branch range 4-512. Rn can be PC.	T, U
	Table Branch Halfword	T2	TBH [Rn, Rm, LSL #1]	PC = PC + ZeroExtend( Memory( Rn + Rm << 1, 2) << 1). Branch range 4-131072. Rn can be PC.	T, U
	PSR to register		MRS Rd, <PSR>	Rd := PSR	
Processor state change	register flags to APSR flags		MSR APSR_<flags>, Rm	APSR_<flags> := Rm	
	immediate flags to APSR flags		MSR APSR_<flags>, #<imm8m>	APSR_<flags> := imm8_r	
	register to PSR		MSR <PSR>_<fields>, Rm	PSR := Rm (selected bytes only)	
	immediate to PSR		MSR <PSR>_<fields>, #<imm8m>	PSR := imm8_r (selected bytes only)	
	Set endianness	6	SETEND <endianness>	Sets endianness for loads and stores. <endianness> can be BE (Big Endian) or LE (Little Endian).	U, N
Processor state change	Change processor state	6	CPSID <iflags> {, #<p_mode>}	Disable specified interrupts, optional change mode.	U, N
	Change processor mode	6	CPSIE <iflags> {, #<p_mode>}	Enable specified interrupts, optional change mode.	U, N
	Set endianness	6	CPS #<p_mode>		U
Processor state change	Set endianness	6	SETEND <endianness>	Sets endianness for loads and stores. <endianness> can be BE (Big Endian) or LE (Little Endian).	U, N

ARM and Thumb-2 Instruction Set  
Quick Reference Card

Single data item loads and stores		\$	Assembler		Action if <op> is LDR	Action if <op> is STR	Notes
Load or store word, byte or halfword	Immediate offset			<op>{size}{T} Rd, [Rn {, #<offset>}]{!}	Rd := [address, size]	[address, size] := Rd	1, N
	Post-indexed, immediate			<op>{size}{T} Rd, [Rn], #<offset>	Rd := [address, size]	[address, size] := Rd	2
	Register offset			<op>{size} Rd, [Rn, +/-Rm {, <opsh>}]{!}	Rd := [address, size]	[address, size] := Rd	3, N
	Post-indexed, register			<op>{size}{T} Rd, [Rn], +/-Rm {, <opsh>}	Rd := [address, size]	[address, size] := Rd	4
	PC-relative			<op>{size} Rd, <label>	Rd := [label, size]	Not available	5, N
Load or store doubleword	Immediate offset	5E		<op>D Rd1, Rd2, [Rn {, #<offset>}]{!}	Rd1 := [address], Rd2 := [address + 4]	[address] := Rd1, [address + 4] := Rd2	6, 9
	Post-indexed, immediate	5E		<op>D Rd1, Rd2, [Rn], #<offset>	Rd1 := [address], Rd2 := [address + 4]	[address] := Rd1, [address + 4] := Rd2	6, 9
	Register offset	5E		<op>D Rd1, Rd2, [Rn, +/-Rm {, <opsh>}]{!}	Rd1 := [address], Rd2 := [address + 4]	[address] := Rd1, [address + 4] := Rd2	7, 9
	Post-indexed, register	5E		<op>D Rd1, Rd2, [Rn], +/-Rm {, <opsh>}	Rd1 := [address], Rd2 := [address + 4]	[address] := Rd1, [address + 4] := Rd2	7, 9
	PC-relative	5E		<op>D Rd1, Rd2, <label>	Rd1 := [label], Rd2 := [label + 4]	Not available	8, 9

Preload data or instruction		\$(PLD)	\$(PLI)	\$(PLDW)	Assembler	Action if <op> is PLD	Action if <op> is PLI	Action if <op> is PLDW	Notes
	Immediate offset	5E	7	7MP	<op> [Rn {, #<offset>}]	Preload [address, 32] (data)	Preload [address, 32] (instruction)	Preload to Write [address, 32] (data)	1, C
	Register offset	5E	7	7MP	<op> [Rn, +/-Rm {, <opsh>}]	Preload [address, 32] (data)	Preload [address, 32] (instruction)	Preload to Write [address, 32] (data)	3, C
	PC-relative	5E	7		<op> <label>	Preload [label, 32] (data)	Preload [label, 32] (instruction)		5, C

Other memory operations		\$	Assembler		Action	Notes
Load multiple	Block data load			LDM{IA IB DA DB} Rn{!}, <reglist-PC>	Load list of registers from [Rn]	N, I
	return (and exchange)			LDM{IA IB DA DB} Rn{!}, <reglist+PC>	Load registers, PC := [address][31:1] (§ 5T: Change to Thumb if [address][0] is 1)	I
	and restore CPSR			LDM{IA IB DA DB} Rn{!}, <reglist+PC>^	Load registers, branch (§ 5T: and exchange), CPSR := SPSR. Exception modes only.	I
	User mode registers			LDM{IA IB DA DB} Rn, <reglist-PC>^	Load list of User mode registers from [Rn]. Privileged modes only.	I
Pop				POP <reglist>	Canonical form of LDM SP!, <reglist>	N
Load exclusive	Semaphore operation	6		LDREX Rd, [Rn]	Rd := [Rn], tag address as exclusive access. Outstanding tag set if not shared address. Rd, Rn not PC.	
	Halfword or Byte	6K		LDREX{H B} Rd, [Rn]	Rd[15:0] := [Rn] or Rd[7:0] := [Rn], tag address as exclusive access. Outstanding tag set if not shared address. Rd, Rn not PC.	
	Doubleword	6K		LDREXD Rd1, Rd2, [Rn]	Rd1 := [Rn], Rd2 := [Rn+4], tag addresses as exclusive access Outstanding tags set if not shared addresses. Rd1, Rd2, Rn not PC.	9
Store multiple	Push, or Block data store			STM{IA IB DA DB} Rn{!}, <reglist>	Store list of registers to [Rn]	N, I
	User mode registers			STM{IA IB DA DB} Rn{!}, <reglist>^	Store list of User mode registers to [Rn]. Privileged modes only.	I
Push				PUSH <reglist>	Canonical form of STMDB SP!, <reglist>	N
Store exclusive	Semaphore operation	6		STREX Rd, Rm, [Rn]	If allowed, [Rn] := Rm, clear exclusive tag, Rd := 0. Else Rd := 1. Rd, Rm, Rn not PC.	
	Halfword or Byte	6K		STREX{H B} Rd, Rm, [Rn]	If allowed, [Rn] := Rm[15:0] or [Rn] := Rm[7:0], clear exclusive tag, Rd := 0. Else Rd := 1 Rd, Rm, Rn not PC.	
	Doubleword	6K		STREXD Rd, Rm1, Rm2, [Rn]	If allowed, [Rn] := Rm1, [Rn+4] := Rm2, clear exclusive tags, Rd := 0. Else Rd := 1 Rd, Rm1, Rm2, Rn not PC.	10
Clear exclusive		6K		CLREX	Clear local processor exclusive tag	C

Notes: availability and range of options for Load, Store, and Preload operations					
Note	ARM Word, B, D	ARM SB, H, SH	ARM T, BT	Thumb-2 Word, B, SB, H, SH, D	Thumb-2 T, BT, SBT, HT, SHT
1	offset: – 4095 to +4095	offset: –255 to +255	Not available	offset: –255 to +255 if writeback, –255 to +4095 otherwise	offset: 0 to +255, writeback not allowed
2	offset: – 4095 to +4095	offset: –255 to +255	offset: – 4095 to +4095	offset: –255 to +255	Not available
3	Full range of {, <opsh>}	{, <opsh>} not allowed	Not available	<opsh> restricted to LSL #<sh>, <sh> range 0 to 3	Not available
4	Full range of {, <opsh>}	{, <opsh>} not allowed	Full range of {, <opsh>}	Not available	Not available
5	label within +/- 4092 of current instruction	Not available	Not available	label within +/- 4092 of current instruction	Not available
6	offset: –255 to +255	-	-	offset: –1020 to +1020, must be multiple of 4.	-
7	{, <opsh>} not allowed	-	-	Not available	-
8	label within +/- 252 of current instruction	-	-	Not available	-
9	Rd1 even, and not r14, Rd2 == Rd1 + 1.	-	-	Rd1 != PC, Rd2 != PC	-
10	Rm1 even, and not r14, Rm2 == Rm1 + 1.	-	-	Rm1 != PC, Rm2 != PC	-

ARM and Thumb-2 Instruction Set  
Quick Reference Card

Coprocessor operations	§	Assembler	Action	Notes
Data operations		CDP{2} <copr>, <op1>, CRd, CRn, CRm{, <op2>}	Coprocessor defined	C2
Move to ARM register from coprocessor		MRC{2} <copr>, <op1>, Rd, CRn, CRm{, <op2>}	Coprocessor defined	C2
Two ARM register move	5E	MRRC <copr>, <op1>, Rd, Rn, CRm	Coprocessor defined	
Alternative two ARM register move	6	MRRC2 <copr>, <op1>, Rd, Rn, CRm	Coprocessor defined	C
Move to coproc from ARM reg		MCR{2} <copr>, <op1>, Rd, CRn, CRm{, <op2>}	Coprocessor defined	C2
Two ARM register move	5E	MCCR <copr>, <op1>, Rd, Rn, CRm	Coprocessor defined	
Alternative two ARM register move	6	MCCR2 <copr>, <op1>, Rd, Rn, CRm	Coprocessor defined	C
Loads and stores, pre-indexed		<op>{2} <copr>, CRd, [Rn, #+/-<offset8*4>]{!}	op: LDC or STC. offset: multiple of 4 in range 0 to 1020.	C2
Loads and stores, zero offset		<op>{2} <copr>, CRd, [Rn] {, 8-bit copro. option}	op: LDC or STC.	C2
Loads and stores, post-indexed		<op>{2} <copr>, CRd, [Rn], #+/-<offset8*4>	op: LDC or STC. offset: multiple of 4 in range 0 to 1020.	C2

Miscellaneous operations	§	Assembler	Action	Notes
Swap word		SWP Rd, Rm, [Rn]	temp := [Rn], [Rn] := Rm, Rd := temp.	A, D
Swap byte		SWPB Rd, Rm, [Rn]	temp := ZeroExtend([Rn][7:0]), [Rn][7:0] := Rm[7:0], Rd := temp	A, D
Strong return state	6	SRS{IA IB DA DB} SP{!}, #<p_mode>	[SPm] := LR, [SPm + 4] := CPSR	C, I
Return from exception	6	RFE{IA IB DA DB} Rn{!}	PC := [Rn], CPSR := [Rn + 4]	C, I
Breakpoint	5	BKPT <imm16>	Prefetch abort <i>or</i> enter debug state. 16-bit bitfield encoded in instruction.	C, N
Secure Monitor Call	Z	SMC <imm4>	Secure Monitor Call exception. 4-bit bitfield encoded in instruction. Formerly SMI.	
Supervisor Call		SVC <imm24>	Supervisor Call exception. 24-bit bitfield encoded in instruction. Formerly SWI.	N
No operation	6K	NOP	None, might not even consume any time.	N, V
Hints				
Debug Hint	7	DBG	Provide hint to debug and related systems.	
Data Memory Barrier	7	DMB	Ensure the order of observation of memory accesses.	C
Data Synchronization Barrier	7	DSB	Ensure the completion of memory accesses,	C
Instruction Synchronization Barrier	7	ISB	Flush processor pipeline and branch prediction logic.	C
Set event	6K	SEV	Signal event in multiprocessor system. NOP if not implemented.	N
Wait for event	6K	WFE	Wait for event, IRQ, FIQ, Imprecise abort, or Debug entry request. NOP if not implemented.	N
Wait for interrupt	6K	WFI	Wait for IRQ, FIQ, Imprecise abort, or Debug entry request. NOP if not implemented.	N
Yield	6K	YIELD	Yield control to alternative thread. NOP if not implemented.	N

Notes				
A	Not available in Thumb state.	P	Rn can be the PC in Thumb state in this instruction.	
B	Can be conditional in Thumb state without having to be in an IT block.	Q	Sets the Q flag if saturation (addition or subtraction) or overflow (multiplication) occurs. Read and reset the Q flag using MRS and MSR.	
C	Condition codes are not allowed in ARM state.	R	<sh> range is 1-32 in the ARM instruction.	
C2	The optional 2 is available from ARMv5. It provides an alternative operation. Condition codes are not allowed for the alternative form in ARM state.	S	The S modifier is not available in the Thumb-2 instruction.	
D	Deprecated. Use LDREX and STREX instead.	T	Not available in ARM state.	
G	Updates the four GE flags in the CPSR based on the results of the individual operations.	U	Not allowed in an IT block. Condition codes not allowed in either ARM or Thumb state.	
I	IA is the default, and is normally omitted.	V	The assembler inserts a suitable instruction if the NOP instruction is not available.	
L	ARM: <imm8m>. 16-bit Thumb: multiple of 4 in range 0-1020. 32-bit Thumb: 0-4095.			
N	Some or all forms of this instruction are 16-bit (Narrow) instructions in Thumb-2 code. For details see the <i>Thumb 16-bit Instruction Set (UAL) Quick Reference Card</i> .			

# ARM and Thumb-2 Instruction Set

## Quick Reference Card

ARM architecture versions	
<i>n</i>	ARM architecture version <i>n</i> and above
<i>n</i> T, <i>n</i> J	T or J variants of ARM architecture version <i>n</i> and above
5E	ARM v5E, and 6 and above
T2	All Thumb-2 versions of ARM v6 and above
6K	ARMv6K and above for ARM instructions, ARMv7 for Thumb
7MP	ARMv7 architectures that implement Multiprocessing Extensions
Z	All Security extension versions of ARMv6 and above
RM	ARMv7-R and ARMv7-M only
XS	XScale coprocessor instruction

Flexible Operand 2		
Immediate value		#<imm8m>
Register, optionally shifted by constant (see below)		Rm { , <opsh>}
Register, logical shift left by register		Rm, LSL Rs
Register, logical shift right by register		Rm, LSR Rs
Register, arithmetic shift right by register		Rm, ASR Rs
Register, rotate right by register		Rm, ROR Rs

Register, optionally shifted by constant		
(No shift)	Rm	Same as Rm, LSL #0
Logical shift left	Rm, LSL #<shift>	Allowed shifts 0-31
Logical shift right	Rm, LSR #<shift>	Allowed shifts 1-32
Arithmetic shift right	Rm, ASR #<shift>	Allowed shifts 1-32
Rotate right	Rm, ROR #<shift>	Allowed shifts 1-31
Rotate right with extend	Rm, RRX	

PSR fields (use at least one suffix)		
Suffix	Meaning	
c	Control field mask byte	PSR[7:0]
f	Flags field mask byte	PSR[31:24]
s	Status field mask byte	PSR[23:16]
x	Extension field mask byte	PSR[15:8]

### Proprietary Notice

Words and logos marked with ® or ™ are registered trademarks or trademarks of ARM Limited in the EU and other countries, except as otherwise stated below in this proprietary notice. Other brands and names mentioned herein may be the trademarks of their respective owners.

Neither the whole nor any part of the information contained in, or the product described in, this document may be adapted or reproduced in any material form except with the prior written permission of the copyright holder.

The product described in this document is subject to continuous developments and improvements. All particulars of the product and its use contained in this document are given by ARM in good faith. However, all warranties implied or expressed, including but not limited to implied warranties of merchantability, or fitness for purpose, are excluded.

This reference card is intended only to assist the reader in the use of the product. ARM Ltd shall not be liable for any loss or damage arising from the use of any information in this reference card, or any error or omission in such information, or any incorrect use of the product.

Condition Field		
Mnemonic	Description	Description (VFP)
EQ	Equal	Equal
NE	Not equal	Not equal, or unordered
CS / HS	Carry Set / Unsigned higher or same	Greater than or equal, or unordered
CC / LO	Carry Clear / Unsigned lower	Less than
MI	Negative	Less than
PL	Positive or zero	Greater than or equal, or unordered
VS	Overflow	Unordered (at least one NaN operand)
VC	No overflow	Not unordered
HI	Unsigned higher	Greater than, or unordered
LS	Unsigned lower or same	Less than or equal
GE	Signed greater than or equal	Greater than or equal
LT	Signed less than	Less than, or unordered
GT	Signed greater than	Greater than
LE	Signed less than or equal	Less than or equal, or unordered
AL	Always (normally omitted)	Always (normally omitted)
All ARM instructions (except those with Note C or Note U) can have any one of these condition codes after the instruction mnemonic (that is, before the first space in the instruction as shown on this card). This condition is encoded in the instruction.		
All Thumb-2 instructions (except those with Note U) can have any one of these condition codes after the instruction mnemonic. This condition is encoded in a preceding IT instruction (except in the case of conditional Branch instructions). Condition codes in instructions must match those in the preceding IT instruction.		
On processors without Thumb-2, the only Thumb instruction that can have a condition code is B <label>.		

Processor Modes	
16	User
17	FIQ Fast Interrupt
18	IRQ Interrupt
19	Supervisor
23	Abort
27	Undefined
31	System

Prefixes for Parallel Instructions	
S	Signed arithmetic modulo 2 <sup>8</sup> or 2 <sup>16</sup> , sets CPSR GE bits
Q	Signed saturating arithmetic
SH	Signed arithmetic, halving results
U	Unsigned arithmetic modulo 2 <sup>8</sup> or 2 <sup>16</sup> , sets CPSR GE bits
UQ	Unsigned saturating arithmetic
UH	Unsigned arithmetic, halving results

### Document Number

ARM QRC 0001M

### Change Log

Issue	Date	Change	Issue	Date	Change
A	June 1995	First Release	B	Sept 1996	Second Release
C	Nov 1998	Third Release	D	Oct 1999	Fourth Release
E	Oct 2000	Fifth Release	F	Sept 2001	Sixth Release
G	Jan 2003	Seventh Release	H	Oct 2003	Eighth Release
I	Dec 2004	Ninth Release	J	May 2005	RVCT 2.2 SP1
K	March 2006	RVCT 3.0	L	March 2007	RVCT 3.1
M	Sept 2008	RVCT 4.0			