

Dual-shaft Electric Pump-fed Rocket Engine Design Review

Cooper Grau-Firkus

September 2024

Contents

1	Introduction and Project Goals	2
1.1	Pump-fed vs. Pressure-fed	5
1.2	Target Performance Metrics	14
1.3	Turbomachinery Experience	14
1.4	Design of Key Engine Components	14
1.5	Flight-like Architecture	14
1.6	Rapid Testing Capabilities	14
1.7	Safety Objectives	14
2	Engine Architecture Overview	15
2.1	Propellants	15
2.2	Tanks	15
2.3	Valves	15
2.4	Flowmeters	15
2.5	Avionics and Sensing	15
2.5.1	Engine Controller	15
2.5.2	Pressure Transducers	15
2.5.3	Thermocouples	15
2.5.4	Communication	15
2.5.5	Power System	15
2.5.6	Load Cell	15
2.6	Torch Igniter	15
2.7	Fuel Pump	15

2.8	Oxidizer Pump	15
2.9	Injector	15
2.10	Thrust Chamber	15
3	Engine Firing Procedure	15
3.1	Nominal Firing Procedure	15
3.2	Contingency Scenarios	15
3.3	Engine Control Interface	15
3.4	Safety Measures	15
4	Strata Development and Testing Roadmap	16
4.1	Test Program Overview	16
4.1.1	Test Program Gantt Chart	16
4.2	Tank Proof Testing	16
4.3	Pump Flow Testing	16
4.3.1	Pump Flow Test Setup	16
4.4	Torch Igniter Testing	16
4.4.1	Torch Igniter Test Setup	16
4.5	Injector Testing	16
5	Notional VTVL Vehicle Design	17
5.1	Vehicle Architecture and Performance Metrics	17
5.2	Vehicle Use Case	17
6	Primary Remaining Design Questions	17
7	Long-term Roadmap	17
7.1	Advanced Capabilities	17
7.2	Next-generation Electric Pump-fed Engine	17
7.2.1	Potential Performance Metrics	17
7.3	Future Vehicles	17
7.3.1	High Altitude Hopper	18
7.4	More Advanced Engine Cycles	18

1 Introduction and Project Goals

Potentially the most revolutionary development in the space industry in recent times has been the increasing access to spaceflight technologies by a

greater number of people. This democratization of space technology has increased the rate of development by opening up to a much larger group of people. Part of this trend is the takeover of launch operations, in-space mobility, and mission operations by private industry. However, another major factor is the democratization of space technology and know-how not just to well-funded space industry startups, but also to students and hobbyists who have been able to take on ever more ambitious projects that would have been deemed near-impossible not very long ago. Twenty years ago, the first amateur rocket reached space, launched by the Civilian Space Exploration Team. Five years ago, the first student-built rocket to reach space, USC RPL's Traveler IV, crossed the Kármán line and reached speeds of over Mach 5. This year, the Gruyère Space Program student group demonstrated the first student-built Vertical Takeoff, Vertical Landing (VTVL) vehicle, called Colibri, and have carried out a rapid testing program of dozens of flights in only a few months. These incredible achievements and numerous others demonstrate that the standard ways of viewing space technology, as an inaccessible, expensive, and risky field of endeavor that can only be pushed forward by government or gargantuan companies may not be standard for much longer.




Figure 1: Gruyère Space Program's Colibri VTVL Testbed



Figure 2: USC RPL Traveler IV Launch to Space

This expansion of grassroots innovation in the space industry is a shift that has the potential to change the way that spaceflight technology is developed. Oftentimes, it is those who are considered outsiders in a field who are able to approach it from a new perspective and make the most impactful advancements. As more people gain access to space technology, more ideas will be not only generated, but also tested and sometimes proven. Our ability to move to and through space will expand in a positive feedback cycle in which the technologies and guidance developed by the people pushing the field forward today will lead to even more people able to push the field forward tomorrow. If we're lucky, this will result in a space industry that mirrors other industries with huge bases of support from hobbyists. Maybe one day soon, individuals will be able to go out and build or modify a high-power rocket, a VTVL craft, or a spacecraft the same way automotive hobbyists do today with their cars.

However, an area in which many of the most prominent technologies used in government and industry have not become available to students and hobbyists is the realm of liquid rocket propulsion. While the number of individuals and student groups who have hotfired an engine or even flown a liquid-fueled vehicle has seemed to increase rapidly, nearly all of these engines have been limited to a single class: the pressure-fed engine. While pressure-

fed engines can teach many of the fundamental lessons of liquid propulsion, they omit the essential turbomachinery used to achieve high performance and thrust-to-weight ratio by just about every launch vehicle, and by many in-space vehicles and landers as well. An analysis of pressure-fed vs. pump-fed designs will be presented in the next section along with an attempt to explain why most student and hobbyist rockets have been pressure-fed designs up to this point.

The purpose of this document is to lay out in detail the process of creating a relatively small electric pump-fed liquid rocket engine, which I believe to be a good architecture for a first step toward engines which use turbomachinery. It is meant to serve as a guidebook and learning resource to those who may be interested in learning about these kinds of engines or in building one themselves. My hope is that this could serve as an effective and approachable enough resource to help encourage others to delve beyond pressure-fed engines and have some small part in spurring the positive feedback cycle of space technology development.

In addition, this document is meant to be a resource for design reviews of my electric pump-fed rocket engine and as a way for me to receive as much feedback as possible before lighting anything on fire. My goal for this project is to learn as much as possible about liquid propulsion technology and to grow as an amateur propulsion engineer. I hope that by open sourcing the majority of my work, I will be able to share my work more and receive more feedback than I otherwise would have. As I have made my way through the initial phases of my engine project, I have also found that it can often be very helpful to lay out my own thought and design processes as if I am presenting them to someone. This oftentimes exposes my own mistakes and leads to greater clarity.

1.1 Pump-fed vs. Pressure-fed

To understand why it is so important to gain experience with pump-fed engines, an analysis of the performance and operational differences between pump-fed and pressure-fed designs is pertinent. This analysis will also help to describe the fundamental differences, identify the reasons that amateur propulsion engineers have so far shied away from pump-fed engines, and will inform later analysis in this document of pump-fed vs. pressure-fed engines for specific flight vehicle designs.

While pressure-fed engines can also include simple thrusters, such as cold

gas thrusters which use only propellant kinetic energy imparted via pressure and monopropellant thrusters that flow reactive propellants over a catalyst to create additional pressure and heat for thrust generation, here we are focused on bipropellant pressure-fed systems that are most comparable to pump-fed systems.

A likely reason why students and hobbyists most often choose to build pressure-fed systems is also one of the primary reasons they are used in the first place: mechanical simplicity, and the corresponding lower cost and developmental work required. In its most fundamental form, the only components that you need for a pressure-fed engine are:

- Something to hold your propellants and pressurant, which is done by the tanks.
- Devices to control when your propellants flow, and how much, if needed. This is the job of the valves.
- Devices for combustion and thrust generation, primarily, the injector and thrust chamber.

These components can often be bought off-the-shelf, with the exception of the thrust chamber and injector. Compare this to a pump-fed design, which will require turbomachinery which must be specifically sized and meticulously tested for the given parameters of an engine, an often lengthy and costly process due to the necessity of hardware-rich testing which often includes testing to failure, leading to the destruction of early component iterations. Additionally, the added components of a pump-fed design will increase the weight of the engine in comparison to a pressure-fed design. This means that for identical vehicles powered by pressure-fed and pump-fed engines of equal and sufficiently low performance, the pressure-fed vehicle may actually achieve better performance due to a higher thrust to weight ratio.




Figure 3: Simplified Schematics of Pressure-fed and Pump-fed Rocket Engines




Figure 4: Specific Impulse Relationship with Chamber Pressure for Kerosene-LOX Engines

So why don't orbital rockets use pressure-fed engines? The problem is that pressure-fed engines, when viewed in the context of the overall vehicle architecture, have a low practical limit to the performance that can be obtained from the engine. This is because the primary factor in the performance, or specific impulse, of a rocket engine is its chamber pressure. In a pressure-fed engine, there is no method of increasing the pressure between the tanks and the thrust chamber. This means that, after accounting for pressure drops in the hardware between the tanks and thrust chamber, the tanks actually must be kept at higher pressure than the thrust chamber itself. Essentially, the energy to boost the propellants up to chamber pressure must be sourced from somewhere, and pressure-fed cycles simplify matters by storing this energy as what is needed in the end anyway: pressure energy. However, this is a very mass-inefficient way of storing the energy necessary to increase your chamber pressure because your entire vehicle must be able to withstand the same extremely high pressures that only need to be present in your thrust chamber. This means that as you try to increase your engine's performance by increasing its chamber pressure, all of that performance is lost (and then some) because your tanks must become stronger and thus heavier.

In a pump-fed vehicle, it is possible to achieve much higher performance by converting other, much more mass-efficient, types of energy into pressure




Figure 5: Simplified Comparison of Vehicle Mass for Pressure-fed, Turbopump-fed, and Electric Pump-fed Vehicles




Figure 6: Simplified ΔV Comparison Against Chamber Pressure for Pressure-fed, Turbopump-fed, and Electric Pump-fed Vehicles

energy. Most vehicles opt to use the same energy source that is being used to boost the rocket in the first place: chemical energy in the propellants. By taking a small amount of the overall chemical energy available in the propellant and dedicating it to increasing chamber pressure, a much higher overall engine performance can be obtained in a flight-worthy engine. In an open cycle, this chemical energy is only used to create pressure energy, and the propellant is dumped after it has accomplished this job. However, closed cycle engines are able to use this propellant to create thrust after it is used to generate the necessary pressures and flow rates. These categories of engine cycles, but especially closed cycle engines, require much greater complexity in engine operations and plumbing. This is because in addition to complex, custom components, turbopump-fed engines often must strike a delicate balance between various parts of the engine due to interconnected operations. This can especially complicate the startup procedure for the engine, as the pumps may rely on the combustion chamber to spool up. They also open up areas of potential risk to engine reliability and longevity, such as high-speed rotating shaft seals and combustion devices that may cause engine coking (gumming up) or pose a risk of component degradation due to high temperatures and pressures.

Electric pump-fed engines are also able to achieve high chamber pressures without the need for high pressure tanks. However, they eliminate much of




Figure 7: Simplified Vehicle Mass Comparison of Pump-fed Vehicles

the complexity introduced by turbopumps by simply powering the pumps using an electric motor or motors. This removes many components, such as turbines and gas generators/preburners. However, this also changes the energy source that is being tapped to generate the pressure energy and flow needed to run the engine. Rather than using chemical energy in the propellants, the chemical energy in a battery is used instead. This adds an additional energy source not needed for thrust generation that must be included on the vehicle. Because higher chamber pressure increases the power required by the pumps, this also necessitates a larger battery that can deliver this power and increases the overall mass of the vehicle. This is shown in Figure 7, which shows the steady increase in electric pump-fed vehicle mass as chamber pressure increases, while the turbopump-fed vehicle remains approximately the same mass. This is estimated using both the energy and power required by the pumps for a given chamber pressure and using energy and power density (Wh/kg and W/kg) values achievable by today's batteries. These values are calculated for the same 5 metric ton wet mass vehicle with steel tanks.

As can be seen in Figure 8, this means that at very high chamber pressures, electric pump-fed engines lose some of the performance gained to battery mass. The turbopump-fed vehicle continues to achieve appreciable ΔV gains as chamber pressures are increased, while electric pump-fed vehicles effectively reach a performance limit. If we look closer at these relationships,




Figure 8: Simplified ΔV Comparison of Pump-fed Vehicles

however, it becomes clear that electric pump-fed engines can achieve much of the performance gains of turbopumps for small-scale, medium-to-high performance vehicles. Up to chamber pressures of nearly 10,000 kPa (around 1500 psi), the vehicles with electric pumps and turbopumps achieve nearly equal performance. Even up to 20,000 kPa (around 2900 psi, or about the chamber pressure of the RS-25), the electric pump-fed vehicle achieves only about 1% lower performance than the turbopump-fed vehicle.

If we were to scale up the vehicles in this comparison, the performance differences would become larger. The reason for this is the square-cube law, which dictates that because tank mass grows with the square of vehicle size and propellant volume grows with the cube of vehicle size, the ratio of wet to dry mass increases as vehicles are scaled up. Said in another way, larger rockets are able to hold more propellant in proportionally lighter tanks. Because of this relationship and because pump power requirements scale proportionally with mass flow rate of propellant, this means that a larger electric pump-fed vehicle's battery will increase its dry mass by a greater proportion than a smaller electric pump-fed vehicle, which also increases the performance penalty of this extra mass. The maximum power that electric motors are able to deliver and the mass of the motors is also a bottleneck that will affect the maximum size of vehicle that electric pump-fed engines can realistically power. However, the threshold past which this performance penalty from battery mass is too large to be tenable and electric motors cannot provide

the necessary power is somewhere between the sizes of a small and medium-lift orbital launch vehicles. Which means that I am confident in saying that this isn't likely to be an issue for most hobbyists and student teams in the near-term (if this does become a problem for you, you are doing something right). This makes electric pump-fed engines a very favorable choice for small vehicles like those likely to be built by a hobbyist or student team, especially because most vehicles of this type would never have been designed for chamber pressures high enough that the performance limits of electric pump-fed engines become significant. In summary, with electric pump-fed engines, it is possible to achieve very good performance while eliminating a huge portion of the design, manufacturing, and operational complexity.

This also explains why electric pump-fed engines have been used for many of the small launch vehicles that have been developed in recent years. The Rutherford engine that powers Rocket Lab's Electron is a high-performance kerosene-LOX dual-shaft electric pump-fed engine and power one of the most dependable workhorse rockets flying today. It is also one of the only engines to be recovered and refired following an orbital flight. This is also indicative of the reusability benefits of this kind of engine, as it eliminates many of the sources of wear that engines experience. Some hobbyists have also delved into electric pump-fed cycles, including some successful firings of partially pump-fed engines, one of which is pictured below. This has been a rare occurrence, however, and one of the goals of this document is to help more hobbyists and students get a start with this cycle.



Figure 9: Rocket Lab's Rutherford is Fired After Powering an Electron to Orbit



Figure 10: Five Delphin Engines Power Astra's Rocket 3.2



Figure 11: LOX Pump Assembly and Test Firing of Akarin's LOX and Ethanol Partially Electric Pump-fed Engine

1.2 Target Performance Metrics

1.3 Turbomachinery Experience

1.4 Design of Key Engine Components

1.5 Flight-like Architecture

1.6 Rapid Testing Capabilities

1.7 Safety Objectives

Lack of need for high-pressure tanks (at least non-GSE high-pressure tanks) when personnel are present at the pad

2 Engine Architecture Overview

2.1 Propellants

2.2 Tanks

2.3 Valves

2.4 Flowmeters

2.5 Avionics and Sensing

2.5.1 Engine Controller

2.5.2 Pressure Transducers

2.5.3 Thermocouples

2.5.4 Communication

2.5.5 Power System

2.5.6 Load Cell

2.6 Torch Igniter

2.7 Fuel Pump

2.8 Oxidizer Pump

2.9 Injector

2.10 Thrust Chamber

3 Engine Firing Procedure

3.1 Nominal Firing Procedure

3.2 Contingency Scenarios

3.3 Engine Control Interface

3.4 Safety Measures

4 Strata Development and Testing Roadmap

4.1 Test Program Overview

4.1.1 Test Program Gantt Chart

4.2 Tank Proof Testing

4.3 Pump Flow Testing

4.3.1 Pump Flow Test Setup

4.4 Torch Igniter Testing

4.4.1 Torch Igniter Test Setup

4.5 Injector Testing

5 Notional VTVL Vehicle Design

5.1 Vehicle Architecture and Performance Metrics

Vehicle weight breakdown:

- Propellant - LOX 90lbs, Kero 40lbs
- Valves - 100lbs
- Tanks - 20lbs ox, 10 lbs fuel
- Landing Legs - 10lbs
- Piping, Fittings, etc - 20lbs
- Pumps and Motors - 10lbs + 20lbs
- Battery - 5lbs
- Thrust Chamber and Injector - 25lbs
- Total: 365lbs

5.2 Vehicle Use Case

6 Primary Remaining Design Questions

7 Long-term Roadmap

7.1 Advanced Capabilities

7.2 Next-generation Electric Pump-fed Engine

7.2.1 Potential Performance Metrics

What are the limits of performance for an electric pump-fed engine?

7.3 Future Vehicles

High altitude (karman line) rocket and high-speed/high-altitude hopper based on scaled up version of engine and upsized tanks made in the same way

7.3.1 High Altitude Hopper

Structural analysis to make sure the rocket can make it through max dynamic pressure

7.4 More Advanced Engine Cycles