

0.025 (64) SPACE CREATED BY 3 SPACER PADS WHEN SURFACE MOUNTED. DO NOT OBSTRUCT PROVIDES PATH FOR RELIEF OF OVERPRESSURE.

RUBBER PRESSURE RELIEF PLUG WILL UNSEAT ITSELF WHEN GAGE IS OVERPRESSURIZED

(3) 6-32 X 3/16 (4.76) DEEP HOLES EQUALLY SPACED ON Ø4-1/8 (104.78) BOLT CIRCLE FOR PANEL MOUNTING

1/8 FEMALE NPT HIGH PRESSURE CONNECTION

1/8 FEMALE NPT LOW PRESSURE CONNECTION

1/8 FEMALE NPT HIGH PRESSURE CONNECTION

1/8 FEMALE NPT LOW PRESSURE CONNECTION

Ø4-3/4 (120.65)

Ø5-1/2 (139.70)

MOUNTING RING

Ø4-1/2 (114.3)

1-1/4 (31.75)

15/32 (11.91)

1-11/16 (42.86)

17/32 (13.49)

7/16 (11.11)

Ø4-3/4 (120.65) PANEL CUTOUT

Ø5 (127)

Ø4-1/2 (114.3)

1-1/4 (31.75)

15/32 (11.91)

2-17/32 (64.29)

3/16 (4.76)

Ø4-47/64 (120.27)

11/16 (17.46)

1/2 (12.70)

1-3/4 (44.45)

information@itm.com