

Common Lisp Webdriver Client

A.U. Thor <bug-sample@gnu.org>

Table of Contents

1	Introduction	1
2	Usage	2
2.1	Sessions	2
2.2	Capabilities	3
2.2.1	alwaysMatch	4
2.2.2	firstMatch	4
2.2.3	Combining alwaysMatch and firstMatch	4
2.2.4	List of capabilities	5
2.2.5	Vendor-specific capabilities	5
2.3	Actions	5
3	Installation	7
4	Utils	8
4.1	Interactive session	8
4.2	Utils API conventions	8
4.3	Waiting for the reaction	9
4.4	Running tests	9
5	API	10
5.1	WEBDRIVER-CLIENT package	10
5.2	WEBDRIVER-CLIENT-UTILS package	20
6	Index	22

1 Introduction

CL Webdriver Client is client library for WebDriver.

WebDriver is a remote control interface that enables introspection and control of user agents. It provides a platform- and language-neutral wire protocol as a way for out-of-process programs to remotely instruct the behavior of web browsers.

Provided is a set of interfaces to discover and manipulate DOM elements in web documents and to control the behavior of a user agent. It is primarily intended to allow web authors to write tests that automate a user agent from a separate controlling process, but may also be used in such a way as to allow in-browser scripts to control a — possibly separate — browser.

See W3C Webdriver spec (<https://www.w3.org/TR/webdriver>).

2 Usage

```
;; see examples/*.lisp and t/*.lisp
(in-package :cl-user)

(eval-when (:compile-toplevel :load-toplevel :execute)
  (ql:quickload :cl-webdriver-client))

(defpackage go-test
  (:use :cl :webdriver-client))

(in-package :go-test)

(defparameter *code* "
package main
import \"fmt\"

func main() {
    fmt.Print(\"Hello WebDriver!\")
}")

(with-session ()
  (setf (url) "http://play.golang.org/?simple=1")
  (let ((elem (find-element "#code" :by :css-selector)))
    (element-clear elem)
    (element-send-keys elem *code*))
  (let ((btn (find-element "#run")))
    (element-click btn))

  (loop
    with div = (find-element "#output")
    for ouput = (element-text div)
    while (equal ouput "Waiting for remote server...")
    do (sleep 0.1)
    finally (print ouput)))
```

2.1 Sessions

A session is equivalent to a single instantiation of a particular user agent, including all its child browsers. WebDriver gives each session a unique session ID that can be used to differentiate one session from another, allowing multiple user agents to be controlled from a single HTTP server, and allowing sessions to be routed via a multiplexer (known as an intermediary node).

A WebDriver session represents the connection between a local end and a specific remote end.

A session is started when a New Session is invoked. It is an error to send any commands before starting a session, or to continue to send commands after the session has been closed.

Maintaining session continuity between commands to the remote end requires passing a session ID.

A session is torn down at some later point; either explicitly by invoking Delete Session, or implicitly when Close Window is called at the last remaining top-level browsing context.

An intermediary node will maintain an associated session for each active session. This is the session on the upstream neighbor that is created when the intermediary node executes the New Session command. Closing a session on an intermediary node will also close the session of the associated session.

All commands, except New Session and Status, have an associated current session, which is the session in which that command will run.

Use [START-INTERACTIVE-SESSION], page 18 function to start an interactive session, and [WITH-SESSION], page 18 macro to evaluate WebDriver code in the context of a session.

2.2 Capabilities

WebDriver capabilities are used to communicate the features supported by a session. A client may also use capabilities to define which features it requires the driver to satisfy when creating a new session.

When a WebDriver session is created it returns a set of capabilities describing the negotiated, effective capabilities of the session. Some of the capabilities included in this set are standard and shared between all browsers, but the set may also contain browser-specific capabilities and these are always prefixed. Capabilities negotiation

Capabilities can be used to require a driver that supports a certain subset of features. This can be used to require certain browser features, such as the ability to resize the window dimensions, but is also used in distributed environments to select a particular browser configuration from a matrix of choices.

Selecting a particular web browser or platform only makes sense when you use a remote WebDriver. In this case the client makes contact with WebDriver through one or more intermediary nodes which negotiates which driver to return to you based on the capabilities it receives.

The capabilities object is a selection mechanism that limits which driver configurations the server will return. If you request a Firefox instance using `browserName` and Firefox is not installed on the remote, or macOS from a remote that only supports Linux, you may be out of luck. But occasionally you may not care which specific operating system or web browser your session has: you just want a session that has some capability.

The selection process, or the capabilities negotiation, is done through `alwaysMatch` and `firstMatch`.

In *CL-WEBDRIVER-CLIENT* capabilities are created using [MAKE-CAPABILITIES], page 19. The key argument `:always-match` should be the 'alwaysMatch' capabilities as an association list. The key argument `:first-match` are the 'firstMatch' capabilities, a list of association lists.

Also, capabilities are constructed from arguments in [MAKE-SESSION], page 17 and [WITH-SESSION], page 18.

2.2.1 alwaysMatch

As the name suggests, capabilities described inside the `alwaysMatch` capabilities object are features you require the session to have. If the server can not provide what features you require, it will fail.

If for example you ask for Firefox version 62 on a system that only has 60 installed, the session creation will fail:

```
(make-capabilities
  :always-match '(:browser-name . "firefox")
                (:browser-version . "60")))

or:

(with-session '(:always-match (:browser-name . "firefox")
                              (:browser-version . "60")))

... )
```

2.2.2 firstMatch

The `firstMatch` field accepts an array of capabilities objects which will be matched in turn until one matches what the server can provide, or it will fail.

This can be useful when you want a driver that runs on macOS or Linux, but not Windows:

```
(make-capabilities
  :first-match (list
    '(:platform-name . "macos"))
    '(:platform-name . "linux"))))
```

2.2.3 Combining alwaysMatch and firstMatch

`firstMatch` can of course be combined with `alwaysMatch` to narrow down the selection. If for example you a driver that runs on macOS or Linux but it has to be Firefox:

```
(make-capabilities
  :always-match '(:browser-name . "firefox")
  :first-match (list
    '(:platform-name . "macos"))
    '(:platform-name . "linux"))))
```

The previous example is exactly equivalent to putting the Firefox requirement in each `firstMatch` arm:

```
(make-capabilities
  :first-match (list
    '(:browser-name . "firefox") (:platform-name . "macos"))
    '(:browser-name . "firefox") (:platform-name . "linux"))))
```

Which you choose of the two preceding examples is not important, but it can matter when pass along browser configuration. To avoid unnecessarily repeating data, such as profiles, it is advisable to make use of `alwaysMatch` so that this data is only transmitted across the wire once:

```
(make-capabilities
  :always-match '(:browser-name . "firefox")
```

```

        ,(firefox-capabilities
          :profile "<base64 encoded profile>"
          :args #("--headless")
          :prefs '(("dom.ipc.processCount" . 8))
          :log '(:level . "trace"))))
      :first-match (list
        '(:platform-name . "macos"))
        '(:platform-name . "linux"))))

```

2.2.4 List of capabilities

- *:browser-name* – a string. The name of the browser to use. e.g. “chrome”, “firefox”.
- *:browser-version* – a string. The browser version required.
- *:platform-name* – a string. Identifies the operating system of the endpoint node. e.g. 'Linux', 'Windows'.
- *:accept-insecure-certs* – a boolean. The `acceptInsecureCerts` capability communicates whether expired or invalid TLS certificates are checked when navigating. If the capability is false, an insecure certificate error will be returned as navigation encounters domains with certificate problems. Otherwise, self-signed or otherwise invalid certificates will be implicitly trusted by the browser on navigation. The capability has effect for the lifetime of the session.
- *:page-load-strategy* – a string.
- *:proxy* – object. Defines the current session’s proxy configuration (<https://www.w3.org/TR/webdriver1/#dfn-proxy-configuration>).
- *:set-window-rect* – boolean. Indicates whether the remote end supports all of the commands in Resizing and Positioning Windows (<https://www.w3.org/TR/webdriver1/#resizing-and-positioning-windows>).
- *:timeouts* – object. Describes the timeouts (<https://www.w3.org/TR/webdriver1/#dfn-timeouts>) imposed on certain session operations.
- *:unhandled-prompt-behaviour* – string. Describes the current session’s user prompt handler.

Reference: <https://www.w3.org/TR/webdriver1/#capabilities>.

2.2.5 Vendor-specific capabilities

In addition to the standard capabilities WebDriver allows third-parties to extend the set of capabilities to match their needs. Browser vendors and suppliers of drivers typically use extension capabilities to provide configuration to the browser, but they can also be used by intermediaries for arbitrary blobs of information.

You can use [CHROME-CAPABILITIES], page 18 and [FIREFOX-CAPABILITIES], page 18 for these.

2.3 Actions

The Actions API provides a low-level interface for providing virtualised device input to the web browser. Conceptually, the Actions commands divide time into a series of ticks.

The local end sends a series of actions which correspond to the change in state, if any, of each input device during each tick. For example, pressing a key is represented by an action sequence consisting of a single key input device and two ticks, the first containing a `keyDown` action, and the second a `keyUp` action, whereas a pinch-zoom input is represented by an action sequence consisting of three ticks and two pointer input devices of type `touch`, each performing a sequence of actions `pointerDown`, followed by `pointerMove`, and then `pointerUp`.

See <https://www.w3.org/TR/webdriver/#actions> for the whole explanation.

To perform actions in *cl-webdriver-client* use [PERFORM-ACTIONS], page 14. That function implements a little language, with the following syntax:

Syntax:

```
actions ::= ({actions-input-source}*)
actions-input-source ::= (input-source-type {action}*)
input-source-type ::= :none | :pointer | :mouse | :pen | :touch | :key
action ::= pause | pointer-move | pointer-down | pointer-up | key-down | key-up
pause ::= (:pause duration)
pointer-move ::= (:pointer-move x y)
pointer-down ::= (:pointer-down button-number)
pointer-up ::= (:pointer-up button-number)
key-down ::= (:key-down key)
key-up ::= (:key-up key)
```

Arguments and values:

- *actions*—a list of actions-input-sources. One list for each type of input source that wants to be used.
- *actions-input-source*—a list. Specifies the list of actions to perform for a particular input source.
- *duration*—an integer. The time to pause in milliseconds.
- *key*—a string. A string with the character (e.g. “a”). Use [KEY], page 15 for entering special characters.
- *button-number*—an integer greater than or equal to 0.
- *x*—an integer. Horizontal screen coordinate.
- *y*—an integer. Vertical screen coordinate.

Examples:

```
(perform-actions '((:pen
  (:pointer-move 22 33)
  (:pause 2000)
  (:pointer-move 23 54))))
```

3 Installation

```
git clone https://github.com/copyleft/cl-webdriver-client ~/quicklisp/local-projects/
(ql:quickload :cl-webdriver-client)
```

You need a running instance of selenium-server-standalone.

[Download](<http://www.seleniumhq.org/download/>) it and run:

```
curl -LO https://goo.gl/SP94ZB -o selenium-server-standalone.jar
java -jar selenium-server-standalone.jar
```

4 Utils

There is a `:webdriver-client-utils` package which should reduce boilerplate. For example:

```
(defpackage my-test
  (:use :cl :webdriver-client)
  (:import-from :webdriver-client-utils
    :send-keys
    :click
    :wait-for
    :classlist))

(in-package :my-test)

(with-session ()
  (setf (url) "http://google.com")
  (send-keys "cl-webdriver-client")
  (click "[name=btnK]")
  (wait-for "#resultStats"))
```

4.1 Interactive session

You can just start the session and control it from your repl:

```
(in-package :my-test)

(start-interactive-session)

(setf (url) "http://google.com")
(send-keys "cl-webdriver-client")
(send-keys (key :enter))
(classlist "#slim_appbar") ; prints ("ab_tnav_wrp")

(stop-interactive-session)
```

4.2 Utils API conventions

If utility function needs an element to work on it defaults to `‘(active-element)’`.

```
(click) ; click on the current active element.
```

You can also pass a css selector as a last parameter.

```
(print (id "#submit")) ; print id the of matched element
```

```
(assert (= (first (classlist "div")) "first-div-ever"))
```

To change default element you can:

```
(setf webdriver-client-utils:*default-element-func* (lambda () (find-element "input[ty
```

4.3 Waiting for the reaction

Often you need to wait for some action to be done. For example if you do a `(click)` on the button to load search results, you need to wait them to load.

```
(wait-for ".search-result" :timeout 10) ; wait 10 seconds
```

Timeout defaults to 30 seconds. You can globally change it:

```
(setf webdriver-client-utils:*timeout* 3)
```

4.4 Running tests

REPL

```
(ql:quickload '(:cl-selenium :prove))  
(setf prove:*enable-colors* nil)  
(prove:run :cl-webdriver-client-test)
```

Shell

```
sh  
./test.sh
```

5 API

5.1 WEBDRIVER-CLIENT package

WEBDRIVER-CLIENT [PACKAGE]

This package exports functions for working with Selenium WebDriver.

For documentation see:

- <https://github.com/SeleniumHQ/selenium/wiki/JsonWireProtocol>
- <https://www.w3.org/TR/webdriver1>

External definitions

Contexts

GET-WINDOW-HANDLE (&key (session *session*)) [WEBDRIVER-CLIENT]

Returns the window handle associated with the current top-level browsing context.

See: <https://www.w3.org/TR/webdriver1/#get-window-handle>

Category: Contexts

SWITCH-TO-FRAME (id &key (session *session*)) [WEBDRIVER-CLIENT]

Change focus to another frame on the page. If the frame *id* is null, the server should switch to the page's default content.

In the context of a web browser, a frame is a part of a web page or browser window which displays content independent of its container, with the ability to load content independently.

Category: Contexts

See: <https://www.w3.org/TR/webdriver1/#switch-to-frame>

GET-WINDOW-HANDLES (&key (session *session*)) [WEBDRIVER-CLIENT]

Returns the window handles associated with each top-level browsing context.

See: <https://www.w3.org/TR/webdriver1/#get-window-handles>

Category: Contexts

SWITCH-TO-WINDOW (window-handle &key (session *session*)) [WEBDRIVER-CLIENT]

Switching window will select the current top-level browsing context used as the target for all subsequent commands. In a tabbed browser, this will typically make the tab containing the browsing context the selected tab.

WINDOW-HANDLE is the handle of the window obtained via [GET-WINDOW-HANDLE], page 10.

See: <https://www.w3.org/TR/webdriver1/#switch-to-window>

Category: Contexts

CLOSE-WINDOW (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Close the current window.

See: <https://www.w3.org/TR/webdriver1/#close-window>
Category: Contexts

NEW-WINDOW (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Create a new top-level browsing context.

Category: Contexts
See: <https://w3c.github.io/webdriver/#new-window>

User prompts

DISMISS-ALERT (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]
The Dismiss Alert command dismisses a simple dialog if present. A request to dismiss an alert user prompt, which may not necessarily have a dismiss button, has the same effect as accepting it.

Category: User prompts
See: <https://www.w3.org/TR/webdriver1/#dismiss-alert>

ACCEPT-ALERT (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Accept Alert.

Category: User prompts
See: <https://www.w3.org/TR/webdriver1/#dfn-accept-alert>

ALERT-TEXT (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Get Alert Text.

Category: User prompts
See: <https://www.w3.org/TR/webdriver1/#get-alert-text>

Elements

ELEMENT-RECT (*element* **&key** (*session* **session**)) [WEBDRIVER-CLIENT]

The Get *Element* Rect command returns the dimensions and coordinates of the given web *element*. The returned value is a dictionary with the following members:

x

X axis position of the top-left corner of the web *element* relative to the current browsing context's document *element* in CSS pixels.

y

Y axis position of the top-left corner of the web *element* relative to the current browsing context's document *element* in CSS pixels.

height

Height of the web *element*'s bounding rectangle in CSS pixels.
width

Width of the web *element*'s bounding rectangle in CSS pixels.

Category: Elements

ELEMENT-ENABLED (*element* **&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Returns if *ELEMENT* is enabled.

Category: Elements

See: <https://www.w3.org/TR/webdriver1/#is-element-enabled> .

ELEMENT-ATTRIBUTE (*element name* **&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Return the *ELEMENT*'s attribute named *NAME*.

Category: Elements

ELEMENT-DISPLAYED (*element* **&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Returns if *ELEMENT* is visible.

Category: Elements

See: <https://www.w3.org/TR/webdriver1/#element-displayedness> .

ELEMENT-TAGNAME (*element* **&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Return the *ELEMENT*'s tag name.

Category: Elements

FIND-ELEMENTS (*value* **&key** (*by* *:css-selector*) (*session* **session**)) [WEBDRIVER-CLIENT]
Find elements that match *VALUE* using location strategy in *BY*.

Category: Elements

See [FIND-ELEMENT], page 12.

See <https://www.w3.org/TR/webdriver1/#find-elements> .

ELEMENT-TEXT (*element* **&key** (*session* **session**)) [WEBDRIVER-CLIENT]
The Get *Element* Text command intends to return an *element*'s text “as rendered”.
An *element*'s rendered text is also used for locating a elements by their link text and partial link text.

Category: Elements

See: <https://www.w3.org/TR/webdriver1/#get-element-text> .

FIND-ELEMENT (*value* **&key** (*by* *:css-selector*) (*session* **session**)) [WEBDRIVER-CLIENT]
The Find Element command is used to find an element in the current browsing context that can be used as the web element context for future element-centric commands.

For example, consider this pseudo code which retrieves an element with the `#toremove` ID and uses this as the argument for a script it injects to remove it from the HTML document:

```
let body <undefined> [=], page <undefined> session.find.css("#toremove");
session.execute("arguments[0].remove()", [body]);
```

The *BY* parameter represents the element location strategy.

It can be one of:

- *:id* : Finds element *by* id.
- *:class-name* : Finds element *by* class name.
- *:css-selector* : Returns element that matches css selector.
- *:link-text* : Returns element that matches `<a>` element text.
- *:partial-link-text*: Returns element that matches `<a>` element text partially.
- *:tag-name*: Returns element that matches tag name.
- *:xpath*: Returns element that matches the XPath expression.

If result is empty, a `<undefined> [HANDLE-FIND-ERROR]`, page `<undefined>` is signaled.

Category: Elements

See: <https://www.w3.org/TR/webdriver1/#dfn-find-element> .

ACTIVE-ELEMENT (*&key* (*session* **session**)) [WEBDRIVER-CLIENT]

Return the active element of the current browsing context's document.

The active element is the Element within the DOM that currently has focus.

If there's no active element, an error is signaled.

Category: Elements

See: <https://www.w3.org/TR/webdriver2/#get-active-element> .

See: <https://developer.mozilla.org/en-US/docs/Web/API/Document/activeElement> .

Document handling

EXECUTE-SCRIPT (*script* *args* *&key* (*session* **session**)) [WEBDRIVER-CLIENT]

Inject a snippet of JavaScript into the page for execution in the context of the currently selected frame. The executed *script* is assumed to be synchronous and the result of evaluating the *script* is returned to the client.

The *script* argument defines the *script* to execute in the form of a function body. The value returned by that function will be returned to the client. The function will be invoked with the provided *args* array and the values may be accessed via the *arguments* object in the order specified.

Arguments may be any JSON-primitive, array, or JSON object. JSON objects that

define a `WebElement` reference will be converted to the corresponding DOM element. Likewise, any `WebElements` in the *script* result will be returned to the client as `WebElement` JSON objects.

Category: Document handling

See: <https://www.w3.org/TR/webdriver1/#executing-script> .

Element interaction

ELEMENT-CLEAR (*element* &key (session *session*)) [WEBDRIVER-CLIENT]
Clear the contents of *ELEMENT* (for example, a form field *element*).

Category: *Element* interaction

See: <https://www.w3.org/TR/webdriver1/#dfn-element-clear> .

ELEMENT-CLICK (*element* &key (session *session*)) [WEBDRIVER-CLIENT]
The *Element* Click command scrolls into view the *element* if it is not already pointer-interactable, and clicks its in-view center point.

If the *element*'s center point is obscured by another *element*, an *element* click intercepted error is returned. If the *element* is outside the viewport, an *element* not interactable error is returned.

Category: *Element* interaction

See: <https://www.w3.org/TR/webdriver1/#element-click> .

ELEMENT-SEND-KEYS (*element* keys &key (session *session*)) [WEBDRIVER-CLIENT]

The *Element* Send Keys command scrolls into view the form control *element* and then sends the provided *keys* to the *element*. In case the *element* is not keyboard-interactable, an *element* not interactable error is returned.

KEYS should be a string or a list of characters or control character keywords.

For example:

```
(element-send-keys el (list :control #t))
```

See [KEY], page 15 and *KEYS* functions.

Category: *Element* interaction

See: <https://www.w3.org/TR/webdriver1/#element-send-keys> .

Actions

PERFORM-ACTIONS (*actions* &optional (session *session*)) [WEBDRIVER-CLIENT]

The *Actions* API provides a low-level interface for providing virtualised device input to the web browser.

Conceptually, the *Actions* commands divide time into a series of ticks. The local end sends a series of *actions* which correspond to the change in state, if any, of each input device during each tick. For example, pressing a key is represented by an action sequence consisting of a single key input device and two ticks, the first containing a keyDown action, and the second a keyUp action, whereas a pinch-zoom input is represented by an action sequence consisting of three ticks and two pointer input devices of type touch, each performing a sequence of *actions* pointerDown, followed by pointerMove, and then pointerUp.

Category: *Actions*

See: <https://www.w3.org/TR/webdriver/#actions>

KEYS (**&rest** *keys*) [WEBDRIVER-CLIENT]
Returns a string with characters and control keyword characters in *KEYS* list.

Example:

(*keys* :control #t)

Category: *Actions*

See: <https://www.w3.org/TR/webdriver/#keyboard-actions>

KEY (*key*) [WEBDRIVER-CLIENT]
Returns a string with *KEY*'s codepoint.

Category: *Actions*

See: <https://www.w3.org/TR/webdriver/#keyboard-actions>

Navigation

URL (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Get the current url in *session*.

Category: *Navigation*

See: <https://www.w3.org/TR/webdriver1/#dfn-get-current-url> .

REFRESH (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Refresh the current page.

Category: *Navigation*

PAGE-SOURCE (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]
Returns a string serialization of the DOM of the current browsing context active document.

Category: *Navigation*

See: <https://www.w3.org/TR/webdriver1/#get-page-source>

PAGE-TITLE (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]

This command returns the document title of the current top-level browsing context, equivalent to calling `document.title`.

Category: Navigation

See: <https://www.w3.org/TR/webdriver2/#get-title> .

BACK (**&key** (*session* **session**)) [WEBDRIVER-CLIENT]

This command causes the browser to traverse one step backward in the joint *session* history of the current top-level browsing context. This is equivalent to pressing the back button in the browser chrome or invoking `window.history.back`.

Category: Navigation

See: <https://www.w3.org/TR/webdriver1/#dfn-back> .

Cookies

COOKIE [WEBDRIVER-CLIENT]

A cookie is described in [RFC6265] by a name-value pair holding the cookie's data, followed by zero or more attribute-value pairs describing its characteristics.

Category: Cookies

Class precedence list: `cookie`, `standard-object`, `t`

Slots:

- **name** — initarg: `:name`
The name of the cookie
- **value** — initarg: `:value`
The cookie value
- **path** — initarg: `:path`
The cookie path. Defaults to `'/'` if omitted when adding a cookie.
- **domain** — initarg: `:domain`
The domain the cookie is visible to. Defaults to the current browsing context's active document's URL domain if omitted when adding a cookie.
- **secure** — initarg: `:secure`
Whether the cookie is a secure cookie. Defaults to false if omitted when adding a cookie.
- **http-only** — initarg: `:http-only`
Whether the cookie is an HTTP only cookie. Defaults to false if omitted when adding a cookie.
- **expiry** — initarg: `:expiry`
When the cookie expires, specified in seconds since Unix Epoch. Must not be set if omitted when adding a cookie.

COOKIE (&key (session *session*)) [WEBDRIVER-CLIENT]

Retrieve all cookies visible to the current page.

Category: Cookies

See: <https://www.w3.org/TR/webdriver1/#get-all-cookies> .

See: <https://github.com/SeleniumHQ/selenium/wiki/JsonWireProtocol#sessionsessionidcookie> .

DELETE-ALL-COOKIES (&key (session *session*)) [WEBDRIVER-CLIENT]

Deletes all cookies

Category: Cookies

See: <https://www.w3.org/TR/webdriver1/#delete-all-cookies>

MAKE-COOKIE (name value &key path domain secure expiry) [WEBDRIVER-CLIENT]

Create a cookie object.

Category: Cookies

FIND-COOKIE (cookie-name &key (session *session*)) [WEBDRIVER-CLIENT]

Retrieve the cookie with name *COOKIE-NAME*.

Category: Cookies

See: <https://www.w3.org/TR/webdriver1/#get-named-cookie>

DELETE-COOKIE (cookie-name &key (session *session*)) [WEBDRIVER-CLIENT]

Delete the cookie with name *COOKIE-NAME*.

Category: Cookies

See: <https://www.w3.org/TR/webdriver1/#delete-cookie>

Session

MAKE-SESSION (&optional capabilities) [WEBDRIVER-CLIENT]

Creates a new WebDriver session with the endpoint node. If the creation fails, a session not created error is returned.

CAPABILITIES are the *capabilities* to negotiate for the new session. If it is NIL, then [**DEFAULT-CAPABILITIES**], page 18 are used. If it is a list, then it is use as parameters for [*MAKE-CAPABILITIES*], page 19 to build a new *CAPABILITIES* object. Otherwise, it is assumed to be a *CAPABILITIES* object.

Category: Session

See: <https://www.w3.org/TR/webdriver1/#new-session> .

See: <https://www.w3.org/TR/webdriver1/#capabilities> .

USE-SESSION (*session*) [WEBDRIVER-CLIENT]
 Make *SESSION* the current *session*.

Category: *Session*

START-INTERACTIVE-SESSION (**&optional** *capabilities*) [WEBDRIVER-CLIENT]
 Start an interactive session. Use this to interact with Selenium driver from a REPL.

Category: *Session*

See: [MAKE-SESSION], page 17

STOP-INTERACTIVE-SESSION *nil* [WEBDRIVER-CLIENT]
 Stop an interactive session.

Category: *Session*

WITH-SESSION (*capabilities* **&body** *body*) [WEBDRIVER-CLIENT]
 Starts a new session, and evaluates *BODY* in the context of that session.
 The session is deleted when finished.

Category: *Session*

See: [MAKE-SESSION], page 17

DELETE-SESSION (*session*) [WEBDRIVER-CLIENT]
 Delete the WebDriver *SESSION*.

Category: *Session*

Capabilities

FIREFOX-CAPABILITIES (**&rest** *options*) [WEBDRIVER-CLIENT]
 Specify capabilities for Firefox browser.

Example usage:

```
(firefox-capabilities :args #("-headless"))
```

Category: *Capabilities*

See: <https://developer.mozilla.org/en-US/docs/Web/WebDriver/Capabilities/firefoxOptions>

DEFAULT-CAPABILITIES [WEBDRIVER-CLIENT]
 The default capabilities.

Category: *Capabilities*

CHROME-CAPABILITIES (**&rest** *options*) [WEBDRIVER-CLIENT]
 Specifies Chrome specific capabilities.

Category: Capabilities

https://chromedriver.chromium.org/capabilities#h.p_ID_102

MERGE-CAPABILITIES (*cap1 cap2*) [WEBDRIVER-CLIENT]

Merge two capabilities

Category: Capabilities

Screen capture

ELEMENT-SCREENSHOT (*element &key (session *session*)*) [WEBDRIVER-CLIENT]

The Take *Element* Screenshot command takes a screenshot of the visible region encompassed by the bounding rectangle of an *element*. If given a parameter argument *scroll* that evaluates to false, the *element* will not be scrolled into view.

Category: Screen capture

See: <https://www.w3.org/TR/webdriver1/#take-element-screenshot> .

SCREENSHOT (*&key (session *session*)*) [WEBDRIVER-CLIENT]

Screenshots are a mechanism for providing additional visual diagnostic information. They work by dumping a snapshot of the initial viewport's framebuffer as a lossless PNG image. It is returned to the local end as a Base64 encoded string.

Category: Screen capture

See: <https://www.w3.org/TR/webdriver2/#screen-capture> .

Uncategorized

LOGS (*type &key (session *session*)*) [WEBDRIVER-CLIENT]

Return the logs of a particular *TYPE*.

See: [LOG-TYPES], page 20.

MAKE-CAPABILITIES (*&key ((:always-match #:always-match) nil) ((:first-match #:first-match) nil)*) [WEBDRIVER-CLIENT]

MOUSE-MOVE-TO (*x y &key element (session *session*)*) [WEBDRIVER-CLIENT]

Move the mouse by an offset of the specified *element*. If no *element* is specified, the move is relative to the current mouse cursor. If an *element* is provided but no offset, the mouse will be moved to the center of the *element*. If the *element* is not visible, it will be scrolled into view.

See: <https://github.com/SeleniumHQ/selenium/wiki/JsonWireProtocol#sessionsessionidmoveto>

NO-SUCH-ELEMENT-ERROR [WEBDRIVER-CLIENT]

Error signaled when no such element is found.

Class precedence list: `no-such-element-error, find-error, error, serious-condition, condition, t`

MOUSE-CLICK (*button* &key (session *session*)) [WEBDRIVER-CLIENT]

Click any mouse *button* (at the coordinates set by the last *moveto* command). Note that calling this command after calling *buttondown* and before calling *button* up (or any out-of-order interactions sequence) will yield undefined behaviour).

See: <https://github.com/SeleniumHQ/selenium/wiki/JsonWireProtocol#sessionsessionidclick>

WEBDRIVER-STATUS *nil* [WEBDRIVER-CLIENT]

Get WebDriver status information

ELEMENT-ID (*sb-pcl::object*) [WEBDRIVER-CLIENT]

LOG-TYPES (&key (session *session*)) [WEBDRIVER-CLIENT]

Return the types of logs supported by the WebDriver.

- browser: Javascript console logs from the browser.
- client: Logs from the client side implementation of the WebDriver protocol (e.g. the Java bindings).
- driver: Logs from the internals of the driver (e.g. FirefoxDriver internals).
- performance: Logs relating to the performance characteristics of the page under test (e.g. resource load timings).
- server: Logs from within the selenium server.

See: <https://github.com/SeleniumHQ/selenium/wiki/Logging> .

5.2 WEBDRIVER-CLIENT-UTILS package

WEBDRIVER-CLIENT-UTILS [PACKAGE]

Package with the purpose of reducing boilerplate.

The exported definitions work with an implicit element. The default implicit element is the current active element. So, it is not necessary to pass the element you are working with around most of the time.

External definitions

Variables

TIMEOUT [WEBDRIVER-CLIENT-UTILS]

Default timeout value to use in selenium-utils functions.

DEFAULT-ELEMENT-FUNC [WEBDRIVER-CLIENT-UTILS]

Function used to get the 'default element' by selenium-utils functions.

It is [ACTIVE-ELEMENT], page 13 function by default.

Functions

ID (&optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
Get active element id.	
GET-COOKIE (<i>cookie name</i>)	[WEBDRIVER-CLIENT-UTILS]
Get value of <i>COOKIE</i> at <i>NAME</i> .	
FIND-ELEM (<i>selector</i> &key (<i>by :css-selector</i>))	[WEBDRIVER-CLIENT-UTILS]
Find element <i>by</i> <i>SELECTOR</i> . Returns NIL if the element is not found.	
WAIT-FOR (<i>selector</i> &key (<i>timeout *timeout*</i>))	[WEBDRIVER-CLIENT-UTILS]
Wait for an element that matches <i>SELECTOR</i> to appear on the screen.	
<i>TIMEOUT</i> indicates how much time to wait (default is <i>*TIMEOUT*</i>).	
CLASSNAME (&optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
Get active element classname.	
TEXT (&optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
Get active element's text.	
SEND-KEY (<i>key</i> &optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
Send a <i>key</i> to active element.	
CLASSLIST (&optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
Get active element class list.	
ATTR (<i>name</i> &optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
Get active element attribute.	
SEND-KEYS (<i>keys</i> &optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
Send <i>keys</i> to active element.	
ELEM (&optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
If <i>SELECTOR</i> is given, wait for an element that matches the <i>selector</i> to appear.	
Otherwise, call [<i>*DEFAULT-ELEMENT-FUNC*</i>], page 20 (the active element is returned by default).	
CLICK (&optional <i>selector</i>)	[WEBDRIVER-CLIENT-UTILS]
Click on active element.	

6 Index

(Index is nonexistent)

*

DEFAULT-CAPABILITIES	18
DEFAULT-ELEMENT-FUNC	20
TIMEOUT	20

A

ACCEPT-ALERT	11
ACTIVE-ELEMENT	13
ALERT-TEXT	11
ATTR	21

B

BACK	16
------	----

C

CHROME-CAPABILITIES	18
CLASSLIST	21
CLASSNAME	21
CLICK	21
CLOSE-WINDOW	11
COOKIE	17

D

DELETE-ALL-COOKIES	17
DELETE-COOKIE	17
DELETE-SESSION	18
DISMISS-ALERT	11

E

ELEM	21
ELEMENT-ATTRIBUTE	12
ELEMENT-CLEAR	14
ELEMENT-CLICK	14
ELEMENT-DISPLAYED	12
ELEMENT-ENABLED	12
ELEMENT-ID	20
ELEMENT-RECT	11
ELEMENT-SCREENSHOT	19
ELEMENT-SEND-KEYS	14
ELEMENT-TAGNAME	12
ELEMENT-TEXT	12
EXECUTE-SCRIPT	13

W

WEBDRIVER-CLIENT-	
UTILS:*DEFAULT-ELEMENT-FUNC*	20
WEBDRIVER-CLIENT-UTILS:*TIMEOUT*	20
WEBDRIVER-CLIENT:*DEFAULT-CAPABILITIES*	18

F

FIND-COOKIE	17
FIND-ELEM	21
FIND-ELEMENT	12
FIND-ELEMENTS	12
FIREFOX-CAPABILITIES	18

G

GET-COOKIE	21
GET-WINDOW-HANDLE	10
GET-WINDOW-HANDLES	10

I

ID	21
----	----

K

KEY	15
KEYS	15

L

LOG-TYPES	20
LOGS	19

M

MAKE-CAPABILITIES	19
MAKE-COOKIE	17
MAKE-SESSION	17
MERGE-CAPABILITIES	19
MOUSE-CLICK	20
MOUSE-MOVE-TO	19

N

NEW-WINDOW	11
------------	----

P

PAGE-SOURCE	15
PAGE-TITLE	16
PERFORM-ACTIONS	14

R

REFRESH	15
---------------	----

S

SCREENSHOT	19
SEND-KEY	21
SEND-KEYS	21
START-INTERACTIVE-SESSION	18
STOP-INTERACTIVE-SESSION	18
SWITCH-TO-FRAME	10
SWITCH-TO-WINDOW	10

T

TEXT	21
------------	----

U

URL	15
USE-SESSION	18

W

WAIT-FOR	21
WEBDRIVER-CLIENT-UTILS:ATTR	21
WEBDRIVER-CLIENT-UTILS:CLASSLIST	21
WEBDRIVER-CLIENT-UTILS:CLASSNAME	21
WEBDRIVER-CLIENT-UTILS:CLICK	21
WEBDRIVER-CLIENT-UTILS:ELEM	21
WEBDRIVER-CLIENT-UTILS:FIND-ELEM	21
WEBDRIVER-CLIENT-UTILS:GET-COOKIE	21
WEBDRIVER-CLIENT-UTILS:ID	21
WEBDRIVER-CLIENT-UTILS:SEND-KEY	21
WEBDRIVER-CLIENT-UTILS:SEND-KEYS	21
WEBDRIVER-CLIENT-UTILS:TEXT	21
WEBDRIVER-CLIENT-UTILS:WAIT-FOR	21
WEBDRIVER-CLIENT:ACCEPT-ALERT	11
WEBDRIVER-CLIENT:ACTIVE-ELEMENT	13
WEBDRIVER-CLIENT:ALERT-TEXT	11
WEBDRIVER-CLIENT:BACK	16
WEBDRIVER-CLIENT:CHROME-CAPABILITIES	18
WEBDRIVER-CLIENT:CLOSE-WINDOW	11
WEBDRIVER-CLIENT:COOKIE	17

WEBDRIVER-CLIENT:DELETE-ALL-COOKIES	17
WEBDRIVER-CLIENT:DELETE-COOKIE	17
WEBDRIVER-CLIENT:DELETE-SESSION	18
WEBDRIVER-CLIENT:DISMISS-ALERT	11
WEBDRIVER-CLIENT:ELEMENT-ATTRIBUTE	12
WEBDRIVER-CLIENT:ELEMENT-CLEAR	14
WEBDRIVER-CLIENT:ELEMENT-CLICK	14
WEBDRIVER-CLIENT:ELEMENT-DISPLAYED	12
WEBDRIVER-CLIENT:ELEMENT-ENABLED	12
WEBDRIVER-CLIENT:ELEMENT-ID	20
WEBDRIVER-CLIENT:ELEMENT-RECT	11
WEBDRIVER-CLIENT:ELEMENT-SCREENSHOT	19
WEBDRIVER-CLIENT:ELEMENT-SEND-KEYS	14
WEBDRIVER-CLIENT:ELEMENT-TAGNAME	12
WEBDRIVER-CLIENT:ELEMENT-TEXT	12
WEBDRIVER-CLIENT:EXECUTE-SCRIPT	13
WEBDRIVER-CLIENT:FIND-COOKIE	17
WEBDRIVER-CLIENT:FIND-ELEMENT	12
WEBDRIVER-CLIENT:FIND-ELEMENTS	12
WEBDRIVER-CLIENT:FIREFOX-CAPABILITIES	18
WEBDRIVER-CLIENT:GET-WINDOW-HANDLE	10
WEBDRIVER-CLIENT:GET-WINDOW-HANDLES	10
WEBDRIVER-CLIENT:KEY	15
WEBDRIVER-CLIENT:KEYS	15
WEBDRIVER-CLIENT:LOG-TYPES	20
WEBDRIVER-CLIENT:LOGS	19
WEBDRIVER-CLIENT:MAKE-CAPABILITIES	19
WEBDRIVER-CLIENT:MAKE-COOKIE	17
WEBDRIVER-CLIENT:MAKE-SESSION	17
WEBDRIVER-CLIENT:MERGE-CAPABILITIES	19
WEBDRIVER-CLIENT:MOUSE-CLICK	20
WEBDRIVER-CLIENT:MOUSE-MOVE-TO	19
WEBDRIVER-CLIENT:NEW-WINDOW	11
WEBDRIVER-CLIENT:PAGE-SOURCE	15
WEBDRIVER-CLIENT:PAGE-TITLE	16
WEBDRIVER-CLIENT:PERFORM-ACTIONS	14
WEBDRIVER-CLIENT:REFRESH	15
WEBDRIVER-CLIENT:SCREENSHOT	19
WEBDRIVER-CLIENT:START- INTERACTIVE-SESSION	18
WEBDRIVER-CLIENT:STOP- INTERACTIVE-SESSION	18
WEBDRIVER-CLIENT:SWITCH-TO-FRAME	10
WEBDRIVER-CLIENT:SWITCH-TO-WINDOW	10
WEBDRIVER-CLIENT:URL	15
WEBDRIVER-CLIENT:USE-SESSION	18
WEBDRIVER-CLIENT:WEBDRIVER-STATUS	20
WEBDRIVER-CLIENT:WITH-SESSION	18
WEBDRIVER-STATUS	20
WITH-SESSION	18