Formalization of Gödel's First Incompleteness Theorem in a Guard/Rose Equational System

1 Overview

We formalize Gödel's first incompleteness theorem in a system combining two ideas:

- *Guard*'s syntax [1]: binary trees with typed unary and binary functors, serving as both the data domain and the term language;
- *Rose*'s purely equational proof style [2]: the only judgement is an equation $t = u$ between terms, with no propositional connectives, no sequents, and no logical rules — only computation axioms, congruence, substitution, and a tree-induction principle (**Schema F**).

The formalization is in Agda with `--safe --without-K --exact-split`. No postulates.

Theorem 1 (Gödel I — `godelII.agda`)**.** *For any hypothesis equation H:*

$$\mathit{ProofE}(H) \;\to\; \mathit{Consistent}(H) \;\to\; H \vdash G \;\to\; \bot$$

This says: if the proof encoding is correct and the system is consistent, then the Gödel sentence G is not derivable. Here:

- $\mathit{ProofE}(H)$: proof encoding correctness — every derivation from H has a proof tree whose thFunTFor image equals the code of the derived equation (proved constructively by thm14E);
- $\mathit{Consistent}(H)$: no derivation of $O = \mathbf{f}$ from H;
- G: the Gödel sentence, which (after diagonalization) says "no proof tree encodes a derivation of this sentence."

Remark 2. *This is Gödel's* first *incompleteness theorem: G is not provable (if the system is consistent). The* second *incompleteness theorem (*Con *is not provable) would additionally require formalizing the proof of Theorem 1* inside *the system, to derive* $\vdash \mathrm{Con} \to G$*. Then if* $\vdash \mathrm{Con}$*, we get* $\vdash G$*, contradicting Theorem 1. This internalization step is not carried out here. In Rose's paper [2], Theorem 18 corresponds to our result; the passage to Gödel II would require Rose's Theorems 15–17 to be formalized inside the object system.*

2 The formal system

Trees

The ground data are finite binary trees:

$$a, b \;::=\; O \;\mid\; \langle a, b\rangle$$

where O is the leaf and $\langle a, b\rangle$ is the node. We define:

$$\mathbf{t} \;=\; O, \qquad \mathbf{f} \;=\; \langle O, O\rangle.$$

Here $\mathbf{t}$ represents equality (or "yes") and $\mathbf{f}$ represents inequality (or "no"). We write $\overline{n}$ for the unary encoding of $n \in \mathbb{N}$: $\overline{0} = O$, $\overline{n+1} = \langle O, \overline{n}\rangle$.

Terms and functors

Terms are built from trees, variables, and functor applications. We use t, u, v for terms, a, b for trees. The system has countably many variables $x_0, x_1, x_2, \ldots$. There are unary functors ($f, g : \mathrm{Fun}_1$) and binary functors ($h : \mathrm{Fun}_2$).

f, g	$::=$	I	identity
	$\mid$	π_1	first projection
	$\mid$	π_2	second projection
	$\mid$	$f \circ g$	composition
	$\mid$	$h[f, g]$	binary composition: $t \mapsto h(f(t), g(t))$
	$\mid$	$\mathrm{R}(z, s)$	tree recursion with base z and step s
	$\mid$	K_c	constant c
h	$::=$	P	pairing: $(t, u) \mapsto \langle t, u\rangle$
	$\mid$	C	left projection: $(t, u) \mapsto t$
	$\mid$	$\mathrm{Lf}(f)$	lift: $(t, u) \mapsto f(t)$
	$\mid$	$\mathrm{Ps}(f, h)$	post-compose: $(t, u) \mapsto f(h(t, u))$
	$\mid$	$\mathrm{Fn}(h_1, h_2, h)$	fan: $(t, u) \mapsto h(h_1(t, u),\ h_2(t, u))$
	$\mid$	If	conditional
	$\mid$	Eq	tree equality test

Terms:

$$t, u \;::=\; O \;\mid\; x_i \;\mid\; f(t) \;\mid\; h(t, u)$$

An *equation* is a pair $t = u$ of terms.

Embedding trees into terms

Every tree a determines a closed term $\hat{a}$:

$$\hat{O} = O, \qquad \widehat{\langle a, b\rangle} = \langle \hat{a}, \hat{b}\rangle.$$

(In Agda: `reify`.) Conversely, every closed term reduces to $\hat{a}$ for a unique a.

Derivation rules

A derivation is built from the rules below. Every rule may use a hypothesis H; we write $H \vdash t = u$.

Computation axioms.

Identity:	$\mathrm{I}(t) = t$
First projection:	$\pi_1(\langle t, u\rangle) = t$
Second projection:	$\pi_2(\langle t, u\rangle) = u$
Constant:	$\mathrm{C}(t, u) = t$
Composition:	$(f \circ g)(t) = f(g(t))$
Binary composition:	$h[f, g](t) = h(f(t),\ g(t))$
Lift:	$\mathrm{Lf}(f)(t, u) = f(t)$
Post-compose:	$\mathrm{Ps}(f, h)(t, u) = f(h(t, u))$
Fan:	$\mathrm{Fn}(h_1, h_2, h)(t, u) = h(h_1(t, u),\ h_2(t, u))$
Constant functor:	$\mathrm{K}_c(t) = c$

Tree recursion.

$$\begin{aligned} &\text{Base:} \quad \mathrm{R}(z, s)(O) = z \\ &\text{Step:} \quad \mathrm{R}(z, s)(\langle t, u\rangle) = s\big(\langle t, u\rangle,\ \langle \mathrm{R}(z, s)(t), \mathrm{R}(z, s)(u)\rangle\big) \end{aligned}$$

Conditional.

$$\begin{aligned} &\text{True branch:} \quad \mathrm{If}(\mathbf{t},\ \langle t, u\rangle) = t \\ &\text{False branch:} \quad \mathrm{If}(\langle t_1, t_2\rangle,\ \langle u_1, u_2\rangle) = u_2 \end{aligned}$$

More generally, If branches on whether its first argument is O (leaf) or a pair (node).

Tree equality.

$$\begin{aligned} &\mathrm{Eq}(O, O) &&= \mathbf{t} \\ &\mathrm{Eq}(O, \langle t, u\rangle) &&= \mathbf{f} \\ &\mathrm{Eq}(\langle t, u\rangle, O) &&= \mathbf{f} \\ &\mathrm{Eq}(\langle t_1, t_2\rangle, \langle u_1, u_2\rangle) &&= \mathrm{If}\big(\mathrm{Eq}(t_1, u_1),\ \langle \mathrm{Eq}(t_2, u_2), \mathbf{f}\rangle\big) \end{aligned}$$

Eq returns **t** for equal trees and **f** for unequal. The last clause says: if the left children differ, return **f** immediately; otherwise, recurse on the right children.

Structural rules.

$$\frac{}{t = t}\ (\mathrm{refl}) \qquad \frac{t = u}{u = t}\ (\mathrm{sym}) \qquad \frac{t = u \qquad u = v}{t = v}\ (\mathrm{trans})$$

$$\frac{t = u}{f(t) = f(u)}\ (\mathrm{cong}_1) \qquad \frac{t = u}{h(t, v) = h(u, v)}\ (\mathrm{cong}_L) \qquad \frac{t = u}{h(v, t) = h(v, u)}\ (\mathrm{cong}_R)$$

Substitution.

$$\frac{H \vdash t = u}{H \vdash t[c/x_i] = u[c/x_i]}\ (\mathrm{inst})$$

Hypothesis.

$$\frac{}{H \vdash H}\ (\mathrm{hyp})$$

Schema F (tree induction). If f and g are unary functors, z a term, s a binary functor, and we have derivations of:

$$f(O) = z, \qquad f(\langle x_0, x_1\rangle) = s(\langle x_0, x_1\rangle,\ \langle f(x_0), f(x_1)\rangle),$$
$$g(O) = z, \qquad g(\langle x_0, x_1\rangle) = s(\langle x_0, x_1\rangle,\ \langle g(x_0), g(x_1)\rangle),$$

then $f(x_0) = g(x_0)$.

Schema F expresses the uniqueness of tree recursion: if f and g satisfy the same recurrence (same base z, same step s), they agree on all inputs. Restricted to unary trees $\overline{n}$, this gives ordinary mathematical induction.

Consistency

The system is *consistent* if $\mathbf{t} = \mathbf{f}$ (i.e., $O = \langle O, O\rangle$) is not derivable.

3 Key components

3.1 Proof encoding (thFunTFor, Theorem 14)

thFunTFor is a unary functor (defined as $\mathrm{R}(O, \mathrm{thFunStep})$) that maps proof-encoding trees to the code of the equation they prove. The step function thFunStep is a 26-branch dispatch handling all derivation rules.

Theorem 14 (thm14E): if $H \vdash t = u$, then there exists a proof tree $\langle p_a, p_b\rangle$ such that

$$H \vdash \ \mathrm{thFunTFor}(\langle \hat{p}_a, \hat{p}_b\rangle) \ = \ \widehat{\ulcorner t = u \urcorner},$$

where $\ulcorner t = u \urcorner$ is the tree encoding of the equation. This is proved by induction on the derivation (1402 lines in `Thm14E.agda`).

3.2 Coded substitution (substTFor)

substTFor is a unary functor implementing coded substitution: given a coded term $\ulcorner t \urcorner$, it replaces every occurrence of variable x_n by a replacement term r.

These two parameters (r and n) are represented by free variables in substTFor. To avoid collision with the variables x_0, x_1 used in **Schema F** and in the template equation, the formalization places them at high indices:

- x_{11} carries the replacement r,
- x_{12} carries the target index $\overline{n}$.

Closing these variables gives the fully applied version:

$$\mathrm{closedSubstTFor}(r, \overline{n}) \ = \ \mathrm{substTFor}[r/x_{11},\ \overline{n}/x_{12}].$$

Correctness: for any term t, $\mathrm{closedSubstTFor}(r, \overline{n})$ applied to $\widehat{\ulcorner t \urcorner}$ equals $\widehat{\ulcorner t[r/x_n] \urcorner}$.

3.3 $\mathrm{Eq}(t,t) = \mathbf{t}$ via Schema F

$\mathrm{Eq}(t,t) = \mathbf{t}$ for all t is proved using **Schema F**. Define $f = \mathrm{Eq}[\mathrm{I},\mathrm{I}]$ (so $f(t) = \mathrm{Eq}(t,t)$) and $g = \mathrm{K}_{\mathbf{t}}$. Both satisfy the same recursion:

- f: by the computation axioms for Eq and the recursive structure of Eq on $\langle t_1, t_2\rangle$;
- g: by $\mathrm{K}_{\mathbf{t}}$; the step reduces to $\mathrm{If}(\mathbf{t}, \langle \mathbf{t}, \mathbf{f}\rangle) = \mathbf{t}$ since g returns $\mathbf{t}$ on all inputs.

Schema F gives $f(t) = g(t)$, i.e., $\mathrm{Eq}(t,t) = \mathbf{t}$. This avoids any heavy metalevel computation.

4 The Gödel sentence and diagonal construction

Template

The Gödel sentence is built from a *template equation* with several free variables:

- x_0: will receive a proof encoding (the "proof slot");
- x_1: will receive a coded term (the "diagonal slot");
- x_{11}, x_{12}: the replacement and target parameters of substTFor (closed later).

The template is:

$$\mathrm{templateEqn} \;=\; \big(\mathrm{Eq}(\mathrm{thFunTFor}(x_0),\ \mathrm{substTFor}(x_1)) = \mathbf{f}\big).$$

It says: "the equation encoded by the proof in x_0 is not equal to the result of substituting via x_1." Leaving x_{11}, x_{12} free at this stage keeps the tree code of the template small.

Diagonalization

Let $N = \ulcorner\mathrm{templateEqn}\urcorner$ be the tree encoding of the template. The Gödel sentence is obtained by substituting $\hat{N}$ (the numeral for N) into the diagonal slot:

$$G \;=\; \mathrm{templateEqn}[\hat{N}/x_1].$$

After this substitution, G says (informally): "for any proof tree in x_0, the equation it encodes is not the result of substituting N into the template" — i.e., "no proof tree proves G."

Abstract definitions (cached)

The following are computed once in `SubstTForPrecomp.agda` and cached:

- N: tree code of the template
- $\hat{N}$: the numeral $\widehat{N}$
- $G = \mathrm{templateEqn}[\hat{N}/x_1]$
- $\ulcorner G\urcorner$: tree encoding of G
- $\mathrm{cstf} = \mathrm{closedSubstTFor}(\widehat{\hat{N}},\ \overline{1})$: the substitution functor closed with replacement = code of the template numeral and target = variable x_1

Heavy computation (one-time)

`SubstTForPrecomp.agda` contains one step requiring ∼108 seconds (computed once, cached in `.agdai`): proving that after instantiating x_{11} and x_{12}, the open substTFor becomes cstf. This requires Agda to traverse $\widehat{\hat{N}}$ (∼400K term nodes) with substitution acting as identity on the closed subterm.

Remark 3. *The mathematical argument does not require this traversal. A general "substitution is identity on closed terms" lemma would eliminate it.*

5 Proof of Gödel I

The proof in `GodelII.agda` (0.2 seconds, 168 lines) follows Rose's Theorem 18 [2]. We assume $H \vdash G$ and derive $H \vdash \mathbf{t} = \mathbf{f}$, contradicting consistency.

1. **Assume** $H \vdash G$.
2. **Theorem 14** gives a proof encoding e with
$$H \vdash \text{thFunTFor}(e) = \widehat{\ulcorner G \urcorner}.$$
3. **diagFTarget** (precomputed): $H \vdash \text{cstf}(\hat{N}) = \widehat{\ulcorner G \urcorner}$.
4. **Chain** steps 2 and 3 through $\widehat{\ulcorner G \urcorner}$ as middle term (trans + sym):
$$H \vdash \text{thFunTFor}(e) = \text{cstf}(\hat{N}).$$
The term $\widehat{\ulcorner G \urcorner}$ appears only as the middle of a transitivity chain — it is never touched by inst.
5. **Instantiate** G with e (inst on x_0):
$$H \vdash \text{Eq}(\text{thFunTFor}(e),\ \text{substTFor}(\hat{N})) = \mathbf{f}.$$
6. **Replace** thFunTFor(e) with cstf($\hat{N}$) using cong_L and the chain from step 4:
$$H \vdash \text{Eq}(\text{cstf}(\hat{N}),\ \text{substTFor}(\hat{N})) = \mathbf{f}.$$
7. **Instantiate** x_{11} and x_{12} (inst, using the cached computation from Section 4): the open substTFor($\hat{N}$) becomes cstf($\hat{N}$):
$$H \vdash \text{Eq}(\text{cstf}(\hat{N}),\ \text{cstf}(\hat{N})) = \mathbf{f}.$$
8. **Reflexivity** ($\text{Eq}(t, t) = \mathbf{t}$ via **Schema F**):
$$H \vdash \text{Eq}(\text{cstf}(\hat{N}),\ \text{cstf}(\hat{N})) = \mathbf{t}.$$
9. **Contradiction**: by trans, $H \vdash \mathbf{t} = \mathbf{f}$, violating consistency.

From Gödel I to Gödel II

Theorem 1 shows G is not provable (assuming consistency and ProofE). For Gödel's *second* incompleteness theorem (Con is not provable), one would need to show that the system can derive $\text{Con} \to G$ internally. This requires formalizing steps 1–9 above as an object-level derivation, which amounts to proving ProofE and the diagonal construction inside the system. This internalization is not carried out in the present formalization.

6 File structure

File	Time	Role
Step.agda	< 1s	Derivation system
Term.agda	< 1s	Terms, functors, coding functions
ThFun.agda	< 1s	Metalevel proof evaluator
ThFunTFor.agda	< 1s	Object-level proof evaluator (26 branches)
Thm14E.agda	< 1s	Theorem 14 (1402 lines)
SubstTForCorrect.agda	< 1s	closedSubstTFor correctness
SubstTForPrecomp.agda	108s	**Heavy**: precomputed abstractions
SubstTForPrecomp2.agda	< 1s	Assembly from opaque pieces
GodelII.agda	< 1s	Gödel I proof (168 lines)

Total: ∼40 files, ∼5000 lines. The 108-second computation is cached and not repeated.

7 Correspondence with Rose

Rose [2]	This formalization
$th(y)$	thFunTFor
$se(x, y, z)$ / $st(x, y, z)$	substTFor / closedSubstTFor
$nu(x)$	implicit via $\hat{N}$
N (template code)	templateCode
Schema F	ruleF (uniqueness of recursion)
Theorem 10	thm14E (ProofE)
Theorem 14	thm14E
Theorems 15–16	Cases of thm14E + $\text{cong}_L/\text{cong}_R$
Theorem 17	diagFTarget
Theorem 18	godelII (= Gödel I in our terminology)

References

[1] Leon Chwistek. A formal proof of Gödel's theorem. *The Journal of Symbolic Logic*, 4(2):61–68, 1939.

[2] H. E. Rose. On the consistency and undecidability of recursive arithmetic. *Zeitschrift für mathematische Logik und Grundlagen der Mathematik*, 7:124–135, 1961.