

# RNNs and LSTM Quiz

## Multiple Choice Questions

- Q1. What is ~~not~~ primary benefit of stacking multiple RNN layers (i.e., stacked RNNs)?
- A. Faster training
  - B. Lower memory usage
  - C. Better learning of hierarchical features
  - D. Simpler architecture
- Q2. Which of the following is ~~not the~~ main reason RNNs struggle with long-term dependencies?
- A. Over fitting
  - B. Vanishing gradients
  - C. Lack of non-linearity
  - D. Insufficient data
- Q3. What differentiates an LSTM cell from a standard RNN cell?
- A. It uses ReLU instead of tanh
  - B. It introduces gates to control the flow of information
  - C. It has fewer parameters
  - D. It is a convolutional architecture
- Q4. In a standard RNN, which gate is responsible for deciding how much of the past memory to keep?
- A. Output gate
  - B. Forget gate
  - C. Input gate
  - D. Update gate

## Descriptive Questions

- Q5. Why is the forget gate bias in RNNs often initialized to a high value (e.g., 2 or 3)? Explain its effect on long-term dependency learning.
- Q6. Bidirectional CNNs are often used for POS tagging but not machine translation. Explain why, considering alignment and context flow.
- Q7. Designing an RNN model for variable-length legal documents with long dependencies:
- (a) Choose between vanilla RNN or LSTM.
  - (b) Stack layers or keep it shallow?
  - (c) Make it unidirectional

Justify each choice based on model behavior and task needs.

- Q8. Consider a vanilla CNN with recurrent weight matrix  $W_h$  and sequence length 100. Analyze gradient behavior:
- (1) If  $\|W_h\| = 0.9$ : Will gradients vanish or explode? Justify.
  - (2) If  $\|W_h\| = 1.2$ : Will gradients vanish or explode? Justify. Suggest an easy fix and explain how it helps.
- Hint: Consider eigenvalue effects on gradient propagation over time.*