

Standard Suite

Common classes and commands for most applications.

save options *enum*

yes : Save the file.

no : Do not save the file.

ask : Ask the user whether or not to save the file.

item *n* : A scriptable object.

PROPERTIES

class (type, r/o) : The class of the object.

properties (record) : All of the object's properties.

RESPONDS TO

[count](#), [delete](#), [duplicate](#), [exists](#), [get](#), [move](#), [set](#).

color *n* : A color.

window *n* : A window.

ELEMENTS

contained by [application](#).

PROPERTIES

name (text) : The full title of the window.

id (number, r/o) : The unique identifier of the window.

bounds (rectangle) : The bounding rectangle of the window.

closeable (boolean, r/o) : Whether the window has a close box.

titled (boolean, r/o) : Whether the window has a title bar.

index (number) : The index of the window in the back-to-front window ordering.

floating (boolean, r/o) : Whether the window floats.

miniaturizable (boolean, r/o) : Whether the window can be miniaturized.

miniaturized (boolean) : Whether the window is currently miniaturized.

modal (boolean, r/o) : Whether the window is the application's current modal window.

resizable (boolean, r/o) : Whether the window can be resized.

visible (boolean) : Whether the window is currently visible.

zoomable (boolean, r/o) : Whether the window can be zoomed.

zoomed (boolean) : Whether the window is currently zoomed.

selection (list of [track](#), r/o) : Currently selected tracks

RESPONDS TO

[close](#), [print](#), [save](#).

open *v* : Open an object.

open file : The file(s) to be opened.

print *v* : Print an object.

print file : The file(s) or document(s) to be printed.

quit *v* : Quit an application.

quit

[**saving** yes/no/ask] : Specifies whether changes should be saved before quitting.

close *v* : Close an object.

close specifier : the object to close

[**saving** yes/no/ask] : Specifies whether changes should be saved before closing.

[**saving in** file] : The file in which to save the object.

count *v* : Return the number of elements of a particular class within an object.

count specifier : the object whose elements are to be counted

[**each** type] : The class of objects to be counted.

→ integer : the number of elements

delete *v* : Delete an object.

delete specifier : the object to delete

duplicate *v* : Copy object(s) and put the copies at a new location.

duplicate specifier : the object(s) to duplicate

to location specifier : The location for the new object(s).

[**with properties** record] : Properties to be set in the new duplicated object(s).

exists *v* : Verify if an object exists.

exists specifier : the object in question

→ boolean : true if it exists, false if not

get *v* : Get the data for an object.

get specifier

→ any

make *v* : Make a new object.

make

new type : The class of the new object.

[**at** location specifier] : The location at which to insert the object.

[**with data** any] : The initial data for the object.

[**with properties** record] : The initial values for properties of the object.

→ specifier : to the new object

move *v* : Move object(s) to a new location.

move specifier : the object(s) to move

to location specifier : The new location for the object(s).

save *v* : Save an object.

save specifier : the object to save, usually a document or window

[**in** file] : The file in which to save the object.

[**as** text] : The file type in which to save the data.

set *v* : Set an object's data.

set specifier

to any : The new value.

Swinsian Suite

picture *n* : picture data

application *n* : The application

ELEMENTS

contains [windows](#), [playlists](#), [smart playlists](#), [normal playlists](#), [tracks](#), [audio devices](#).

PROPERTIES

name (text, r/o) : The name of the application.

frontmost (boolean, r/o) : Is this the frontmost (active) application?

version (text, r/o) : The version of the application.

player position (integer) : the player's position within the currently playing track in seconds.

current track ([track](#), r/o) : the currently playing track

sound volume (number) : the volume. (0 minimum, 100 maximum)

player state (stopped/playing/paused, r/o) : are we stopped, paused or still playing?

playback queue ([queue](#), r/o) : the currently queued tracks

output device ([audio device](#)) : current audio output device

repeat queue (boolean) : repeat playback

repeat single (boolean) : repeat single track

stop after every track (boolean) : stop playback at the end of every track

stop after track (boolean) : stop after the current track

music library ([library](#), r/o) : the music library

shuffle (track shuffle/album shuffle/none) : shuffle mode

RESPONDS TO

[quit](#), [play](#), [pause](#), [stop](#), [playpause](#), [next track](#), [previous track](#), [notify](#), [rescan tags](#), [find track](#).

library track *n* [inh. [track](#) > [item](#)]

playlist *n* [inh. [item](#)] : generic playlist type, subclasses include smart playlist and normal playlist

ELEMENTS

contains [tracks](#); contained by [application](#), [playlist folders](#).

PROPERTIES

name (text) : the name of the playlist

smart (boolean, r/o) : is this a smart playlist

library *n*, *pl* **libraries** [inh. [item](#)]

ELEMENTS

contains [tracks](#).

iPod track *n* [inh. [track](#) > [item](#)]

PROPERTIES

iPod name (text, r/o) : the name of the iPod this track is on

track *n* [inh. [item](#)] : a music track

ELEMENTS

contained by [application](#), [playlists](#), [libraries](#), [queues](#), [normal playlists](#).

PROPERTIES

album (text) : the album of the track

artist (text) : the artist

composer (text) : the composer

genre (text) : the genre

time (text, r/o) : the length of the track in text format as MM:SS

year (integer) : the year the track was recorded

date added (date, r/o) : the date the track was added to the library

duration (real, r/o) : the length of the track in seconds

location (text, r/o) : location on disk

iPod track (boolean, r/o) : TRUE if the track is on an iPod

name (text) : the title of the track (same as title)

bit rate (integer, r/o) : the bitrate of the track

kind (text, r/o) : a text description of the type of file the track is

rating (number) : Track rating. 0-5

track number (integer) : the Track number

file size (integer, r/o) : file size in bytes

album art ([picture](#), r/o) : the album artwork

art format (text, r/o) : the data format for this piece of artwork. text that will be "PNG" or "JPEG". getting the album art property first will mean this information has been retrieved already, otherwise the tags for the file will have to be re-read

disc number (number) : the disc number

disc count (number) : the total number of discs in the album

id (text, r/o) : uuid

album artist (text) : the album artist
album artist or artist (text, r/o) : the album artist of the track, or is none is set, the artist
compilation (boolean) : compilation flag
title (text) : track title (the same as name)
comment (text) : the comment
date created (date, r/o) : the date created
channels (integer, r/o) : audio channel count
sample rate (integer, r/o) : audio sample rate
bit depth (integer, r/o) : the audio bit depth
last played (date) : date track was last played
lyrics (text) : track lyrics
path (text, r/o) : POSIX style path
grouping (text) : grouping
publisher (text) : the publisher
conductor (text) : the conductor
description (text) : the description
encoder (text, r/o) : the encoder
copyright (text, r/o) : the copyright
catalog number (text) : the catalog number
date modified (date, r/o) : the date modified
play count (integer) : the play count
track count (number) : the total number of tracks in the album
enabled (boolean) : the enabled state of the track
sort artist (text) : the sort artist
sort album (text) : the sort album
sort album artist (text) : the sort album artist
bpm (number) : the bpm
barcode (text) : the barcode

RESPONDS TO

[add](#).

queue *n* [inh. [item](#)] : The playback queue

ELEMENTS

contains [tracks](#).

smart playlist *n* [inh. [playlist](#) > [item](#)] : a smart playlist

normal playlist *n* [inh. [playlist](#) > [item](#)] : a normal, non-smart, playlist

PROPERTIES

id (text, r/o) : uuid

RESPONDS TO

[add](#).

playlist folder *n* [inh. [playlist](#) > [item](#)] : folder of playlists

ELEMENTS

contains [playlists](#).

PROPERTIES

id (text, r/o) : uuid

audio device *n* : an audio output device

ELEMENTS

contained by [application](#).

PROPERTIES

name (text, r/o) : device name

id (text) : uuid

play *v* : begin playing the current playlist

play

pause *v* : pause playback

pause

next track *v* : skip to the next track in the current playlist

next track

stop *v* : stop playback

stop

search *v* : search a playlist for tracks matching a string

search

playlist [playlist](#) : the playlist to search

for text : the search string

→ list of [track](#) : the tracks found

previous track *v* : skip back to the previous track

previous track

playpause *v* : toggle play/pause

playpause

add *v* : add a track to a playlist

add

tracks list of [track](#)
to [normal playlist](#) : the playlist

notify v : show currently playing track notification
notify

rescan tags v : rescan tags on tracks
rescan tags list of [track](#) : tracks to rescan

find track v : Finds tracks for the given path
find track text : POSIX style path
→ list of [track](#) : matching tracks

remove v : remove tracks from a playlist
remove
tracks list of [track](#) : tracks to remove
from [normal playlist](#)