

e-STUDIO6529A/7529A/9029A

- **High-Speed – Up to 65, 75 & 90PPM**
- **High-Volume**
- **Advanced Security Features**
- **Solutions Ready**
- **Environmentally Friendly**



TOSHIBA

e-STUDIO6529A/7529A/9029A

Main Specifications

Copy System	Indirect Electrostatic Photographic /OPC/Laser Printing/ Heat Roller Fusing
Display	10.1" Color WSVGA Touch Screen Tilting Display
Copy Speed	65/75/90 PPM (LT)
First Copy Out	Monochrome: Less Than 5.2/4.5/4.1 Seconds
Warm-Up Time	From powering on: Approx. 20/24/25 Seconds, From Sleep: 15.4/15.4/Less than 20Seconds From Low Power: 15.4 Seconds
Copy Resolution	600 x 600 dpi
Stack Feed Bypass	3.9" x 5.8" to 13" x 19", 12" x 47" Banner, Envelope
Multiple Copying	Up to 999 Copies
Paper Capacity	Standard 3,520 Sheets/Max. 8,020 Sheets
Original Feed	300-Sheet DSDf with Double Feed Detection
Max. Original Size	LD/A3
Paper Feed Sizes	Drawers: 540 Sheets-ST-R to 12" x 18" Integral Tandem LCF 1,160 x 2 LT-Only Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner Opt. 2,500-Sheet Ext. LCF LT-Only Opt. 2,000-Sheet Piggyback Ext. LCF LT-Only
Paper Weights	Drawers: Standard 540 Sheets x 2 -16 lb Bond-110 lb Cover Tandem LCF 1,160 Sheets x 2 -16 lb Bond-110 lb Cover Stack Feed Bypass: 120 Sheets -16 lb Bond-110 lb Cover Opt. 2,500-Sheet Ext. LCF LT-Only -16 lb Bond-110 lb Cover Opt. 2,000-Sheet Piggyback Ext. LCF LT-Only -16 lb Bond-110 lb Cover
Duplex	Standard Automatic Duplex Unit (16lb Bond-140lb Index)
Reproduction Ratio	25% to 400%
Max Duty Cycle	Max. 590K/660K/740K Month
Weight	Approx.430lb
Approx. Dimensions	37.6" (W) x 27.5" (D) x 48.3" (H)
Toner Yield	106.6K @ 5%
Power Source	120 Volts, 50/60 Hz, 16 Amps
Power Consumption	Maximum 2.0kW/2.0kW/2.4kW (120V)
Plug Type	NEMA 5-20
Memory	6GB
Hard Disk Drive	128GB Solid State Drive (SSD)

e-BRIDGE Next Print Specifications

PDL	PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG
Print Resolution	600 x 600 dpi, 1,200 x 1,200 dpi, or 3,600 (Equivalence) x 1,200 dpi (with Smoothing) (PS3 Only)
Operating Systems	Windows® 8.1, 10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux®
Network Protocols	TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell® Environments, EtherTalk for Macintosh Environments
Printing Protocols	SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk® PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD w/ iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WSPrint, FTP
Print Drivers	Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit), macOS X 10.12-15, 11, 12
Interface	RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed) Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth
Wireless Device	AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Android (Available via Apple® App Store or Google Play)
Device Management	TopAccess
Account Control	Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function
Accessibility Features	Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, optional Voice Assist



Security Features	User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/ IEC15408)* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication *Conformance with HCD-PPv1.0 in High Security Mode
Environmental Standards	ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65
Certifications	WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

Scan Specifications

Scan Speed & Weights	DSDf Scan: Up to 240 IPM Duplex, 120 IPM Simplex (Monochrome or Color) 9.3-110lb Bond
Scan Modes	Standard: Full Color, Auto Color, Monochrome, Grayscale
OCR	DOC/XLS/PPT/PDF
Scan Resolution	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
File Formats	Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, Searchable PDF, PDF/A, XPS-Multi/Single Page, DOCX, XLSX, PPTX Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, Slim PDF, Searchable PDF, PDF/A, XPS-Multi/Single Page, DOCX, XLSX, PPTX.
Image Compression	Color/Grayscale: JPEG (High, Middle, Low)

Facsimile Specifications

Compatibility	Super G3
Data Compression	MH/MR/MMR/JBIG
Transmission Speed	Approx. 3 Seconds Per Page
Fax Modem Speed	Up to 33.6 Kbps
Memory	100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job
Transmission	

E-Filing Specifications

Operation Method	Color Touch Screen Control Panel or Client PC
Number of Boxes	1 Public Box, 200 Private User Boxes
Capacity of Boxes	100 Folders Per Box, 400 Documents Per Folder/Box, 200 Pages Per Document

Accessories (Options)

Additional Paper Options			
Large Cap. Feeder - 2,500 Sheet	MP2503L	Panel 10-Key Option	GR1340
Large Cap. Feeder - 2,000 Sheet	MP2002L	Manual Pocket	KK5008
LCF Connector (to add 2K LCF)	KN9000	Harness for Coin Controller	GQ1280
Finishing Options			
65-Sheet Staple Finisher	MJ1115	Software Options	
65-Sheet Saddle-Stitch Finisher	MJ1116	e-BRIDGE Global Print	GB2550NODE
Hole Punch for MJ1115/MJ1116	MJ6108N	IPsec Enabler	GP1080NODE
Finisher Guide Rail	KN1103		
Exit Tray	KA6551	Unicode Font Enabler	GS1007NODE
Connectivity/Security Options			
FAX Unit/2nd Line for FAX Unit	GD1370N	Multi-Station Print Enabler	GS1090NODE
Wireless LAN/Bluetooth	GN4030A3	Per Seat License	GS1090NODE
Fax Over IP License Key	GS1100NODE	e-BRIDGE Plus for OneDrive for Business V3.0	GB2300NODE
Bluetooth Keyboard	GR9001	e-BRIDGE Plus for SharePoint Online V3.0	GB2310NODE
2nd NIC Holder	GR1430	e-BRIDGE Plus for Exchange Online V3.0	GB2320NODE
USB Hub	GR1420	Workplace Productivity Bundle	GB2330NODE
Meta Scan Enabler	GS1010NODE	e-BRIDGE Plus for Gmail	GB2380NODE
Security SSD (512GB)	GE1280	e-BRIDGE Plus for Google Workspace	GB2390NODE
FIPS HDD (320GB)	GE1260	e-BRIDGE Plus Voice Guidance	GB2540NODE
Miscellaneous Options			
Card Reader Holder	GR1320		
Accessory Tray	GR1330		

Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

Corporate Office	25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000
East Coast	959 Route 46 East, 5th Floor, Parsippany, NJ 07054 Tel: 973-316-2700
Midwest	8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631 Tel: 773-380-6000
South	2037 Bakers Mill Rd., Dacula, GA 30019 Tel: 678-546-9385
West Coast	25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000
Web Site	www.business.toshiba.com