

Fachgruppe Algorithmen und Komplexität Projektgruppe Schlaue Schwärme



February 28, 2009

# User's Guide

- Alexander Klaas
- Andreas Cord-Landwehr
- Christoph Raupach
- Christoph Weddemann
- Daniel Warner
- Daniel Wonisch
- Kamil Swierkot
- Marcus Märtens
- Martina Hüllmann
- Peter Kling
- Sven Kurras

Contents 3

# Contents

1	Introduction	4
2	Getting Started	4
3	Running the RobotSwarmSimulatorwith Parameters 3.1 General options	<b>4</b> 5 6 6
4	Using the Simulator-Interface	6
5	Robot Definitions by LUA-files	7
6	Statistics	7
Α	Visualization with GNUPlot	9
В	Input-file Specifications           B.1 Main projectfile            B.1.1 Variables            B.1.2 Vector Modifiers            B.1.3 RobotControl            B.1.4 ViewTypes            B.1.5 Example of a main project file            B.2 Robot file	11 11 12 15 16 17 18
	B.2.1 Example of a robot file	
	B.3.1 Example of an obstacle file	
	1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1 1	_

### 1 Introduction

This document shall help you to use the RobotSwarmSimulatorto simulate robot swarms and to get useful information by the visualization and statistics modules.

For this purpose the document is divided in several sections. It will be usefull if you just start this the "Getting Started!" section play a little bit with the simulator and continue with reading the more detailed information on input parameters, input-file specifications, generating simulations and getting statistics.

# 2 Getting Started

For trial use of RobotSwarmSimulatoryou can simply run generation mode, load one of our default algorithms an see how the robots are moving in the space. All example files can be found in subdirectory ProjectFiles. Here we will present a short example how to simulate the behavior of the CENTEROFGRAVITY algorithm (COG).

- 1. Create a new directory "mytest" to keep all avoid unwanted output files everywhere in your system.
- 2. Copy file cog.lua to this directory.
- 3. Run <path to RSS>/RobotSwarmSimulator -generate -distr-pos=20 -algorithm=cog.lua and the following files are being generated:
  - newrandom.swarm here you can edit all global information
  - newrandom.robot here you can edit the robots
  - newrandom.obstacle here you can add obstacles
- 4. Run <path to RSS>/RobotSwarmSimulator -project-file=newrandom and see the simulation works. You can stop the simulation by pressing Q.
- 5. A new statistics file called

TODO which name?

has been generated in your working directory. You can run gnuplot to get charts.

This simple test can be used as base for further tests. Please look at the following chapters to get specifications of the input-files and the user's inferface.

# 3 Running the RobotSwarmSimulatorwith Parameters

TODO describe the package structure

3.1 General options 5

The RobotSwarmSimulatorexists as executable for Linux, MacOS and Windows in the corresponding directories. Each execution of the RobotSwarmSimulatorneeds specific parameters that are mandatory. By running the RobotSwarmSimulatoryou have to specify at least, which kind of execution do you want. By adding the parameter --generate the generation mode is started to create new input-files. On the other side by adding the parameter --project-file=<your input> the common simulation mode is started. Also a run with special parameters like --help or --about is possible. Thus a typical runs look like:

```
./RobotSwarmSimulator --help
./RobotSwarmSimulator --project-file <path_to_testdata>/testfile_2
./RobotSwarmSimulator --project-file <path_to_testdata>/testfile_2
--history-length 10
./RobotSwarmSimulator --generate --distr-pos=17.0
```

All of the options listed in Listing 1 can be used. Further information for this parameters can bin found in the following sections. The definition of most of the parameters can be found in Table 1.

Listing 1: RSS Helpline

```
General options:
2
      --help
                          shows this help message
3
      --version
                          shows version of RobotSwarmSimulator
4
      --about
                          tells you who developed this awesome piece of software
    Generator options:
      --generate
--seed arg (=1)
                                   switch to generator mode
                                   seed for random number generator
      --robots arg (=100)
                                   number of robots
      --algorithm arg (=NONE)
                                   name of algorithm or lua-file
10
      --worldfile arg (=newrandom) world-file for output
11
      --robotfile arg (=newrandom) robot-file for output
12
      --obstaclefile arg (=newrandom) obstacle-file for output
13
      --distr-pos arg (=0)
                                   distribute position in cube [0;distr-pos]^3
14
      --distr-vel arg (=0)
                                   distribute velocity in cube [0;distr-vel]^3
15
                                   distribute acceleration in cube [0;distr-acc]^3
16
      --distr-acc arg (=0)
17
      --distr-coord
                                   distribute robot coordsystems uniformly
18
    Simulation options:
19
      --project-file arg
20
                              Project file to load
      --history-length arg (=25) history length
```

#### 3.1 General options

- --help Lists all possible options.
- --version This option shows the version information of your RobotSwarmSimulator
- **--about** Get information about the developer team, contact information and more.

### 3.2 Generator options

- --generate Switch to generator mode. This is necessary for the further options of this section
- --seed=arg Sets the seed for the random number generator for robot generation. If not set the seed is 1, but you really should set this value. An unsigned integer value is expected.
- --robots=arg The number of robots to be generated. The default number is 100. An unsigned integer value is expected.
- --algorithm=arg The name of the algorithm the robots should use. If not set the algorithm SimpleRobot is used. This is only a stub without any functionality. Also the name of a lua-file can be given. Extensionsion .lua is mandatory for lua-files.
- --worldfile=arg The name of the worldfile that shall be generated. Default is newrandom. File-name without extension is expected.
- -robotfile=arg The name of the robotfile that shall be generated. Default is newrandom. File-name without extension is expected.
- --obstaclefile=arg The name of the obstaclefile that shall be generated. Default is newrandom. File-name without extension is expected.
- --distr-pos=arg Distributes the position of robots uniformly at random in box of size  $arg \times arg \times arg$ . If not set, all robots are at position zero.
- --distr-vel=arg Distributes the velocity of robots uniformly at random by vectors in box of size arg × arg × arg. If not set, all velocities are zero.
- --distr-acc=arg Distributes the acceleration of robots uniformly at random by vectors in box of size arg × arg × arg. If not set, all velocities are zero.

#### 3.3 General options

- --project-file Specifies the project file use. Do not add extension .swarm. Mandatory for simulation.
- --history-length=arg Sets the history length i.e. the length of the ringbuffer to store world-objects until they get visualized. Standard is 25. An unsigned integer is expected.

# 4 Using the Simulator-Interface

During the simulation it is possible to interact with the simulation in different ways. The following hot-keys are supported while simulation:

Space Start/Stop

- Q the Quit RobotSwarmSimulator
- F1 Help
- G Show Center of all gravity of Swarm
- V Show velocity vectors
- B Show acceleration vectors
- K Show global coordinates system
- W,A,S,D In the corresponding camera mode use W for up and S for down

Arrow-Keys left, right, before, behind

**Mouse** Mouse for spinning

- +, increase/ decrease simulation-speed by constant
- \*, / double/ half simulation-speed
- C Change camera

# 5 Robot Definitions by LUA-files

There are two ways to define a new robot. One way is hardcoded in the RobotSwarmSimulator the other way is to define the robots by scripting their behavior in the Lua scripting language. For example Listing 2 shows you how to formulate the COG-algorithm in Lua.

TODO yeah, how can I do this?

!

Listing 2: COG algorithm in Lua

## 6 Statistics

A simulation run results in three output files of statistics:

• gnuplot\_20091224\_184129\_ALL.plt (GNUPlot-configuration file)

8 6 STATISTICS

- output\_20091224\_184129\_ALL.plt (according statistic data)
- output\_20091224\_184129\_DATADUMP\_FULL.plt (complete data dump)

The file-names results from current date (year, month, day), the current time (hour, minute, second), followed by description of screened object subset (e.ġ. ALL, MASTERS,...). For each entry in STATISTICS\_SUBSETS there will be created one such data pair.

### A Visualization with GNUPlot

Anzeige mit GNUPlot Zur Anzeige der Statistiken eines abgeschlossenen Simulationsdurchlaufes muss die entsprechende GNUPlot-Konfigurationsdatei mit GNUPlot geöffnet werden: Unter Unix-System kann man hierfür nach Aufruf von \$ gnuplot die interaktive GNUPlot-Shell verwenden (> load mgnuplotfile.pltm). Weitere Befehle mit > help. Alternativ kann man sich die Ausgabe direkt anzeigen lassen mittels Shellkommando \$ gnuplot -persist mgnuplotfile.pltm, wobei das -persist bewirkt, dass das Anzeigefenster auch nach Erstellen der Ausgabe geöffnet bleibt. Weitere Flags siehe \$ man gnuplot.

Konfiguration der Anzeige Der Inhalt der Datei output\_20091224\_184129\_ALL.plt könnte auszugsweise so aussehen:

#	time	avg_spd	$minball_x$	()
	0	9.2	20.5	
	1	11.3	21.5	
	4	9.1	21.9	
	6	7.5	22.3	

Jede Zeile enthält die statistischen Daten zu einem bestimmten Zeitpunkt. Der Beginn einer neuen Spalte wird hierbei durch (mindestens) ein Leerzeichen gekennzeichnet. '#' leitet eine Kommentarzeile ein.

In der Datei gnuplot\_20091224\_184129\_ALL.plt findet nun die Formatierung der Daten für die Anzeige statt und kann beliebig geändert werden:

Die Angaben haben folgende Bedeutung:

• set title 'Titel' erzeugt einen zentrierten Titel am oberen Teil der grafischen Darstellung.

- set xrange [min:max] begrenzt den horizontal sichtbaren Bereich zwischen den Werten min und max, set xrange [] führt diese Skalierung auf Grundlage der vorliegenden Daten automatisch durch.
- set grid blendet ein Gitternetz ein.
- set pointsize *multiplikator* skaliert die Größe der Punkte (falls eine Darstellung gewählt wird, welche Punkte beinhaltet) gemäß *multiplikator*.
- xlabel 'Label' beschriftet die X-Achse.

Diese Angaben beinhalten also *nur* grafische grafische Aspekte, die z.B. für die Verwendung in Dokumentationen angepasst werden können. Die Einstellungen der anzuzeigenden Daten finden erst daraufhin statt:

- plot 'Dateiname.plt' leitet den tatsächlichen Vorgang der Darstellung ein. Hierbei werden die Daten aus der angegebenen Datei gelesen. Durch using 1:2 werden die erste und die zweite Spalte gegeneinander dargestellt, wobei der erstgenannte Spaltenindex, also time, die X-Koordinate und folglich avg\_spd die Y-Koordinate definiert. title 'avg\_speed' fügt für die definierte Funktion einen Legendeneintrag mit dem Titel avg\_speed hinzu. Der Zusatz with linespoints beschreibt die Darstellung durch mit Linien verbundene Zeichen an den Datenpunkten. linespoints kann auch ersetzt werden durch:
  - lines verbindet jeden Datenpunkt mit einer Linie
  - dots zeigt einzelne Punkte an (sinnvoll bei vielen Datenpunkten)
  - points fügt ein Zeichen an der Position des Datenpunktes ein. Die Größe kann durch den Befehl set pointsize geändert werden
  - linespoints erstellt gleichzeitig points und lines
  - impulses erzeugt eine vertikale Linie ausgehend von der X-Achse zum Datenpunkt

Zum Plotten einer weiteren Funktion in derselben Darstellung wird die gleiche Struktur durch ein Komma getrennt angehangen (auch aus verschiedenen Quelldateien). Dies ermöglicht auf einfache Art, dass die Darstellung der Statistiken unterschiedlicher Simulationsdurchläufe in einer Grafik dargestellt werden können.

## **Ergebnis**

#### Weitere Informationen zu GNUPlot

- [1] offizielle Homepage: http://www.gnuplot.info/
- [2] Grundkurs: http://userpage.fu-berlin.de/~voelker/gnuplotkurs/gnuplotkurs.html




Figure 1: Example output from GNUplot

# **B** Input-file Specifications

There are exactly four kinds of input files for the RobotSwarmSimulator This includes the project specification files and also the Luascript-files that define the robot behaviour.

- 1. The main projectfile containing information about the model. The extension of this type of file is ".swarm".
- 2. A file containing robot information. The extension of this file is ".robot".
- 3. A file containing obstacle information. The extension of this file is ".obstacle".
- 4. Luafile that describes the robot behavouir. The extension of this file is ".lua".

### **B.1** Main projectfile

The following specifications hold only for the main projectfile (with extension .swarm):

- A comment begins with a '#'.
- A line is a comment line (beginning with a '#'), an empty line or a line containing a variable followed by an equal sign followed by a *quoted* value of this variable. Example:

```
VAR_1="value"
VAR_2 = "value"
VAR_3= "value"
VAR_4 ="value"
```

• a variable name has to be of the following form:  $[A-Z0-9_]^+$ 

#### **B.1.1 Variables**

The main project file contains the variables defined in Tables 1 and 2.

Also the following should be considered:

- The order of the variables in the main project file is not important.
- If a variable does not appear in the main projectfile, then its default value will be used if such a default value does exist (otherwise an exception will be thrown while loading the main project-file).

Variable name	Possible Values	Description	Default
PROJECT_NAME	String	Name of the project	ı
COMPASS_MODEL	Still needs to be specified by the ASG-Team. For instance $NO\_COMPASS$	Compass model	FULL_COMPASS
ROBOT_FILENAME	For instance robot_file. The extension of the file must not be appended in this variable.	Filename of the robotfile	same as project file
OBSTACLE_FILENAME	For instance obstacle_file. The extension of the file must not be appended in this variable.	Filename of the robotfile	same as project file
STATISTICS_SUBSETS	A concatenation of none or more of the following strings: {ALL}, {ACTALL}, {INACTALL}, {MASTERS}, {ACTMASTERS}, {INACACTMASTERS}, {SLAVES}, {ACTSLAVES},	Defines the subsets of all robots for which to calculate individual statistical data. E.g. "{ALL} {MASTERS}" will produce statistical information on all robots as well as on masters only	NONE
	{INACTSLAVEŠ}		
STATISTICS_TEMPLATE	One of the following: "ALL", "BASIC" or "NONE"	Identifies the set of informations to calculate for each subset.	ALL
STATISTICS_DATADUMP	Either "FULL" or "NONE"	Whether or not detailled information (e.g. all robots positions at each event) should be	NONE
ASG	SYNCHRONOUS. ASYNCHBONOUS OF SEMISYNCHRONOUS	streamed to a file during simulation.  Type of ASG	SYNCHBONDUS
ASYNC_ASG_SEED	unsigned int	Seed for asynchronous ASG, only set if ASG=ASYNCHRONOUS	
ASYNC_ASG_PART_P	double	Participation Probability for asynch ASG, only set if ASG = ASYNCHRONOUS	1
ASYNC_ASG_TIME_P	double	parameter governing the timing of asynch ASG, only set if ASG = ASYNCHRNOUS	1
ROBOT_CONTROL	see section B.1.3	RobotControl to use	1

Table 1: Variables in the main project file

Variable name	Possible Values	Description	Default
MARKER_REQUEST_HANDLER_TYPE	element from {STANDARD, NONE}	Type of Marker Request Handler to use	{NONE}
TYPE_CHANGE_REQUEST_HANDLER_TYPE	element from {STANDARD, NONE}	Type of Type Change Request Handler to use.	{NONE}
POSITION_REQUEST_HANDLER_TYPE	element from {VECTOR, NONE}	Type of Position Request Handler to use	{NONE}
VELOCITY_REQUEST_HANDLER_TYPE	element from {VECTOR, NONE}	Type of Velocity Request Handler to use	{NONE}
ACCELERATION_REQUEST_HANDLER_TYPE	element from {VECTOR, NONE}	Type of Acceleration Request Handler to use	٧
MARKER_REQUEST_HANDLER_SEED	integer	Seed for Marker Request Handler to use	{NONE}
TYPE_CHANGE_REQUEST_HANDLER_SEED	integer	Seed for Type Change Request Handler to use.	-
POSITION_REQUEST_HANDLER_SEED	integer	Seed for Position Request Handler to use	ı
VELOCITY_REQUEST_HANDLER_SEED	integer	Seed for Velocity Request Handler to use	_
ACCELERATION_REQUEST_HANDLER_SEED	integer	Seed for Acceleration Request Handler to use	1
MARKER_REQUEST_HANDLER_DISCARD_PROB	element from interval [0, 1]	Discard probability for Marker Request Handler	ı
		to use	
TYPE_CHANGE_REQUEST_HANDLER_DISCARD_PROB	element from interval $[0,1]$	Discard probability for Type Change Request	_
		Handler to use.	
POSITION_REQUEST_HANDLER_DISCARD_PROB	element from interval [0, 1]	Discard probability for Position Request Han-	1
		dler to use	
VELOCITY_REQUEST_HANDLER_DISCARD_PROB	element from interval $[0,1]$	Discard probability for Velocity Request Han-	_
		dler to use	
ACCELERATION_REQUEST_HANDLER_DISCARD_PROB	element from interval $[0,1]$	Discard probability for Acceleration Request	-
		Handler to use	
POSITION_REQUEST_HANDLER_MODIFIER	list of vector modifiers (see B.1.2)	List of vector modifiers for Position Request	_
		Handler to use	
VELOCITY_REQUEST_HANDLER_MODIFIER	list of vector modifiers (see B.1.2)	List of vector modifiers for Velocity Request	_
		Handler to use	
ACCELERATION_REQUEST_HANDLER_MODIFIER	list of vector modifiers (see B.1.2)	List of vector modifiers for Acceleration Request	ı
		Handler to use	

Table 2: Variables in the main project file

B.1 Main projectfile 15

#### **B.1.2 Vector Modifiers**

The list of vector modifiers is a (not necessarily nonempty) list, i. e.

```
(VECTOR_MODIFIER_1); (VECTOR_MODIFIER_2); ...
```

The order of the elements of this list is important. If no Vector Modifier shall be used for the corresponding Request Handler, then use VECTOR\_MODIFIERS="".

An element  $VECTOR\_MODIFIER\_k$  of the Vector Modifier list is a tuple, defined as follows:

```
VECTOR_MODIFIER_k=(VECTOR_MODIFIER_TYPE, VECTOR_MODIFIER_PARAM_1, VECTOR_MODIFIER_PARAM_2,...)
```

The number and types of paramters like VECTOR\_MODIFIER\_PARAM\_1, VECTOR\_MODIFIER\_PARAM\_2,... depends on the corresponding type of the Vector Modifier. Currently there are the following types of Vector Modifiers:

- VectorDifferenceTrimmer
- VectorTrimmer
- VectorRandomizer

I.e. the value of VECTOR\_MODIFIER\_TYPE needs to be VECTOR\_DIFFERENCE\_TRIMMER, VECTOR\_TRIMMER or VECTOR\_RANDOMIZER.

**VectorDifferenceTrimmmer** If VECTOR\_MODIFIER\_TYPE is equal to VECTOR\_DIFFERENCE\_TRIMMER, then the following parameters are expected:

1. length of type double

I. e. an element of the VECTOR\_MODIFIERS-list of type VECTOR\_DIFFERENCE\_TRIMMER may look like: (VECTOR\_DIFFERENCE\_TRIMMER,5.2).

**VectorTrimmer** If vector modifier type equals VECTOR\_TRIMMER, then the following parameters are expected:

1. length of type double

I.e. an element of the VECTOR\_MODIFIERS-list of type VECTOR\_TRIMMER may look like: (VECTOR\_TRIMMER, 10.0).

**VectorRandomizer** If vector modifier type equals **VECTOR\_RANDOMIZER**, then the following parameters are expected:

- 1. seed of type unsigned int
- 2. standard derivation of type double

I. e. an element of the VECTOR\_MODIFIERS-list of type VECTOR\_DIFFERENCE\_TRIMMER may look like: (VECTOR\_DIFFERENCE\_TRIMMER,1,0.5).

#### B.1.3 RobotControl

The RobotControl variable defines the class which should be used to control the robots (and in particular to control the views of the robots). Currently one of the following classes has be chosen:

- 1. UNIFORM\_ROBOT\_CONTROL
- 2. ROBOT\_TYPE\_ROBOT\_CONTROL

Each class is explained in detail below. Note that each class expects certain class specific parameters.

**UniformRobotControl** This class assigns each robot the same view type. The concrete view type needs to be defined using a VIEW variable. The possible values for this variable (view types) are definied below (see B.1.4). E.g. you may to assign each robot global view to the world using ROBOT\_TYPE\_ROBOT\_CONTROL="GLOBAL\_VIEW".

**RobotTypeRobotControl** This class assigns each robottype the same view type. Therefore robots with different robot types may have different view types. Currently there are two robot types:

- 1. MASTER
- 2. SLAVE

To specify which view type should be used by each robot type, there must be variables of the form  $RobotType\_{\tt VIEW}$ .

The value of each variable has to be a view type (see B.1.4). Note that the view type parameters are also distinguished using the *RobotType* prefix. E.g. you may specify

MASTER\_VIEW="CHAIN\_VIEW"
MASTER\_CHAIN\_VIEW\_NUM\_ROBOTS="5"

to set the view for master robots to a chain view allowing the robots to see five neighbor robots. Note that exactly one view type should be defined for each robot type.

B.1 Main projectfile 17

#### B.1.4 ViewTypes

The view type of a robot defines its vision model. Whenever a view type is expected you may use one of the following values:

- 1. GLOBAL\_VIEW
- 2. COG\_VIEW
- 3. CHAIN\_VIEW
- 4. ONE\_POINT\_FORMATION\_VIEW
- 5. SELF\_VIEW

Each view type is explained in detail below.

**GLOBAL\_VIEW** Allows robots to see literally everything. There are no parameters expected.

**COG\_VIEW** View model meant to be used for center of gravity algorithms, i.e. every robot can see every other robots position, velocity and acceleration. The coordinate-system and id of each robot is not visible. There are no parameters expected.

**SELF\_VIEW** View model which allows robots to access every self-related information while disallowing to access any other information. There are no parameters expected.

**CHAIN\_VIEW** View model meant to be used for robot chain related algorithms, i.e. every robot can see k neighbor robots position. Besides this no more information is visible. When using this view type you have to specify the variable  $k \in \mathbb{N}$  using the parameter variable CHAIN\_VIEW\_NUM\_ROBOTS.

**ONE\_POINT\_FORMATION\_VIEW** View model meant to be used for one point formation algorithms, i.e. every robot can see every other robots position, velocity and acceleration only in a limited view radius r. The coordinate-system and id of each robot is not visible. When using this view type you have to specify the variable  $r \in \mathbb{R}$  using the parameter variable ONE\_POINT\_FORMATION\_VIEW\_RADIUS.

### B.1.5 Example of a main project file

A main project file may look like:

```
2
      Description about configuration.
3
4
      PROJECT_NAME="My Exciting Project"
5
      COMPASS_MODEL="NO_COMPASS"
6
      ROBOT_FILENAME="myrobots"
      OBSTACLE_FILENAME="myobstacle"
      STATISTICS MODULE="0"
9
      ASG="ASYNCHRONOUS"
10
      ROBOT_CONTROL="ROBOT_TYPE_ROBOT_CONTROL"
11
      MASTER_VIEW="GLOBAL_VIEW"
12
      SLAVE_VIEW="ONE_POINT_FORMATION_VIEW"
13
      SLAVE_ONE_POINT_FORMATION_VIEW_RADIUS="5.0"
      MARKER_REQUEST_HANDLER_TYPE="STANDARD"
16
      STANDARD_MARKER_REQUEST_HANDLER_DISCARD_PROB="0.5"
17
18
      STANDARD_MARKER_REQUEST_HANDLER_SEED="1"
19
      TYPE_CHANGE_REQUEST_HANDLER_TYPE="NONE"
20
      # no additional variables needed
21
22
      POSITION REQUEST HANDLER TYPE="VECTOR"
23
      VECTOR_POSITION_REQUEST_HANDLER_DISCARD_PROB="0.1"
24
25
      VECTOR POSITION REQUEST HANDLER SEED="3"
26
      VECTOR_POSITION_REQUEST_HANDLER_MODIFIER="(VECTOR_TRIMMER,1.5);(
          VECTOR_RANDOMIZER,5,2.5)'
27
      VELOCITY_REQUEST_HANDLER_TYPE="VECTOR"
      VECTOR_VELOCITY_REQUEST_HANDLER_DISCARD_PROB="0.1"
29
      VECTOR_VELOCITY_REQUEST_HANDLER_SEED="3"
30
      VECTOR_VELOCITY_REQUEST_HANDLER_MODIFIER="(VECTOR_TRIMMER,1.5);(
31
          VECTOR_RANDOMIZER,5,2.5)"
```

#### B.2 Robot file

The robotfile uses a csv-compatible format. Therefore the information for one robot has to be saved in exactly one line of the file. Each line contains the following data. The order of this data is important!

- ID-number
- initial position (x, y, z)
- initial type (for instance master, slave,...)
- initial velocity (x, y, z)
- initial acceleration (x, y, z)
- initial status (maybe sleeping or ready; still has to be specified more precisely)
- initial marker information (still has to be specified)
- algorithm to use (shortcut for an algorithm; still needs to be specified)

B.3 Obstacle file 19

• color (using this color a robot is marked for instance for a special treatment during the visualization; this color isn't used anywhere else)

• coordinate system axes (triple  $x_1, x_2, x_3, y_1, y_2, y_3, z_1, z_2, z_3$ ; this field will be left empty, if axes are supposed to be generated uniformly at random)

The first line always is (column headers):

```
"ID", "x-position", "y-position", "z-position", "type", "x-velocity", "y-velocity", "z-velocity", "x-acceleration", "y-acceleration", "z-acceleration", "status", "marker-info", "algorithm", "color", "x-axis-1", "x-axis-2", "x-axis-3", "y-axis-1", "y-axis-2", "z-axis-3", "z-axis-1", "z-axis-2", "z-axis-3"
```

Each non-number is quoted.

#### B.2.1 Example of a robot file

```
"ID", "x-position", "y-position", "z-position", "type", "x-velocity", "y-velocity", "z-velocity", "x-acceleration", "y-acceleration", "z-acceleration", "status", "arker-info", "algorithm", "color", "x-axis-1", "x-axis-2", "x-axis-3", "y-axis-1", "y-axis-2", "y-axis-3", "z-axis-1", "z-axis-2", "z-axis-3"

0,5.3,9.2,6.4, "master", 1.5,2.5,3.5,1.5,2.5,3.5, "sleeping", 0, "MASTER_ALGO", 0,1,0,0,0,1,0,0,0,1

1,2.5,4.2,8.8, "slave", 1.5,2.5,3.5,1.5,2.5,3.5, "ready", 0, "SLAVE_ALGO", 0,1,0,0,0,1,0,0,0,1
```

**TODO** type really "master"/"slave" or rather 0/1? (scenario\_generator generates latter atm)

!

#### **B.3** Obstacle file

Like the robot file the obstacle file uses a csv-compatible format. Therefore the information for one robot has to be saved in exactly one line of the file. Each line contains the following data. The order of this data is important!

- type (marker, sphere or box)
- position (x, y, z)
- marker information (still needs to be specified)
- x/y/z-lengths or radius (depending on type)

The first line always is (column headers):

```
1 "type", "x-position", "y-position", "z-position", "marker-info", "size-info", "", ""
```

Each non-number is quoted.

# B.3.1 Example of an obstacle file

```
"type", "x-position", "y-position", "z-position", "marker-info", "size-info", ""
box", 2.0, 3.0, 4.0, 0, 1.0, 2.0, 3.0,
"sphere", 3.4, 5.2, 5.1, 0, 5.0, "", ""
"marker", 3.5, 1.4, 5.1, 0, "", ""
```

As you can already see in the example, if the type of an obstacle is sphere, then the last two values must be empty, i.e. ",". Analoguos, if the type is marker, the last three values must be empty, i.e. ",",".