

# Constrained Application Protocol (CoAP) over Bundle Protocol (BP)

## draft-ietf-core-coap-bp-01

Intended Status: Standards Track

Carles Gomez

Anna Calveras

Universitat Politècnica de Catalunya



This work was funded in part by the Spanish MCIU/AEI/10.13039/501100011033/FEDER/UE through project PID2023-146378NB-I00

# Status

- Draft adopted after IETF 123 (Madrid)
  - draft-gomez-core-coap-bp-04
- draft-ietf-core-coap-bp-00
  - Same technical content as draft-gomez-core-coap-bp-04
- draft-ietf-core-coap-bp-01
  - Address Marco Tiloca's review (many thanks!)

# Table of contents

- Same structure as in -00

1. Introduction . . . . .	3
2. Terminology . . . . .	3
2.1. Requirements language . . . . .	3
2.2. Background on previous specifications . . . . .	3
2.3. New terms . . . . .	4
3. Architecture . . . . .	4
4. Messages . . . . .	4
4.1. Messaging model . . . . .	5
4.2. Single message format . . . . .	6
4.3. Payload-length option . . . . .	7
4.3.1. Payload-length option and OSCORE . . . . .	8
5. Encapsulating bundle . . . . .	8
6. CoAP parameter settings and related times . . . . .	9
7. Observe . . . . .	12
8. Block-wise transfers . . . . .	12
8.1. Main CoAP block-wise transfer parameters . . . . .	13
9. Proxying . . . . .	14
9.1. Proxying scenarios . . . . .	14
9.2. Proxying over BP . . . . .	15
9.3. Proxy operation and message aggregation . . . . .	16
10. URI Scheme . . . . .	17
11. Securing CoAP over BP . . . . .	18
12. IANA Considerations . . . . .	20
12.1. Creation of two new reserved domains in the .arpa name space . . . . .	20
12.1.1. Domain Name Reservation Considerations . . . . .	20
12.2. ipn URI Scheme Well-known Service Number for CoAP . . . . .	21
12.3. CoAP Option Numbers Registry . . . . .	21
13. Implementation Status . . . . .	21
13.1. Space CoAP . . . . .	22
13.2. Other CoAP over BP implementations . . . . .	24
14. Security Considerations . . . . .	24
15. Acknowledgments . . . . .	25
16. References . . . . .	25
16.1. Normative References . . . . .	25
16.2. Informative References . . . . .	27
Appendix A. Reference CoAP parameter values for interplanetary communication . . . . .	28
Appendix B. Message ID size, EXCHANGE_LIFETIME, and maximum CoAP message rate . . . . .	32
Authors' Addresses . . . . .	34

## 4.3. Payload-length option

- When encapsulated in a bundle, a CoAP message is represented as a definite-length CBOR byte string
  - Thus, the length of the CoAP message is unambiguously represented
  - The Payload-length option **MUST NOT** be included in a Single message
- 4.3.1. Payload-length option and OSCORE
  - Payload-length value may need to be updated
    - E.g., EDHOC + OSCORE request (RFC 9668)

# 5. Encapsulating bundle

- When a CoAP message needs to be sent in response to an incoming CoAP message, and to support one-to-many communication:
  - The Source Node ID SHOULD be the EID of the endpoint that produces the bundle encapsulating the CoAP message sent in response
  - The Source Node ID MAY be the null endpoint ID (anonymous source, RFC 9171)


## 6. CoAP parameter settings and related times

- CoAP group communication:
  - Minimum time between reuse of Token values for group requests: MIN\_TOKEN\_REUSE\_TIME
  - By default, MIN\_TOKEN\_REUSE\_TIME > 500 seconds.
  - Not suitable for many BP scenarios, needs to be increased, based on expected delay in the scenario
    - See Appendix A

## 9.3. Proxy operation and message aggregation (I/II)

- A proxy MAY aggregate CoAP messages destined for the same endpoint

- NEW:
- Additional motivation: aggregate incoming messages while there is connectivity on the correspond. side of the proxy
  - However, risk of contributing delay



## 9.3. Proxy operation and message aggregation (II/II)

- When a proxy aggregates CoAP messages, the proxy adds the Payload-length option to each Single message
  - The proxy MUST recompute the deltas of the outer CoAP options from each Single message accordingly
- When a proxy sends a Single message that was part of an Aggregate message, the proxy MUST remove its Payload-length option prior to its transmission.
  - The proxy MUST recompute the deltas of the outer CoAP options accordingly



# 11. Securing CoAP over BP (I/II)

- In the presence of CoAP proxies, BPSec cannot ensure the end-to-end protection of application-layer data.
  - OSCORE SHOULD be used to protect application-layer data between the two CoAP endpoints

NEW:

- BPSec is still useful to protect all fields of the carried CoAP message (including the Payload-length option: “Class U” for OSCORE) in each BP end-to-end path:
  - From the origin CoAP source until the first CoAP proxy,
  - between consecutive CoAP proxies, or
  - from the last CoAP proxy until the final CoAP destination

# 11. Securing CoAP over BP (II/II)

- BP freshness feature:
  - A bundle includes a creation timestamp and a lifetime field
  - Provides additional protection against replay attacks
- The Echo option in CoAP [RFC 9175] allows a server to verify the freshness of a request:
  - When the freshness of a request cannot be verified, the server rejects the request and includes the Echo option in the response
  - The client resends the original request with the Echo option value, also includes it in at least the next request
  - The round trip to check the freshness of the first request may incur significant delay penalty in BP environments.
  - In a scenario with proxies, the freshness of BP is limited to the scope of a BP path. The Echo option would be needed to verify the end-to-end freshness of a CoAP request

# 14. Security considerations

- Risk (Payload-length is “Class U” for OSCORE):
  - An attacker might infer some features of the communication based on the payload size of the messages
- Added:
  - NEW:
    - Exposing the individual sizes of the Single messages in an Aggregate message provides more information than the Aggregate message size
      - Assuming that the latter can be obtained by the attacker

# **Thanks!**

## **Questions? Comments?**

**Carles Gomez**

**Anna Calveras**

Universitat Politècnica de Catalunya