




	I	G	F	E	D	C	B	A																																																	
4	CABLE SPECIFICATION : RG-178 1) Inner Conductor 2) Dielectric Type 3) Shield 4) Velocity of Propagation(%) 5) Jacket Diameter(in) 6) Jacket Material 7) Capacitance (pF/m) 8) Impedance (Ohms) 9) Conductor DCR(Ohm/km) 10)Outer Shield DCR(Ohm/km) 11)Max Operating Temperature (°C) 12)Max Operating frequency(MHz) 13)Max Operating Voltage(RMS) 14)Corona Extinction voltage(Vrms) 15)Voltage Withstand (Vrms) 16)Spark Test (Vrms) - Silver Plated Copper Clad Steel - PTFE - 95% Silver Plated Copper Braid - 69.5 - 0.098±0.004 in - FEP - 95 - 50±2 - 277.2 - 20 - -55 to 200 - 6000 - 1200 - 1200 - 2000 - 2000 								4																																																
3									3																																																
2	CONNECTOR SPECIFICATION : 1) Type 2) Configuration 3) Frequency Range 4) Impedance 5) Contact Material & plating 6) Insulator 7) Body Material & Plating 8) Heat Shrink - TNCFBH - Straight - DC to 6 GHz - 50 Ohms - PB, Gold - PTFE - Brass, Gold - Polyolefin MMCX Male Right Angle DC to 6GHz 50 Ohms PB, Gold/ PTFE Brass, Gold Polyolefin								2																																																
1	<table><tr><td colspan="2">DESIGNED BY: GURU BIRADAR</td><td colspan="2" rowspan="2">TNCFEMALEBULKHEAD</td><td>I</td><td>-</td></tr><tr><td colspan="2">DATE: 03/01/2018</td><td>H</td><td>-</td></tr><tr><td colspan="2">CHECKED BY: Mr. S. METRI</td><td colspan="2" rowspan="2">-MMCXRIGHT ANGLE CONNECTOR ASSY</td><td>G</td><td>-</td></tr><tr><td colspan="2">DATE: 03/01/2018</td><td>F</td><td>-</td></tr><tr><td>SIZE A4</td><td></td><td colspan="2" rowspan="2">ANAND TECHNOLOGIES</td><td>E</td><td>-</td></tr><tr><td>SCALE 1:1</td><td>WEIGHT (kg) NA</td><td>D</td><td>-</td></tr><tr><td colspan="2">DRAWING NUMBER AT-CA-MMCXRT-TNCFBH-120-RG178</td><td colspan="2">SHEET 1 / 1</td><td>C</td><td>-</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>B</td><td>-</td></tr><tr><td colspan="2"></td><td colspan="2"></td><td>A</td><td>-</td></tr></table> This drawing is our property; it can't be reproduced or communicated without our written agreement.								DESIGNED BY: GURU BIRADAR		TNCFEMALEBULKHEAD		I	-	DATE: 03/01/2018		H	-	CHECKED BY: Mr. S. METRI		-MMCXRIGHT ANGLE CONNECTOR ASSY		G	-	DATE: 03/01/2018		F	-	SIZE A4		ANAND TECHNOLOGIES		E	-	SCALE 1:1	WEIGHT (kg) NA	D	-	DRAWING NUMBER AT-CA-MMCXRT-TNCFBH-120-RG178		SHEET 1 / 1		C	-					B	-					A	-	1
DESIGNED BY: GURU BIRADAR		TNCFEMALEBULKHEAD		I	-																																																				
DATE: 03/01/2018				H	-																																																				
CHECKED BY: Mr. S. METRI		-MMCXRIGHT ANGLE CONNECTOR ASSY		G	-																																																				
DATE: 03/01/2018				F	-																																																				
SIZE A4		ANAND TECHNOLOGIES		E	-																																																				
SCALE 1:1	WEIGHT (kg) NA			D	-																																																				
DRAWING NUMBER AT-CA-MMCXRT-TNCFBH-120-RG178		SHEET 1 / 1		C	-																																																				
				B	-																																																				
				A	-																																																				
	H	G					B	A																																																	