

4

3

2

1

H

G

F

E

D

C

B

A

Specifications

Cable Length : 457.55mm / 18"
Connector Type A : SMA Straight Male Connector
Connector Type B : SMP Right Angle Jack
Cable Type : RG-405
Impedance : 50 ohms
Frequency : 0 – 12.5/18.6/26.5 GHz
VSWR : = 1.1@1GHz
Return Loss : = 26.444dB@1GHz
Voltage Rating : 335V RMS
Insulation Resistance : 5,000 Mohm Min.
Dielectric Withstanding Voltage : 500V AC / 1 min. hold with no breakdown or flashover
SMA Contact Resistance : Centre Contact: 3m ohms Max.
Outer Contact: 2m ohms Max.
SMP Contact Resistance : Centre Contact: 2m ohms Max.
Outer Contact: 6m ohms Max.
Mating : ¼" – 36 Threaded Coupling / Snap-on Coupling
Durability : 500 times
Body Material : Beryllium Copper/Brass, Gold Plated
Centre Contact Material : Beryllium Copper, Gold Plated
Insulating Material : PTFE




4

3

2

1

DESIGNED BY: GURU BIRADAR		SMPRA-SMA MALE ST LOW LOSS CABLE ASSY	I	—
DATE: 07/03/2017			H	—
CHECKED BY: Mr. S. METRI			G	—
DATE: 07/03/2017			F	—
SIZE A3		ANAND TECHNOLOGIES	E	—
SCALE 1 : 1	WEIGHT (kg) 0 . 00		D	—
DRAWING NUMBER AT-CA-SMPRA-SMAM-405-XX		SHEET 1 / 1	C	—
This drawing is our property; it can't be reproduced or communicated without our written agreement.			B	—
			A	—

H

G

B

A