




Specifications

Part No.	:	AT-UHF-RFID-2CH4PO-MR6132 A
IP Level	:	Level 56
Protocol	:	ISO18000-6B, ISO18000-6C(EPC GEN2)
Frequency Range	:	ISM 902~928MHZ or ISM 865~868MHz option
Operation Mode	:	FHSS
RF Power out	:	0~30dBm,software configurable
Output/Input port	:	4 Team OUTPUT(Control output high/low level), 2 team input
Reading Clue	:	Buzzer and Led
Antenna	:	Antenna 1(transmit) and Antenna 3(receive) work as one team; Antenna 2(transmit) and Antenna 4(receive) 4(receive) work as one team;
Net Weight(kg)	:	2
Operating Temperature	:	-20 to +80 (°C)
Power Consumed	:	DC +9v (Supply AC/DC power adapter)
Dimension (mm)	:	310×210×40
Communication interface	:	Standard RS232 RJ45_TCP/IP_, RS485

DESIGNED BY: Kiran Kumar		UHF RFID READER		I	-
DATE: 03/10/2016				H	-
CHECKED BY: Mr. S. Metri				G	-
DATE: 03/10/2016				F	-
SIZE A3		ANAND TECHNOLOGIES		E	-
				D	-
SCALE 1 : 1	WEIGHT (kg) XXX	DRAWING NUMBER AT-UHF-RFID-2CH4PO-MR6132 A	SHEET 1 / 1	C	-
This drawing is our property; it can't be reproduced or communicated without our written agreement.				B	-
				A	-