RG-58 CABLE SPECIFICATION :

1) Inner Conductor Material and Plating - Copper Clad Steel, Silver
2) Dielectric Type - PE
3) Shield Materials - Silver Plated Copper Braid
4) Jacket Material and Color - FEP (BLUE JACKET)
5) Impedance, Ohms - 50
6) Velocity of Propagation, % - 69.90
7) Maximum Operating Frequency, GHz - DC TO 6 GHz
8) Capacitance, pF/m - 95
9) Maximum Operating Voltage, Vrms - 1,900
10) Operating Range, deg C - -40 to +80
11) Material - Copper Clad Steel
12) Diameter, mm - 4.35

BNC CONNECTOR SPECIFICATION :

1) INSULATORS - PTFE
2) BODY - SS BODY
3) CRIMP SLEEVE - SEAMLESS LOWLEAD BRASS TUBE, ALLOY 330, SOFT ANNEAL TEMPER
4) HEAT SHRINK SLEEVE - RNF100
5) CONTACT PIN - BERYLIUM COPPER

.

DESIGNED BY: GURU BIRADAR DATE: 07/03/2017		RF LOW LOSS CABLE ASSEMNLY N MALE TO BNC MALE	
CHECKED BY: Mr. S. METRI DATE: 07/03/2017			
SIZE A4		ANAND TECHNOLOGIES	
SCALE 1:1	WEIGHT (kg) NA	DRAWING NUMBER AT-CA-NM-BNCM-402-2000	SHEET 1/1

This drawing is our property; it can't be reproduced or communicated without our written agreement.