


RG-58 CABLE SPECIFICATION :

- | | |
|---|------------------------------|
| 1) Inner Conductor Material and Plating | - Copper Clad Steel, Silver |
| 2) Dielectric Type | - PE |
| 3) Shield Materials | - Silver Plated Copper Braid |
| 4) Jacket Material and Color | - FEP (BLUE JACKET) |
| 5) Impedance, Ohms | - 50 |
| 6) Velocity of Propagation, % | - 69.90 |
| 7) Maximum Operating Frequency, GHz | - DC TO 6 GHz |
| 8) Capacitance, pF/m | - 95 |
| 9) Maximum Operating Voltage, Vrms | - 1,900 |
| 10) Operating Range, deg C | - -40 to +80 |
| 11) Material | - Copper Clad Steel |
| 12) Diameter, mm | - 4.35 |



BNC CONNECTOR SPECIFICATION :

- | | |
|-----------------------|--|
| 1) INSULATORS | - PTFE |
| 2) BODY | - SS BODY |
| 3) CRIMP SLEEVE | - SEAMLESS LOWLEAD BRASS TUBE, ALLOY 330, SOFT ANNEAL TEMPER |
| 4) HEAT SHRINK SLEEVE | - RNF100 |
| 5) CONTACT PIN | - BERYLIUM COPPER |

DESIGNED BY: GURU BIRADAR		RF LOW LOSS CABLE ASSEMBLY N MALE TO N MALE		I	—
DATE: 07/03/2017				H	—
CHECKED BY: Mr. S. METRI				G	—
DATE: 07/03/2017				F	—
SIZE A4		ANAND TECHNOLOGIES		E	—
SCALE 1:1	WEIGHT (kg) NA			D	—
DRAWING NUMBER AT-CA-NM-NM-402-2000		SHEET 1 / 1		C	—
This drawing is our property; it can't be reproduced or communicated without our written agreement.				B	—
				A	—