


	I	G	F	E	D	C	B	A	
4	CABLE SPECIFICATION : 1) Inner Conductor 2) Dielectric Type 3) Shield 4) Velocity of Propagation (%) 5) Jacket Diameter (in) 6) Jacket Material 7) Capacitance (pF/m) 8) Impedance(Ohms) 9) Conductor DCR (Ohm/km) 10)Outer Shield DCR (Ohm/km) 11)Max Operating Temperature (°C) 12) Max Operating frequency (MHz) 13)Max Operating Voltage (RMS) 14)Corona Extinction voltage (Vrms) 15)Voltage Withstand (Vrms) 16)Spark Test (Vrms) RG-316 - Silver Plated Copper Clad Steel - PTFE - 95% Silver Plated Copper Braid - 69.5 - 0.098±0.004 - FEP - 95 - 50±2 - 277.2 - 20 - -55 to 200 -3000 - 1200 - 1200 - 2000 - 2000 RG-174 Copper Clad Steel,7 Strands PE Tinned Copper Braid 66 0.11 PVC 101 50±2 97 10.7 80 -3000 1500 1500 1100 2000 								4
3									3
2	CONNECTOR SPECIFICATIONS 1) Type 2) Configuration 3) Frequency Range 4) Impedance 5) Contact Material & plating 6) Insulator 7) Body Material & Plating 8) Gasket 9) heat Shrink 10)Hexa Nut/Plating 11)Lock Washer/Plating -SMB Female Straight DC-6GHz - 50 Ohms - BeCu/Silver - PTFE - Brass/Bronze - Silicone Rubber - Polyolefin - Brass/Bronze - brass/Bronze SMA FEMALE BULK HEAD Straight DC-9GHz 50 Ohms Brass, Gold/Ni PTFE Brass, Gold/Ni Silicone Rubber Polyolefin - -								2
1	DESIGNED BY: GURU BIRADAR DATE: 03/01/2018 CHECKED BY: Mr. S. METRI DATE: 03/01/2018 SIZE A4  SCALE 1:1 WEIGHT (kg) NA CABLE ASSY SMBFEMALE -SMAFEMALE BULKHEAD ANAND TECHNOLOGIES DRAWING NUMBER AT-CA-SMBF-SMAF-RG174-1000 SHEET 1 / 1 I H G F E D C B A - - - - - - - - - This drawing is our property; it can't be reproduced or communicated without our written agreement.								1
	H	G					B	A	