




Electrical Specification

Part No	:	AT-COUPLER-117.975
Frequency Range	:	117.975-137
Insertion Loss	:	(0.5-0.2)dB adjustable
Return Loss	:	<-14dB
Configuration	:	Dual cavity
Filter Characterstics	:	Band Pass
Nominal Impedance	:	50 (Ω)
I/P and O/P VSWR	:	<1.5:1 or Betteer
Isolation(O/P to O/P)	:	>20dB
Isolation(O/P to I/P)	:	>20dB
Selectivity With 1.0 dB	:	>15dB @500 khz offset
Tunning Accuracy	:	2KHz
Minimum Channel	:	100KHz
Operating Temperature	:	-30° to 60,RH-90% Non-Condensing
Connector	:	N(F)
Number Of Ports	:	4
Dimensions	:	Should Be Mountable to 19" rack

DESIGNED BY: Kiran Kumar		AT - COUPLER - 117.975		I	—
DATE: 15/12/2016				H	—
CHECKED BY: Mr. S. Metri				G	—
DATE: 16/12/2016				F	—
SIZE A3				E	—
ANAND TECHNOLOGIES				D	—
SCALE	WEIGHT (kg)	DRAWING NUMBER	SHEET	C	—
1:1	XXX	AT - COUPLER - 117.975	1 / 1	B	—
This drawing is our property; it can't be reproduced or communicated without our written agreement.				A	—