CFD results report

Sample: 90° water bend · Job CF-SAMPLE · 19 Oct 2026

Important: this report is not binding

This report was generated automatically by software from the geometry and inputs you supplied. It is not binding: it carries no guarantee, warranty or certification and is not a professional engineering opinion or sign-off. Check the figures, then review and adapt the report for your use before you rely on it or share it with anyone, and have a qualified engineer verify critical values independently. Coreframe's liability is limited to the fee paid for this job. The full terms are at the end of this report.

Summary

We simulated steady water (liquid) flow through the pipe or fitting in your geometry (bend90.stl), with the inlet set to 4 m/s (a flow rate of 0.007832 m^3/s). The headline result is a static pressure drop of 5,294 Pa from inlet to outlet: the pressure the flow loses passing through the part. The calculation converged after 226 iterations, so the solution is numerically stable.

Convergence: CONVERGED

Judged against: residual targets p < 0.0001, other residuals < 0.001; stop when settled: ON (static pressure drop change < 0.5% over 200 iterations).

Converged at iteration 226: every residual met its target (p 0.0001, others 0.001).

Headline results

Static pressure drop (inlet – outlet)	5,294 Pa
Total pressure drop	5,294 Pa
Loss coefficient K (inlet velocity)	0.663
Flow rate	0.007832 m^3/s
Mean inlet velocity	4 m/s

SAMPLE
FRAME

Job and inputs

Application	Hydraulics / Pipe Network
Flow type	Internal flow through the uploaded fluid volume
Fluid	Water (liquid) (ρ = 998 kg/m³, ν = 1e-06 m²/s)
Turbulence model	k-ω SST
Analysis package	Standard
Iterations run / budget	226 / 1500
Geometry file	bend90.stl

Boundary conditions

In	Velocity Inlet: 4 m/s
Out	Pressure Outlet: 0 Pa

Assumptions

- Steady state (SIMPLE pressure-velocity algorithm).
- Incompressible, isothermal (no heat transfer), single-phase Newtonian fluid.
- RANS turbulence (k-ω SST); near-wall flow resolved to y+ ≈ 1 with prism layers; walls smooth, no-slip.
- Inlet speed 4 m/s over the inlet area 0.001958 m² = 0.007832 m³/s.
- Internal flow through the uploaded fluid volume: 1 inlet, 1 outlet(s) at the outlet pressure, no-slip walls; cell size 4.99 mm, 2.49 mm at the walls (hydraulic diameter 49.89 mm).

Mesh and convergence

Mesh


Cells	913,825
Wall layers	y+ ≈ 1 (resolved sublayer), 100 % of wall faces
Mesh quality checks	passed
Max non-orthogonality	54.87°
Max skewness	0.6225
Negative volumes	none


SAMPLE
FRAME

y+ on walls

Walls	min 0.2735 · avg 1.042 · max 2.326

y+ ≈ 1: the viscous sublayer is resolved (low-Re wall treatment). y+ ≈ 30–300: wall functions model it. In between, the Spalding wall function blends the two.






SAMPLE
FRAME

Mid-plane fields


Velocity magnitude



Velocity, close-up of the fastest region



Static pressure (relative to the outlet)




Pressure, close-up



SAMPLE
FRAME

Surfaces and streamlines

Surface pressure



Streamlines coloured by speed



SAMPLE
FRAME

Disclaimer and limitations

How it was made.

This report was generated automatically by software from the geometry and inputs you supplied. No engineer has reviewed it, and its accuracy depends entirely on those inputs.

Not binding.

Coreframe gives no guarantee, warranty or certification of any kind for these results. The report is not a professional engineering opinion and is not an engineering sign-off.

Your responsibility.

Before you rely on this report or share it with anyone, you must check the figures yourself and review and adapt the report for your use. Critical values must be verified independently by a qualified engineer, in particular wherever safety, compliance or warranty decisions depend on them.

Liability.

Coreframe's liability in connection with this job and this report is limited to the fee paid for the job.

Technical limits.

Results come from a steady, incompressible, isothermal RANS simulation of the geometry and conditions supplied; they depend on the accuracy of those inputs, the mesh and the turbulence model. Verify critical values independently before relying on them for safety, compliance or warranty decisions.

SAMPLE

FRAME