

Package ‘drimmR’

February 24, 2021

Type Package

Title Estimation, Simulation and Reliability of drifting Markov Models

Version 1.0.0

Author Vlad Stefan Barbu,
Geoffray Brelurut,
Annthomy Gilles,
Arnaud Lefebvre,
Victor Mataigne,
Alexandre Seiller,
Nicolas Vergne

Maintainer Nicolas Vergne <Nicolas.Vergne@univ-rouen.fr>

Description This package introduces the drifting Markov models (DMMs) which are non-homogeneous Markov models designed for modeling the heterogeneities of sequences in a more flexible way than homogeneous Markov chains or even hidden Markov models. In this context, we developed an R package dedicated to the estimation, simulation and reliability of drifting Markov models.

The implemented methods are described in

Vergne, N. (2008), <doi:10.2202/1544-6115.1326> and

Barbu, V.S., Vergne, N. (2019) <doi:10.1007/s11009-018-9682-8> .

License GPL

Encoding UTF-8

LazyData true

Suggests utils,
knitr,
rmarkdown

Imports seqinr,
Biostrings,
testthat,
stats,
ggplot2,
parallel,
foreach,
future,
doParallel,
doSNOW,
tidyverse,
dplyr,

reshape2,
Rdpack
RdMacros Rdpack
RoxygenNote 7.1.1
VignetteBuilder knitr
Depends R (>= 2.10)

R topics documented:

aic	2
aic.dmm	3
availability	4
bic	5
bic.dmm	6
distributions	7
dmm	8
failureRate	10
getDistribution	11
getDistribution.dmm	12
getStationaryLaw	13
getStationaryLaw.dmm	14
getTransitionMatrix	15
getTransitionMatrix.dmm	16
lambda	17
lengthWord_probabilities	17
loglik	18
loglik.dmm	19
maintainability	20
reliability	21
simulate	22
simulate.dmm	23
stationary_distributions	24
words_probabilities	25
word_probabilities	26
word_probability	27
Index	28

aic	<i>Akaike Information Criterion (AIC)</i>
-----	---

Description

Generic function computing the Akaike Information Criterion of the model x, with the list of sequences sequences.

Usage

aic(x, sequences)

Arguments

x	An object for which AIC of the DMM can be computed.
sequences	A vector of character or a list of vector of character representing the sequences for which the AIC criterion must be computed.

Value

A list of AIC (numeric)

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1) . doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

aic.dmm

Evaluate AIC

Description

Evaluate AIC

Usage

```
## S3 method for class 'dmm'
aic(x, sequences)
```

Arguments

x	An object of class dmm
sequences	A character vector or a list of character vector representing the sequence

Value

A list of AIC (numeric)

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getTransitionMatrix](#), [loglik](#), [aic](#)

Examples

```
data(lambda, package = "drimmR")
sequence <- c("a","g","g","t","c","g","a","t","a","a","a")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
aic(dmm,sequence)
```

availability

Availability function

Description

Pointwise (or instantaneous) availability of a system at time $l \in N$

Usage

```
availability(x, k1, k2, upstates, output_file = NULL, plot = FALSE)
```

Arguments

x	An object of class dmm
k1	Start position : a positive integer giving the start position along the sequence from which the availabilities of the DMM should be computed
k2	End position : a positive integer giving the end position along the sequence until which the availabilities of the DMM should be computed
upstates	Character vector of the subspace working states among the state space vector such that <code>upstates < s</code>
output_file	(Optional) A file containing matrix of availability probabilities (e.g. "C:/.../AVAL.txt")
plot	FALSE (no figure plot of availability by position); TRUE (figure plot)

Details

The pointwise (or instantaneous) availability is the probability that the system is in a working state at time l , independently of the fact that the system worked or not during the time interval $[0; l)$

Value

A matrix with positions and availability probabilities of states (and figure plot)

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>.

See Also

[dmm](#), [getTransitionMatrix](#), [reliability](#), [maintainability](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
k1 <- 1
k2 <- 200
upstates <- c("c","t") # vector of working states
availability(dmm,k1,k2,upstates,plot=TRUE)
```

bic

Bayesian Information Criterion (BIC)

Description

Generic function computing the Bayesian Information Criterion of the model *x*, with the list of sequences *sequences*.

Usage

```
bic(x, sequences)
```

Arguments

<i>x</i>	An object for which BIC of the DMM can be computed.
<i>sequences</i>	A vector or a list of vector of character representing the sequences for which the BIC criterion must be computed.

Value

A list of BIC (numeric)

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

bic.dmm

Evaluate BIC

Description

Evaluate BIC

Usage

```
## S3 method for class 'dmm'
bic(x, sequences)
```

Arguments

x	An object of class dmm
sequences	A character vector or a list of character vector representing the sequence

Value

A list of BIC (numeric)

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getTransitionMatrix](#), [loglik](#), [bic](#)

Examples

```
data(lambda, package = "drimmR")
sequence <- c("a","g","g","t","c","g","a","t","a","a","a")
dmm<-dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
bic(dmm,sequence)
```

distributions	<i>Plot distributions for a range of positions between <start> and <end></i>
---------------	--

Description

Plot distributions for a range of positions between <start> and <end>

Usage

```
distributions(  
  x,  
  start = 1,  
  end = NULL,  
  step = NULL,  
  output_file = NULL,  
  plot = FALSE  
)
```

Arguments

x	An object of class <code>dmm</code>
start	Start position : a positive integer giving the start position along the sequence from which the distributions of the DMM should be computed
end	End position : a positive integer giving the end position along the sequence until which the distributions of the DMM should be computed
step	A step (integer)
output_file	(Optional) A file containing matrix of distributions (e.g, "C:/.../DIST.txt")
plot	FALSE (no figure plot of dist evolution); TRUE (figure plot)

Value

A matrix with positions and distributions of states (and figure plot)

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getDistribution](#), [getStationaryLaw](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
distributions(dmm,start=1,end=1000,step=100, plot=TRUE)
```

dmm

Point by point estimates of a k-th order drifting Markov Model

Description

Estimation of $d+1$ points of support transition matrices and $|E|^k$ initial law of a k -th order drifting Markov Model starting from one or several sequences.

Usage

```
dmm(
  sequences,
  order,
  degree,
  states,
  init.estim = c("mle", "freq", "prod", "stationary", "unif"),
  fit.method = c("sum", "mean")
)
```

Arguments

sequences	A list of character vector(s) representing one (several) sequence(s)
order	Order of the Markov chain
degree	Degree of the polynomials (e.g., linear drifting if degree=1, etc.)
states	Vector of states space of length $s > 1$
init.estim	Default="mle". Method used to estimate the initial law. If <code>init.estim = "mle"</code> , then the classical Maximum Likelihood Estimator is used, if <code>init.estim = "freq"</code> , then, the initial distribution <code>init.estim</code> is estimated by taking the frequencies of the words of length k for all sequences. If <code>init.estim = "prod"</code> , then, <code>init.estim</code> is estimated by using the product of the frequencies of each letter (for all the sequences) in the word of length k . If <code>init.estim = "stationary"</code> , then <code>init.estim</code> is estimated by using the stationary law of the point of support transition matrices of each letter. If <code>init.estim = "unif"</code> , then, <code>init.estim</code> of each letter is estimated by using $\frac{1}{s}$. Or 'init.estim'= customisable vector of length $ E ^k$. See Details for the formulas.

Details

The `dmm` function creates a drifting Markov model object (`dmm`, `dmm`).

Let $E = 1, \dots, s$, $s < \infty$ be random system with finite state space, with a time evolution governed by discrete-time stochastic process of values in E . A sequence X_0, X_1, \dots, X_n with state space $E = 1, 2, \dots, s$ is said to be a linear drifting Markov chain (of order 1) of length n between the Markov transition matrices Π_0 and Π_1 if the distribution of X_t , $t = 1, \dots, n$, is defined by $P(X_t = v \mid X_{t-1} = u, X_{t-2}, \dots) = \Pi_{\frac{t}{n}}(u, v)$, $u, v \in E$, where $\Pi_{\frac{t}{n}}(u, v) = (1 - \frac{t}{n})\Pi_0(u, v) +$

$\frac{t}{n} \Pi_1(u, v)$, $u, v \in E$. The linear drifting Markov model of order 1 can be generalized to polynomial drifting Markov model of order k and degree d . Let $\Pi_{\frac{i}{d}} = (\Pi_{\frac{i}{d}}(u_1, \dots, u_k, v))_{u_1, \dots, u_k, v \in E}$ be d Markov transition matrices (of order k) over a state space E .

The initial distribution of a k -th order drifting Markov Model is defined as $\mu_i = P(X_1 = i)$. The initial distribution of the k first letters is freely be customisable by the user, but five methods are proposed for the estimation of the latter :

Estimation based on the Maximum Likelihood Estimator: The Maximum Likelihood Estimator for the initial distribution. The formula is: $\hat{\mu}_i = \frac{Nstart_i}{L}$, where $Nstart_i$ is the number of occurrences of the word i (of length k) at the beginning of each sequence and L is the number of sequences. This estimator is reliable when the number of sequences L is high.

Estimation based on the frequency: The initial distribution is estimated by taking the frequencies of the words of length k for all sequences. The formula is $\hat{\mu}_i = \frac{N_i}{N}$, where N_i is the number of occurrences of the word i (of length k) in the sequences and N is the sum of the lengths of the sequences.

Estimation based on the product of the frequencies of each state: The initial distribution is estimated by using the product of the frequencies of each state (for all the sequences) in the word of length k .

Estimation based on the stationary law of point of support transition matrix for a word of length k :
The initial distribution is estimated using $\mu(\Pi_{\frac{k-1}{n}})$

Estimation based on the uniform law : $\frac{1}{s}$

Value

An object of class `dmm`

Author(s)

Geoffray Brelurut, Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/1544-6115.1326](https://doi.org/10.2202/1544-6115.1326), <https://doi.org/10.2202/1544-6115.1326>.

Examples

```
data(lambda, package = "drimmR")
states <- c("a", "c", "g", "t")
order <- 1
degree <- 1
dmm(lambda, order, degree, states, init.estim = "freq", fit.method = "sum")
```

failureRate	<i>Failure rates function</i>
-------------	-------------------------------

Description

Estimation of two different definition of the failure rate : the BMP-failure rate and RG-failure rate.

As for BMP-failure rate, consider a system S starting to work at time $l = 0$. The BMP-failure rate at time $l \in N$ is the conditional probability that the failure of the system occurs at time l , given that the system has worked until time $l - 1$.

The RG-failure rate is a discrete-time adapted failure-rate proposed by D. Roy and R. Gupta. Classification of discrete lives. *Microelectronics Reliability*, 32(10):1459–1473, 1992.

Usage

```
failureRate(
  x,
  k1,
  k2,
  upstates,
  failure.rate = c("BMP", "RG"),
  output_file = NULL,
  plot = FALSE
)
```

Arguments

<code>x</code>	An object of class <code>dmm</code>
<code>k1</code>	Start position : a positive integer giving the start position along the sequence from which the failure rates of the DMM should be computed
<code>k2</code>	End position : a positive integer giving the end position along the sequence until which the failure rates of the DMM should be computed
<code>upstates</code>	Character vector of the subspace working states among the state space vector such that <code>upstates < s</code>
<code>output_file</code>	(Optional) A file containing matrix of failure rates at each position (e.g, "C:/.../ER.txt")
<code>plot</code>	FALSE (no figure plot of failure rates by position); TRUE (figure plot)
<code>failure.rate</code>	Default="BMP", then BMP-failure-rate is the method used to estimate the failure rate. If <code>failure.rate= "RG"</code> , then RG-failure rate is the method used to estimate the failure rate.

Details

The BMP-failure rate denoted by $\lambda(l)$, $l \in N$ is usually considered for continuous time systems.

The RG-failure rate denoted by $r(l)$, $l \in N$ is adapted to work in discrete time systems.

Value

A matrix with positions and failure rate scores of states (and figure plot)

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Roy D, Gupta R (1992). “Classification of discrete lives. Microelectronics Reliability.” *Microelectronics Reliability*, 1459–1473. doi: [10.1016/00262714\(92\)90015D](https://doi.org/10.1016/00262714(92)90015D), [https://doi.org/10.1016/0026-2714\(92\)90015-D](https://doi.org/10.1016/0026-2714(92)90015-D).

See Also[dmm](#), [getTransitionMatrix](#), [reliability](#)**Examples**

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
k1 <- 1
k2 <- 200
upstates <- c("c","t") # vector of working states
failureRate(dmm,k1,k2,upstates,failure.rate="BMP",plot=TRUE)
```

getDistribution

*Get the distributions of the DMM***Description**

Generic function evaluating the distribution of a model x at a given position code or at every position `all.pos`

Usage

```
getDistribution(x, pos, all.pos = FALSE, internal = FALSE)
```

Arguments

<code>x</code>	An object for which the distributions of the DMM can be computed.
<code>pos</code>	A positive integer giving the position along the sequence on which the distribution of the DMM should be computed
<code>all.pos</code>	‘FALSE’ (evaluation at position index) ; ‘TRUE’ (evaluation for all position indices)
<code>internal</code>	‘FALSE’ (default) ; ‘TRUE’ (for internal use of the distributions function)

Details

Distribution at position l is evaluated by $\mu_l = \mu_0 \prod_{t=k}^l \pi_{\frac{t}{n}}, \forall l \geq k, k \in N^*$ order of the DMM

Value

A vector or matrix of distribution probabilities

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/1544-6115.1326](https://doi.org/10.2202/1544-6115.1326), <https://doi.org/10.2202/1544-6115.1326>.

getDistribution.dmm *Get the distributions of the DMM*

Description

Evaluate the distribution of the DMM at a given position or at every position

Usage

```
## S3 method for class 'dmm'
getDistribution(x, pos, all.pos = FALSE, internal = FALSE)
```

Arguments

x	An object of class <code>dmm</code>
pos	A positive integer giving the position along the sequence on which the distribution of the DMM should be computed
all.pos	‘FALSE’ (default, evaluation at position index) ; ‘TRUE’ (evaluation for all position indices)
internal	‘FALSE’ (default) ; ‘TRUE’ (for internal use of <code>distributions</code> function)

Details

Distribution at position l is evaluated by $\mu_l = \mu_0 \prod_{t=k}^l \pi_{\frac{t}{n}}, \forall l \geq k, k \in N^*$ order of the DMM

Value

A vector or matrix of distribution probabilities

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getTransitionMatrix](#), [distributions](#), [getStationaryLaw](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
t <- 10
getDistribution(dmm,pos=t)
```

getStationaryLaw

Get the stationary laws of the DMM

Description

Generic function evaluating the stationary law of a model `x` at a given position `pos` or at every position `all.pos`

Usage

```
getStationaryLaw(x, pos, all.pos = FALSE, internal = FALSE)
```

Arguments

<code>x</code>	An object for which the stationary laws of the DMM can be computed.
<code>pos</code>	A positive integer giving the position along the sequence on which the stationary law of the DMM should be computed
<code>all.pos</code>	‘FALSE’ (default, evaluation at position index) ; ‘TRUE’ (evaluation for all position indices)
<code>internal</code>	‘FALSE’ (default) ; ‘TRUE’ (for internal use of the initial law computation)

Details

Stationary law at position t is evaluated by solving $\mu_t \pi_{\frac{t}{n}} = \mu$

Value

A vector or matrix of stationary law probabilities

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

getStationaryLaw.dmm *Get the stationary laws of the DMM*

Description

Evaluate the stationary law of the DMM at a given position or at every position

Usage

```
## S3 method for class 'dmm'
getStationaryLaw(x, pos, all.pos = FALSE, internal = FALSE)
```

Arguments

x	An object of class <code>dmm</code>
pos	A positive integer giving the position along the sequence on which the stationary law of the DMM should be computed
all.pos	‘FALSE’ (default, evaluation at position index) ; ‘TRUE’ (evaluation for all position indices)
internal	‘FALSE’ (default) ; ‘TRUE’ (for internal use of the initial law of <code>dmm</code> and word applications)

Details

Stationary law at position t is evaluated by solving $\mu_t \pi_{\frac{t}{n}} = \mu$

Value

A vector or matrix of stationary law probabilities

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getTransitionMatrix](#), [stationary_distributions](#), [getDistribution](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
t <- 10
getStationaryLaw(dmm,pos=t)
```

getTransitionMatrix	<i>Get transition matrix of the drifting Markov Model</i>
---------------------	---

Description

Generic function evaluating the transition matrix of a model `x` at a given position `pos`

Usage

```
getTransitionMatrix(x, pos)
```

Arguments

<code>x</code>	An object for which the transition matrices of the DMM can be computed.
<code>pos</code>	A positive integer giving the position along the sequence on which the transition matrix of the DMM should be computed

Value

A transition matrix at a given position

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1) . doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

`getTransitionMatrix.dmm`*Get transition matrix of the drifting Markov Model*

Description

Evaluate the transition matrix of the DMM at a given position

Usage

```
## S3 method for class 'dmm'  
getTransitionMatrix(x, pos)
```

Arguments

x	An object of class <code>dmm</code>
pos	A positive integer giving the position along the sequence on which the transition matrix of the DMM should be computed

Value

A transition matrix at a given position

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/1544-6115.1326](https://doi.org/10.2202/1544-6115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

`dmm`

Examples

```
data(lambda, package = "drimmR")  
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'),init.estim = "freq", fit.method="sum")  
t <- 10  
getTransitionMatrix(dmm,pos=t)
```

lambda	<i>lambda genome</i>
--------	----------------------

Description

Complete data from phage genome [WT71] of length 48502

Usage

```
data(lambda)
```

Format

A vector object of class "Rdata".

Examples

```
data(lambda)
```

lengthWord_probabilities

Probability of occurrence of the observed word of size n in a sequence at several positions

Description

Probability of occurrence of the observed word of size n in a sequence at several positions

Usage

```
lengthWord_probabilities(m, sequence, pos, x, output_file = NULL, plot = FALSE)
```

Arguments

m	An integer, the length word
sequence	A vector of characters
pos	A vector of integer positions
x	An object of class dmm
output_file	(Optional) A file containing the vector of probabilities (e.g, "C:/.../PROB.txt")
plot	FALSE (no figure plot of words probabilities); TRUE (figure plot)

Value

A dataframe of probability by position (and probability plots)

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getTransitionMatrix](#), [word_probability](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq")
m <- 2
lengthWord_probabilities(m, lambda, c(1,length(lambda)-m+1), dmm,plot=TRUE, fit.method="sum")
```

loglik

Loglikelihood S3

Description

Generic function computing the loglikelihood of the model x, with the list of sequences sequences.

Usage

```
loglik(x, sequences)
```

Arguments

x	An object for which the loglikelihood of the DMM can be computed.
sequences	A vector of character or list of vectors representing the sequences for which the log-likelihood of the model must be computed.

Value

A list of log-likelihood (numeric)

Author(s)

Annthomy Gilles, Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

loglik.dmm

*Evaluate Log-likelihood***Description**

Evaluate Log-likelihood

Usage

```
## S3 method for class 'dmm'
loglik(x, sequences)
```

Arguments

x	An object of class dmm
sequences	A character vector or a list of character vectors representing the sequence

Value

A list of log-likelihood (numeric)

Author(s)

Annthomy Gilles, Alexandre Seiller

References

Barbu VS, Vergne N (2018). “Reliability and survival analysis for drifting Markov models: modelling and estimation.” *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8). Vergne N (2008). “Drifting Markov models with polynomial drift and applications to DNA sequences.” *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/1544-6115.1326](https://doi.org/10.2202/1544-6115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also[dmm](#), [getTransitionMatrix](#)**Examples**

```
data(lambda, package = "drimmR")
sequence <- c("a","g","g","t","c","g","a","t","a","a","a")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
loglik(dmm, sequence)
```

maintainability	<i>Maintainability function</i>
-----------------	---------------------------------

Description

Maintainability of a system at time $k \in N$.

Usage

```
maintainability(x, k1, k2, upstates, output_file = NULL, plot = FALSE)
```

Arguments

x	An object of class <code>dmm</code>
k1	Start position : a positive integer giving the start position along the sequence from which the maintainabilities of the DMM should be computed
k2	End position : a positive integer giving the end position along the sequence until which the maintainabilities of the DMM should be computed
upstates	Character vector of the subspace working states among the state space vector such that $\text{upstates} < s$
output_file	(Optional) A file containing matrix of maintainability probabilities (e.g. "C:/.../MAIN.txt")
plot	FALSE (no figure plot of maintainability by position); TRUE (figure plot)

Details

The maintainability at time $k \in N$ of a system is the probability that the system is repaired up to time l , given that it has failed at time $l = 0$.

Value

A matrix with positions and maintainability probabilities of states (and figure plot)

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>.

See Also

`dmm`, `getTransitionMatrix`

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
k1 <- 1
k2 <- 200
upstates <- c("c","t") # vector of working states
maintainability(dmm,k1,k2,upstates,plot=TRUE)
```

reliability	<i>Reliability function</i>
-------------	-----------------------------

Description

Reliability or the survival function of a system at time $l \in N$

Usage

```
reliability(x, k1, k2, upstates, output_file = NULL, plot = FALSE)
```

Arguments

x	An object of class <code>dmm</code>
k1	Start position : a positive integer giving the start position along the sequence from which the reliabilities of the DMM should be computed
k2	End position : a positive integer giving the end position along the sequence until which the reliabilities of the DMM should be computed
upstates	Character vector of the subspace working states among the state space vector such that <code>upstates < s</code>
output_file	(Optional) A file containing matrix of reliability probabilities (e.g, "C:/.../REL.txt")
plot	FALSE (no figure plot of reliability by position); TRUE (figure plot)

Details

The reliability at time $l \in N$ is the probability that the system has functioned without failure in the period $[0, l]$

Value

A matrix with positions and reliability probabilities of states (and figure plot)

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>.

See Also

[dmm](#), [getTransitionMatrix](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
k1 <- 1
k2 <- 200
upstates <- c("c","t") # vector of working states
reliability(dmm,k1,k2,upstates,plot=TRUE)
```

simulate	<i>Simulate a sequence under a drifting Markov model</i>
----------	--

Description

Generic function simulating a sequence of length `model_size` under a model `x`

Usage

```
simulate(x, output_file, model_size = 1e+05)
```

Arguments

<code>x</code>	An object for which simulated sequences of the DMM can be computed.
<code>output_file</code>	(Optional) File containing the simulated sequence (e.g, "C:/.../SIM.txt")
<code>model_size</code>	Size of the model

Value

the vector of simulated sequence

Author(s)

Annthomy Gilles, Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1) . doi: [10.2202/1544-6115.1326](https://doi.org/10.2202/1544-6115.1326), <https://doi.org/10.2202/1544-6115.1326>.

simulate.dmm	<i>Simulate a sequence under a drifting Markov model</i>
--------------	--

Description

Simulate a sequence under a k-th order DMM.

Usage

```
## S3 method for class 'dmm'
simulate(x, output_file = NULL, model_size = NULL)
```

Arguments

x	An object of class <code>dmm</code>
output_file	(Optional) File containing the simulated sequence (e.g, "C:/.../SIM.txt")
model_size	Size of the model

Value

the vector of simulated sequence

Author(s)

Annthomy Gilles, Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/1544-6115.1326](https://doi.org/10.2202/1544-6115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

`dmm`, `getTransitionMatrix`, `getStationaryLaw`

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
simulate(dmm, model_size=100)
```

stationary_distributions

Plot stationary laws for a range of positions between <start> and <end>

Description

Plot stationary laws for a range of positions between <start> and <end>

Usage

```
stationary_distributions(
  x,
  start = 1,
  end = NULL,
  step = NULL,
  output_file = NULL,
  plot = FALSE
)
```

Arguments

x	An object of class <code>dmm</code>
start	Start position : a positive integer giving the start position along the sequence from which the stationary laws of the DMM should be computed
end	End position : a positive integer giving the end position along the sequence until which the stationary laws of the DMM should be computed
step	A step (integer)
output_file	(Optional) A file containing matrix of stationary laws (e.g, "C:/.../SL.txt")
plot	FALSE (no figure plot of SL evolution); TRUE (figure plot)

Value

A matrix with positions and stationary laws of states (and figure plot)

Author(s)

Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s1100901896828](https://doi.org/10.1007/s1100901896828), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1) . doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

`dmm`, `getStationaryLaw`

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
stationary_distributions(dmm,start=1,end=1000,step=100, plot=TRUE)
```

words_probabilities	<i>Probability of appearance of dmmseveral words at several positions of a DMM</i>
---------------------	--

Description

Probability of appearance of dmmseveral words at several positions of a DMM

Usage

```
words_probabilities(words, pos, x, output_file = NULL, plot = FALSE)
```

Arguments

words	A vector of characters containing words
pos	A vector of integer positions
x	An object of class <code>dmm</code>
output_file	(Optional) A file containing the matrix of probabilities (e.g,"C:/.../PROB.txt")
plot	FALSE (no figure plot of words probabilities); TRUE (figure plot)

Value

A dataframe of word probabilities along the positions of the sequence

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/15446115.1326](https://doi.org/10.2202/15446115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getTransitionMatrix](#), [word_probability](#), [word_probabilities](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
words_probabilities(c("atcgattc", "taggct", "ggatcgg"),c(100,300),dmm, plot=TRUE)
```

word_probabilities	<i>Probabilities of a word at several positions of a DMM</i>
--------------------	--

Description

Probabilities of a word at several positions of a DMM

Usage

```
word_probabilities(word, pos, x, output_file = NULL, plot = FALSE)
```

Arguments

word	A subsequence (string of characters)
pos	A vector of integer positions
x	An object of class <code>dmm</code>
output_file	(Optional) A file containing the vector of probabilities (e.g, "C:/.../PROB.txt")
plot	FALSE (no figure plot of word probabilities); TRUE (figure plot)

Value

A numeric vector, probabilities of word

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1) . doi: [10.2202/1544-6115.1326](https://doi.org/10.2202/1544-6115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getTransitionMatrix](#), [word_probability](#), [words_probabilities](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
word_probabilities("aggctga",c(100,300),dmm, plot=TRUE)
```

word_probability	<i>Probability of a word at a position t of a DMM</i>
------------------	---

Description

Probability of a word at a position t of a DMM

Usage

```
word_probability(word, pos, x, output_file = NULL, internal = FALSE)
```

Arguments

word	A subsequence (string of characters)
pos	A position (numeric)
x	An object of class dmm
output_file	(Optional) A file containing the probability (e.g, "C:/.../PROB.txt")
internal	FALSE (default) ; TRUE (for internal use of word applications)

Value

A numeric, probability of word

Author(s)

Victor Mataigne, Alexandre Seiller

References

Barbu VS, Vergne N (2018). "Reliability and survival analysis for drifting Markov models: modelling and estimation." *Methodology and Computing in Applied Probability*, 1–33. doi: [10.1007/s11009-018-9682-8](https://doi.org/10.1007/s11009-018-9682-8), <https://doi.org/10.1007/s11009-018-9682-8>. Vergne N (2008). "Drifting Markov models with polynomial drift and applications to DNA sequences." *Statistical Applications in Genetics Molecular Biology*, **7**(1). doi: [10.2202/1544-6115.1326](https://doi.org/10.2202/1544-6115.1326), <https://doi.org/10.2202/1544-6115.1326>.

See Also

[dmm](#), [getTransitionMatrix](#), [word_probabilities](#), [words_probabilities](#)

Examples

```
data(lambda, package = "drimmR")
dmm <- dmm(lambda, 1, 1, c('a','c','g','t'), init.estim = "freq", fit.method="sum")
word_probability("aggctga", 4, dmm)
```

Index

* datasets

lambda, 17

aic, 2, 4

aic.dmm, 3

availability, 4

bic, 5, 6

bic.dmm, 6

distributions, 7, 11–13

dmm, 3–8, 8, 9–27

failureRate, 10

getDistribution, 7, 11, 15

getDistribution.dmm, 12

getStationaryLaw, 7, 13, 13, 23, 24

getStationaryLaw.dmm, 14

getTransitionMatrix, 4–6, 11, 13, 15, 15,
18–20, 22, 23, 25–27

getTransitionMatrix.dmm, 16

lambda, 17

lengthWord_probabilities, 17

loglik, 4, 6, 18

loglik.dmm, 19

maintainability, 5, 20

reliability, 5, 11, 21

simulate, 22

simulate.dmm, 23

stationary_distributions, 15, 24

word_probabilities, 25, 26, 27

word_probability, 18, 25, 26, 27

words_probabilities, 25, 26, 27