GOOGLE APPS SCRIPT · SETUP GUIDE

Interview Assessment Form → Sheet

A Google Apps Script web app that recreates the interview assessment form for the MM & IMBA admission process, saves every submission to a Google Sheet, and auto-computes section scores, total score and predikat.

PACKAGE

Code.gs · Index.html · Setup-Guide.pdf

NOVEMBER 2026

1. What You Received

This package contains a complete, ready-to-deploy Google Apps Script web app that recreates the interview assessment form used for the Magister Manajemen (MM) and International MBA (IMBA) admission process. The form keeps the exact question set visible in the reference form: the rating grids for Bisnis and Manajemen, KOMUNIKASI and KOMITMEN, plus the Potensi IMBA, Pilihan Bidang Minat and HASIL WAWANCARA questions. Every submission is written to a Google Sheet automatically, together with a timestamp and computed scores.

File	What it is
Code.gs	Apps Script server code: serves the form, validates the data, appends each response to the Google Sheet and computes the scores.
Index.html	The form user interface (Google Forms style, Indonesian labels, mobile-friendly). Also works standalone for preview purposes.
Setup-Guide.pdf	This document: deployment steps, sheet layout, scoring rules and troubleshooting.
preview-desktop.png / preview-mobile.png	Rendered previews of the form so you can see the design before deploying.

Table 1. Package contents

> **No server, no hosting, no cost.** Everything runs inside your Google account: the form is served by Apps Script and the data lands in your own Google Sheet.

2. How It Works

The system has three parts that live in different places, and understanding the flow makes troubleshooting much easier. The browser displays the form defined by Index.html. When the interviewer presses Submit, the page collects all answers into one payload object and calls the server function simpanData() through the google.script.run bridge, which is Apps Script's built-in remote procedure mechanism. On the server side, Code.gs validates the required fields again (never trust the client alone), computes the scores from the rating labels, and appends one row to the Responses tab of the spreadsheet.

Four implementation details are worth knowing. First, validation runs twice: instantly in the browser (red cards with the message "Pertanyaan ini wajib diisi") and again inside simpanData(), which rejects incomplete submissions even if someone bypasses the page. Second, LockService serializes concurrent writes so two interviewers submitting at the same moment cannot corrupt the sheet. Third, the Responses tab and its formatted header row are created automatically on the first run, so there is nothing to set up by hand in the sheet. Fourth, the grid answers are stored as their full labels, for example "Baik (3)", and the numeric

value used for scoring is parsed from the label on the server.

3. Deployment: Step by Step

The whole deployment takes about ten minutes and only needs a browser. Follow the steps below in order; the authorization step in Step 5 is mandatory and is also what creates the Responses tab in your sheet.

Step 1. Open the Google Sheet that will store the responses, or create a new one at `sheets.new`. Give it a clear name such as “Penilaian Wawancara MM-IMBA”.

Step 2. In the sheet, open the menu **Extensions > Apps Script**. This creates a script bound to the spreadsheet, which is the easiest setup because the script then knows which sheet to write to.

Step 3. In the editor, replace the whole content of the default `Code.gs` with the content of the `Code.gs` file from this package, then save (Ctrl+S).

Step 4. Add the interface file: click **File > + > HTML**, name it exactly `Index` (Apps Script strips the .html extension itself), paste the content of Index.html and save.

Step 5. Run `testSimpan` once from the toolbar: select it in the function dropdown and press **Run**. Approve the authorization prompts. This writes one clearly-marked TEST row and creates the Responses tab with formatted headers. You can delete that row afterwards.

Step 6. Click **Deploy > New deployment > Web app** and use the settings from Table 2, then press **Deploy** and copy the Web app URL.

Step 7. Open the URL, fill the form once as a real test and check that the row appears in the Responses tab with correct scores.

Step 8. Share the URL with your interviewers. Each submission appends one row; the sheet is your single source of truth.

Deployment setting	Value	Why
Type	Web app	Serves the HTML form at a public URL.
Execute as	Me	Responses are written by your account, so interviewers need no access to the sheet itself.
Who has access	Anyone (or Anyone within your organization)	Lets interviewers open the form without signing in.

Table 2. Required “New deployment” settings

> **First-time authorization:** Google shows “Google hasn’t verified this app”. This is normal for your own script. Press **Advanced > Go to project (unsafe)** and allow the requested Spreadsheet permissions.

4. What Gets Saved to the Sheet

Responses are appended to a tab named **Responses**. The tab and its header row are created automatically the first time the script runs, so do not rename the tab unless you also change SHEET_NAME in Code.gs. There are twenty columns: four identity fields, eleven answer fields, and five computed columns. The computed columns arrive filled in, so the sheet can be filtered and sorted immediately without building your own formulas.

Col	Header	Content
A	Timestamp	Server date and time of the submission.
B–D	Nama Kandidat, Nama Interviewer, Tanggal Wawancara	Identity block filled by the interviewer.
E–F	C1–C2 Bisnis & Manajemen rows	Rating label, e.g. “Baik Sekali (4)”.
G–I	D1–D3 KOMUNIKASI rows	Rating label.
J–K	E1–E2 KOMITMEN rows	Rating label.
L–N	Potensi IMBA, Pilihan Bidang Minat, Hasil Wawancara	Selected option text (YA / TIDAK, Finance, Highly Recommended (HR), ...).
O	Catatan Tambahan	Free-text notes; may be empty.
P–S	Skor C, Skor D, Skor E, Total Skor	Numeric subtotals and total, computed by the script.
T	Predikat	Score band label, see Section 5.

Table 3. Responses tab layout (20 columns)

5. Scoring and Predikat

Every row of the three rating grids uses the same four-point scale: Baik Sekali (4), Baik (3), Cukup (2) and Kurang (1). The script reads the number inside the label, sums the rows of each section, and adds the three subtotals into a total score. Because there are seven rated rows in total, the maximum is 28 points. The predikat in column T is a simple banding of the total, as defined in Code.gs.

Section	Rows	Max score
C. Bisnis & Manajemen	2	8
D. Komunikasi	3	12
E. Komitmen	2	8
Total	**7**	**28**

Table 4. Score structure

Total score	Predikat
24–28	Sangat Baik
18–23	Baik
12–17	Cukup
Below 12	Kurang

Table 5. Predikat bands (editable in predikat_() in Code.gs)

> **Worked example:** a candidate rated 4, 3 in section C, 3, 4, 2 in section D and 3, 4 in section E scores Skor C = 7, Skor D = 9, Skor E = 7, Total = 23, Predikat = Baik. The confirmation screen shows the same numbers after submitting.

6. Editing the Form Questions

The question set lives in two files and the two must stay in sync. In Index.html, the three rating grids are generated from the SECTIONS configuration near the top of the script block: you can rename a section title, edit a row text, or add and remove rows there. The single-choice options (IMBA, Bidang Minat, Hasil Wawancara) are plain HTML radio inputs that you can edit directly. In Code.gs, the HEADERS array must mirror the questions in the same order, because it defines the sheet columns; GRID_IDS lists the seven grid row IDs.

When adding a grid row, follow this checklist. Give the row a new unique id (for example c3) inside SECTIONS. Add that id to GRID_IDS in Code.gs. Add a matching header string to HEADERS in the right position. Save both files. If you only edit labels or option texts, nothing else is needed. After any code change, use **Deploy > Manage deployments > Edit > New version** so the public URL serves the updated code; editing files alone does not update an existing deployment.

7. Troubleshooting

The table below covers the issues that account for nearly all support questions on first deployment. Read the error message carefully: failures raised by the server validation are shown in the red banner inside the form, while infrastructure problems usually appear as a full-page Apps Script error.

Symptom	Cause	Fix
“Google hasn’t verified this app” screen	First authorization of your own script.	Advanced > Go to project (unsafe) > Allow.
“Script function not found: doGet”	Code.gs content was not saved, or the file is empty.	Paste Code.gs again, press Ctrl+S, reload the web app URL.
Form opens but submissions never appear	Standalone script without SPREADSHEET_ID, or authorization not granted.	Run testSimpan once and authorize; or paste the Sheet ID into SPREADSHEET_ID.
Red banner “Kolom wajib diisi” or “Masih ada pertanyaan penilaian”	A required field or a grid row was left empty.	Complete every required question; unanswered cards are outlined in red.
Edited the form, but the URL still shows the old version	Deployments are versioned snapshots.	Deploy > Manage deployments > Edit > Version: New version > Deploy.
Header row duplicated or shifted after editing HEADERS	The Responses tab already existed with the old headers.	Delete the Responses tab and run testSimpan again to regenerate it.

Table 6. Common issues and fixes

For anything else, open **Executions** in the Apps Script editor: every form submission is logged there with its error message and timestamp, which is usually enough to pinpoint the cause quickly.