

Learn C#: Logic and Conditionals

Boolean Expressions

A *boolean expression* is any expression that evaluates to, or returns, a boolean value.

```
// These expressions all evaluate to a
boolean value.

// Therefore their values can be stored
in boolean variables.

bool a = (2 > 1);
bool b = a && true;
bool c = !false || (7 < 8);
```

Boolean Type

The `bool` data type can be either `true` or `false` and is based on the concept that the validity of all logical statements must be either true or false.

Booleans encode the science of logic into computers, allowing for logical reasoning in programs. In a broad sense, the computer can encode the truthfulness or falseness of certain statements, and based on that information, completely alter the behavior of the program.

```
bool skyIsBlue = true;
bool penguinsCanFly = false;
Console.WriteLine($"True or false, is the
sky blue? {skyIsBlue}.");

// This simple program illustrates how
booleans are declared. However, the real
power of booleans requires additional
programming constructs such as
conditionals.
```

Logical Operators

Logical operators receive boolean expressions as input and return a boolean value.

The `&&` operator takes two boolean expressions and returns `true` only if they both evaluate to `true`.

The `||` operator takes two boolean expressions and returns `true` if either one evaluates to `true`.

The `!` operator takes one boolean expression and returns the opposite value.

```
// These variables equal true.

bool a = true && true;
bool b = false || true;
bool c = !false;

// These variables equal false.

bool d = true && false;
bool e = false || false;
bool f = !true;
```

Comparison Operators

A *comparison operator*, as the name implies, compares two expressions and returns either `true` or `false` depending on the result of the comparison. For example, if we compared two `int` values, we could test

```
int x = 5;
Console.WriteLine(x < 6); // Prints
"True" because 5 is less than 6.
```

to see if one number is greater than the other, or if both numbers are equal. Similarly, we can test one `string` for equality against another `string`.

```
Console.WriteLine(x > 8); // codecademy
"False" because 5 is not greater than 8.
```

```
string foo = "foo";
Console.WriteLine(foo == "bar"); //
Prints "False" because "foo" does not
equal "bar".
```

Truth Tables

A *truth table* is a way to visualize boolean logic. Since booleans only have two possible values, that means that we can compactly list out in a table all the possible input and output pairs for unary and binary boolean operators.

The image below gives the *truth tables* for the *AND*, *OR*, and *NOT* operators. For each row, the last column represents the output given that the other columns were fed as input to the corresponding operator.

Boolean Operators								
AND			OR			NOT		
A	B	A AND B	A	B	A OR B	A	NOT A	
True	True	True	True	True	True	True	False	
True	False	False	True	False	True	False	True	
False	True	False	False	True	True			
False	False	False	False	False	False			

Conditional Control

Conditional statements or *conditional control* structures allow a program to have different behaviors depending on certain *conditions* being met.

Intuitively, this mimics the way humans make simple decisions and act upon them. For example, reasoning about whether to go outside might look like:

- Condition: *Is it raining outside?*
 - If it is raining outside, then *bring an umbrella*.
 - Otherwise, *do not bring an umbrella*.

We could keep adding clauses to make our reasoning more sophisticated, such as “If it is sunny, then wear sunscreen”.

Control Flow

In programming, *control flow* is the order in which statements and instructions are executed.

Programmers are able to change a program’s *control flow* using *control structures* such as conditionals.

Being able to alter a program’s *control flow* is powerful, as it lets us adapt a running program’s behavior depending on the state of the program. For example, suppose a user is using a banking application and wants to withdraw \$500. We certainly want the application to

behave differently depending on whether the user has \$20 or \$1000 in their bank account!

If Statements

In C#, an *if statement* executes a block of code based on whether or not the *boolean expression* provided in the parentheses is `true` or `false`.

If the expression is `true` then the block of code inside the braces, `{}`, is executed. Otherwise, the block is skipped over.

```
if (true) {  
    // This code is executed.  
    Console.WriteLine("Hello User!");  
}  
  
if (false) {  
    // This code is skipped.  
    Console.WriteLine("This won't be seen :  
    (");  
}
```

Break Keyword

One of the uses of the `break` keyword in C# is to exit out of `switch / case` blocks and resume program execution after the `switch` code block. In C#, each `case` code block inside a `switch` statement needs to be exited with the `break` keyword (or some other jump statement), otherwise the program will not compile. It should be called once all of the instructions specific to that particular `case` have been executed.

```
string color = "blue";  
  
switch (color) {  
    case "red":  
        Console.WriteLine("I don't like that  
color.");  
        break;  
    case "blue":  
        Console.WriteLine("I like that  
color.");  
        break;  
    default:  
        Console.WriteLine("I feel ambivalent  
about that color.");  
        break;  
}  
  
// Regardless of where the break  
statement is in the above switch  
statement,  
// breaking will resume the program  
execution here.  
Console.WriteLine("- Steve");
```

Ternary Operator

In C#, the *ternary operator* is a special syntax of the form: `condition ? expression1 : expression2` . It takes one boolean condition and two expressions as inputs. Unlike an `if` statement, the *ternary operator* is an expression itself. It evaluates to either its first input expression or its second input expression depending on whether the condition is `true` or `false` , respectively.

Else Clause

An `else` followed by braces, `{}` , containing a code block, is called an `else clause`. `else` clauses must always be preceded by an `if` statement. The block inside the braces will only run if the expression in the accompanying `if` condition is `false` . It is useful for writing code that runs *only if* the code inside the `if` statement is not executed.

If and Else If

A common pattern when writing multiple `if` and `else` statements is to have an `else` block that contains another nested `if` statement, which can contain another `else` , etc. A better way to express this pattern in C# is with `else if` statements. The first condition that evaluates to `true` will run its associated code block. If none are `true` , then the optional `else` block will run if it exists.

```
bool isRaining = true;
// This sets umbrellaOrNot to "Umbrella"
if isRaining is true,
// and "No Umbrella" if isRaining is
false.
string umbrellaOrNot = isRaining ?
"Umbrella" : "No Umbrella";

// "Umbrella"
Console.WriteLine(umbrellaOrNot);
```

```
if (true) {
    // This block will run.
    Console.WriteLine("Seen!");
} else {
    // This will not run.
    Console.WriteLine("Not seen!");
}

if (false) {
    // Conversely, this will not run.
    Console.WriteLine("Not seen!");
} else {
    // Instead, this will run.
    Console.WriteLine("Seen!");
}
```

```
int x = 100, y = 80;

if (x > y)
{
    Console.WriteLine("x is greater than
y");
}
else if (x < y)
{
    Console.WriteLine("x is less than y");
}
else
{
}
```

```
Console.WriteLine("x is equal to y");  
}
```

Switch Statements

A `switch` statement is a control flow structure that evaluates one expression and decides which code block to run by trying to match the result of the expression to each `case`. In general, a code block is executed when the value given for a `case` equals the evaluated expression, i.e, when `==` between the two values returns `true`. `switch` statements are often used to replace `if else` structures when all conditions test for equality on one value.

```
// The expression to match goes in  
parentheses.  
switch (fruit) {  
    case "Banana":  
        // If fruit == "Banana", this block  
        will run.  
        Console.WriteLine("Peel first.");  
        break;  
    case "Durian":  
        Console.WriteLine("Strong smell.");  
        break;  
    default:  
        // The default block will catch  
        expressions that did not match any above.  
        Console.WriteLine("Nothing to say.");  
        break;  
}  
  
// The switch statement above is  
equivalent to this:  
if (fruit == "Banana") {  
    Console.WriteLine("Peel first.");  
} else if (fruit == "Durian") {  
    Console.WriteLine("Strong smell.");  
} else {  
    Console.WriteLine("Nothing to say.");  
}
```