

# Package ‘RMySQL’

December 14, 2021

**Version** 0.10.23

**Title** Database Interface and 'MySQL' Driver for R

**Description** Legacy 'DBI' interface to 'MySQL' / 'MariaDB' based on old code ported from S-PLUS. A modern 'MySQL' client based on 'Rcpp' is available from the 'RMariaDB' package.

**Depends** R (>= 2.8.0), DBI (>= 0.4)

**Imports** methods

**License** GPL-2

**URL** <https://downloads.mariadb.org/connector-c/> (upstream)

**BugReports** <https://github.com/r-dbi/rmysql/issues>

**SystemRequirements** libmariadb-client-dev | libmariadb-client-lgpl-dev  
| libmysqlclient-dev (deb), mariadb-devel (rpm), mariadb |  
mysql-connector-c (brew), mysql56\_dev (csw)

**NeedsCompilation** yes

**Collate** 'mysql.R' 'driver.R' 'connection.R' 'data-type.R' 'default.R'  
'escaping.R' 'result.R' 'extension.R' 'is-valid.R' 'table.R'  
'transaction.R'

**Suggests** testthat, curl

**RoxygenNote** 7.0.2

**Author** Jeroen Ooms [aut, cre] (<<https://orcid.org/0000-0002-4035-0289>>),  
David James [aut],  
Saikat DebRoy [aut],  
Hadley Wickham [aut],  
Jeffrey Horner [aut],  
RStudio [cph]

**Maintainer** Jeroen Ooms <jeroen@berkeley.edu>

**Repository** CRAN

**Date/Publication** 2021-12-14 13:00:15 UTC

R topics documented:

constants . . . . .	2
db-meta . . . . .	2
dbApply . . . . .	3
dbConnect,MySQLDriver-method . . . . .	5
dbDataType,MySQLDriver-method . . . . .	7
dbEscapeStrings . . . . .	7
dbFetch,MySQLResult,numeric-method . . . . .	8
dbGetInfo,MySQLDriver-method . . . . .	10
dbNextResult . . . . .	11
dbReadTable,MySQLConnection,character-method . . . . .	12
dbUnloadDriver,MySQLDriver-method . . . . .	13
dbWriteTable,MySQLConnection,character,data.frame-method . . . . .	14
isIdCurrent . . . . .	15
make.db.names,MySQLConnection,character-method . . . . .	16
mysqlClientLibraryVersions . . . . .	17
MySQLDriver-class . . . . .	18
mysqlHasDefault . . . . .	19
result-meta . . . . .	19
transactions . . . . .	20
<b>Index</b>	<b>22</b>

---

constants	<i>Constants</i>
-----------	------------------

---

Description

Constants

Constants

.MySQLPkgName (currently "RMySQL"), .MySQLPkgVersion (the R package version), .MySQLPkgRCS (the RCS revision), .MySQLSQLKeywords (a lot!)

---

db-meta	<i>Database interface meta-data</i>
---------	-------------------------------------

---

Description

Database interface meta-data

**Usage**

```
## S4 method for signature 'MySQLConnection'
dbGetInfo(dbObj, what = "", ...)

## S4 method for signature 'MySQLConnection'
dbListResults(conn, ...)

## S4 method for signature 'MySQLConnection'
summary(object, verbose = FALSE, ...)

## S4 method for signature 'MySQLConnection'
dbGetException(conn, ...)

## S4 method for signature 'MySQLConnection'
show(object)
```

**Arguments**

what	optional
...	Other arguments for compatibility with generic.
conn, dbObj, object	MySQLConnection object.
verbose	If TRUE, add extra info.

**Examples**

```
if (mysqlHasDefault()) {
  con <- dbConnect(RMySQL::MySQL(), dbname = "test")

  summary(con)

  dbGetInfo(con)
  dbListResults(con)
  dbListTables(con)

  dbDisconnect(con)
}
```

dbApply

---

*Apply R/S-Plus functions to remote groups of DBMS rows (experimental)*

---

**Description**

Applies R/S-Plus functions to groups of remote DBMS rows without bringing an entire result set all at once. The result set is expected to be sorted by the grouping field.

**Usage**

```
dbApply(res, ...)

## S4 method for signature 'MySQLResult'
dbApply(
  res,
  INDEX,
  FUN = stop("must specify FUN"),
  begin = NULL,
  group.begin = NULL,
  new.record = NULL,
  end = NULL,
  batchSize = 100,
  maxBatch = 1e+06,
  ...,
  simplify = TRUE
)
```

**Arguments**

<code>res</code>	a result set (see <a href="#">dbSendQuery</a> ).
<code>...</code>	any additional arguments to be passed to FUN.
<code>INDEX</code>	a character or integer specifying the field name or field number that defines the various groups.
<code>FUN</code>	a function to be invoked upon identifying the last row from every group. This function will be passed a data frame holding the records of the current group, a character string with the group label, plus any other arguments passed to dbApply as "...".
<code>begin</code>	a function of no arguments to be invoked just prior to retrieve the first row from the result set.
<code>group.begin</code>	a function of one argument (the group label) to be invoked upon identifying a row from a new group
<code>new.record</code>	a function to be invoked as each individual record is fetched. The first argument to this function is a one-row data.frame holding the new record.
<code>end</code>	a function of no arguments to be invoked just after retrieving the last row from the result set.
<code>batchSize</code>	the default number of rows to bring from the remote result set. If needed, this is automatically extended to hold groups bigger than batchSize.
<code>maxBatch</code>	the absolute maximum of rows per group that may be extracted from the result set.
<code>simplify</code>	Not yet implemented

**Details**

This function is meant to handle somewhat gracefully(?) large amounts of data from the DBMS by bringing into R manageable chunks (about batchSize records at a time, but not more than

maxBatch); the idea is that the data from individual groups can be handled by R, but not all the groups at the same time.

### Value

A list with as many elements as there were groups in the result set.

### Examples

```
if (mysqlHasDefault()) {
  con <- dbConnect(RMySQL::MySQL(), dbname = "test")

  dbWriteTable(con, "mtcars", mtcars, overwrite = TRUE)
  res <- dbSendQuery(con, "SELECT * FROM mtcars ORDER BY cyl")
  dbApply(res, "cyl", function(x, grp) quantile(x$mpg, names=FALSE))

  dbClearResult(res)
  dbRemoveTable(con, "mtcars")
  dbDisconnect(con)
}
```

---

dbConnect,MySQLDriver-method

*Connect/disconnect to a MySQL DBMS*

---

### Description

These methods are straight-forward implementations of the corresponding generic functions.

### Usage

```
## S4 method for signature 'MySQLDriver'
dbConnect(
  drv,
  dbname = NULL,
  username = NULL,
  password = NULL,
  host = NULL,
  unix.socket = NULL,
  port = 0,
  client.flag = 0,
  groups = "rs-dbi",
  default.file = NULL,
  ...
)

## S4 method for signature 'MySQLConnection'
dbConnect(drv, ...)
```

```
## S4 method for signature 'MySQLConnection'
dbDisconnect(conn, ...)
```

### Arguments

drv	an object of class <code>MySQLDriver</code> , or the character string <code>"MySQL"</code> or an <code>MySQLConnection</code> .
dbname	string with the database name or <code>NULL</code> . If not <code>NULL</code> , the connection sets the default database to this value.
username, password	Username and password. If username omitted, defaults to the current user. If password is omitted, only users without a password can log in.
host	string identifying the host machine running the MySQL server or <code>NULL</code> . If <code>NULL</code> or the string <code>"localhost"</code> , a connection to the local host is assumed.
unix.socket	(optional) string of the unix socket or named pipe.
port	(optional) integer of the TCP/IP default port.
client.flag	(optional) integer setting various MySQL client flags. See the MySQL manual for details.
groups	string identifying a section in the <code>default.file</code> to use for setting authentication parameters (see <a href="#">MySQL</a> ).
default.file	string of the filename with MySQL client options. Defaults to <code>\\\$HOME/.my.cnf</code>
...	Unused, needed for compatibility with generic.
conn	an <code>MySQLConnection</code> object as produced by <code>dbConnect</code> .

### Examples

```
## Not run:
# Connect to a MySQL database running locally
con <- dbConnect(RMySQL::MySQL(), dbname = "mydb")
# Connect to a remote database with username and password
con <- dbConnect(RMySQL::MySQL(), host = "mydb.mycompany.com",
  user = "abc", password = "def")
# But instead of supplying the username and password in code, it's usually
# better to set up a group in your .my.cnf (usually located in your home
# directory). Then it's less likely you'll inadvertently share them.
con <- dbConnect(RMySQL::MySQL(), group = "test")

# Always cleanup by disconnecting the database
dbDisconnect(con)

## End(Not run)

# All examples use the rs-dbi group by default.
if (mysqlHasDefault()) {
  con <- dbConnect(RMySQL::MySQL(), dbname = "test")
  summary(con)
  dbDisconnect(con)
}
```

---

dbDataType,MySQLDriver-method

*Determine the SQL Data Type of an S object*


---

### Description

This method is a straight-forward implementation of the corresponding generic function.

### Usage

```
## S4 method for signature 'MySQLDriver'
dbDataType(dbObj, obj)
```

```
## S4 method for signature 'MySQLConnection'
dbDataType(dbObj, obj)
```

### Arguments

dbObj	A MySQLDriver or MySQLConnection.
obj	R/S-Plus object whose SQL type we want to determine.

### Examples

```
dbDataType(RMySQL::MySQL(), "a")
dbDataType(RMySQL::MySQL(), 1:3)
dbDataType(RMySQL::MySQL(), 2.5)
```

---

dbEscapeStrings      *Escape SQL-special characters in strings.*


---

### Description

Escape SQL-special characters in strings.

### Usage

```
dbEscapeStrings(con, strings, ...)
```

```
## S4 method for signature 'MySQLConnection,character'
dbEscapeStrings(con, strings)
```

```
## S4 method for signature 'MySQLResult,character'
dbEscapeStrings(con, strings, ...)
```

**Arguments**

con                    a connection object (see [dbConnect](#)).

strings                a character vector.

...                    any additional arguments to be passed to the dispatched method.

**Value**

A character vector with SQL special characters properly escaped.

**Examples**

```
if (mysqlHasDefault()) {
con <- dbConnect(RMySQL::MySQL(), dbname = "test")

tmp <- sprintf("SELECT * FROM emp WHERE lname = %s", "O'Reilly")
dbEscapeStrings(con, tmp)

dbDisconnect(con)
}
```

---

dbFetch,MySQLResult,numeric-method

*Execute a SQL statement on a database connection.*

---

**Description**

To retrieve results a chunk at a time, use `dbSendQuery`, `dbFetch`, then `dbClearResult`. Alternatively, if you want all the results (and they'll fit in memory) use `dbGetQuery` which sends, fetches and clears for you.

**Usage**

```
## S4 method for signature 'MySQLResult,numeric'
dbFetch(res, n = -1, ...)

## S4 method for signature 'MySQLResult,numeric'
fetch(res, n = -1, ...)

## S4 method for signature 'MySQLResult,missing'
dbFetch(res, n = -1, ...)

## S4 method for signature 'MySQLResult,missing'
fetch(res, n = -1, ...)

## S4 method for signature 'MySQLConnection,character'
dbSendQuery(conn, statement)
```



```
## S4 method for signature 'MySQLResult'
dbClearResult(res, ...)

## S4 method for signature 'MySQLResult'
dbGetInfo(dbObj, what = "", ...)

## S4 method for signature 'MySQLResult'
dbGetStatement(res, ...)

## S4 method for signature 'MySQLResult,missing'
dbListFields(conn, name, ...)
```

### Arguments

<code>res, dbObj</code>	A <a href="#">MySQLResult</a> object.
<code>n</code>	maximum number of records to retrieve per fetch. Use -1 to retrieve all pending records; use 0 for to fetch the default number of rows as defined in <a href="#">MySQL</a>
<code>...</code>	Unused. Needed for compatibility with generic.
<code>conn</code>	an <a href="#">MySQLConnection</a> object.
<code>statement</code>	a character vector of length one specifying the SQL statement that should be executed. Only a single SQL statment should be provided.
<code>what</code>	optional
<code>name</code>	Table name.

### Details

`fetch()` will be deprecated in the near future; please use `dbFetch()` instead.

### Examples

```
if (mysqlHasDefault()) {
  con <- dbConnect(RMySQL::MySQL(), dbname = "test")
  dbWriteTable(con, "arrests", datasets::USArrests, overwrite = TRUE)

  # Run query to get results as dataframe
  dbGetQuery(con, "SELECT * FROM arrests limit 3")

  # Send query to pull requests in batches
  res <- dbSendQuery(con, "SELECT * FROM arrests")
  data <- dbFetch(res, n = 2)
  data
  dbHasCompleted(res)

  dbListResults(con)
  dbClearResult(res)
  dbRemoveTable(con, "arrests")
  dbDisconnect(con)
}
```

---

`dbGetInfo,MySQLDriver-method`*Get information about a MySQL driver.*

---

## Description

Get information about a MySQL driver.

## Usage

```
## S4 method for signature 'MySQLDriver'
dbGetInfo(dbObj, what = "", ...)

## S4 method for signature 'MySQLDriver'
dbListConnections(drv, ...)

## S4 method for signature 'MySQLDriver'
summary(object, verbose = FALSE, ...)

## S4 method for signature 'MySQLDriver'
show(object)
```

## Arguments

<code>dbObj</code> , <code>object</code> , <code>drv</code>	Object created by <a href="#">MySQL</a> .
<code>what</code>	Optional
<code>...</code>	Ignored. Needed for compatibility with generic.
<code>verbose</code>	If TRUE, print extra info.

## Examples

```
db <- RMySQL::MySQL()

db
dbGetInfo(db)
dbListConnections(db)
summary(db)
```

---

dbNextResult	<i>Fetch next result set from an SQL script or stored procedure (experimental)</i>
--------------	--

---

### Description

SQL scripts (i.e., multiple SQL statements separated by `;`) and stored procedures oftentimes generate multiple result sets. These generic functions provide a means to process them sequentially. `dbNextResult` fetches the next result from the sequence of pending results sets; `dbMoreResults` returns a logical to indicate whether there are additional results to process.

### Usage

```
dbNextResult(con, ...)

## S4 method for signature 'MySQLConnection'
dbNextResult(con, ...)

dbMoreResults(con, ...)

## S4 method for signature 'MySQLConnection'
dbMoreResults(con, ...)
```

### Arguments

`con` a connection object (see [dbConnect](#)).

`...` any additional arguments to be passed to the dispatched method

### Value

`dbNextResult` returns a result set or `NULL`.

`dbMoreResults` returns a logical specifying whether or not there are additional result sets to process in the connection.

### Examples

```
if (mysqlHasDefault()) {
  con <- dbConnect(RMySQL::MySQL(), dbname = "test", client.flag = CLIENT_MULTI_STATEMENTS)
  dbWriteTable(con, "mtcars", datasets::mtcars, overwrite = TRUE)

  sql <- "SELECT cyl FROM mtcars LIMIT 5; SELECT vs FROM mtcars LIMIT 5"
  rs1 <- dbSendQuery(con, sql)
  dbFetch(rs1, n = -1)

  if (dbMoreResults(con)) {
    rs2 <- dbNextResult(con)
    dbFetch(rs2, n = -1)
  }
}
```

```

dbClearResult(rs1)
dbClearResult(rs2)
dbRemoveTable(con, "mtcars")
dbDisconnect(con)
}

```

---

dbReadTable,MySQLConnection,character-method

*Convenience functions for importing/exporting DBMS tables*

---

## Description

These functions mimic their R/S-Plus counterpart get, assign, exists, remove, and objects, except that they generate code that gets remotely executed in a database engine.

## Usage

```
## S4 method for signature 'MySQLConnection,character'
dbReadTable(conn, name, row.names, check.names = TRUE, ...)
```

```
## S4 method for signature 'MySQLConnection'
dbListTables(conn, ...)
```

```
## S4 method for signature 'MySQLConnection,character'
dbExistsTable(conn, name, ...)
```

```
## S4 method for signature 'MySQLConnection,character'
dbRemoveTable(conn, name, ...)
```

```
## S4 method for signature 'MySQLConnection,character'
dbListFields(conn, name, ...)
```

## Arguments

conn	a <a href="#">MySQLConnection</a> object, produced by <a href="#">dbConnect</a>
name	a character string specifying a table name.
row.names	A string or an index specifying the column in the DBMS table to use as row.names in the output data.frame. Defaults to using the row_names column if present. Set to NULL to never use row names.
check.names	If TRUE, the default, column names will be converted to valid R identifiers.
...	Unused, needed for compatibility with generic.

## Value

A data.frame in the case of dbReadTable; otherwise a logical indicating whether the operation was successful.

**Note**

Note that the data.frame returned by dbReadTable only has primitive data, e.g., it does not coerce character data to factors.

**Examples**

```
if (mysqlHasDefault()) {
  con <- dbConnect(RMySQL::MySQL(), dbname = "test")

  # By default, row names are written in a column to row_names, and
  # automatically read back into the row.names()
  dbWriteTable(con, "mtcars", mtcars[1:5, ], overwrite = TRUE)
  dbReadTable(con, "mtcars")
  dbReadTable(con, "mtcars", row.names = NULL)
}
```

---

dbUnloadDriver,MySQLDriver-method  
*Unload MySQL driver.*

---

**Description**

Unload MySQL driver.

**Usage**

```
## S4 method for signature 'MySQLDriver'
dbUnloadDriver(drv, ...)
```

**Arguments**

drv	Object created by <a href="#">MySQL</a> .
...	Ignored. Needed for compatibility with generic.

**Value**

A logical indicating whether the operation succeeded or not.

---

dbWriteTable,MySQLConnection,character,data.frame-method

*Write a local data frame or file to the database.*

---

## Description

Write a local data frame or file to the database.

## Usage

```
## S4 method for signature 'MySQLConnection,character,data.frame'
dbWriteTable(
  conn,
  name,
  value,
  field.types = NULL,
  row.names = TRUE,
  overwrite = FALSE,
  append = FALSE,
  ...,
  allow.keywords = FALSE
)

## S4 method for signature 'MySQLConnection,character,character'
dbWriteTable(
  conn,
  name,
  value,
  field.types = NULL,
  overwrite = FALSE,
  append = FALSE,
  header = TRUE,
  row.names = FALSE,
  nrows = 50,
  sep = ",",
  eol = "\n",
  skip = 0,
  quote = "\"",
  ...
)
```

## Arguments

conn	a <a href="#">MySQLConnection</a> object, produced by <a href="#">dbConnect</a>
name	a character string specifying a table name.

value	a data.frame (or coercible to data.frame) object or a file name (character). In the first case, the data.frame is written to a temporary file and then imported to SQLite; when value is a character, it is interpreted as a file name and its contents imported to SQLite.
field.types	character vector of named SQL field types where the names are the names of new table's columns. If missing, types inferred with <a href="#">dbDataType</a> ).
row.names	A logical specifying whether the row.names should be output to the output DBMS table; if TRUE, an extra field whose name will be whatever the R identifier "row.names" maps to the DBMS (see <a href="#">make.db.names</a> ). If NA will add rows names if they are characters, otherwise will ignore.
overwrite	a logical specifying whether to overwrite an existing table or not. Its default is FALSE. (See the BUGS section below)
append	a logical specifying whether to append to an existing table in the DBMS. Its default is FALSE.
...	Unused, needs for compatibility with generic.
allow.keywords	logical indicating whether column names that happen to be MySQL keywords be used as column names in the resulting relation (table) being written. Defaults to FALSE, forcing mysqlWriteTable to modify column names to make them legal MySQL identifiers.
header	logical, does the input file have a header line? Default is the same heuristic used by read.table, i.e., TRUE if the first line has one fewer column than the second line.
nrows	number of lines to rows to import using read.table from the input file to create the proper table definition. Default is 50.
sep	field separator character
eol	End-of-line separator
skip	number of lines to skip before reading data in the input file.
quote	the quote character used in the input file (defaults to "\".)

---

isIdCurrent

---

*Check if a database object is valid.*


---

## Description

Support function that verifies that an object holding a reference to a foreign object is still valid for communicating with the RDBMS. isIdCurrent will be deprecated in the near future; please use the [dbIsValid\(\)](#) generic instead.

**Usage**

```
isIdCurrent(obj)

## S4 method for signature 'MySQLDriver'
dbIsValid(dbObj)

## S4 method for signature 'MySQLConnection'
dbIsValid(dbObj)

## S4 method for signature 'MySQLResult'
dbIsValid(dbObj)
```

**Arguments**

dbObj, obj      A MySQLDriver, MySQLConnection, MySQLResult.

**Details**

dbObjects are R/S-Plus remote references to foreign objects. This introduces differences to the object's semantics such as persistence (e.g., connections may be closed unexpectedly), thus this function provides a minimal verification to ensure that the foreign object being referenced can be contacted.

**Value**

a logical scalar.

**Examples**

```
dbIsValid(MySQL())
```

---

```
make.db.names,MySQLConnection,character-method
```

*Make R/S-Plus identifiers into legal SQL identifiers*

---

**Description**

These methods are straight-forward implementations of the corresponding generic functions.

**Usage**

```
## S4 method for signature 'MySQLConnection,character'
make.db.names(
  dbObj,
  snames,
  keywords = .SQL92Keywords,
  unique = TRUE,
```



```

        allow.keywords = TRUE,
        ...
    )

## S4 method for signature 'MySQLConnection'
SQLKeywords(dbObj, ...)

## S4 method for signature 'MySQLConnection,character'
isSQLKeyword(
    dbObj,
    name,
    keywords = .MySQLKeywords,
    case = c("lower", "upper", "any")[3],
    ...
)

```

### Arguments

dbObj	any MySQL object (e.g., MySQLDriver).
snames	a character vector of R/S-Plus identifiers (symbols) from which we need to make SQL identifiers.
keywords	a character vector with SQL keywords, by default it is .MySQLKeywords define in RMySQL. This may be overridden by users.
unique	logical describing whether the resulting set of SQL names should be unique. Its default is TRUE. Following the SQL 92 standard, uniqueness of SQL identifiers is determined regardless of whether letters are upper or lower case.
allow.keywords	logical describing whether SQL keywords should be allowed in the resulting set of SQL names. Its default is TRUE
...	Unused, needed for compatibility with generic.
name	a character vector of SQL identifiers we want to check against keywords from the DBMS.
case	a character string specifying whether to make the comparison as lower case, upper case, or any of the two. it defaults to any.

---

mysqlClientLibraryVersions

*MySQL Check for Compiled Versus Loaded Client Library Versions*

---

### Description

This function prints out the compiled and loaded client library versions.

### Usage

```
mysqlClientLibraryVersions()
```

**Value**

A named integer vector of length two, the first element representing the compiled library version and the second element representing the loaded client library version.

**Examples**

```
mysqlClientLibraryVersions()
```

---

MySQLDriver-class	<i>Class MySQLDriver with constructor MySQL.</i>
-------------------	--

---

**Description**

An MySQL driver implementing the R database (DBI) API. This class should always be initialized with the `MySQL()` function. It returns a singleton that allows you to connect to MySQL.

**Usage**

```
MySQL(max.con = 16, fetch.default.rec = 500)
```

**Arguments**

<code>max.con</code>	maximum number of connections that can be open at one time. There's no intrinsic limit, since strictly speaking this limit applies to MySQL <i>servers</i> , but clients can have (at least in theory) more than this. Typically there are at most a handful of open connections, thus the internal RMySQL code uses a very simple linear search algorithm to manage its connection table.
<code>fetch.default.rec</code>	number of records to fetch at one time from the database. (The <code>fetch</code> method uses this number as a default.)

**Examples**

```
if (mysqlHasDefault()) {
  # connect to a database and load some data
  con <- dbConnect(RMySQL::MySQL(), dbname = "test")
  dbWriteTable(con, "USArrests", datasets::USArrests, overwrite = TRUE)

  # query
  rs <- dbSendQuery(con, "SELECT * FROM USArrests")
  d1 <- dbFetch(rs, n = 10)      # extract data in chunks of 10 rows
  dbHasCompleted(rs)
  d2 <- dbFetch(rs, n = -1)      # extract all remaining data
  dbHasCompleted(rs)
  dbClearResult(rs)
  dbListTables(con)

  # clean up
```

```

dbRemoveTable(con, "USArrests")
dbDisconnect(con)
}

```

---

mysqlHasDefault	<i>Check if default database is available.</i>
-----------------	--

---

## Description

RMySQL examples and tests connect to a database defined by the `rs-dbi` group in `~/ .my.cnf`. This function checks if that database is available, and if not, displays an informative message.

## Usage

```
mysqlHasDefault()
```

## Examples

```

if (mysqlHasDefault()) {
  db <- dbConnect(RMySQL::MySQL(), dbname = "test")
  dbListTables(db)
  dbDisconnect(db)
}

```

---

result-meta	<i>Database interface meta-data.</i>
-------------	--------------------------------------

---

## Description

See documentation of generics for more details.

## Usage

```

## S4 method for signature 'MySQLResult'
dbColumnInfo(res, ...)

## S4 method for signature 'MySQLResult'
dbGetRowsAffected(res, ...)

## S4 method for signature 'MySQLResult'
dbGetRowCount(res, ...)

## S4 method for signature 'MySQLResult'
dbHasCompleted(res, ...)

## S4 method for signature 'MySQLResult'

```

```

dbGetException(conn, ...)

## S4 method for signature 'MySQLResult'
summary(object, verbose = FALSE, ...)

## S4 method for signature 'MySQLResult'
show(object)

```

### Arguments

```

res, conn, object      An object of class MySQLResult

...                    Ignored. Needed for compatibility with generic

verbose                If TRUE, print extra information.

```

### Examples

```

if (mysqlHasDefault()) {
  con <- dbConnect(RMySQL::MySQL(), dbname = "test")
  dbWriteTable(con, "t1", datasets::USArrests, overwrite = TRUE)

  rs <- dbSendQuery(con, "SELECT * FROM t1 WHERE UrbanPop >= 80")
  dbGetStatement(rs)
  dbHasCompleted(rs)

  dbGetInfo(rs)
  dbColumnInfo(rs)

  dbClearResult(rs)
  dbRemoveTable(con, "t1")
  dbDisconnect(con)
}

```

---

transactions

*DBMS Transaction Management*

---

### Description

Commits or roll backs the current transaction in an MySQL connection. Note that in MySQL DDL statements (e.g. CREATE TABLE) can not be rolled back.

### Usage

```

## S4 method for signature 'MySQLConnection'
dbCommit(conn, ...)

## S4 method for signature 'MySQLConnection'
dbBegin(conn, ...)

```

```
## S4 method for signature 'MySQLConnection'  
dbRollback(conn, ...)
```

### Arguments

conn	a MySQLConnection object, as produced by <a href="#">dbConnect</a> .
...	Unused.

### Examples

```
if (mysqlHasDefault()) {  
  con <- dbConnect(RMySQL::MySQL(), dbname = "test")  
  df <- data.frame(id = 1:5)  
  
  dbWriteTable(con, "df", df)  
  dbBegin(con)  
  dbGetQuery(con, "UPDATE df SET id = id * 10")  
  dbGetQuery(con, "SELECT id FROM df")  
  dbRollback(con)  
  
  dbGetQuery(con, "SELECT id FROM df")  
  
  dbRemoveTable(con, "df")  
  dbDisconnect(con)  
}
```

# Index

.MySQLPkgName (constants), [2](#)  
.MySQLPkgRCS (constants), [2](#)  
.MySQLPkgVersion (constants), [2](#)  
.MySQLSQLKeywords (constants), [2](#)  
  
CLIENT\_COMPRESS (constants), [2](#)  
CLIENT\_CONNECT\_WITH\_DB (constants), [2](#)  
CLIENT\_FOUND\_ROWS (constants), [2](#)  
CLIENT\_IGNORE\_SIGPIPE (constants), [2](#)  
CLIENT\_IGNORE\_SPACE (constants), [2](#)  
CLIENT\_INTERACTIVE (constants), [2](#)  
CLIENT\_LOCAL\_FILES (constants), [2](#)  
CLIENT\_LONG\_FLAG (constants), [2](#)  
CLIENT\_LONG\_PASSWORD (constants), [2](#)  
CLIENT\_MULTI\_RESULTS (constants), [2](#)  
CLIENT\_MULTI\_STATEMENTS (constants), [2](#)  
CLIENT\_NO\_SCHEMA (constants), [2](#)  
CLIENT\_ODBC (constants), [2](#)  
CLIENT\_PROTOCOL\_41 (constants), [2](#)  
CLIENT\_RESERVED (constants), [2](#)  
CLIENT\_SECURE\_CONNECTION (constants), [2](#)  
CLIENT\_SSL (constants), [2](#)  
CLIENT\_TRANSACTIONS (constants), [2](#)  
constants, [2](#)  
  
db-meta, [2](#)  
dbApply, [3](#)  
dbApply, MySQLResult-method (dbApply), [3](#)  
dbBegin, MySQLConnection-method  
(transactions), [20](#)  
dbClearResult, MySQLResult-method  
(dbFetch, MySQLResult, numeric-method),  
[8](#)  
dbColumnInfo, MySQLResult-method  
(result-meta), [19](#)  
dbCommit, MySQLConnection-method  
(transactions), [20](#)  
dbConnect, [8](#), [11](#), [12](#), [14](#), [21](#)  
dbConnect, MySQLConnection-method  
(dbConnect, MySQLDriver-method),  
[5](#)  
dbConnect, MySQLDriver-method, [5](#)  
dbDataType, [15](#)  
dbDataType, MySQLConnection-method  
(dbDataType, MySQLDriver-method),  
[7](#)  
dbDataType, MySQLDriver-method, [7](#)  
dbDisconnect, MySQLConnection-method  
(dbConnect, MySQLDriver-method),  
[5](#)  
dbEscapeStrings, [7](#)  
dbEscapeStrings, MySQLConnection, character-method  
(dbEscapeStrings), [7](#)  
dbEscapeStrings, MySQLResult, character-method  
(dbEscapeStrings), [7](#)  
dbExistsTable, MySQLConnection, character-method  
(dbReadTable, MySQLConnection, character-method),  
[12](#)  
dbFetch, MySQLResult, missing-method  
(dbFetch, MySQLResult, numeric-method),  
[8](#)  
dbFetch, MySQLResult, numeric-method, [8](#)  
dbGetException, MySQLConnection-method  
(db-meta), [2](#)  
dbGetException, MySQLResult-method  
(result-meta), [19](#)  
dbGetInfo, MySQLConnection-method  
(db-meta), [2](#)  
dbGetInfo, MySQLDriver-method, [10](#)  
dbGetInfo, MySQLResult-method  
(dbFetch, MySQLResult, numeric-method),  
[8](#)  
dbGetRowCount, MySQLResult-method  
(result-meta), [19](#)  
dbGetRowsAffected, MySQLResult-method  
(result-meta), [19](#)  
dbGetStatement, MySQLResult-method  
(dbFetch, MySQLResult, numeric-method),  
[8](#)

dbHasCompleted, MySQLResult-method  
     (result-meta), 19  
 dbIsValid, 15  
 dbIsValid, MySQLConnection-method  
     (isIdCurrent), 15  
 dbIsValid, MySQLDriver-method  
     (isIdCurrent), 15  
 dbIsValid, MySQLResult-method  
     (isIdCurrent), 15  
 dbListConnections, MySQLDriver-method  
     (dbGetInfo, MySQLDriver-method),  
     10  
 dbListFields, MySQLConnection, character-method  
     (dbReadTable, MySQLConnection, character-method),  
     12  
 dbListFields, MySQLResult, missing-method  
     (dbFetch, MySQLResult, numeric-method),  
     8  
 dbListResults, MySQLConnection-method  
     (db-meta), 2  
 dbListTables, MySQLConnection-method  
     (dbReadTable, MySQLConnection, character-method),  
     12  
 dbMoreResults (dbNextResult), 11  
 dbMoreResults, MySQLConnection-method  
     (dbNextResult), 11  
 dbNextResult, 11  
 dbNextResult, MySQLConnection-method  
     (dbNextResult), 11  
 dbReadTable, MySQLConnection, character-method,  
     12  
 dbRemoveTable, MySQLConnection, character-method  
     (dbReadTable, MySQLConnection, character-method),  
     12  
 dbRollback, MySQLConnection-method  
     (transactions), 20  
 dbSendQuery, 4  
 dbSendQuery, MySQLConnection, character-method  
     (dbFetch, MySQLResult, numeric-method),  
     8  
 dbUnloadDriver, MySQLDriver-method, 13  
 dbWriteTable, MySQLConnection, character, character-method  
     (dbWriteTable, MySQLConnection, character, data.frame-method),  
     14  
 dbWriteTable, MySQLConnection, character, data.frame-method,  
     14  
 fetch, 18  
 fetch, MySQLResult, missing-method  
     (dbFetch, MySQLResult, numeric-method),  
     8  
 fetch, MySQLResult, numeric-method  
     (dbFetch, MySQLResult, numeric-method),  
     8  
 isIdCurrent, 15  
 isSQLKeyword, MySQLConnection, character-method  
     (make.db.names, MySQLConnection, character-method),  
     16  
 make.db.names, 15  
 make.db.names, MySQLConnection, character-method,  
     16  
 MySQL, 6, 9, 10, 13  
 MySQL (MySQLDriver-class), 18  
 mysqlClientLibraryVersions, 17  
 MySQLConnection, 9, 12, 14  
 MySQLDriver-class, 18  
 mysqlHasDefault, 19  
 MySQLResult, 9, 20  
 result-meta, 19  
 RMySQL (MySQLDriver-class), 18  
 RMySQL-package (MySQLDriver-class), 18  
 show, MySQLConnection-method (db-meta), 2  
 show, MySQLDriver-method  
     (dbGetInfo, MySQLDriver-method),  
     10  
 show, MySQLResult-method (result-meta),  
     19  
 show, MySQLDriver-method (db-meta), 2  
 show, MySQLDriver-method (dbGetInfo, MySQLDriver-method),  
     10  
 summary, MySQLConnection-method  
     (db-meta), 2  
 summary, MySQLDriver-method  
     (dbGetInfo, MySQLDriver-method),  
     10  
 summary, MySQLResult-method  
     (result-meta), 19  
 summary, MySQLDriver-method (dbGetInfo, MySQLDriver-method),  
     10  
 transactions, 20