

Design Concepts

■ Modeling: Chapter 12

Slide Set to accompany

Software Engineering: A Practitioner's Approach, 8/e

by Roger S. Pressman and Bruce R. Maxim

Slides copyright © 1996, 2001, 2005, 2009, 2014 by Roger S. Pressman


For non-profit educational use only

May be reproduced ONLY for student use at the university level when used in conjunction with *Software Engineering: A Practitioner's Approach, 8/e*. Any other reproduction or use is prohibited without the express written permission of the author.

All copyright information MUST appear if these slides are posted on a website for student use.

Agenda

- Design Overview
- Design Concepts
- Design Models



Design Overview

Requirements, Design, and Implementation

- Requirements (Analysis) Model
 - Model of “**what** we need?”
 - Problem space
- Design Model
 - Model of “**how to** create or implement?”
 - Solution space
- Software Product (Implementations, Programs, ...)
 - Actual creation (no model)

Software Design

- Software design encompasses the set of **principles**, **concepts**, and **practices** that lead to the development of a high-quality product.
- Design principles establish an overriding philosophy that guides you in the design work
 - E.g., The design should exhibit uniformity and integration
- Design concepts must be understood before the mechanics of design practice apply
 - E.g., modularity, pattern, ...
- Design practices lead to the creation of various software models that guide the construction activity

Software Design Manifesto

- Mitch Kapor, presented a “software design manifesto” in *Dr. Dobbs Journal*. He said:
 - **Well-designed software programs** should exhibit:
 1. ***Firmness***: A program should not have any bugs that inhibit its function.
 2. ***Commodity***: A program should be suitable for the purposes for which it was intended.
 3. ***Delight***: The experience of using the program should be pleasurable one.

Design and Quality

1. The design must cover **all the requirements**
 - Both functional and non-functional requirements
2. The design must be a **readable and understandable**
 - For those who generate code, test and subsequently support the software
3. The design should provide **a complete picture** of the software
 - Addressing the informational, functional, and behavioral domains

Design Principles

- The design process should not suffer from ‘tunnel vision.’
 - There are always alternative design solutions
 - The best designers consider all (or most) of them before settling on the final design model.
- The design should be traceable to the analysis model.
- The design should not reinvent the wheel.
- The design should exhibit uniformity and integration.
- The design should be structured to accommodate change.
- Design is not coding, coding is not design.
- The design should be assessed for quality as it is being created, not after the fact.
- ...

From Davis [DAV95]


Design Concepts

Fundamental Concepts

- **Abstraction**—data and procedure
- **Architecture**—the overall structure of the software
- **Patterns**—“conveys the essence” of a proven design solution
- **Separation of concerns**—any complex problem can be more easily handled if it is subdivided into pieces
- **Modularity**—compartmentalization of data and function
- **Hiding**—controlled interfaces
- **Functional independence**—single-minded function and low coupling
- **Refinement**—elaboration of detail for all abstractions
- **Aspects**—a mechanism for understanding how global requirements affect design
- **Refactoring**—a reorganization technique that simplifies the design
- **OO design concepts**—Appendix II
- **Design Classes**—provide design detail that will enable analysis classes to be implemented


1) Data Abstraction

- A data abstraction is a named collection of data that describes a **data object**.



2) Procedural Abstraction

- A procedural abstraction refers to the ability of naming and later calling a set of instructions.
 - The name of a procedural abstraction implies its function.
 - It is called abstraction because the caller of the procedure only needs to know what the procedure does **not how it does it**.



3) Architecture

- Software architecture is:
 - the structure or organization of program components (modules),
 - the manner in which these components interact,
 - and the structure of data that are used by the components.

“The overall structure of the software and the ways in which that structure provides **conceptual integrity** for a system.” [SHA95a]

What is conceptual integrity?

- Conceptual integrity is the principle that anywhere you look in your system, you can tell that the design is part of the **same overall design**.
- Even if multiple people work on it, it would seem **cohesive** and **consistent** as if **only one mind** was guiding the work.
 - The system reflects one set of design ideas, instead of containing many good but independent, conflicting and uncoordinated ideas.
 - Development teams must have in their **collective minds** the **same vision** for the software

Architectural Design

There are a set of properties for an architectural design:

1. Structural properties.

- components of a system (e.g., modules, objects)
- and the manner in which those components are packaged and interact with one another

2. Extra-functional properties. The architectural design should address how to achieve **non-functional requirements**

- e.g., performance, reliability, security, etc

3. Families of related systems. The architectural design should draw upon **repeatable patterns** that are **commonly encountered** in the design of **similar systems**.

- The design should reuse architectural building blocks

4) Patterns

- A software design pattern is a **general, reusable solution** to a **commonly occurring problem** within a **certain context** in software design

Design Pattern Template

Pattern name—describes the essence of the pattern in a short but expressive name

Intent—describes the pattern and what it does

Also-known-as—lists any synonyms for the pattern

Motivation—provides an example of the problem

Applicability—notes specific design situations in which the pattern is applicable


Structure—describes the classes that are required to implement the pattern

....

For an example, see Slide 62
(**Mediator** design pattern)

Design Pattern Examples

- Singleton
 - Ensure a class has only one instance
- Object pool
 - Avoid expensive acquisition and release of resources
- Adapter
 - Convert the interface of a class into another interface clients expect
- ...



5) Separation of Concerns



- A *concern* is a feature or behavior that is specified as part of the requirements
- Any complex problem can be more easily handled if it is subdivided into pieces
 - pieces that can be solved and/or optimized independently
- A problem takes less effort and time to solve:
 - By separating concerns into smaller, and therefore more manageable pieces
 - Divide-and-conquer strategy

6) Modularity

- Modularity is the most common manifestation of separation of concerns.
- **Monolithic** software
(i.e., a large program composed of a single module) cannot be easily grasped by a software engineer.
 - The overall complexity would make understanding impossible.
- You should break the design into many modules
 - hoping to make understanding easier
 - and reduce the cost required to build [and maintain] the software
- What is the risk of “many modules”?
 - **Integration**


Modularity: Trade-offs

What is the "right" number of modules for a specific software design?



7) Information Hiding

- Modules should be specified and designed so that:
 - information (algorithms and data) contained within a module is **inaccessible** to other modules that have **no need** for such information.



Why Information Hiding?

- reduces the likelihood of “**side effects**”
- limits the global impact of **local design decisions**
- emphasizes communication through controlled **interfaces**
- discourages the use of **global data**
- leads to **encapsulation**—an attribute of high quality design
- results in higher **quality** software

8) Functional Independence


- Functional independence is achieved by developing modules with "single-minded" function and a "dislike" to excessive interaction with other modules.
- *Cohesion*: The relative functional strength of a module
- *Coupling*: The relative interdependence among modules
 - Collaboration between modules should be kept to an acceptable minimum (**loosely coupled**)
 - If a design model is tightly coupled (each design class collaborates with another), the system is difficult to implement, test and maintain

Cohesion


- Cohesion is the degree to which elements inside a module (e.g., class, package, ...) are **functionally related** to each other and **united in their purpose**
- A cohesive module
 - has a **small, focused** set of responsibilities
 - and **single-mindedly** applies attributes and methods to implement those responsibilities
 - performs a single task, requiring little interaction with other components in other parts of a program
- For example, all methods within class **User** should represent the user behavior
- Modules that perform many unrelated functions must be avoided

Cohesion: Examples


- Example 1: class **VideoClip** might contain a set of methods for editing the video clip.
 - **VideoClip** is a cohesive class as long as:
 1. Each method focuses solely on attributes associated with the video clip
 2. All methods related to the video editing are incorporated in **VideoClip**
- Example 2: class **User** can be responsible for storing the email address of the user but not for validating it
 - That should belong to some other class like **Email**




A Loosely Coupled and Highly Cohesive System



9) Refinement




- Stepwise refinement is a top-down design strategy.
- An application is developed by **successively refining levels of procedural detail**.
 - Decomposing a macroscopic statement of function in a stepwise fashion until programming language statements are reached.



10) Aspects

- Consider two requirements, *A* and *B*:
Requirement *A* **crosscuts** requirement *B*,
if *B* cannot be satisfied without taking *A* into account.
- Cross-cutting concerns often **cannot be cleanly decomposed** from the rest of the system
- An **aspect** is a representation of a cross-cutting concern



11) Refactoring

- Martin Fowler defines refactoring in the following manner:
 - *"Refactoring is the process of changing a software system in such a way that it does not alter the external behavior of the code [design] yet improves its internal structure."*
- When software is refactored, the existing design is examined for:
 - redundancy
 - unused design elements
 - inefficient or unnecessary algorithms
 - poorly constructed or inappropriate data structures
 - or any other design failure [**bad smells**] that can be corrected to yield a better design



12) OO Design Concepts

- **Design classes**
 - Entity classes
 - Boundary classes
 - Controller classes
- **Inheritance**—all responsibilities of a superclass is immediately inherited by all subclasses
- **Messages**—stimulate some behavior to occur in the receiving object
- **Polymorphism**—a characteristic that greatly reduces the effort required to extend the design

Design Classes: Entity

- Entity classes are extracted directly from the **problem statement**
 - Also called **business** classes
 - e.g., **FloorPlan** and **Sensor**
 - Things that are to be stored in a **database** and **persist**
 - **Analysis classes** are **refined** during design to become entity classes
 - The analysis model defines a set of analysis classes
 - The **abstraction** level of an analysis class is relatively **high**
 - As the design model evolves, design classes refine the analysis classes by providing **more details** that will enable the classes to be implemented

Analysis Class vs Design Class




Design Classes: Boundary

- Boundary classes are **developed during design** to create the **user interface** that the user sees and interacts
 - E.g., interactive screen or **printed reports**
 - Entity objects contain information that is important to users, but they do not display themselves
 - Boundary classes are designed with the responsibility of managing **how entity objects are represented** to users
 - For example: **CameraWindow**
 - This class has the responsibility of displaying surveillance camera output for the SafeHome homeowner

Design Classes: Controller


- Controller classes are designed to manage
 - the **creation** or **update** of **entity** objects;
 - the **instantiation** of boundary objects as they [controllers] obtain information from entity objects;
 - **complex communication** between sets of objects;
 - **validation** of data communicated between objects or between the user and the application.
 - In general, controller classes are **not considered until the design** activity has begun

Entity, Boundary, Controller: An Example




An Example of Analysis Class Diagram vs Design Class Diagram

Analysis Class Diagram



An Example of Analysis Class Diagram vs Design Class Diagram



Design Class Diagram (partial)

کلاس‌های جدید موقت (مرزی و کنترلی) که در مرحله طراحی اضافه شده‌اند

Design Class Characteristics

- Each design class be reviewed to ensure that it is “well-formed”
- Four characteristics of a well-formed design class:
 1. **Complete and sufficient** - includes **all necessary attributes and methods** and contains **only** those methods **needed** to achieve class intent (no more and no less)
 2. **Primitiveness** – **each class method** focuses on providing **one service**
 3. **High cohesion** – small, focused, single-minded classes
 4. **Low coupling** – class collaboration kept to minimum

Primitiveness: An Example

- Once the service has been implemented with a method
 - The class **should not provide another way to accomplish the same thing**
- For example, the class **VideoClip** for video editing software
- It has attributes **startPoint** and **endpoint** to indicate the start and end points of the clip
- The methods, *setStartPoint()* and *setEndPoint()*, provide the only means for establishing start and end points for the clip.

Design Model


Design Model Elements

- **Data elements**
 - Data model --> data structures (using ER for example)
 - Data model --> database architecture
- **Architectural elements**
 - Application domain
 - Analysis classes, their relationships, collaborations and behaviors are transformed into design realizations
 - Architectural patterns and “styles” (Chapters 13 and 16)
- **Interface elements**
 - the user interface (UI) (Chapter 15)
 - external interfaces to other systems, devices, networks or other producers or consumers of information
 - internal interfaces between various design components.
- **Component elements**
- **Deployment elements**

Data Design Elements

- Focuses on the data domain
 - Data objects independently of processing
 - The structure of data
 - Indicates how data objects relate to one another

*An example of
a data model
(using ER)*



Architectural Design Elements

- The architectural model is usually depicted as a set of interconnected subsystems
 - often derived from analysis packages within the requirements model
 - Each subsystem may have its own architecture
 - The architectural model is derived from three sources:
 1. Information about the **application domain**
 2. Specific **requirements model** (the problem at hand)
 - Such as use cases or analysis classes
 3. The availability of **architectural patterns and styles**
- (More details: next sessions)

Interface Design Elements

- The interface design elements depict:
 - information flows into and out of a system
 - External communications
 - and how it is communicated among the components defined as part of the architecture
 - Internal communications
- Important elements
 - **User interface** (UI)
 - **External interfaces** to other systems
 - **Internal interfaces** between various design components

Interface Elements—UI

- UI design incorporates:
 - **aesthetic** elements (e.g., layout, color, graphics)
 - **ergonomic** elements (e.g., information layout and placement, UI navigation)
 - **technical** elements (e.g., UI patterns, reusable components)
- Details in Chapter 15

Interface Elements—External Interfaces

- The design of external interfaces **requires information about the sender and receiver entities**
- This information should be
 - **collected during requirements engineering**
 - and **verified** once the interface design commences
 - The designer should ensure that the specification for the interface is **accurate** and **complete**
- The design of external interfaces should incorporate error checking and appropriate security features.


Interface Elements—Internal Interfaces

- The design of internal interfaces is closely aligned with **component-level design**
 - represents all **operations** and the **messaging schemes** required to enable communication between various classes or components
- Two tasks are required:
 1. Specifying message details when classes or components collaborate
 2. Identify appropriate interfaces for each component
- Details in Chapter 14

1) Designing Messaging Schema

- The design model can show the details of collaborations by **specifying the structure of messages** that are passed between objects within a system
- **During requirements modeling**, collaboration diagrams show how analysis classes collaborate with one another
- **Example:**
 - Three objects collaborate to prepare a print job for submission to the production stream.
 - Messages are passed between objects as shown by arrows

Collaboration diagram with messaging



1) Designing Messaging Schema

- As design proceeds, each message is elaborated by expanding its syntax in the following manner:

```
[guard condition] sequence expression (return value) :=  
message name (argument list)
```

- [guard condition] specifies **conditions** that must be met before the message can be sent;
- sequence expression is an integer value that indicates the sequential **order** in which a message is sent;
- (return value) is the name of the **information** that is returned by the invoked operation
- message name identifies the invoked **operation** (e.g., buildJob);
- (argument list) is the list of **attributes** passed to the operation.


2) Designing the Interface of Objects

- A UML interface is a classifier that declares a set of **public operations**
- The interface contains no internal structure, it has no attributes and no associations
- Two notations:



*Interface SiteSearch is **realized** (implemented) by SearchService.*


"lollipop" symbol is shorthand for a realization relationship of an interface classifier



*Interface SiteSearch is **realized** (implemented) by SearchService.*

An Example of Interface Representation


- **ControlPanel** provides the behavior associated with a keypad
 - It implements the operations *readKeyStroke()* and *decodeKey()*
 - ControlPanel provides these two services to other classes (i.e., **WirelessPDA** and **Mobilephone**)
 - Interface **KeyPad** is realized (implemented) by **ControlPanel**



Component-Level Design Elements


- Describes the **internal detail** of each software component
 - **Data structures** for all local data objects within a component
 - **Algorithmic detail** for all processing functions that occurs within a component
 - An **interface** that allows access to all operations (behaviors) of a component
- Details in Chapter 14

An Example of Component-Level Design



Component Diagram


- In UML, a component is represented as follows:




- Provided Interface and the Required Interface:




- **Provided interface:** An interface (or services) that the component provides
- **Required interface:** An interface (or services) that the component requires




Component Diagram: Example 1



Component Diagram: Example 2



- What is **port**?




Deployment-Level Design Elements


- Indicates how software functionality and subsystems will be allocated within the **physical computing environment**
- Modeled using UML deployment diagrams
 1. *Descriptor form* deployment diagrams show the computing environment but does not indicate hardware configuration details
 2. *Instance form* deployment diagrams explicitly indicate hardware configuration details
- Developed during the latter stages of design

Deployment Diagram: *Descriptor Form*

- The elements of the *SafeHome* product are configured to operate within three primary computing environments:
 1. A homebased PC
 2. The SafeHome control panel
 3. A server housed at CPI Corp



Deployment Diagram: *Instance Form*




Further Reading

PART TWO **MODELING** 103

CHAPTER 7	Principles That Guide Practice	104
CHAPTER 8	Understanding Requirements	131
CHAPTER 9	Requirements Modeling: Scenario-Based Methods	166
CHAPTER 10	Requirements Modeling: Class-Based Methods	184
CHAPTER 11	Requirements Modeling: Behavior, Patterns, and Web/Mobile Apps	202
CHAPTER 12	Design Concepts	224
CHAPTER 13	Architectural Design	252
CHAPTER 14	Component-Level Design	285
CHAPTER 15	User Interface Design	317
CHAPTER 16	Pattern-Based Design	347
CHAPTER 17	WebApp Design	371
CHAPTER 18	MobileApp Design	391

The End

Mediator Design Pattern



- Intent

- Mediator is a **behavioral design pattern** that lets you **reduce dependencies** between objects
- Promotes **loose coupling**

- Solution

- Restricts direct communications between objects and forces them to **collaborate only** via a mediator object
- components **collaborate indirectly** by calling a special mediator object that redirects the calls to appropriate components
- So, the components depend only on a single mediator class instead of being coupled to dozens of their colleagues

Mediator Design Pattern

- Each component has a reference to a mediator
- The Mediator interface declares a method for communication between components (usually a single notification method).
- Concrete mediator often keep references to all components it manage and sometimes even manages their lifecycle
- Components must not be aware of other components
- When something happens with a component, it notifies the mediator
- Mediator can easily identify the sender and decide what should be done in return
(may do something on its own or pass the request to another component)

