## CS 5220

# Project 2 - Shallow Water Simulation

Marc Aurele Gilles (mtg79) Sheroze Sheriffdeen(mss385)

October 19, 2015

## 1 Introduction

The goal of this project to profile, parallelize and tune a particular structured grid computation: a shallow-water equations solver.

The shallow-water equations are a two-dimensional PDE system that describes waves that are very long compared to the water depth. The variables of the PDE system are the water height h, and the velocity components (u, v). The governing equations are

$$U_t = F(U)_x + G(U)_y)$$

where

$$U = \begin{bmatrix} h \\ hu \\ hv \end{bmatrix}, F = \begin{bmatrix} hu \\ h^2u + gh^2/2 \\ huv \end{bmatrix}, G = \begin{bmatrix} hv \\ huv \\ h^2v + gh^2/2 \end{bmatrix}$$

# 2 Design Decisions

The following sections describe the implementation changes from the original code found at https://github.com/cornell-cs5220-f15/water. The current stable solution can be found at https://github.com/sheroze1123/water/tree/vector\_parallel branch.

## 2.1 Memory Layout

The original solution a two dimensional vectors of 3-vectors to represent  $U_t$ ,  $F(U)_x$ , and  $G(U)_y$ . During each time step, the solution accesses each element in the 2-D grid sequentially. Then, the vector<vector<real>> representation leads to memory accesses that are not local spatially.

Therefore, our solution chooses to use 3 separate two dimensional vectors per objects,  $U_t$ ,  $F(U)_x$ , and  $G(U)_y$ . Thus, we are required in general to perform three loop iterations in place of a single loop in the original solution. But this approach leverages spatial locality, especially in compute\_step and limited\_derivs functions.

#### 2.2 Vectorization

By observing the profiling information, we noticed that the original solution spends majority of its computational time in the functions limited\_derivs, compute\_step and compute\_fg\_speeds. By adopting the newer memory layout, we enabled spatially local memory accesses. We were also able to decompose for loops in the solution to improve vectorization. Refer to ipo\_out\_vectorization.optrpt in https://github.com/sheroze1123/water/tree/vectorization for more information.

In compute\_fg\_speeds, we performed two separate loops to compute flux and wave speeds. The flux computation and the wave speed computation for the complete grid is not handled by the Physics class. We used #pragma simd directives to instruct the compiler the ability to vectorize these computations. The compiler was successfully able to vectorize these functions with an estimated potential speedup of 6.7.

limited\_derivs uses the limdiff function in minmod.h. To improve the vectorization of this computation, we changed the implementation of limdiff in the following ways.

- 1. limdiff now performs the computation on the complete grid instead of at one grid point.
- 2. limdiff was decomposed as limdiff\_x and limdiff\_y to perform the limiter along the x dimension and the y dimension separately while still retaining unit stride.

## 2.3 Parallelization

The updated memory layout is amenable to parallelization via OpenMP, particular during the costly operations of limited\_derivs and compute\_step.

At the beginning of a call to limited\_derivs we initialize a team of threads using #pragma omp parallel. Each application of the limiter to the components of  $U_t$ ,  $F(U)_x$ , and  $G(U)_y$  can be computed in parallel since we removed the data dependencies by creating 3 separate two dimensional arrays per component. We use the #pragma omp for directive to parallelize the grid computation of each component.

In compute\_step, we initialize a team of threads using #pragma omp parallel. The predictor step is now performed in parallel. Then, we create a barrier before proceeding to the corrector step since the the corrector step needs information from the predictor. After computing the corrector step, we perform a barrier before finally copying back to storage in parallel. The performance increase we observed via parallelization reached up to 3+ speedup. Results are plotted in section 3.2.

## 2.4 Domain Decomposition

Our domain decomposition code suffers from instability. The simulation is stable if the sub-grid is set to be the whole grid plus the layers of ghost cells and also, if the time steps taken are very small: about 10 times smaller than they ought to be. In all other situation we observe some small scale instability which is certainly due to a bug in our implementation. We hope to have this fixed by the final report submission deadline.

#### 2.4.1 General Setup

We decomposed the main grid into equally sized sub-grids, by first copying each sub-grid into a separate array. Each sub-grid array contains its part of the main grid an outer layer of ghost

cells which contain information about the neighboring cells or the cells on the opposite side of the main grid if the sub-domain is close to the boundary of the main grid as we use periodic boundary condition. We then perform some number of time steps on each independent sub-grid and finally synchronize by copying back the sub-grid (without the ghost cells) onto the main grid.

#### 2.4.2 Ghost cells

The width of the layer of ghost cells for each sub-grid is 3t, where t is the number of time steps we wish to advance before synchronizing back onto the main grid. For each sub-grid, we declare a simulation object, and run the simulation essentially in the same manner as we would on the whole grid, except we never apply periodic boundary conditions on the sub-grids. Because of this, at each time step we perform without synchronization, we "loose" 3 layers of ghost cells, in the sense that the computation within this layer is erroneous.

However, the rest of the grid is not contaminated with error, as information spreads through our simulation only by 3 layers per time step.

#### 2.4.3 Estimating the wave speed

The main barrier to in adopting domain decomposition parallelization for this simulation is that we need to estimate the wave speed at each time step to be able to estimate a how big of a time step we can perform for the next iteration. Hence to allow each sub-grid to run from time t = 0 to time  $t = t_{final}$ , we would need know in advance the speeds at time t,  $t + dt_1$ ,  $t + (dt_1 + dt_2)$  ...  $t + \sum_{i=1}^{k-1} dt_i$ . But we obviously do not have access to those speeds at time t.

The problem is that we need to know at least an upper bound on the wave speed at each time step to be able to decide how many time steps it will take to reach  $t_{final}$ , as the number of time steps needed is directly proportional to the number of ghost cells we need to allocate for each sub-grid at time t. Our solution is to estimate an upper bound on the max wave speed, set the max wave speed for the next k iterations to a be a multiple r of the speed of the wave at time t which we can compute before parallelizing. (in our code, we set r = 2).

Furthermore, for each sub grid at each time checks independently if the wave speed on the subdomain is greater than our bound, if it is the case our program throws an error and stops. This failure check occurs locally to each thread, so there is no need for synchronization. A better alternative, which we have not yet implemented would be to stop the computation if the wave speed is greater than our bound at time, double k and start the computation all over again from time t.

## 3 Analysis

#### 3.1 Profiling

The following time profiles were obtained on a 200x200 grid by advancing 100 frames.

## 3.1.1 Original solution

We began the optimization by analyzing the time profiles of the original code. The following table shows the top 4 functions by CPU time. We note that the bottleneck in the original solution lies

in limited\_derivs and compute\_step.

Function	Module	CPU Time	Spin Time	Overhead Time
Central2D < Shallow2D, MinMod < float >>::limited_derivs	shallow	$2.529 \mathrm{s}$	$0\mathrm{s}$	0 s
$Central 2D < Shallow 2D \;, \; MinMod < float >> :: compute\_step$	shallow	$1.210  \mathrm{s}$	$0\mathrm{s}$	$0\mathrm{s}$
$Central 2D < Shallow 2D \;, \; MinMod < float >> :: compute\_fg\_speeds$	shallow	$0.426  \mathrm{s}$	$0\mathrm{s}$	$0\mathrm{s}$
_IO_file_xsputn	libc-2.12.so	$0.027  \mathrm{s}$	$0  \mathrm{s}$	0 s
_IO_fwrite	libc-2.12.so	$0.025  \mathrm{s}$	$0\mathrm{s}$	0 s

## 3.1.2 Vectorization

Profiling of vectorization shows good improvements in performance, especially in the limited\_derivs and compute\_fg\_speeds functions, but a reduction in performance in the compute\_step function. The repetition of limdiff\_x and limdiff\_y is due to separation of components and axes in limited\_derivs.

Function	Module	CPU Time	Spin Time	Overhead Time
compute_step	shallow	2.136 s	0 s	0 s
limited_derivs	shallow	$0.448  \mathrm{s}$	$0  \mathrm{s}$	0 s
compute_fg_speeds	shallow	0.362 s	$0  \mathrm{s}$	0 s
limdiff_y	shallow	$0.204  \mathrm{s}$	$0  \mathrm{s}$	0 s
limdiff_x	shallow	$0.201  \mathrm{s}$	$0\mathrm{s}$	0 s
limdiff_x	shallow	$0.200  \mathrm{s}$	$0\mathrm{s}$	0 s
limdiff_y	shallow	$0.200  \mathrm{s}$	$0  \mathrm{s}$	0 s
limdiff_x	shallow	$0.197  \mathrm{s}$	$0\mathrm{s}$	0 s
limdiff_x	shallow	$0.192  \mathrm{s}$	0 s	0 s
limdiff_y	shallow	0.192 s	$0\mathrm{s}$	0 s
limdiff_x	shallow	0.188s	$0\mathrm{s}$	0 s
limdiff_y	shallow	0.186s	$0  \mathrm{s}$	0 s
limdiff_y	shallow	$0.184  \mathrm{s}$	$0\mathrm{s}$	0 s
vector < float , allocator < float >>:: operator []	shallow	0.062 s	$0  \mathrm{s}$	0 s
vector < float , allocator < float >>::operator []	shallow	$0.061  \mathrm{s}$	$0\mathrm{s}$	0 s
vector <float ,="" allocator<float="">&gt;::operator[]</float>	shallow	$0.051  \mathrm{s}$	$0\mathrm{s}$	$0\mathrm{s}$

#### 3.1.3 Parallelization

For parallelization, we list the functions that take up the most CPU time and their associated OpenMP spin times. Although we see speedups in the parallel code, the profiling shows that we spend a lot of CPU time spinning. This indicates load imbalance issues in our code that we aim to address in the final report.

Function	Module	CPU Time	${\tt Spin Time}({\tt OpenMP})$
kmp_wait_template <kmp_flag_64></kmp_flag_64>	libiomp5.so	47.056s	47.056s
compute_step	shallow	$3.919  \mathrm{s}$	0 s
kmp_wait_template <kmp_flag_64></kmp_flag_64>	libiomp5.so	$3.001  \mathrm{s}$	$3.001  \mathrm{s}$
[Outside any known module]	[Unknown]	$2.635\mathrm{s}$	0 s
kmp_yield	libiomp5.so	$1.114  \mathrm{s}$	$1.114  \mathrm{s}$
notdone_check	libiomp5.so	$1.097  \mathrm{s}$	$1.097  \mathrm{s}$
_kmp_x86_pause	libiomp5.so	$0.973  \mathrm{s}$	$0.973  \mathrm{s}$
kmp_x86_pause	libiomp5.so	$0.887  \mathrm{s}$	$0.887  \mathrm{s}$
compute_fg_speeds	shallow	$0.648  \mathrm{s}$	0 s
limdiff_x	shallow	$0.424  \mathrm{s}$	0 s
limdiff_x	shallow	$0.419  \mathrm{s}$	0 s
limdiff_x	shallow	$0.418  \mathrm{s}$	0 s
limdiff_x	shallow	$0.417  \mathrm{s}$	0 s
limdiff_x	shallow	$0.417  \mathrm{s}$	0 s
limdiff_y	shallow	$0.413  \mathrm{s}$	0 s
limdiff_y	shallow	$0.406  \mathrm{s}$	0 s
limdiff_x	shallow	$0.402  \mathrm{s}$	0 s
limdiff_y	shallow	$0.386  \mathrm{s}$	0 s
limdiff_y	shallow	$0.380  \mathrm{s}$	0 s
limdiff_y	shallow	$0.374\mathrm{s}$	0 s
limdiff_y	shallow	$0.357\mathrm{s}$	0 s

## 3.2 Scaling Study

## 3.2.1 Strong Scaling Study

Using a 500x500 grid and 100 frames, we observe the speedup with respect to the number of threads in our parallel implementation. Here, speedup s is defined to be,

$$s = \frac{t_{parallel}}{t_{serial}} \tag{1}$$

The observed best performance occurs when the number of threads are  $\approx 10$ . Increasing the number of threads further results in plateauing in speedup which can be attributed to extra threads not being employed due to limited parallelization. The plateau is lower than the observed maximum speedup. We believe that this is due to thread scheduling overhead. Note that the original solution has a speedup; 1 in the following plot.




Figure 1: Speedup as a function of the number of threads

## 3.2.2 Weak Scaling Study

We vary the threads but keep the problem size per thread constant. In figure 2, each thread ideally computes a sub-problem equivalent to advancing a 300 x 300 grid by 100 frames. We plot the speedup observed while increasing the number of threads and the problem size such that work done per thread is approximately equal. We observe a exponential decrease in speedup. We believe that this can be attributed to load imbalance between threads and thread scheduling overhead.




Figure 2: Speedup as a function of the number of threads

# References

- [1] Data Alignment to Assist Vectorization. (n.d.). Retrieved September 30, 2015, from https://software.intel.com/en-us/articles/data-alignment-to-assist-vectorization
- [2] Yliluoma, J. (n.d.). Guide into OpenMP: Easy multithreading programming for C. Retrieved October 19, 2015, from http://bisqwit.iki.fi/story/howto/openmp/