Changing plot style and color

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN

Erin Case
Data Scientist

datacamp

Why customize?

Reasons to change style:

- Personal preference
- Improve readability
- Guide interpretation

Changing the figure style

- Figure "style" includes background and axes
- Preset options: "white", "dark", "whitegrid", "darkgrid", "ticks"
- `sns.set_style()`

Default figure style ("white")

```
sns.catplot(x="age",
            y="masculinity_important",
            data=masculinity_data,
            hue="feel_masculine",
            kind="point")

plt.show()
```



Figure style: "whitegrid"

```
sns.set_style("whitegrid")

sns.catplot(x="age",
            y="masculinity_important",
            data=masculinity_data,
            hue="feel_masculine",
            kind="point")

plt.show()
```



Other styles

```
sns.set_style("ticks")

sns.catplot(x="age",
            y="masculinity_important",
            data=masculinity_data,
            hue="feel_masculine",
            kind="point")

plt.show()
```



Other styles

```
sns.set_style("dark")

sns.catplot(x="age",
            y="masculinity_important",
            data=masculinity_data,
            hue="feel_masculine",
            kind="point")

plt.show()
```



Other styles

```
sns.set_style("darkgrid")

sns.catplot(x="age",
            y="masculinity_important",
            data=masculinity_data,
            hue="feel_masculine",
            kind="point")

plt.show()
```



Changing the palette

- Figure "palette" changes the color of the main elements of the plot
- `sns.set_palette()`
- Use preset palettes or create a custom palette

Diverging palettes

“RdBu”	
“PRGn”	
“RdBu_r”	
“PRGn_r”	

Example (default palette)

```
category_order = ["No answer",
                  "Not at all",
                  "Not very",
                  "Somewhat",
                  "Very"]

sns.catplot(x="how_masculine",
            data=masculinity_data,
            kind="count",
            order=category_order)

plt.show()
```



Example (diverging palette)

```
sns.set_palette("RdBu")

category_order = ["No answer",
                  "Not at all",
                  "Not very",
                  "Somewhat",
                  "Very"]

sns.catplot(x="how_masculine",
            data=masculinity_data,
            kind="count",
            order=category_order)

plt.show()
```



Sequential palettes

“Greys”	
“Blues”	
“PuRd”	
“GnBu”	

Sequential palette example



[1] Waskom, M. L. (2021). seaborn: statistical data visualization. https://seaborn.pydata.org/

Custom palettes

```
custom_palette = ["red", "green", "orange", "blue",
                  "yellow", "purple"]

sns.set_palette(custom_palette)
```



Custom palettes

```
custom_palette = ['#FBB4AE', '#B3CDE3', '#CCEBC5',
                  '#DECBE4', '#FED9A6', '#FFFFCC',
                  '#E5D8BD', '#FDDAEC', '#F2F2F2']

sns.set_palette(custom_palette)
```



Changing the scale

- Figure "context" changes the scale of the plot elements and labels
- `sns.set_context()`
- Smallest to largest: "paper", "notebook", "talk", "poster"

Default context: "paper"

```
sns.catplot(x="age",
            y="masculinity_important",
            data=masculinity_data,
            hue="feel_masculine",
            kind="point")

plt.show()
```



Larger context: "talk"

```
sns.set_context("talk")

sns.catplot(x="age",
            y="masculinity_important",
            data=masculinity_data,
            hue="feel_masculine",
            kind="point")

plt.show()
```



Let's practice!

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN

Part-02

Adding titles and labels: Part 1

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN

Erin Case
Data Scientist

datacamp

Creating informative visualizations





FacetGrid vs. AxesSubplot objects

Seaborn plots create two different types of objects: `FacetGrid` and `AxesSubplot`

```
g = sns.scatterplot(x="height", y="weight", data=df)
type(g)
```

```
> matplotlib.axes._subplots.AxesSubplot
```

An Empty FacetGrid



FacetGrid vs. AxesSubplot objects

Object Type	Plot Types	Characteristics
`FacetGrid`	`relplot()`, `catplot()`	Can create subplots
`AxesSubplot`	`scatterplot()`, `countplot()`, etc.	Only creates a single plot



Seaborn-specific object

Matplotlib object (also used by Seaborn)

FacetGrid :Can create multiple subplots (facets) automatically

AxesSubplot:Only one plot per call

Adding a title to FacetGrid

```
g = sns.catplot(x="Region",
                y="Birthrate",
                data=gdp_data,
                kind="box")
g.fig.suptitle("New Title")
plt.show()
```



Adjusting height of title in FacetGrid

```
g = sns.catplot(x="Region",
                y="Birthrate",
                data=gdp_data,
                kind="box")

g.fig.suptitle("New Title",  title for the whole plot
               y=1.03)    default y=1

plt.show()
```



Let's practice!

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN

Part - 02

Adding titles and labels: Part 2

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN

Erin Case
Data Scientist

Adding a title to AxesSubplot

FacetGrid

```
g = sns.catplot(x="Region",
                y="Birthrate",
                data=gdp_data,
                kind="box")

g.fig.suptitle("New Title",
               y=1.03)
```

title for the entire plot

default title height y=1

AxesSubplot

```
g = sns.boxplot(x="Region",
                y="Birthrate",
                data=gdp_data)

g.set_title("New Title",
            y=1.03)
```

The y=1.03 parameter controls how high the title is placed vertically:

Titles for subplots

```
g = sns.catplot(x="Region",
                y="Birthrate",
                data=gdp_data,
                kind="box",
                col="Group")
```



Titles for subplots

```
g = sns.catplot(x="Region",
                y="Birthrate",
                data=gdp_data,
                kind="box",
                col="Group")

g.fig.suptitle("New Title",
               y=1.03)
```



Titles for subplots

```
g = sns.catplot(x="Region",
                y="Birthrate",
                data=gdp_data,
                kind="box",
                col="Group")
```

title for entire plot

```
g.fig.suptitle("New Title",
               y=1.03)
```

title for each subplot

```
g.set_titles("This is {col_name}")
```



Adding axis labels

```
g = sns.catplot(x="Region",
                y="Birthrate",
                data=gdp_data,
                kind="box")
`

g.set(xlabel="New X Label",
      ylabel="New Y Label")

plt.show()
```



Rotating x-axis tick labels

```
g = sns.catplot(x="Region",
                y="Birthrate",
                data=gdp_data,
                kind="box") Q1,Q2,Q3
plt.xticks(rotation=90)
plt.show()
```



Let's practice!

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN

Part 03

Putting it all together

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN

Erin Case
Data Scientist

datacamp

Getting started

To import Seaborn:

```
import seaborn as sns
```

To import Matplotlib:

```
import matplotlib.pyplot as plt
```

To show a plot:

```
plt.show()
```

Relational plots

- Show the relationship between two quantitative variables
- Examples: scatter plots, line plots

```
sns.relplot(x="x_variable_name",
            y="y_variable_name",
            data=pandas_df,
            kind="scatter")
```

Categorical plots

- Show the distribution of a quantitative variable within categories defined by a categorical variable
- Examples: bar plots, count plots, box plots, point plots

```
sns.catplot(x="x_variable_name",
            y="y_variable_name",
            data=pandas_df,
            kind="bar")
```

Adding a third variable (hue)

Setting `hue` will create subgroups that are displayed as different colors on a single plot.



[1] Waskom, M. L. (2021). seaborn: statistical data visualization. https://seaborn.pydata.org/

Adding a third variable (row/col)

Setting `row` and/or `col` in `relplot()` or `catplot()` will create subgroups that are displayed on separate subplots.



[1] Waskom, M. L. (2021). seaborn: statistical data visualization. https://seaborn.pydata.org/

Customization

- Change the background: `sns.set_style()`
- Change the main element colors: `sns.set_palette()`
- Change the scale: `sns.set_context()`

Adding a title

Object Type	Plot Types	How to Add Title
`FacetGrid`	`relplot()`, `catplot()`	`g.fig.suptitle()`
`AxesSubplot`	`scatterplot()`, `countplot()`, etc.	`g.set_title()`

adding title to the whole plot

Final touches

Add x- and y-axis labels:

```
g.set(xlabel="new x-axis label",
      ylabel="new y-axis label")
```

Rotate x-tick labels:

```
plt.xticks(rotation=90)
```

Let's practice!

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN



Well done! What's next?

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN

Erin Case
Data Scientist

datacamp

Where does Seaborn fit in?



Where does Seaborn fit in?



Next Steps: Explore and communicate results



Next steps:

- Seaborn advanced visualizations
- Matplotlib advanced customizations

Next steps: Gather data



Next steps:

- Python
- SQL

Next steps: Transform and clean



Next steps:

- Getting data into pandas DataFrames
- Cleaning data
- Transforming into tidy format

Next steps: Analyze and build models



Next steps:

- Statistical analysis
- Calculating and interpreting confidence intervals

Congratulations!

INTRODUCTION TO DATA VISUALIZATION WITH SEABORN