

Overview of Machine Learning

with focus on Supervised Learning

Chris Cornwell

Aug 26, 2025

Machine Learning

Supervised learning

Machine Learning

Supervised learning

What is Machine Learning?

- Concerned with designing, understanding algorithms which allow computer program to “learn.”

What is Machine Learning?

- Concerned with designing, understanding algorithms which allow computer program to “learn.”
- Not as new as it seems, but rapid growth in last 2 decades.
 - field of study since 1950's;
 - related to much older statistical modeling.

What is Machine Learning?

- Concerned with designing, understanding algorithms which allow computer program to “learn.”
- Not as new as it seems, but rapid growth in last 2 decades.
 - field of study since 1950's;
 - related to much older statistical modeling.
- Can be single ML model performing task (e.g., finding person in an image, speech-to-text, sentiment analysis)

What is Machine Learning?

- Concerned with designing, understanding algorithms which allow computer program to “learn.”
- Not as new as it seems, but rapid growth in last 2 decades.
 - field of study since 1950's;
 - related to much older statistical modeling.
- Can be single ML model performing task (e.g., finding person in an image, speech-to-text, sentiment analysis)
- Or, many separate models combined together ← what makes AI work (e.g., self-driving cars, LLM's or chatbots).

What is Machine Learning?

Very general, academic definition by Tom Mitchell:

*A “computer program” is said to **learn** from experience E , with respect to some task T and performance measure M if: its performance on T , as measured by M , improves with experience E .*

What is Machine Learning?

Very general, academic definition by Tom Mitchell:

*A “computer program” is said to **learn** from experience E , with respect to some task T and performance measure M if: its performance on T , as measured by M , improves with experience E .*

- Often, the experience E is called “training” (updates to how program runs); based on observed data.

What is Machine Learning?

Very general, academic definition by Tom Mitchell:

*A “computer program” is said to **learn** from experience E , with respect to some task T and performance measure M if: its performance on T , as measured by M , improves with experience E .*

- Often, the experience E is called “training” (updates to how program runs); based on observed data.
- “computer program,” for us “learning algorithm”, determines a function that produces output from given input (the data). After training, the resulting input-output function represents achieving the task T .

What is Machine Learning?

Very general, academic definition by Tom Mitchell:

*A “computer program” is said to **learn** from experience E , with respect to some task T and performance measure M if: its performance on T , as measured by M , improves with experience E .*

- Often, the experience E is called “training” (updates to how program runs); based on observed data.
- “computer program,” for us “learning algorithm”, determines a function that produces output from given input (the data). After training, the resulting input-output function represents achieving the task T .
- In class, we will discuss algorithms made for *regression* tasks, and others for *classification* tasks, that fit this paradigm.

What is Machine Learning?

Very general, academic definition by Tom Mitchell:

*A “computer program” is said to **learn** from experience E , with respect to some task T and performance measure M if: its performance on T , as measured by M , improves with experience E .*

- Often, the experience E is called “training” (updates to how program runs); based on observed data.
- “computer program,” for us “learning algorithm”, determines a function that produces output from given input (the data). After training, the resulting input-output function represents achieving the task T .
- In class, we will discuss algorithms made for *regression* tasks, and others for *classification* tasks, that fit this paradigm.
- Performance measure M : for us, called a *cost function* or *loss function*.

Two general categories in machine learning

Supervised learning: algorithm uses sample (input) data that have output “labels.” Goal: determine a good underlying function from sample data.

Two general categories in machine learning

Supervised learning: algorithm uses sample (input) data that have output “labels.” Goal: determine a good underlying function from sample data.

- Housing price prediction

Two general categories in machine learning

Supervised learning: algorithm uses sample (input) data that have output “labels.” Goal: determine a good underlying function from sample data.

- Housing price prediction
- Whether emails are junk or not.

Two general categories in machine learning

Supervised learning: algorithm uses sample (input) data that have output “labels.” Goal: determine a good underlying function from sample data.

- Housing price prediction
- Whether emails are junk or not.
- Detect space debris, or trash on ocean surface.

Two general categories in machine learning

Supervised learning: algorithm uses sample (input) data that have output “labels.” Goal: determine a good underlying function from sample data.

- Housing price prediction
- Whether emails are junk or not.
- Detect space debris, or trash on ocean surface.

Unsupervised learning: algorithm uses sample data, but it is unlabeled. Goal: discover something (a pattern, grouping, or some insight) about the data based on its coordinates (features).

Two general categories in machine learning

Supervised learning: algorithm uses sample (input) data that have output “labels.” Goal: determine a good underlying function from sample data.

- Housing price prediction
- Whether emails are junk or not.
- Detect space debris, or trash on ocean surface.

Unsupervised learning: algorithm uses sample data, but it is unlabeled. Goal: discover something (a pattern, grouping, or some insight) about the data based on its coordinates (features).

- Market segmentation.

Two general categories in machine learning

Supervised learning: algorithm uses sample (input) data that have output “labels.” Goal: determine a good underlying function from sample data.

- Housing price prediction
- Whether emails are junk or not.
- Detect space debris, or trash on ocean surface.

Unsupervised learning: algorithm uses sample data, but it is unlabeled. Goal: discover something (a pattern, grouping, or some insight) about the data based on its coordinates (features).

- Market segmentation.
- News feed (grouping similar news articles).

Two general categories in machine learning

Supervised learning: algorithm uses sample (input) data that have output “labels.” Goal: determine a good underlying function from sample data.

- Housing price prediction
- Whether emails are junk or not.
- Detect space debris, or trash on ocean surface.

Unsupervised learning: algorithm uses sample data, but it is unlabeled. Goal: discover something (a pattern, grouping, or some insight) about the data based on its coordinates (features).

- Market segmentation.
- News feed (grouping similar news articles).
- Separate audio sources in a mixed signal.

Machine Learning

Supervised learning

The goal of Supervised learning

In Section 1.2, the textbook uses the term “Predictive learning” to mean same as Supervised learning.

- (Supervised \iff labels)
- The labeled sample data is called **training data**. The goal is to “learn” a function from the training data that will do well labeling new data, not seen during learning process.
- “Doing well” is measured by a loss function (M from Mitchell’s description).

Example Images

Example 1 - Supervised learning, Section 1.1 of textbook

Cat or Dog?




Figure 1.1 from textbook

- Training data. The images, each with label 'cat' or 'dog'.
- Computer sees each image, pixels in 2D array with RGB value (a vector in \mathbb{R}^3) at each pixel.
- **Designing features.** “Cartoon image” of ML model’s function: computes N **features** from each image \leadsto vectors (points) in $\mathbb{R}^N \leadsto$ points with one label separated from those with other label (by graph of linear function).

Designing features, to easily separate data

Compute N **features** from each image \leadsto vectors (points) in $\mathbb{R}^N \leadsto$ points with one label separated from those with other label (by graph of linear function).




Figure 1.3 from textbook

Example 2 - Supervised learning, Section 1.2 of textbook

Predict share price




Figure 1.7, upper-left from textbook

- From training data, pick one feature: revenue. Label: the share price.
- Each revenue, a number in \mathbb{R} . One “independent variable,” call it x .
- **Designing features.** Here, have used a feature already at hand. Not always best idea when there are multiple independent variables (we’ll see examples later, where you design features).

Example 2 - Predict response variable, share price

Revenue value: x . Find a function $f(x) = \hat{m}x + \hat{b}$, so that if y is share price for x and we set $\hat{y} = f(x)$ then y and \hat{y} are close, on average.
(Linear Regression)




Figure 1.7, upper-right from textbook

Supervised learning, very generally

Have an “input space” (often is \mathbb{R}^N , for some N , or subset of it¹). Have an output space, or label space, Y . (Y is a finite list of labels for classification; it is \mathbb{R} or an interval in \mathbb{R} for regression.)

¹The domain (input space) *could* be some different space.

Supervised learning, very generally

Have an “input space” (often is \mathbb{R}^N , for some N , or subset of it¹). Have an output space, or label space, Y . (Y is a finite list of labels for classification; it is \mathbb{R} or an interval in \mathbb{R} for regression.)

- Given a sample $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^P$, with $\mathbf{x}_i \in \mathbb{R}^N$ and $y_i \in Y$, drawn from an (unknown) joint probability distribution $\rho_{X,Y} : \mathbb{R}^N \times Y \rightarrow [0, \infty)$.

¹The domain (input space) *could* be some different space.

Supervised learning, very generally

Have an “input space” (often is \mathbb{R}^N , for some N , or subset of it¹). Have an output space, or label space, Y . (Y is a finite list of labels for classification; it is \mathbb{R} or an interval in \mathbb{R} for regression.)

- Given a sample $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^P$, with $\mathbf{x}_i \in \mathbb{R}^N$ and $y_i \in Y$, drawn from an (unknown) joint probability distribution $\rho_{X,Y} : \mathbb{R}^N \times Y \rightarrow [0, \infty)$.
- Goal: to learn, from \mathcal{S} , a function $f^* : \mathbb{R}^N \rightarrow Y$ that “fits” (*approximates well*) the distribution $\rho_{X,Y}$.

¹The domain (input space) *could* be some different space.

Supervised learning, very generally

Have an “input space” (often is \mathbb{R}^N , for some N , or subset of it¹). Have an output space, or label space, Y . (Y is a finite list of labels for classification; it is \mathbb{R} or an interval in \mathbb{R} for regression.)

- Given a sample $\mathcal{S} = \{(\mathbf{x}_i, y_i)\}_{i=1}^P$, with $\mathbf{x}_i \in \mathbb{R}^N$ and $y_i \in Y$, drawn from an (unknown) joint probability distribution $\rho_{X,Y} : \mathbb{R}^N \times Y \rightarrow [0, \infty)$.
- Goal: to learn, from \mathcal{S} , a function $f^* : \mathbb{R}^N \rightarrow Y$ that “fits” (*approximates well*) the distribution $\rho_{X,Y}$.
- Might not be possible for points on graph of f^* to be typically “close” to samples from $\rho_{X,Y}$. However, for an $\mathbf{x} \in \mathbb{R}^N$, the corresponding $f^*(\mathbf{x})$ should be near expected value of y , given \mathbf{x} .

¹The domain (input space) *could* be some different space.

Achieving the general goal

Most often, we choose a *parameterized class* of functions², and we get f^* from that class.

²Sometimes called a *hypothesis class*.

Achieving the general goal

Most often, we choose a *parameterized class* of functions², and we get f^* from that class.

- Have space of parameters Ω ; an $\omega \in \Omega$ determines a function $f_\omega : \mathbb{R}^N \rightarrow Y$. The parameterized class is the set of all such f_ω .

²Sometimes called a *hypothesis class*.

Achieving the general goal

Most often, we choose a *parameterized class* of functions², and we get f^* from that class.

- Have space of parameters Ω ; an $\omega \in \Omega$ determines a function $f_\omega : \mathbb{R}^N \rightarrow Y$. The parameterized class is the set of all such f_ω .
- Change parameters to find a function that fits well.

²Sometimes called a *hypothesis class*.

Achieving the general goal

Most often, we choose a *parameterized class* of functions², and we get f^* from that class.

- Have space of parameters Ω ; an $\omega \in \Omega$ determines a function $f_\omega : \mathbb{R}^N \rightarrow Y$. The parameterized class is the set of all such f_ω .
- Change parameters to find a function that fits well.

How to change parameters? Select a performance measure: **(empirical) loss function** $\mathcal{L}_S : \Omega \rightarrow \mathbb{R}$.

²Sometimes called a *hypothesis class*.

Achieving the general goal

Most often, we choose a *parameterized class* of functions², and we get f^* from that class.

- Have space of parameters Ω ; an $\omega \in \Omega$ determines a function $f_\omega : \mathbb{R}^N \rightarrow Y$. The parameterized class is the set of all such f_ω .
- Change parameters to find a function that fits well.

How to change parameters? Select a performance measure: **(empirical) loss function** $\mathcal{L}_S : \Omega \rightarrow \mathbb{R}$.

- Want to make value of \mathcal{L}_S small; use the function itself to do this.

²Sometimes called a *hypothesis class*.

Achieving the general goal

Most often, we choose a *parameterized class* of functions², and we get f^* from that class.

- Have space of parameters Ω ; an $\omega \in \Omega$ determines a function $f_\omega : \mathbb{R}^N \rightarrow Y$. The parameterized class is the set of all such f_ω .
- Change parameters to find a function that fits well.

How to change parameters? Select a performance measure: **(empirical) loss function** $\mathcal{L}_S : \Omega \rightarrow \mathbb{R}$.

- Want to make value of \mathcal{L}_S small; use the function itself to do this.
- Ideally, converge to some ω^* , a minimizer of \mathcal{L}_S , and set $f^* = f_{\omega^*}$.

²Sometimes called a *hypothesis class*.

Questions?