

Cost Functions for Half-space Models

Chris Cornwell

November 3, 2025

Outline

The Perceptron Cost and Softmax

The Margin Perceptron and Other Cost Functions

Accuracy and Counting Costs

The Logistic Regression Cost

Outline

The Perceptron Cost and Softmax

The Margin Perceptron and Other Cost Functions

Accuracy and Counting Costs

The Logistic Regression Cost

Outline

The Perceptron Cost and Softmax

The Margin Perceptron and Other Cost Functions

Accuracy and Counting Costs


The Logistic Regression Cost

Returning to the “Simple Example” for Perceptron algorithm

Example in \mathbb{R}^2 , with $P = 4$ points.

$$\mathbf{x}: \begin{bmatrix} -1 & 3 \\ -1 & -1 \\ 3 & -1 \\ 0 & 1.5 \end{bmatrix} \quad \mathbf{y}: \begin{bmatrix} -1 \\ -1 \\ 1 \\ 1 \end{bmatrix}$$

Final $\tilde{\mathbf{w}} = \begin{bmatrix} 1 \\ 4 \\ -0.5 \end{bmatrix}$; hyperplane in \mathbb{R}^2 (a line) shown below.



What if this data were part of a sample, which has noise? What about the point near the hyperplane?

Getting a Buffer – a “margin”

Say that $S = \{\mathbf{x}_i, y_i\}_{i=1}^P$ (with $y_i = \pm 1$) is linearly separable. Instead of simply trying to find a hyperplane that successfully separates the data, try to find one that has some distance from points on each side.

Getting a Buffer – a “margin”

Say that $S = \{\mathbf{x}_i, y_i\}_{i=1}^P$ (with $y_i = \pm 1$) is linearly separable. Instead of simply trying to find a hyperplane that successfully separates the data, try to find one that has some distance from points on each side.

Can express this as wanting no points between two parallel hyperplanes – between the set of \mathbf{x} where $\tilde{\mathbf{x}}^\top \tilde{\mathbf{w}} = 1$ and where $\tilde{\mathbf{x}}^\top \tilde{\mathbf{w}} = -1$.




Figure: Taken from Figure 4.4 in textbook, p. 79. (Note: they used blue for the -1 label.)

This is equivalent to wanting $y_i(\tilde{\mathbf{x}}_i^\top \tilde{\mathbf{w}}) \geq 1$ for all $i = 1, \dots, P$. Recall, S being linearly separable implies that there must be a $\tilde{\mathbf{w}}$ that achieves this.

Outline

The Perceptron Cost and Softmax

The Margin Perceptron and Other Cost Functions

Accuracy and Counting Costs

The Logistic Regression Cost

Outline

The Perceptron Cost and Softmax

The Margin Perceptron and Other Cost Functions

Accuracy and Counting Costs

The Logistic Regression Cost