

Introduction to Python

Chris Cornwell

September 2, 2025

Variables and Types

Operations on different types

Lists

Intro to Python functions

Variables and Types

Operations on different types

Lists

Intro to Python functions

Assigning variables

- A variable is assigned by placing, on one line,
<variable name> = <assigned value>.

```
1 | # The lines below assign three variables: x, y, and name_full
2 | x = 5.11
3 | y = 5
4 | name_full = 'Chris Cornwell'
```

Assigning variables

- A variable is assigned by placing, on one line,
`<variable name> = <assigned value>.`

```
1 | # The lines below assign three variables: x, y, and name_full
2 | x = 5.11
3 | y = 5
4 | name_full = 'Chris Cornwell'
```

- “Commenting out”, done by starting line with #.

Assigning variables

- A variable is assigned by placing, on one line,
`<variable name> = <assigned value>`.

```
1 | # The lines below assign three variables: x, y, and name_full  
2 | x = 5.11  
3 | y = 5  
4 | name_full = 'Chris Cornwell'
```

- “Commenting out”, done by starting line with #.
- Possible to assign more than one variable in one line.

```
1 | x, y = 5.11, 5  
2 | # or, you could use  
3 | x = 5.11; y = 5
```

Data type

Each variable has a *data type* (or, simply *type*). ¹

```
1 | x = 5.11
2 | y = 5
3 | name_full = 'Chris Cornwell'
```

↑ the types of the assigned vars are `float`, `int`, and `str` respectively.

¹[Information from Python documentation](#) about standard types.

Data type

Each variable has a *data type* (or, simply *type*). ¹

```
1 | x = 5.11
2 | y = 5
3 | name_full = 'Chris Cornwell'
```

↑ the types of the assigned vars are `float`, `int`, and `str` respectively.

Unlike in other programming languages, don't need to declare the types of the variables. Python *interprets* it. (The type might even *change* at a later point.)

¹[Information from Python documentation](#) about standard types.

Data type

Each variable has a *data type* (or, simply *type*). ¹

```
1 | x = 5.11
2 | y = 5
3 | name_full = 'Chris Cornwell'
```

↑ the types of the assigned vars are `float`, `int`, and `str` respectively.

Unlike in other programming languages, don't need to declare the types of the variables. Python *interprets* it. (The type might even *change* at a later point.)

- type `int`: like an integer.
- type `float`: like a real number in decimal form ...*kind of*.

¹[Information from Python documentation](#) about standard types.

Data type

Each variable has a *data type* (or, simply *type*). ¹

```
1 | x = 5.11
2 | y = 5
3 | name_full = 'Chris Cornwell'
```

↑ the types of the assigned vars are `float`, `int`, and `str` respectively.

Unlike in other programming languages, don't need to declare the types of the variables. Python *interprets* it. (The type might even *change* at a later point.)

- type `int`: like an integer.
- type `float`: like a real number in decimal form ...*kind of*.
- type `str`: a “string,” or sequence of *characters* (that can be typed from keyboard).

¹[Information from Python documentation](#) about standard types.

Variables and Types

Operations on different types

Lists

Intro to Python functions

Numerical types

The four main operations² `+`, `-`, `*`, and `/` work as you would expect on numerical types `int` and `float`.

²Representing addition, subtraction, multiplication, and division.

Numerical types

The four main operations² +, -, *, and / work as you would expect on numerical types `int` and `float`.

Assigning after an operation. Often want to change a variable by some amount (e.g., increase it by 1), and keep the new value.

```
1 | # Compute y+1, then assign that to y
2 | y = y + 1
3 | # A convenient shorthand for line above is
4 | y += 1
```

²Representing addition, subtraction, multiplication, and division.

Numerical types

The four main operations² +, -, *, and / work as you would expect on numerical types `int` and `float`.

Assigning after an operation. Often want to change a variable by some amount (e.g., increase it by 1), and keep the new value.

```
1 | # Compute y+1, then assign that to y
2 | y = y + 1
3 | # A convenient shorthand for line above is
4 | y += 1
```

Equation above is an assignment, not mathematical. The shorthand works for other operations (like -, *, etc).

²Representing addition, subtraction, multiplication, and division.

Numerical types

The four main operations² +, -, *, and / work as you would expect on numerical types `int` and `float`.

Assigning after an operation. Often want to change a variable by some amount (e.g., increase it by 1), and keep the new value.

```
1 | # Compute y+1, then assign that to y
2 | y = y + 1
3 | # A convenient shorthand for line above is
4 | y += 1
```

Equation above is an assignment, not mathematical. The shorthand works for other operations (like -, *, etc).

Other operations.

`**`, raises to a power; so, `y**2` has value y^2 .

²Representing addition, subtraction, multiplication, and division.

Numerical types

The four main operations² +, -, *, and / work as you would expect on numerical types `int` and `float`.

Assigning after an operation. Often want to change a variable by some amount (e.g., increase it by 1), and keep the new value.

```
1 | # Compute y+1, then assign that to y
2 | y = y + 1
3 | # A convenient shorthand for line above is
4 | y += 1
```

Equation above is an assignment, not mathematical. The shorthand works for other operations (like -, *, etc).

Other operations.

******, raises to a power; so, `y**2` has value y^2 .

% (called “mod”), finds the remainder; so, `5%3` is 2 and `6%3` is 0.

²Representing addition, subtraction, multiplication, and division.

Variables and Types

Operations on different types

Lists

Intro to Python functions

Basics of lists

`list` is a *sequential* data type in Python – it holds a sequence of “items.”

- Each item could be an `int`, each could be a `list`; possibly, can have some with one type, some with another.

Basics of lists

`list` is a *sequential* data type in Python – it holds a sequence of “items.”

- Each item could be an `int`, each could be a `list`; possibly, can have some with one type, some with another.
- Example below: a list with `int` and `str` type items (and an empty list).

```
1 | my_list = [2, 3, 5, 'p']  
2 | empty_list = []
```

Basics of lists

`list` is a *sequential* data type in Python – it holds a sequence of “items.”

- Each item could be an `int`, each could be a `list`; possibly, can have some with one type, some with another.
- Example below: a list with `int` and `str` type items (and an empty list).

```
1 | my_list = [2, 3, 5, 'p']  
2 | empty_list = []
```

Referring to a list item by index:

`my_list[0]` is 2 above, `my_list[1]` is 3, and so on.

Basics of lists

`list` is a *sequential* data type in Python – it holds a sequence of “items.”

- Each item could be an `int`, each could be a `list`; possibly, can have some with one type, some with another.
- Example below: a list with `int` and `str` type items (and an empty list).

```
1 | my_list = [2, 3, 5, 'p']  
2 | empty_list = []
```

Referring to a list item by index:

`my_list[0]` is 2 above, `my_list[1]` is 3, and so on.

The `+` operation is defined on lists. It results in the *concatenation* of the lists – putting them together, end to end.

```
1 | # the code below outputs [2, 3, 5, 'p', 11, 13]  
2 | my_list + [11, 13]
```

Other operations on lists

- Multiplication by an integer: adds that many copies of the list together. For example, $[1, 2] * 3$ will result in $[1, 2, 1, 2, 1, 2]$, since

$$[1, 2] + [1, 2] + [1, 2] = [1, 2, 1, 2, 1, 2].$$

Other operations on lists

- Multiplication by an integer: adds that many copies of the list together. For example, `[1,2]*3` will result in `[1,2,1,2,1,2]`, since

$$[1,2] + [1,2] + [1,2] = [1,2,1,2,1,2].$$

- Length of a list: use the function `len()`, with your list as input, to get the number of items in your list.

Other operations on lists

- Multiplication by an integer: adds that many copies of the list together. For example, `[1,2]*3` will result in `[1,2,1,2,1,2]`, since

$$[1,2] + [1,2] + [1,2] = [1,2,1,2,1,2].$$

- Length of a list: use the function `len()`, with your list as input, to get the number of items in your list.
- Checking if an item is in a list: use the *keyword* `in` to check this. For example, if `my_list` is `[2, 3, 5, 'p']` then the first line below would result in `True`, the second would be `False`.

```
1 | print( 2 in my_list )  
2 | print( 4 in my_list )
```


f-strings

To produce an output string that uses values of some variables in memory, the best approach is to use what are called f-strings: in the string, a variable between ' {} ' will print out its value.

f-strings

To produce an output string that uses values of some variables in memory, the best approach is to use what are called f-strings: in the string, a variable between '`{}`' will print out its value.

Say a variable `i` is in memory, with `i = 2`.

```
1 | # the next line will print out 'The value of i is 2.'  
2 | print(f'The value of i is {i}.')
```

f-strings

To produce an output string that uses values of some variables in memory, the best approach is to use what are called f-strings: in the string, a variable between `'{}'` will print out its value.

Say a variable `i` is in memory, with `i = 2`.

```
1 | # the next line will print out 'The value of i is 2.'  
2 | print(f'The value of i is {i}.')
```

- It doesn't have to be the variable only. Could put something like `'{3*i}'` and Python will compute the value and print that.
- *Escape characters* can be handled inside strings also: e.g., `'\t'` will produce a tab; `'\n'` produces a newline.

Variables and Types

Operations on different types

Lists

Intro to Python functions

Basic functions

Similar to most programming languages, Python uses *functions*, each of which takes some number of *arguments* (sometimes an argument is optional).

Basic functions

Similar to most programming languages, Python uses *functions*, each of which takes some number of *arguments* (sometimes an argument is optional).

- Common function, already encountered: `print()`.

Basic functions

Similar to most programming languages, Python uses *functions*, each of which takes some number of *arguments* (sometimes an argument is optional).

- Common function, already encountered: `print()`.
- Absolute value: `abs()`. Takes a numeric argument – either `int` or `float` type.

Basic functions

Similar to most programming languages, Python uses *functions*, each of which takes some number of *arguments* (sometimes an argument is optional).

- Common function, already encountered: `print()`.
- Absolute value: `abs()`. Takes a numeric argument – either `int` or `float` type.
- Round to nearest integer: `round()`. Takes argument that is `float`. (If passed an `int` argument, will simply return it.)
 - Optional 2nd argument, the number of decimal digits.

Basic functions

Similar to most programming languages, Python uses *functions*, each of which takes some number of *arguments* (sometimes an argument is optional).

- Common function, already encountered: `print()`.
- Absolute value: `abs()`. Takes a numeric argument – either `int` or `float` type.
- Round to nearest integer: `round()`. Takes argument that is `float`. (If passed an `int` argument, will simply return it.)
 - Optional 2nd argument, the number of decimal digits.

In Python, run the following to see how `round()` works.

```
1 | a = -3**2/8
2 | print( a+8 )
3 | print( (round(a+8), round(a+8, 2)) )
```

Basic list methods

Methods are functions that you call on an instance of a class. There are several methods for lists. Here are two.

Basic list methods

Methods are functions that you call on an instance of a class. There are several methods for lists. Here are two.

- `append()`: the command `my_list.append(x)` puts `x` at the end of `my_list`.
 - Changes `my_list` “in place.”

Basic list methods

Methods are functions that you call on an instance of a class. There are several methods for lists. Here are two.

- `append()`: the command `my_list.append(x)` puts `x` at the end of `my_list`.
 - Changes `my_list` “in place.”
 - Is equivalent to `my_list += [x]`.

Basic list methods

Methods are functions that you call on an instance of a class. There are several methods for lists. Here are two.

- `append()`: the command `my_list.append(x)` puts `x` at the end of `my_list`.
 - Changes `my_list` “in place.”
 - Is equivalent to `my_list += [x]`.
- `remove()`: the command `my_list.remove(x)` takes out the *first* item in `my_list` that is equal to `x`.
 - Changes `my_list` in place, making it shorter.

Basic list methods

Methods are functions that you call on an instance of a class. There are several methods for lists. Here are two.

- `append()`: the command `my_list.append(x)` puts `x` at the end of `my_list`.
 - Changes `my_list` “in place.”
 - Is equivalent to `my_list += [x]`.
- `remove()`: the command `my_list.remove(x)` takes out the *first* item in `my_list` that is equal to `x`.
 - Changes `my_list` in place, making it shorter.
 - `my_list.pop(i)` does something similar with item at index `i`, but also returns (has as output) that item.

More information on working with lists and other basic classes, like strings, tuples, sets, and dictionaries: [Tutorial from the Python documentation](#).