

• POLYMER SEALING FOR RECIPROCATING COMPRESSORS

Piston rings, rider bands & packing rings — in every style and every grade.

Corvex manufactures piston rings, rider bands and packing rings for reciprocating compressors based on drawing, OEM part number or the sample, using engineered PTFE compounds, PEEK-based materials and proprietary formulations. Our solutions are developed to suit the gas composition, operating pressure, temperature and lubrication conditions of each application.



1963

Making compressor rings since

13

Compressor grades

7

Proprietary compounds


50+

Institutional & PSU customers

Where the rings do their work.

In a reciprocating compressor a piston moves back and forth in a cylinder, drawing gas in and pushing it out at higher pressure through the valves. Piston rings seal the chamber, rider bands carry the piston, and packing rings seal the rod where it leaves the cylinder — together they decide how efficiently it runs, and for how long between overhauls.

Polymer rings run dry or lubricated, conform to the bore, and protect the cylinder and rod from wear. Choosing the right **style** and the right **grade** for the gas, pressure and temperature is what we do every day.



SUPPLIER TO

**Burckhardt
Compression**
Since 2024

REPLACEMENT SPARES FOR

Bharat Pumps & Compressors Ltd (BP&CL)

**Chicago
Pneumatic**

**Kirloskar
Pneumatic**

K.G. Khosla

Ingersoll Rand

Dresser-Rand

Atlas Copco

Piston rings

Seal the piston against the cylinder wall



One-piece rings

Straight, angle, step and overlap cuts, including gas-tight overlap joints, pressure-balanced designs and T-section rings.



Two-piece rings

Straight, angle or overlap cut, with pressure-balanced and gas-tight variants for larger bores.



Three- and four-piece rings

Straight, angle, step or overlap cut segments, including continuously pressure-balanced designs.



Rings with expanders

One-, two- and three-piece rings on round or flat metal expanders, in right- and left-hand cut.



Twin, double & spacer rings

Pegged and cam-type twin rings, double rings, solid spacer rings and solid rings with radial bores.


Rider bands

Carry the piston - solid, cut or multi-piece




Solid rider bands

Plain, or with axial or radial grooves; also for mounting on an expander.



One-piece cut bands

Angle, straight or overlap cut with axial, radial or staggered grooves; with locating hole or peg.



Multi-piece bands

Two-, three- and four-piece bands, angle or straight cut, plain or grooved.

Packing rings

Pressure breakers to oil wipers · complete packing sets



Pressure breakers

Single- and double-acting, with zero gap, bore clearance or gap; solid or segmented backup rings; polymer or metal.



Sealing ring pairs

Radial-tangent, tangent and six-segment tangent pairs; single- and double-acting; tangent-to-rod designs.




Pairs with backup & spacer rings

Segment or solid backup rings, spacer rings and sandwich types, including low-emission designs.



Vent & purge seals

Side-loaded pressure rings, single or double, with plain or tapered bore, for vented and purged packings.



Oil wiper rings

Radial wiper sets, one- and two-piece multi-edge wipers, and oil-tight wiper sets with throttle ring.


Every style, every grade

We manufacture all piston-ring, rider-band and packing-ring styles in every grade on the next page — single rings, matched sets or complete packings, for any make of compressor.

Bores from 8 mm to 1200 mm

PEEK valve plates

Suction and delivery valves · made to sample or drawing



Valve plates, discs & seats

Virgin and carbon-fibre-filled PEEK valve plates, discs and seats for suction and delivery valves.

● Virgin PEEK ● Carbon-fibre filled PEEK

Material families

Filled PTFE, PEEK-based and proprietary compounds

Carbon / graphite filled PTFE

Higher compressive strength and hardness, good heat conduction; low wear in dry running.

Glass / MoS₂ filled PTFE

Better wear and creep resistance with full chemical resistance; low-friction surface.

Bronze filled PTFE

High wear resistance and heat dissipation for rider bands and guide duty.

PEEK-based compounds

Strength and stiffness at high pressure and temperature, where PTFE would extrude.

Proprietary blends

Our 7 in-house compressor compounds, matched to the gas, pressure and duty.

Grade selection guide

according to the application is provided on the next page →

13 compressor grades, matched to your application.

Grade	Description	Air	Industrial gases	Natural gas	Refinery	Olefins	Alcohols	Chemicals	Refrigeration
CX101	Premium filled-PTFE alloy for the widest range of gases, refrigeration included.	●	●	●	●	●		●	●
CX103	PEEK-based compound for hot service, lubricated or non-lubricated.	●	●	●	●	●	●	●	
CX534	PEEK-based compound for high-pressure, high-temperature lubricated duty.	●	●	●	●	●	●	●	
CX29	Glass-fibre filled PTFE for industrial gases and chemical service.		●					●	
CX52	Field-proven grade for non-lubricated air compressors.	●	●						
CX54	Versatile all-rounder from wet to dry gas, lubricated or non-lubricated.	●	●	●	●	●		●	●
CX60	Filled PTFE for pure gases and oxygen-rich service.		●						
CX79	Stiffer, low-extrusion compound for demanding air duty.	●							
CX121	Low friction with high wear resistance at very low dew points.		●	●	●	●			
CX509	Glass / MoS ₂ filled PTFE with fibre; gentle on soft counter-faces.	●	●	●	●	●	●	●	
CX538	Low-creep PTFE for bone-dry gas (dew point -60 °C or lower), non-lubricated.	●	●	●	●	●			
CX22	Carbon-graphite filled PTFE; lowest wear of the medium-to-high filled grades.	●	●	●	●	●	●	●	●
CX112	Carbon-filled PTFE; dependable value grade for lubricated natural gas.			●					

● Standard ● Performance ● Premium

Typical applications for guidance only. Cross-reference to OEM grades available on request.

Machined to perfection

Tolerances matched and quality-checked on every batch before delivery.

Minimum lead time

Precision-engineered rings delivered in the shortest lead time possible.

REQUEST A QUOTE

Send a sample, a drawing or the part number.


Ask for a quote on WhatsApp, call or email — we reply with the recommended style, grade and price.

WHATSAPP +91 73508 08899

CALL +91 85116 44445

EMAIL sales@corvex.co.in

WORKS 7-B Anjani Industrial Estate, Narol, Ahmedabad
Pin code 382405, Gujarat, India



Compressor range



WhatsApp us

Images are representative illustrations of ring styles. Brand names belong to their respective owners; Corvex supplies compatible replacement parts. Corvex is a brand of Corrosion Engineers, an ISO 9001:2015 certified company, Ahmedabad · GSTIN 24AKDPJ6708RIZQ.