

Introduction to Layering and Network Layering



COS 316: Principles of Computer System Design

Lecture 11

Amit Levy & Jennifer Rexford

1



Barbara Liskov

**“Modularity based on abstraction
is the way things get done”**

2009 Turing Award Lecture


2

Modularity Through Layering

- Systems on systems on systems though layering
- Each layer hides complexity with abstraction
- Network layers today!

3


The Problem of Communication



- Re-implement every application for every new transmission medium?
- Change every application on any change to a transmission medium?
- No! But how does the Internet design avoid this?

4

Solution: Layering



- Intermediate **layers** provide a set of abstractions for applications and media
- New applications or media need only implement for intermediate layer's interface


5

The Art of Layering

- How many layers?
- What goes in each layer?
- What abstraction (interface) does each layer provide?

6


Internet Protocol Layers



7

Logical Communication Between Layers

- How to forge agreement on meaning of bits exchanged between two hosts?
- **Protocol:** Rules that govern the format, contents, and meaning of messages
 - Each layer on a host interacts with peer host's corresponding layer via **protocol interface**




8

8

Physical communication


- Communication goes down to the **physical network**
- Then from **network** peer to peer
- Then up to the **relevant application**



9

Communication Between Peers


- How do peer protocols coordinate with each other?
- Layer attaches its own **header (H)** to communicate with peer
 - Higher layers' headers, data **encapsulated** inside message
 - Lower layers generally do not inspect higher layers' headers



10

10

Teaching TCP/IP Headers With Legos



<https://boingboing.net/2013/04/30/teaching-tcpip-headers-with-l.html>

11

IP is the “Narrow Waist” of the Internet

- **The** network-layer protocol
 - Enables portability above and below
- Lots of link layer protocols underneath
- Several transport protocols on top
 - TCP, UDP, QUIC



12

IP: Best-Effort Global Packet Delivery


- Never having to say you're sorry
 - Don't have to reserve bandwidth and memory
 - Don't have to do error detection and correction
 - Don't have to remember anything across packets
- Easier to survive failures
 - Transient disruptions are okay during failure recovery
- Can run on nearly any link technology
 - Greater interoperability and evolution
 - RFC 1149: IP Datagrams Over Avian Carriers



13

IP: Statistical Multiplexing

- Data traffic is bursty
 - Logging in to remote machines
 - Exchanging e-mail messages
- Don't waste bandwidth
 - No traffic exchanged during idle periods
- Better to allow multiplexing
 - Different transfers share access to same links



14

Transport: Application to Application

- Network layer is host-to-host
- Transport layer is port-on-host-to-port-on-host
 - think application to application
 - demultiplexing
 - e.g., port 80 is HTTP, port 443 is HTTPS, port 22 is SSH
- *Why transport and not network layer?*

15


Transport: Application to Application

- Network doesn't have error detection
- Transport layer does have error detection
- *Why transport and not network layer?*
- *Why not both?*

16

Transport: Transmission Control Protocol (TCP)

- Ordered, reliable stream of bytes
 - Built on top of best-effort packet delivery at the network layer
- Challenges with IP
 - Lost or delayed packets
 - Corrupted packets
 - Out-of-order packet arrivals
 - Receiver runs out of space
 - Network cannot handle current load




17

TCP: Lost or Delayed Packets

Problem: Lost or Delayed Data




Solution: Timeout and Retransmit



18

TCP: Corrupted Data





- Sender computes a checksum

	134
• Sender sums up all bytes in the payload	+ 212
• And sends the sum to the receiver	= 346
- Receiver checks a checksum

	134	<i>Then what?</i>
• Receiver sums up all bytes in the payload	+ 216	
• And compares against the checksum	= 350	

19

TCP: Out-of-Order Packet Arrivals



20

TCP: Receiver that Runs Out of Space



?



- Receiver maintains a *window size*
 - Amount of data it can buffer
- Advertises window to the sender
 - Amount sender can send without acknowledgment
- Ensures that sender does not send too much
 - While still sending as much as possible

Flow control!

21

TCP: Network that Cannot Handle the Load

- Problem: Too many packets at once
- Solution: Congestion control
 - Future lecture!



22

Transport: User Datagram Protocol (UDP)

- Datagram of bytes
 - A message

*UDP does less than TCP,
why do we want UDP too?*

- Challenges with IP
 - Lost or delayed packets X
 - Corrupted packets ✓
 - Out-of-order packet arrivals X
 - Receiver runs out of space X
 - Network cannot handle current load X

My favorite UDP joke

"I'd tell you a joke about UDP packets, but I'm not sure you'd get it."

23

Layering & Network Layers Conclusion

- The art of layering
- Network layers
 - Protocol, headers, encapsulation
- IP layer: best-effort global packet delivery between host
- TCP layer: ordered, reliable byte stream between applications

24