

# Mandatory Access Control

COS 316: Principles of Computer System Design

*Amit Levy & Ravi Netravali*


# Last Times - Discretionary Access Control

**Discretionary Access Control** - *[Access] controls are discretionary in the sense that a subject with a certain access permission is capable of passing that permission (perhaps indirectly) on to any other subject (unless restrained by mandatory access control).*

- Trusted Computer System Evaluation Criteria, 1985 (the “Orange Book”)

- Most prevalent form of access control system
- Access Control Lists
  - Restrict access to objects based on the identity of subjects
  - Subjects can pass object contents after reading
- Capabilities
  - Restrict access to objects based on possession of a capability
  - Capabilities can be passed directly to other subjects
  - Subjects can pass object contents after reading

# Who enforces policy under DAC?



Legend




FBI




SNCC

# Who enforces policy under DAC?



# Who enforces policy under DAC?



# Limitations of Discretionary Access Control

- Discretionary means *subjects* with access to *objects* can propagate information:
  - UNIX process reads `~/.ssh/ida_rsa` and writes output to public log
  - In UNIX, owners determine read/write/execute access for themselves, group, and “other”
  - Subject can pass capabilities to anyone
  - Can’t (trivially) revoke capabilities
- This is *one* reason it is sufficient to compromise a single high privilege application, not whole system, in order to extract private data

# The non-interference property

Informally:

A program is non-interferent if its transformations of data in low security domains (*low*) are not influenced by data in higher security domains (*high*)

# The non-interference property

$M$ , a memory state including *low* and *high* memory,  $M_H$  and  $M_L$ , respectively


$P: (M) \rightarrow M^*$ , a non-interference program execution over a memory state resulting in a new memory state, if:

$$\begin{aligned} \forall M1, M2 \text{ s.t. } & M1_L = M2_L \\ & \wedge P(M1) \rightarrow M1^* \\ & \wedge P(M2) \rightarrow M2^* \\ \Rightarrow & \mathbf{M1^*_L = M2^*_L} \end{aligned}$$




# Enforcing Non-Interference with DAC

Discretionary Access Control policies can enforce non-interference by completely partitioning the system



# Enforcing Non-Interference with DAC


Discretionary Access Control policies can enforce non-interference by completely partitioning the system, or with careful, static sharing



# Mandatory Access Control (MAC)

- Goal: data secrecy & integrity don't rely on trusting applications *at all*
- All resource accesses governed by a global policy
- Subjects cannot change or circumvent global policy
- Typically policy articulated in terms of data sources and sinks
- E.g.
  - *label* data with it's sensitivity
  - define permitted flows between labels
  - Permit operations as long as information flow rules are not violated

# A simple security label lattice



# Implementing MAC

There are very few MAC systems used *in practice*:



- SELinux - an extension to Linux originating from the NSA
  - Used in Android
- Mandatory Integrity Control - a Windows kernel subsystem limited to integrity
- TrustedBSD (in development)



But lots of *research* systems

# Implementing MAC

One general approach:



- Assign a security label to object (file, network endpoint, console, etc)
- Assign a *floating* label to subjects (running processes)
  - “Floating” because it changes dynamically
- Whenever moving/copying data, check that source label *can flow to* sink label
- Allow subject to “raise” its floating label, but not to “lower” it







Permissible, because write could only involve data secret to Repo 2





**Prohibited**, because write to **Repo 1** could involve data secret to **Repo 2**



**Prohibited**, because write could involve data secret from **Repo 2** or **Repo 1**

# Mandatory Access Control in Practice

- Dates back to at least 1983
  - Defined in the DoDs *Trusted Computer System Evaluation Criteria* (aka the Orange Book)
- Very powerful guarantee!
  - Security policies on data *do not* rely on application correctness
- Why is it not more prevalent?

# Why isn't MAC more prevalent?

- Complexity: implementing MAC can be hard to get right
- Performance: lattice checks can be slow
- Flexibility: by design, applications cannot get around security policy
- Simplicity: MAC is harder to administer